

[MS-OXPROPS]: Exchange Server Protocols Master Property List

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Updated references to reflect date of initial release.
09/03/2008	1.02		Changed title of document.
10/01/2008	1.03		Revised and edited technical content.
12/03/2008	1.04		Revised and edited technical content.
02/04/2009	1.05		Revised and edited technical content.
03/04/2009	1.06		Revised and edited technical content.
04/10/2009	2.0		Updated technical content and applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	4.0.0	Major	Updated and revised the technical content.
02/10/2010	5.0.0	Major	Updated and revised the technical content.
05/05/2010	6.0.0	Major	Updated and revised the technical content.
08/04/2010	7.0	Major	Significantly changed the technical content.
11/03/2010	8.0	Major	Significantly changed the technical content.
03/18/2011	9.0	Major	Significantly changed the technical content.
08/05/2011	10.0	Major	Significantly changed the technical content.
10/07/2011	11.0	Major	Significantly changed the technical content.

Table of Contents

1 Introduction	25
1.1 Glossary	25
1.2 References	28
1.2.1 Normative References	28
1.2.2 Informative References	30
1.3 Overview	31
1.3.1 Common Message Classes	32
1.3.2 Commonly Used Property Sets	33
1.3.3 Property ID Ranges	34
1.3.4 WebDAV Property Naming	35
1.3.4.1 http://schemas.microsoft.com/mapi/proptag Namespace	35
1.3.4.2 http://schemas.microsoft.com/mapi/id Namespace	36
1.3.4.3 http://schemas.microsoft.com/mapi/string Namespace	36
1.4 Relationship to Protocols and Other Structures	36
1.5 Applicability Statement	37
1.6 Versioning and Localization	37
1.7 Vendor-Extensible Fields	37
2 Structures	38
2.1 PidLidAddressBookProviderArrayType	38
2.2 PidLidAddressBookProviderEmailList	38
2.3 PidLidAddressCountryCode	38
2.4 PidLidAgingDontAgeMe	39
2.5 PidLidAllAttendeesString	39
2.6 PidLidAllowExternalCheck	39
2.7 PidLidAnniversaryEventEntryId	40
2.8 PidLidAppointmentAuxiliaryFlags	40
2.9 PidLidAppointmentColor	40
2.10 PidLidAppointmentCounterProposal	41
2.11 PidLidAppointmentDuration	41
2.12 PidLidAppointmentEndDate	41
2.13 PidLidAppointmentEndTime	42
2.14 PidLidAppointmentEndWhole	42
2.15 PidLidAppointmentLastSequence	42
2.16 PidLidAppointmentMessageClass	43
2.17 PidLidAppointmentNotAllowedPropose	43
2.18 PidLidAppointmentProposalNumber	43
2.19 PidLidAppointmentProposedDuration	44
2.20 PidLidAppointmentProposedEndWhole	44
2.21 PidLidAppointmentProposedStartWhole	44
2.22 PidLidAppointmentRecur	45
2.23 PidLidAppointmentReplyName	45
2.24 PidLidAppointmentReplyTime	45
2.25 PidLidAppointmentSequence	46
2.26 PidLidAppointmentSequenceTime	46
2.27 PidLidAppointmentStartDate	47
2.28 PidLidAppointmentStartTime	47
2.29 PidLidAppointmentStartWhole	47
2.30 PidLidAppointmentStateFlags	48
2.31 PidLidAppointmentSubType	48

2.32	PidLidAppointmentTimeZoneDefinitionEndDisplay	48
2.33	PidLidAppointmentTimeZoneDefinitionRecur	49
2.34	PidLidAppointmentTimeZoneDefinitionStartDisplay	49
2.35	PidLidAppointmentUnsendableRecipients	49
2.36	PidLidAppointmentUpdateTime	50
2.37	PidLidAttendeeCriticalChange	50
2.38	PidLidAutoFillLocation	50
2.39	PidLidAutoLog	51
2.40	PidLidAutoProcessState	51
2.41	PidLidAutoStartCheck	51
2.42	PidLidBilling	52
2.43	PidLidBirthdayEventEntryId	52
2.44	PidLidBirthdayLocal	52
2.45	PidLidBusinessCardCardPicture	53
2.46	PidLidBusinessCardDisplayDefinition	53
2.47	PidLidBusyStatus	53
2.48	PidLidCalendarType	54
2.49	PidLidCategories	54
2.50	PidLidCcAttendeesString	55
2.51	PidLidChangeHighlight	55
2.52	PidLidClassification	55
2.53	PidLidClassificationDescription	56
2.54	PidLidClassificationGuid	56
2.55	PidLidClassificationKeep	56
2.56	PidLidClassified	57
2.57	PidLidCleanGlobalObjectId	57
2.58	PidLidClientIntent	57
2.59	PidLidClipEnd	58
2.60	PidLidClipStart	58
2.61	PidLidCollaborateDoc	58
2.62	PidLidCommonEnd	59
2.63	PidLidCommonStart	59
2.64	PidLidCompanies	59
2.65	PidLidConferencingCheck	60
2.66	PidLidConferencingType	60
2.67	PidLidContactCharacterSet	60
2.68	PidLidContactItemData	61
2.69	PidLidContactLinkEntry	61
2.70	PidLidContactLinkName	61
2.71	PidLidContactLinkSearchKey	62
2.72	PidLidContacts	62
2.73	PidLidContactUserField1	62
2.74	PidLidContactUserField2	63
2.75	PidLidContactUserField3	63
2.76	PidLidContactUserField4	63
2.77	PidLidConversationActionLastAppliedTime	64
2.78	PidLidConversationActionMaxDeliveryTime	64
2.79	PidLidConversationActionMoveFolderEid	64
2.80	PidLidConversationActionMoveStoreEid	65
2.81	PidLidConversationActionVersion	65
2.82	PidLidConversationProcessed	65
2.83	PidLidCurrentVersion	66
2.84	PidLidCurrentVersionName	66

2.85	PidLidDayInterval.....	66
2.86	PidLidDayOfMonth.....	67
2.87	PidLidDelegateMail	67
2.88	PidLidDepartment	67
2.89	PidLidDirectory	68
2.90	PidLidDistributionListChecksum	68
2.91	PidLidDistributionListMembers	68
2.92	PidLidDistributionListName	69
2.93	PidLidDistributionListOneOffMembers.....	69
2.94	PidLidDistributionListStream	69
2.95	PidLidEmail1AddressType	70
2.96	PidLidEmail1DisplayName	70
2.97	PidLidEmail1EmailAddress	70
2.98	PidLidEmail1OriginalDisplayName.....	71
2.99	PidLidEmail1OriginalEntryId.....	71
2.100	PidLidEmail2AddressType	71
2.101	PidLidEmail2DisplayName.....	72
2.102	PidLidEmail2EmailAddress	72
2.103	PidLidEmail2OriginalDisplayName	72
2.104	PidLidEmail2OriginalEntryId	73
2.105	PidLidEmail3AddressType	73
2.106	PidLidEmail3DisplayName	73
2.107	PidLidEmail3EmailAddress	74
2.108	PidLidEmail3OriginalDisplayName	74
2.109	PidLidEmail3OriginalEntryId	74
2.110	PidLidEndRecurrenceDate	75
2.111	PidLidEndRecurrenceTime.....	75
2.112	PidLidExceptionReplaceTime	75
2.113	PidLidFax1AddressType	76
2.114	PidLidFax1EmailAddress	76
2.115	PidLidFax1OriginalDisplayName	76
2.116	PidLidFax1OriginalEntryId	77
2.117	PidLidFax2AddressType	77
2.118	PidLidFax2EmailAddress	77
2.119	PidLidFax2OriginalDisplayName	78
2.120	PidLidFax2OriginalEntryId	78
2.121	PidLidFax3AddressType	78
2.122	PidLidFax3EmailAddress	79
2.123	PidLidFax3OriginalDisplayName	79
2.124	PidLidFax3OriginalEntryId	79
2.125	PidLidFExceptionalAttendees	79
2.126	PidLidFExceptionalBody	80
2.127	PidLidFileUnder	80
2.128	PidLidFileUnderId	80
2.129	PidLidFileUnderList	81
2.130	PidLidFInvited	81
2.131	PidLidFlagRequest	82
2.132	PidLidFlagString	82
2.133	PidLidForwardInstance	82
2.134	PidLidForwardNotificationRecipients	83
2.135	PidLidFOthersAppointment	83
2.136	PidLidFreeBusyLocation	83
2.137	PidLidGlobalObjectId	84

2.138	PidLidHasPicture.....	84
2.139	PidLidHomeAddress	84
2.140	PidLidHomeAddressCountryCode	85
2.141	PidLidHtml.....	85
2.142	PidLidICalendarDayOfWeekMask	85
2.143	PidLidInboundICalStream	86
2.144	PidLidInfoPathFormName	86
2.145	PidLidInstantMessagingAddress.....	86
2.146	PidLidIntendedBusyStatus	87
2.147	PidLidInternetAccountName.....	87
2.148	PidLidInternetAccountStamp.....	87
2.149	PidLidIsException	88
2.150	PidLidIsRecurring	88
2.151	PidLidIsSilent.....	88
2.152	PidLidLinkedTaskItems.....	89
2.153	PidLidLocation.....	89
2.154	PidLidLogDocumentPosted	90
2.155	PidLidLogDocumentPrinted	90
2.156	PidLidLogDocumentRouted	90
2.157	PidLidLogDocumentSaved	90
2.158	PidLidLogDuration	91
2.159	PidLidLogEnd	91
2.160	PidLidLogFlags	91
2.161	PidLidLogStart	92
2.162	PidLidLogType.....	92
2.163	PidLidLogTypeDesc	92
2.164	PidLidMeetingType.....	93
2.165	PidLidMeetingWorkspaceUrl	93
2.166	PidLidMonthInterval	93
2.167	PidLidMonthOfYear	94
2.168	PidLidMonthOfYearMask	94
2.169	PidLidNetShowUrl	94
2.170	PidLidNoEndDateFlag	95
2.171	PidLidNonSendableBcc	95
2.172	PidLidNonSendableCc.....	95
2.173	PidLidNonSendableTo.....	96
2.174	PidLidNonSendBccTrackStatus	96
2.175	PidLidNonSendCcTrackStatus.....	96
2.176	PidLidNonSendToTrackStatus.....	97
2.177	PidLidNoteColor.....	97
2.178	PidLidNoteHeight.....	97
2.179	PidLidNoteWidth.....	98
2.180	PidLidNoteX	98
2.181	PidLidNoteY	98
2.182	PidLidOccurrences	99
2.183	PidLidOldLocation	99
2.184	PidLidOldRecurrenceType	99
2.185	PidLidOldWhenEndWhole	100
2.186	PidLidOldWhenStartWhole	100
2.187	PidLidOnlinePassword	100
2.188	PidLidOptionalAttendees.....	101
2.189	PidLidOrganizerAlias	101
2.190	PidLidOriginalStoreEntryId.....	101

2.191	PidLidOtherAddress	102
2.192	PidLidOtherAddressCountryCode	102
2.193	PidLidOwnerCriticalChange	102
2.194	PidLidOwnerName	103
2.195	PidLidPercentComplete.....	103
2.196	PidLidPostalAddressId	103
2.197	PidLidPostRssChannel	104
2.198	PidLidPostRssChannelLink.....	104
2.199	PidLidPostRssItemGuid.....	104
2.200	PidLidPostRssItemHash	105
2.201	PidLidPostRssItemLink	105
2.202	PidLidPostRssItemXml.....	105
2.203	PidLidPostRssSubscription	106
2.204	PidLidPrivate.....	106
2.205	PidLidPromptSendUpdate	106
2.206	PidLidRecurrenceDuration.....	107
2.207	PidLidRecurrencePattern.....	107
2.208	PidLidRecurrenceType	107
2.209	PidLidRecurring	108
2.210	PidLidReferenceEntryId	108
2.211	PidLidReferredBy	108
2.212	PidLidReminderDelta.....	109
2.213	PidLidReminderFileParameter.....	109
2.214	PidLidReminderOverride	110
2.215	PidLidReminderPlaySound	110
2.216	PidLidReminderSet	110
2.217	PidLidReminderSignalTime	111
2.218	PidLidReminderTime	111
2.219	PidLidReminderTimeDate.....	111
2.220	PidLidReminderTimeTime	112
2.221	PidLidReminderType	112
2.222	PidLidRemoteStatus.....	113
2.223	PidLidRequiredAttendees	113
2.224	PidLidResourceAttendees.....	113
2.225	PidLidResponseStatus	114
2.226	PidLidServerProcessed	114
2.227	PidLidServerProcessingActions	114
2.228	PidLidSharingAnonymity.....	115
2.229	PidLidSharingBindingEntryId	115
2.230	PidLidSharingBrowseUrl	115
2.231	PidLidSharingCapabilities.....	116
2.232	PidLidSharingConfigurationUrl.....	116
2.233	PidLidSharingDataRangeEnd	116
2.234	PidLidSharingDataRangeStart	117
2.235	PidLidSharingDetail	117
2.236	PidLidSharingExtensionXml.....	117
2.237	PidLidSharingFilter	118
2.238	PidLidSharingFlags	118
2.239	PidLidSharingFlavor	118
2.240	PidLidSharingFolderEntryId.....	119
2.241	PidLidSharingIndexEntryId	119
2.242	PidLidSharingInitiatorEntryId	119
2.243	PidLidSharingInitiatorName	120

2.244	PidLidSharingInitiatorSmtp	120
2.245	PidLidSharingInstanceId	120
2.246	PidLidSharingLastAutoSyncTime	121
2.247	PidLidSharingLastSyncTime	121
2.248	PidLidSharingLocalComment	121
2.249	PidLidSharingLocalLastModificationTime	122
2.250	PidLidSharingLocalName	122
2.251	PidLidSharingLocalPath	122
2.252	PidLidSharingLocalStoreUid	123
2.253	PidLidSharingLocalType	123
2.254	PidLidSharingLocalUid	123
2.255	PidLidSharingOriginalMessageEntryId	124
2.256	PidLidSharingParentBindingEntryId	124
2.257	PidLidSharingParticipants	124
2.258	PidLidSharingPermissions	125
2.259	PidLidSharingProviderExtension	125
2.260	PidLidSharingProviderGuid	125
2.261	PidLidSharingProviderName	126
2.262	PidLidSharingProviderUrl	126
2.263	PidLidSharingRangeEnd	126
2.264	PidLidSharingRangeStart	127
2.265	PidLidSharingReciprocation	127
2.266	PidLidSharingRemoteByteSize	127
2.267	PidLidSharingRemoteComment	128
2.268	PidLidSharingRemoteCrc	128
2.269	PidLidSharingRemoteLastModificationTime	128
2.270	PidLidSharingRemoteMessageCount	129
2.271	PidLidSharingRemoteName	129
2.272	PidLidSharingRemotePass	129
2.273	PidLidSharingRemotePath	130
2.274	PidLidSharingRemoteStoreUid	130
2.275	PidLidSharingRemoteType	130
2.276	PidLidSharingRemoteUid	131
2.277	PidLidSharingRemoteUser	131
2.278	PidLidSharingRemoteVersion	131
2.279	PidLidSharingResponseTime	132
2.280	PidLidSharingResponseType	132
2.281	PidLidSharingRoamLog	132
2.282	PidLidSharingStart	133
2.283	PidLidSharingStatus	133
2.284	PidLidSharingStop	133
2.285	PidLidSharingSyncFlags	134
2.286	PidLidSharingSyncInterval	134
2.287	PidLidSharingTimeToLive	134
2.288	PidLidSharingTimeToLiveAuto	135
2.289	PidLidSharingWorkingHoursDays	135
2.290	PidLidSharingWorkingHoursEnd	135
2.291	PidLidSharingWorkingHoursStart	136
2.292	PidLidSharingWorkingHoursTimeZone	136
2.293	PidLidSideEffects	136
2.294	PidLidSingleBodyICal	137
2.295	PidLidSmartNoAttach	137
2.296	PidLidSpamOriginalFolder	137

2.297	PidLidStartRecurrenceDate	138
2.298	PidLidStartRecurrenceTime	138
2.299	PidLidTaskAcceptanceState	138
2.300	PidLidTaskAccepted	139
2.301	PidLidTaskActualEffort	139
2.302	PidLidTaskAssigner	139
2.303	PidLidTaskAssigners	140
2.304	PidLidTaskComplete	140
2.305	PidLidTaskCustomFlags	140
2.306	PidLidTaskDateCompleted	141
2.307	PidLidTaskDeadOccurrence	141
2.308	PidLidTaskDueDate	141
2.309	PidLidTaskEstimatedEffort	142
2.310	PidLidTaskFCreator	142
2.311	PidLidTaskFFixOffline	142
2.312	PidLidTaskFRecurring	143
2.313	PidLidTaskGlobalId	143
2.314	PidLidTaskHistory	143
2.315	PidLidTaskLastDelegate	144
2.316	PidLidTaskLastUpdate	144
2.317	PidLidTaskLastUser	144
2.318	PidLidTaskMode	145
2.319	PidLidTaskMultipleRecipients	145
2.320	PidLidTaskNoCompute	145
2.321	PidLidTaskOrdinal	146
2.322	PidLidTaskOwner	146
2.323	PidLidTaskOwnership	146
2.324	PidLidTaskRecurrence	147
2.325	PidLidTaskResetReminder	147
2.326	PidLidTaskRole	147
2.327	PidLidTaskStartDate	148
2.328	PidLidTaskState	148
2.329	PidLidTaskStatus	149
2.330	PidLidTaskStatusOnComplete	149
2.331	PidLidTaskUpdates	149
2.332	PidLidTaskVersion	150
2.333	PidLidTeamTask	150
2.334	PidLidTimeZone	150
2.335	PidLidTimeZoneDescription	151
2.336	PidLidTimeZoneStruct	151
2.337	PidLidToAttendeesString	151
2.338	PidLidToDoOrdinalDate	152
2.339	PidLidToDoSubOrdinal	152
2.340	PidLidToDoTitle	152
2.341	PidLidTrustRecipientHighlights	153
2.342	PidLidUseTnef	153
2.343	PidLidValidFlagStringProof	153
2.344	PidLidVerbResponse	154
2.345	PidLidVerbStream	154
2.346	PidLidWeddingAnniversaryLocal	154
2.347	PidLidWeekInterval	155
2.348	PidLidWhere	155
2.349	PidLidWorkAddress	156

2.350	PidLidWorkAddressCity.....	156
2.351	PidLidWorkAddressCountry	156
2.352	PidLidWorkAddressCountryCode	157
2.353	PidLidWorkAddressPostalCode.....	157
2.354	PidLidWorkAddressPostOfficeBox.....	157
2.355	PidLidWorkAddressState.....	158
2.356	PidLidWorkAddressStreet	158
2.357	PidLidYearInterval	158
2.358	PidLidYomiCompanyName	159
2.359	PidLidYomiFirstName	159
2.360	PidLidYomiLastName.....	160
2.361	PidNameAcceptLanguage	160
2.362	PidNameApplicationName	160
2.363	PidNameApprovalAllowedDecisionMakers.....	161
2.364	PidNameApprovalRequestor.....	161
2.365	PidNameApproved	161
2.366	PidNameAttachmentMacContentType	162
2.367	PidNameAttachmentMacInfo	162
2.368	PidNameAudioNotes	162
2.369	PidNameAuthenticatedAs.....	163
2.370	PidNameAuthenticatedDomain	163
2.371	PidNameAuthenticatedMechanism	163
2.372	PidNameAuthenticatedSource	164
2.373	PidNameAuthor	164
2.374	PidNameAutomaticSpeechRecognitionData	164
2.375	PidNameBcc	165
2.376	PidNameByteCount.....	165
2.377	PidNameCalendarAttendeeRole	165
2.378	PidNameCalendarBusystatus.....	166
2.379	PidNameCalendarContact	166
2.380	PidNameCalendarContactUrl	166
2.381	PidNameCalendarCreated	167
2.382	PidNameCalendarDescriptionUrl	167
2.383	PidNameCalendarDuration	167
2.384	PidNameCalendarExceptionDate.....	168
2.385	PidNameCalendarExceptionRule	168
2.386	PidNameCalendarGeoLatitude	168
2.387	PidNameCalendarGeoLongitude.....	169
2.388	PidNameCalendarInstanceType	169
2.389	PidNameCalendarIsOrganizer.....	169
2.390	PidNameCalendarLastModified	170
2.391	PidNameCalendarLocationUrl	170
2.392	PidNameCalendarMeetingStatus	170
2.393	PidNameCalendarMethod.....	171
2.394	PidNameCalendarProductId	171
2.395	PidNameCalendarRecurrenceIdRange.....	171
2.396	PidNameCalendarReminderOffset	172
2.397	PidNameCalendarResources	172
2.398	PidNameCalendarRsvp	172
2.399	PidNameCalendarSequence	173
2.400	PidNameCalendarTimeZone	173
2.401	PidNameCalendarTimeZoneId	173
2.402	PidNameCalendarTransparent	174

2.403	PidNameCalendarUid	174
2.404	PidNameCalendarVersion	174
2.405	PidNameCategory	175
2.406	PidNameCc	175
2.407	PidNameCharacterCount	175
2.408	PidNameComments	176
2.409	PidNameCompany	176
2.410	PidNameContactsAlternateRecipient	176
2.411	PidNameContactsCountry	177
2.412	PidNameContactsEmail1	177
2.413	PidNameContactsEmail2	177
2.414	PidNameContactsEmail3	178
2.415	PidNameContactsFileAs	178
2.416	PidNameContactsFileasId	178
2.417	PidNameContactsHomeLatitude	179
2.418	PidNameContactsHomeLongitude	179
2.419	PidNameContactsHomeTimeZone	179
2.420	PidNameContactsMapUrl	180
2.421	PidNameContactsOtherCountryCode	180
2.422	PidNameContactsOtherPager	180
2.423	PidNameContactsOtherTimeZone	181
2.424	PidNameContactsProxyAddresses	181
2.425	PidNameContactsSecretaryUrl	181
2.426	PidNameContactsSourceUrl	182
2.427	PidNameContentBase	182
2.428	PidNameContentClass	182
2.429	PidNameContentDisposition	183
2.430	PidNameContentID	183
2.431	PidNameContentLanguage	183
2.432	PidNameContentLocation	184
2.433	PidNameContentTransferEncoding	184
2.434	PidNameContentType	184
2.435	PidNameControl	185
2.436	PidNameCreateDateTimeReadOnly	185
2.437	PidNameCrossReference	185
2.438	PidNameDavGetContentType	186
2.439	PidNameDavId	186
2.440	PidNameDavIsCollection	186
2.441	PidNameDavIsStructuredDocument	187
2.442	PidNameDavParentName	187
2.443	PidNameDavResourceType	187
2.444	PidNameDavSearchRequest	188
2.445	PidNameDavSearchType	188
2.446	PidNameDavUid	188
2.447	PidNameDisposition	189
2.448	PidNameDispositionNotificationTo	189
2.449	PidNameDistribution	189
2.450	PidNameDocumentParts	190
2.451	PidNameEditTime	190
2.452	PidNameExchangeIntendedBusyStatus	190
2.453	PidNameExchangeJunkEmailMoveStamp	191
2.454	PidNameExchangeModifyExceptionStructure	191
2.455	PidNameExchangeNoModifyExceptions	191

2.456	PidNameExchangePatternEnd	192
2.457	PidNameExchangePatternStart.....	192
2.458	PidNameExchangePublicFolderEmailAddress	192
2.459	PidNameExchangeReminderInterval	193
2.460	PidNameExchDatabaseSchema	193
2.461	PidNameExchDataExpectedContentClass	193
2.462	PidNameExchDataSchemaCollectionReference	194
2.463	PidNameExpires	194
2.464	PidNameExpiryDate	194
2.465	PidNameFollowupTo.....	195
2.466	PidNameFrom	195
2.467	PidNameHeadingPairs	195
2.468	PidNameHiddenCount	196
2.469	PidNameHttpmailCalendar	196
2.470	PidNameHttpmailCc	196
2.471	PidNameHttpmailContacts	197
2.472	PidNameHttpmailContentMediaType	197
2.473	PidNameHttpmailFrom	197
2.474	PidNameHttpmailFromEmail.....	197
2.475	PidNameHttpmailHtmlDescription	198
2.476	PidNameHttpmailOutbox	198
2.477	PidNameHttpmailSendMessage	198
2.478	PidNameHttpmailSubmitted	199
2.479	PidNameHttpmailTo	199
2.480	PidNameICalendarRecurrenceDate	199
2.481	PidNameICalendarRecurrenceRule	200
2.482	PidNameImportance	200
2.483	PidNameInReplyTo	200
2.484	PidNameInternetComment	201
2.485	PidNameInternetKeywords	201
2.486	PidNameInternetSubject	201
2.487	PidNameKeywords.....	202
2.488	PidNameLastAuthor	202
2.489	PidNameLastPrinted.....	202
2.490	PidNameLastSaveDateTime	203
2.491	PidNameLineCount	203
2.492	PidNameLines	203
2.493	PidNameLinksDirty	204
2.494	PidNameLocationUrl.....	204
2.495	PidNameMailSubmissionUri	204
2.496	PidNameManager	205
2.497	PidNameMessageId	205
2.498	PidNameMimeType	205
2.499	PidNameMultimediaClipCount.....	206
2.500	PidNameNewsgroups	206
2.501	PidNameNntpPostingHost	206
2.502	PidNameNoteCount	207
2.503	PidNameOMSAccountGuid	207
2.504	PidNameOMSMobileModel.....	207
2.505	PidNameOMSScheduleTime	208
2.506	PidNameOMSServiceType	208
2.507	PidNameOMSSourceType	208
2.508	PidNameOrganization.....	208

2.509	PidNameOriginalRecipient.....	209
2.510	PidNameOriginalSpamConfidenceLevel	209
2.511	PidNameOutlookProtectionRuleOverridden	209
2.512	PidNameOutlookProtectionRuleTimestamp	210
2.513	PidNameOutlookProtectionRuleVersion	210
2.514	PidNamePageCount	210
2.515	PidNameParagraphCount	211
2.516	PidNamePath	211
2.517	PidNamePhishingStamp	211
2.518	PidNamePostingVersion	212
2.519	PidNamePresentationFormat	212
2.520	PidNamePriority	212
2.521	PidNameQuarantineOriginalSender	213
2.522	PidNameReceived	213
2.523	PidNameReferences	213
2.524	PidNameRelayVersion	214
2.525	PidNameReplyBy	214
2.526	PidNameReplyTo	214
2.527	PidNameReturnPath	215
2.528	PidNameReturnReceiptTo	215
2.529	PidNameRevisionNumber	215
2.530	PidNameRightsManagementLicense	216
2.531	PidNameRightsProtectMessage	216
2.532	PidNameScale	216
2.533	PidNameSecurity	217
2.534	PidNameSender	217
2.535	PidNameSensitivity	217
2.536	PidNameSlideCount	218
2.537	PidNameSubject	218
2.538	PidNameSummary	218
2.539	PidNameTemplate	219
2.540	PidNameThreadIndex	219
2.541	PidNameThreadTopic	219
2.542	PidNameThumbnail	220
2.543	PidNameTitle	220
2.544	PidNameTo	220
2.545	PidNameWordCount	221
2.546	PidNameXCallId	221
2.547	PidNameXFaxNumberOfPages	221
2.548	PidNameXMailer	222
2.549	PidNameXMessageCompleted	222
2.550	PidNameXMessageFlag	222
2.551	PidNameXRequireProtectedPlayOnPhone	223
2.552	PidNameXSenderTelephoneNumber	223
2.553	PidNameXSharingBrowseUrl	223
2.554	PidNameXSharingCapabilities	223
2.555	PidNameXSharingConfigUrl	224
2.556	PidNameXSharingExendedCaps	224
2.557	PidNameXSharingFlavor	224
2.558	PidNameXSharingInstanceId	225
2.559	PidNameXSharingLocalType	225
2.560	PidNameXSharingProviderGuid	225
2.561	PidNameXSharingProviderName	226

2.562	PidNameXSharingProviderUrl	226
2.563	PidNameXSharingRemoteName.....	226
2.564	PidNameXSharingRemotePath.....	226
2.565	PidNameXSharingRemoteStoreUid.....	227
2.566	PidNameXSharingRemoteType	227
2.567	PidNameXSharingRemoteUid	227
2.568	PidNameXUnifiedMessagingPartnerAssignedId.....	228
2.569	PidNameXUnifiedMessagingPartnerContent	228
2.570	PidNameXUnifiedMessagingPartnerContext	228
2.571	PidNameXUnifiedMessagingPartnerStatus	229
2.572	PidNameXUnsent.....	229
2.573	PidNameXVoiceMessageAttachmentOrder	229
2.574	PidNameXVoiceMessageDuration	230
2.575	PidNameXVoiceMessageSenderName	230
2.576	PidTagAccess	230
2.577	PidTagAccessControlListData	230
2.578	PidTagAccessLevel.....	231
2.579	PidTagAccount	231
2.580	PidTagAdditionalRenEntryIds	231
2.581	PidTagAdditionalRenEntryIdsEx	232
2.582	PidTagAddressBookAuthorizedSenders	232
2.583	PidTagAddressBookContainerId	232
2.584	PidTagAddressBookDeliveryContentLength	233
2.585	PidTagAddressBookDisplayNamePrintable.....	233
2.586	PidTagAddressBookDisplayTypeExtended	233
2.587	PidTagAddressBookDistributionListExternalMemberCount	234
2.588	PidTagAddressBookDistributionListMemberCount	234
2.589	PidTagAddressBookDistributionListMemberSubmitAccepted	234
2.590	PidTagAddressBookDistributionListMemberSubmitRejected	235
2.591	PidTagAddressBookDistributionListRejectMessagesFromDLMembers	235
2.592	PidTagAddressBookEntryId	235
2.593	PidTagAddressBookExtensionAttribute1.....	235
2.594	PidTagAddressBookExtensionAttribute15	236
2.595	PidTagAddressBookFolderPathname.....	236
2.596	PidTagAddressBookHierarchicalChildDepartments	236
2.597	PidTagAddressBookHierarchicalDepartmentMembers	237
2.598	PidTagAddressBookHierarchicalIsHierarchicalGroup	237
2.599	PidTagAddressBookHierarchicalParentDepartment	237
2.600	PidTagAddressBookHierarchicalRootDepartment	237
2.601	PidTagAddressBookHierarchicalShowInDepartments	238
2.602	PidTagAddressBookHomeMessageDatabase	238
2.603	PidTagAddressBookIsMaster	238
2.604	PidTagAddressBookIsMemberOfDistributionList	239
2.605	PidTagAddressBookManageDistributionList	239
2.606	PidTagAddressBookManager	239
2.607	PidTagAddressBookManagerDistinguishedName	240
2.608	PidTagAddressBookMember	240
2.609	PidTagAddressBookMessageId	240
2.610	PidTagAddressBookModerationEnabled.....	241
2.611	PidTagAddressBookNetworkAddress	241
2.612	PidTagAddressBookObjectDistinguishedName	241
2.613	PidTagAddressBookObjectGuid.....	241
2.614	PidTagAddressBookOrganizationalUnitRootDistinguishedName	242

2.615	PidTagAddressBookOwner	242
2.616	PidTagAddressBookOwnerBackLink	242
2.617	PidTagAddressBookParentEntryId	243
2.618	PidTagAddressBookPhoneticCompanyName	243
2.619	PidTagAddressBookPhoneticDepartmentName	243
2.620	PidTagAddressBookPhoneticDisplayName	244
2.621	PidTagAddressBookPhoneticGivenName	244
2.622	PidTagAddressBookPhoneticSurname	244
2.623	PidTagAddressBookProxyAddresses	245
2.624	PidTagAddressBookPublicDelegates	245
2.625	PidTagAddressBookReports	245
2.626	PidTagAddressBookRoomCapacity	246
2.627	PidTagAddressBookRoomContainers	246
2.628	PidTagAddressBookRoomDescription	246
2.629	PidTagAddressBookSenderHintTranslations	246
2.630	PidTagAddressBookSeniorityIndex	247
2.631	PidTagAddressBookTargetAddress	247
2.632	PidTagAddressBookUnauthorizedSenders	247
2.633	PidTagAddressBookX509Certificate	248
2.634	PidTagAddressType	248
2.635	PidTagAlternateRecipientAllowed	248
2.636	PidTagAnr	249
2.637	PidTagArchiveDate	249
2.638	PidTagArchivePeriod	249
2.639	PidTagArchiveTag	249
2.640	PidTagAssistant	250
2.641	PidTagAssistantTelephoneNumber	250
2.642	PidTagAssociated	250
2.643	PidTagAttachAdditionalInformation	251
2.644	PidTagAttachContentBase	251
2.645	PidTagAttachContentId	251
2.646	PidTagAttachContentLocation	252
2.647	PidTagAttachDataBinary	252
2.648	PidTagAttachDataObject	252
2.649	PidTagAttachEncoding	253
2.650	PidTagAttachExtension	253
2.651	PidTagAttachFilename	253
2.652	PidTagAttachFlags	254
2.653	PidTagAttachLongFilename	254
2.654	PidTagAttachLongPathname	254
2.655	PidTagAttachmentContactPhoto	255
2.656	PidTagAttachmentFlags	255
2.657	PidTagAttachmentHidden	255
2.658	PidTagAttachmentLinkId	256
2.659	PidTagAttachMethod	256
2.660	PidTagAttachMimeType	256
2.661	PidTagAttachNumber	257
2.662	PidTagAttachPathname	257
2.663	PidTagAttachPayloadClass	257
2.664	PidTagAttachPayloadProviderGuidString	258
2.665	PidTagAttachRendering	258
2.666	PidTagAttachSize	258
2.667	PidTagAttachTag	259

2.668	PidTagAttachTransportName.....	259
2.669	PidTagAttributeHidden	259
2.670	PidTagAttributeReadOnly.....	260
2.671	PidTagAutoForwarded	260
2.672	PidTagAutoForwardComment	260
2.673	PidTagAutoResponseSuppress.....	261
2.674	PidTagBirthday	261
2.675	PidTagBlockStatus.....	261
2.676	PidTagBody	261
2.677	PidTagBodyContentId	262
2.678	PidTagBodyContentLocation.....	262
2.679	PidTagBodyHtml.....	262
2.680	PidTagBusiness2TelephoneNumber.....	263
2.681	PidTagBusiness2TelephoneNumber.....	263
2.682	PidTagBusinessFaxNumber	263
2.683	PidTagBusinessHomePage	264
2.684	PidTagBusinessTelephoneNumber.....	264
2.685	PidTagCallbackTelephoneNumber	264
2.686	PidTagCallId	265
2.687	PidTagCarTelephoneNumber	265
2.688	PidTagCdoRecurrenceid.....	265
2.689	PidTagChangeKey.....	266
2.690	PidTagChangeNumber.....	266
2.691	PidTagChildrensNames.....	266
2.692	PidTagClientActions	267
2.693	PidTagClientSubmitTime	267
2.694	PidTagCodePageId.....	267
2.695	PidTagComment.....	268
2.696	PidTagCompanyMainTelephoneNumber	268
2.697	PidTagCompanyName	268
2.698	PidTagComputerNetworkName	269
2.699	PidTagConflictEntryId	269
2.700	PidTagConflictItems.....	269
2.701	PidTagContainerClass	269
2.702	PidTagContainerContents	270
2.703	PidTagContainerFlags.....	270
2.704	PidTagContainerHierarchy	271
2.705	PidTagContentCount	271
2.706	PidTagContentFilterPhishingConfidenceLevel	271
2.707	PidTagContentFilterSpamConfidenceLevel.....	271
2.708	PidTagContentUnreadCount	272
2.709	PidTagConversationId	272
2.710	PidTagConversationIndex	272
2.711	PidTagConversationIndexTracking	273
2.712	PidTagConversationTopic.....	273
2.713	PidTagCountry	273
2.714	PidTagCreationTime.....	274
2.715	PidTagCreatorEntryId	274
2.716	PidTagCreatorName.....	274
2.717	PidTagCustomerId	275
2.718	PidTagDamBackPatched	275
2.719	PidTagDamOriginalEntryId.....	275
2.720	PidTagDefaultPostMessageClass	276

2.721	PidTagDeferredActionMessageOriginalEntryId	276
2.722	PidTagDeferredDeliveryTime.....	276
2.723	PidTagDeferredSendNumber.....	276
2.724	PidTagDeferredSendTime	277
2.725	PidTagDeferredSendUnits	277
2.726	PidTagDelegatedByRule	277
2.727	PidTagDelegateFlags.....	278
2.728	PidTagDeleteAfterSubmit	278
2.729	PidTagDeletedOn.....	278
2.730	PidTagDepartmentName	279
2.731	PidTagDepth	279
2.732	PidTagDisplayBcc	279
2.733	PidTagDisplayCc.....	280
2.734	PidTagDisplayName	280
2.735	PidTagDisplayNamePrefix	280
2.736	PidTagDisplayTo.....	281
2.737	PidTagDisplayType	281
2.738	PidTagDisplayTypeEx	281
2.739	PidTagEmailAddress	282
2.740	PidTagEndDate	282
2.741	PidTagEntryId	282
2.742	PidTagExceptionEndTime.....	283
2.743	PidTagExceptionReplaceTime	283
2.744	PidTagExceptionStartTime	283
2.745	PidTagExchangeNTSecurityDescriptor	284
2.746	PidTagExpiryNumber	284
2.747	PidTagExpiryTime.....	284
2.748	PidTagExpiryUnits	285
2.749	PidTagExtendedFolderFlags	285
2.750	PidTagExtendedRuleMessageActions	285
2.751	PidTagExtendedRuleMessageCondition	286
2.752	PidTagExtendedRuleSizeLimit	286
2.753	PidTagFaxNumberOfPages	286
2.754	PidTagFlagCompleteTime	286
2.755	PidTagFlagStatus.....	287
2.756	PidTagFlatUrlName	287
2.757	PidTagFolderAssociatedContents	287
2.758	PidTagFolderId.....	288
2.759	PidTagFolderType	288
2.760	PidTagFollowupIcon	288
2.761	PidTagFreeBusyCountMonths	289
2.762	PidTagFreeBusyEntryIds.....	289
2.763	PidTagFreeBusyMessageEmailAddress.....	289
2.764	PidTagFreeBusyPublishEnd	290
2.765	PidTagFreeBusyPublishStart.....	290
2.766	PidTagFreeBusyRangeTimestamp	290
2.767	PidTagFtpSite	290
2.768	PidTagGatewayNeedsToRefresh.....	291
2.769	PidTagGender	291
2.770	PidTagGeneration	291
2.771	PidTagGivenName	292
2.772	PidTagGovernmentIdNumber	292
2.773	PidTagHasAttachments	292

2.774	PidTagHasDeferredActionMessages	293
2.775	PidTagHasNamedProperties	293
2.776	PidTagHasRules	293
2.777	PidTagHierarchyChangeNumber	294
2.778	PidTagHobbies	294
2.779	PidTagHome2TelephoneNumber	294
2.780	PidTagHome2TelephoneNumbers	294
2.781	PidTagHomeAddressCity	295
2.782	PidTagHomeAddressCountry	295
2.783	PidTagHomeAddressPostalCode	295
2.784	PidTagHomeAddressPostOfficeBox	296
2.785	PidTagHomeAddressStateOrProvince	296
2.786	PidTagHomeAddressStreet	296
2.787	PidTagHomeFaxNumber	297
2.788	PidTagHomeTelephoneNumber	297
2.789	PidTagHtml	297
2.790	PidTagICalendarEndTime	298
2.791	PidTagICalendarReminderNextTime	298
2.792	PidTagICalendarStartTime	298
2.793	PidTagIconIndex	299
2.794	PidTagImportance	299
2.795	PidTagInConflict	299
2.796	PidTagInitialDetailsPane	300
2.797	PidTagInitials	300
2.798	PidTagInReplyToId	300
2.799	PidTagInstanceKey	301
2.800	PidTagInstanceNum	301
2.801	PidTagInstID	301
2.802	PidTagInternetArticleNumber	302
2.803	PidTagInternetCodepage	302
2.804	PidTagInternetMailOverrideFormat	302
2.805	PidTagInternetMessageId	303
2.806	PidTagInternetReferences	303
2.807	PidTagIpmAppointmentEntryId	303
2.808	PidTagIpmContactEntryId	304
2.809	PidTagIpmDraftsEntryId	304
2.810	PidTagIpmJournalEntryId	304
2.811	PidTagIpmNoteEntryId	304
2.812	PidTagIpmTaskEntryId	305
2.813	PidTagIsdnNumber	305
2.814	PidTagJunkAddRecipientsToSafeSendersList	305
2.815	PidTagJunkIncludeContacts	306
2.816	PidTagJunkPermanentlyDelete	306
2.817	PidTagJunkPhishingEnableLinks	306
2.818	PidTagJunkThreshold	307
2.819	PidTagKeyword	307
2.820	PidTagLanguage	307
2.821	PidTagLastModificationTime	307
2.822	PidTagLastModifierEntryId	308
2.823	PidTagLastModifierName	308
2.824	PidTagLastVerbExecuted	308
2.825	PidTagLastVerbExecutionTime	309
2.826	PidTagListHelp	309

2.827	PidTagListSubscribe	309
2.828	PidTagListUnsubscribe	310
2.829	PidTagLocalCommitTime	310
2.830	PidTagLocaleId.....	310
2.831	PidTagLocality.....	311
2.832	PidTagLocation.....	311
2.833	PidTagMailboxOwnerEntryId	311
2.834	PidTagMailboxOwnerName	312
2.835	PidTagManagerName	312
2.836	PidTagMappingSignature	312
2.837	PidTagMaximumSubmitMessageSize	313
2.838	PidTagMemberId	313
2.839	PidTagMemberName	313
2.840	PidTagMemberRights	313
2.841	PidTagMessageAttachments.....	314
2.842	PidTagMessageCcMe	314
2.843	PidTagMessageClass	314
2.844	PidTagMessageCodepage	315
2.845	PidTagMessageDeliveryTime	315
2.846	PidTagMessageEditorFormat	316
2.847	PidTagMessageFlags	316
2.848	PidTagMessageHandlingSystemCommonName	316
2.849	PidTagMessageLocaleId.....	317
2.850	PidTagMessageRecipientMe.....	317
2.851	PidTagMessageRecipients	317
2.852	PidTagMessageSize.....	318
2.853	PidTagMessageSizeExtended.....	318
2.854	PidTagMessageStatus	318
2.855	PidTagMessageSubmissionId	319
2.856	PidTagMessageToMe	319
2.857	PidTagMid	319
2.858	PidTagMiddleName	320
2.859	PidTagMimeType.....	320
2.860	PidTagMobileTelephoneNumber.....	320
2.861	PidTagNativeBody	321
2.862	PidTagNextSendActt	321
2.863	PidTagNickname.....	321
2.864	PidTagNormalizedSubject	322
2.865	PidTagNormalMessageSize	322
2.866	PidTagObjectType	322
2.867	PidTagOfficeLocation.....	323
2.868	PidTagOfflineAddressBookContainerGuid	323
2.869	PidTagOfflineAddressBookDistinguishedName	323
2.870	PidTagOfflineAddressBookMessageClass	324
2.871	PidTagOfflineAddressBookName	324
2.872	PidTagOfflineAddressBookSequence.....	324
2.873	PidTagOfflineAddressBookTruncatedProperties	324
2.874	PidTagOrdinalMost.....	325
2.875	PidTagOrganizationalIdNumber	325
2.876	PidTagOriginalDeliveryTime	325
2.877	PidTagOriginalDisplayBcc	326
2.878	PidTagOriginalDisplayCc	326
2.879	PidTagOriginalDisplayTo	326

2.880	PidTagOriginalEntryId	327
2.881	PidTagOriginalMessageClass	327
2.882	PidTagOriginalMessageId.....	327
2.883	PidTagOriginalSenderAddressType.....	328
2.884	PidTagOriginalSenderEmailAddress	328
2.885	PidTagOriginalSenderEntryId	328
2.886	PidTagOriginalSenderName	328
2.887	PidTagOriginalSenderSearchKey.....	329
2.888	PidTagOriginalSensitivity	329
2.889	PidTagOriginalSentRepresentingAddressType	329
2.890	PidTagOriginalSentRepresentingEmailAddress	330
2.891	PidTagOriginalSentRepresentingEntryId	330
2.892	PidTagOriginalSentRepresentingName.....	330
2.893	PidTagOriginalSentRepresentingSearchKey	331
2.894	PidTagOriginalSubject	331
2.895	PidTagOriginalSubmitTime.....	331
2.896	PidTagOriginatorDeliveryReportRequested	332
2.897	PidTagOriginatorNonDeliveryReportRequested	332
2.898	PidTagOtherAddressCity	332
2.899	PidTagOtherAddressCountry	333
2.900	PidTagOtherAddressPostalCode	333
2.901	PidTagOtherAddressPostOfficeBox	333
2.902	PidTagOtherAddressStateOrProvince.....	334
2.903	PidTagOtherAddressStreet.....	334
2.904	PidTagOtherTelephoneNumber	334
2.905	PidTagOutOfOfficeState.....	335
2.906	PidTagOwnerAppointmentId	335
2.907	PidTagPagerTelephoneNumber	335
2.908	PidTagParentEntryId	336
2.909	PidTagParentFolderId.....	336
2.910	PidTagParentKey	336
2.911	PidTagParentSourceKey	336
2.912	PidTagPersonalHomePage.....	337
2.913	PidTagPolicyTag	337
2.914	PidTagPostalAddress	337
2.915	PidTagPostalCode	338
2.916	PidTagPostOfficeBox	338
2.917	PidTagPredecessorChangeList	338
2.918	PidTagPrimaryFaxNumber	339
2.919	PidTagPrimarySendAccount	339
2.920	PidTagPrimaryTelephoneNumber	339
2.921	PidTagPriority	340
2.922	PidTagProcessed	340
2.923	PidTagProfession	340
2.924	PidTagProhibitReceiveQuota	341
2.925	PidTagProhibitSendQuota	341
2.926	PidTagProviderSubmitTime	341
2.927	PidTagPublicFolderAdministrativeDescription.....	342
2.928	PidTagPublicFolderProxy	342
2.929	PidTagPurportedSenderDomain	342
2.930	PidTagRadioTelephoneNumber	342
2.931	PidTagRead	343
2.932	PidTagReadReceiptAddressType	343

2.933	PidTagReadReceiptEmailAddress	343
2.934	PidTagReadReceiptEntryId.....	344
2.935	PidTagReadReceiptName	344
2.936	PidTagReadReceiptRequested	344
2.937	PidTagReadReceiptSearchKey	345
2.938	PidTagReceivedByAddressType	345
2.939	PidTagReceivedByEmailAddress	345
2.940	PidTagReceivedByEntryId	346
2.941	PidTagReceivedByFlags	346
2.942	PidTagReceivedByName	346
2.943	PidTagReceivedBySearchKey	346
2.944	PidTagReceivedRepresentingAddressType.....	347
2.945	PidTagReceivedRepresentingEmailAddress.....	347
2.946	PidTagReceivedRepresentingEntryId	347
2.947	PidTagReceivedRepresentingFlags	348
2.948	PidTagReceivedRepresentingName	348
2.949	PidTagReceivedRepresentingSearchKey	348
2.950	PidTagRecipientDisplayName	349
2.951	PidTagRecipientEntryId	349
2.952	PidTagRecipientFlags	349
2.953	PidTagRecipientOrder.....	349
2.954	PidTagRecipientProposed.....	350
2.955	PidTagRecipientProposedEndTime.....	350
2.956	PidTagRecipientProposedStartTime.....	350
2.957	PidTagRecipientReassignmentProhibited	351
2.958	PidTagRecipientResourceState	351
2.959	PidTagRecipientTrackStatus	351
2.960	PidTagRecipientTrackStatusTime	352
2.961	PidTagRecipientType.....	352
2.962	PidTagRecordKey	352
2.963	PidTagReferredByName.....	353
2.964	PidTagRemindersOnlineEntryId	353
2.965	PidTagRemoteMessageTransferAgent	353
2.966	PidTagRenderingPosition	353
2.967	PidTagReplyRecipientEntries	354
2.968	PidTagReplyRecipientNames	354
2.969	PidTagReplyRequested	354
2.970	PidTagReplyTemplateId.....	355
2.971	PidTagReplyTime.....	355
2.972	PidTagReportEntryId.....	355
2.973	PidTagReportingMessageTransferAgent	356
2.974	PidTagReportName.....	356
2.975	PidTagReportSearchKey	356
2.976	PidTagReportTag	357
2.977	PidTagReportText	357
2.978	PidTagReportTime	357
2.979	PidTagResolveMethod	357
2.980	PidTagResponseRequested	358
2.981	PidTagResponsibility	358
2.982	PidTagRetentionDate	358
2.983	PidTagRetentionFlags.....	359
2.984	PidTagRetentionPeriod	359
2.985	PidTagRights.....	359

2.986	PidTagRoamingDatatypes.....	360
2.987	PidTagRoamingDictionary	360
2.988	PidTagRoamingXmlStream	360
2.989	PidTagRowid	360
2.990	PidTagRowType.....	361
2.991	PidTagRtfCompressed	361
2.992	PidTagRtfInSync.....	361
2.993	PidTagRuleActionNumber	362
2.994	PidTagRuleActions	362
2.995	PidTagRuleActionType	362
2.996	PidTagRuleCondition	362
2.997	PidTagRuleError	363
2.998	PidTagRuleFolderEntryId	363
2.999	PidTagRuleId	363
2.1000	PidTagRuleIds	364
2.1001	PidTagRuleLevel	364
2.1002	PidTagRuleMessageLevel	364
2.1003	PidTagRuleMessageName	365
2.1004	PidTagRuleMessageProvider	365
2.1005	PidTagRuleMessageProviderData	365
2.1006	PidTagRuleMessageSequence	365
2.1007	PidTagRuleMessageState	366
2.1008	PidTagRuleMessageUserFlags	366
2.1009	PidTagRuleName	366
2.1010	PidTagRuleProvider	367
2.1011	PidTagRuleProviderData	367
2.1012	PidTagRuleSequence	367
2.1013	PidTagRuleState	368
2.1014	PidTagRuleUserFlags	368
2.1015	PidTagRwRulesStream	368
2.1016	PidTagScheduleInfoAppointmentTombstone	369
2.1017	PidTagScheduleInfoAutoAcceptAppointments	369
2.1018	PidTagScheduleInfoDelegateEntryIds	369
2.1019	PidTagScheduleInfoDelegateNames	369
2.1020	PidTagScheduleInfoDelegateNamesW	370
2.1021	PidTagScheduleInfoDelegatorWantsCopy	370
2.1022	PidTagScheduleInfoDelegatorWantsInfo	370
2.1023	PidTagScheduleInfoDisallowOverlappingAppts	371
2.1024	PidTagScheduleInfoDisallowRecurringAppts	371
2.1025	PidTagScheduleInfoDontMailDelegates	371
2.1026	PidTagScheduleInfoFreeBusy	372
2.1027	PidTagScheduleInfoFreeBusyAway	372
2.1028	PidTagScheduleInfoFreeBusyBusy	372
2.1029	PidTagScheduleInfoFreeBusyMerged	372
2.1030	PidTagScheduleInfoFreeBusyTentative	373
2.1031	PidTagScheduleInfoMonthsAway	373
2.1032	PidTagScheduleInfoMonthsBusy	373
2.1033	PidTagScheduleInfoMonthsMerged	374
2.1034	PidTagScheduleInfoMonthsTentative	374
2.1035	PidTagScheduleInfoResourceType	374
2.1036	PidTagSchedulePlusFreeBusyEntryId	374
2.1037	PidTagScriptData	375
2.1038	PidTagSearchFolderDefinition	375

2.1039	PidTagSearchFolderEfpFlags.....	375
2.1040	PidTagSearchFolderExpiration	376
2.1041	PidTagSearchFolderId	376
2.1042	PidTagSearchFolderLastUsed.....	376
2.1043	PidTagSearchFolderRecreateInfo	376
2.1044	PidTagSearchFolderStorageType.....	377
2.1045	PidTagSearchFolderTag	377
2.1046	PidTagSearchFolderTemplateId	377
2.1047	PidTagSearchKey.....	378
2.1048	PidTagSecureSubmitFlags.....	378
2.1049	PidTagSecurityDescriptor.....	378
2.1050	PidTagSecurityDescriptorAsXml	379
2.1051	PidTagSelectable	379
2.1052	PidTagSenderAddressType.....	379
2.1053	PidTagSenderEmailAddress	380
2.1054	PidTagSenderEntryId	380
2.1055	PidTagSenderFlags	380
2.1056	PidTagSenderIdStatus	381
2.1057	PidTagSenderName	381
2.1058	PidTagSenderSearchKey	381
2.1059	PidTagSenderSmtpAddress	382
2.1060	PidTagSenderTelephoneNumber	382
2.1061	PidTagSendInternetEncoding	382
2.1062	PidTagSendRichInfo	383
2.1063	PidTagSensitivity	383
2.1064	PidTagSentMailSvrEID	383
2.1065	PidTagSentRepresentingAddressType	384
2.1066	PidTagSentRepresentingEmailAddress	384
2.1067	PidTagSentRepresentingEntryId	384
2.1068	PidTagSentRepresentingFlags	385
2.1069	PidTagSentRepresentingName	385
2.1070	PidTagSentRepresentingSearchKey	385
2.1071	PidTagSessionInitiationProtocolUri	386
2.1072	PidTagSmtpAddress	386
2.1073	PidTagSortLocaleId	386
2.1074	PidTagSourceKey	387
2.1075	PidTagSpokenName	387
2.1076	PidTagSpouseName	387
2.1077	PidTagStartDate	388
2.1078	PidTagStartDateEtc	388
2.1079	PidTagStateOrProvince	388
2.1080	PidTagStoreEntryId	389
2.1081	PidTagStoreState	389
2.1082	PidTagStoreSupportMask	389
2.1083	PidTagStreetAddress	389
2.1084	PidTagSubfolder	390
2.1085	PidTagSubfolders	390
2.1086	PidTagSubject	390
2.1087	PidTagSubjectPrefix	391
2.1088	PidTagSurname	391
2.1089	PidTagSwappedToDoData	391
2.1090	PidTagSwappedToDoStore	392
2.1091	PidTagTargetEntryId	392

2.1092	PidTagTelecommunicationsDeviceForDeafTelephoneNumber	392
2.1093	PidTagTelexNumber	393
2.1094	PidTagTemplateData	393
2.1095	PidTagTemplateid	393
2.1096	PidTagTemporaryDefaultDocument	394
2.1097	PidTagTextAttachmentCharset	394
2.1098	PidTagThumbnailPhoto	394
2.1099	PidTagTitle	395
2.1100	PidTagTnefCorrelationKey	395
2.1101	PidTagToDoItemFlags	395
2.1102	PidTagTransmittableDisplayName	396
2.1103	PidTagTransportMessageHeaders.....	396
2.1104	PidTagTrustSender	396
2.1105	PidTagUrlCompName	397
2.1106	PidTagUrlCompNameSet.....	397
2.1107	PidTagUrlName	397
2.1108	PidTagUserCertificate	397
2.1109	PidTagUserEntryId	398
2.1110	PidTagUserX509Certificate.....	398
2.1111	PidTagViewDescriptorBinary.....	398
2.1112	PidTagViewDescriptorName	399
2.1113	PidTagViewDescriptorStrings.....	399
2.1114	PidTagViewDescriptorVersion	399
2.1115	PidTagVoiceMessageAttachmentOrder	400
2.1116	PidTagVoiceMessageDuration	400
2.1117	PidTagVoiceMessageSenderName	400
2.1118	PidTagWeddingAnniversary	400
2.1119	PidTagWlinkAddressBookEID	401
2.1120	PidTagWlinkAddressBookStoreEID	401
2.1121	PidTagWlinkCalendarColor	401
2.1122	PidTagWlinkClientID.....	402
2.1123	PidTagWlinkEntryId	402
2.1124	PidTagWlinkFlags.....	402
2.1125	PidTagWlinkFolderType	402
2.1126	PidTagWlinkGroupCsid.....	403
2.1127	PidTagWlinkGroupHeaderID	403
2.1128	PidTagWlinkGroupName	403
2.1129	PidTagWlinkOrdinal.....	404
2.1130	PidTagWlinkRecordKey	404
2.1131	PidTagWlinkROGroupType	404
2.1132	PidTagWlinkSaveStamp	404
2.1133	PidTagWlinkSection	405
2.1134	PidTagWlinkStoreEntryId	405
2.1135	PidTagWlinkType	405
3	Structure Examples	407
4	Security Considerations.....	408
5	Appendix A: Product Behavior.....	409
6	Change Tracking.....	410
7	Index	422

1 Introduction

The Exchange Server Protocols Master Property List provides implementers with a single source of information about all of properties that are described by the specifications that comprise the Exchange Server Protocols documentation. If a property is not described by the specifications included in the Exchange Server Protocols documentation, it is not included in this document.

The criteria for including a property in the Exchange Server Protocols documentation are that it is set by a client in order to affect server behavior, or that it is set by a server in order to affect client behavior. Properties that are merely stored by the server on behalf of the client, or generated by the server for its own use and ignored by the client, are not necessarily documented. As a result, the properties that are included in the Exchange Server Protocols documentation, and therefore this document, are the critical **Message object** properties used for communication between clients and servers.

This document provides implementers with a convenient catalog of all of these critical properties, a source of navigation to the individual technical specifications that describe these properties in detail, and a resource for additional helpful property information that is unique to this document.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

8.3 name
ambiguous name resolution (ANR)
Augmented Backus-Naur Form (ABNF)
class
common name (CN)
Coordinated Universal Time (UTC)
cyclic redundancy check (CRC)
distinguished name (DN)
domain
flags
GUID
Hypertext Transfer Protocol (HTTP)
name service provider interface (NSPI)
property set
resource
Transmission Control Protocol (TCP)
Unicode
XML

The following terms are defined in [\[MS-OXGLOS\]](#):

address book container
Address Book object
address list
address type
alias
Appointment object
Attachment object
base64 encoding
blind carbon copy (Bcc) recipient
body part
calendar

Calendar folder
Calendar object
carbon copy (Cc) recipient
contents table
conversation
conversation action
counter proposal
Deferred Action Message (DAM)
delivery receipt
departmental group
display name
display template
distribution list
double-byte character set (DBCS)
E-mail object
EntryID
Exception Embedded Message object
Exception object
File Transfer Protocol (FTP)
folder associated information (FAI)
Folder object
free/busy status
Global Address List (GAL)
group header
Hypertext Markup Language (HTML)
instance
Integrated Services Digital Network (ISDN)
Journal object
locale
Logon object
long ID (LID)
mail tip
mail user
mailbox
meeting
Meeting object
meeting request
Meeting Request object
Meeting Response object
Meeting Update object
Meeting Workspace
meeting-related object
message body
message class
Message object
Messaging Application Programming Interface (MAPI)
messaging object
Multipurpose Internet Mail Extensions (MIME)
named property
navigation shortcut
Network News Transfer Protocol (NNTP)
non-Unicode
Note object
offline address book (OAB)
optional attendee

organizer
orphan instance
Out of Office (OOF)
Outbox folder
Permanent Entry ID
permission
phishing
plain text
primary recipient
property ID
property name
property type
public folder
read receipt
recipient
recurrence pattern
Recurring Calendar object
recurring series
recurring task
reminder
Resource object
retention tag
Rich Text Format (RTF)
rights-managed e-mail message
Root folder
ROP buffer
Sent Items folder
Server object
Short Message Service (SMS)
signal time
Simple Mail Transfer Protocol (SMTP)
soft delete
spam
spam filter
special folder
store
tagged property
Task object
task request
Transport Neutral Encapsulation Format (TNEF)
Uniform Resource Identifier (URI)
Uniform Resource Locator (URL)
unsendable attendee
Use License
Web Distributed Authoring and Versioning Protocol (WebDAV)
WebDAV client
X500 DN

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[ISO/IEC8802-3] ISO/IEC, "Information technology -- Telecommunications and information exchange between systems -- Local and metropolitan area networks -- Specific requirements -- Part 3", Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications, ISO/IEC 8802-3:2000,
http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=31002

[MS-NSPI] Microsoft Corporation, "[Name Service Provider Interface \(NSPI\) Protocol Specification](#)".

[MS-OXABREF] Microsoft Corporation, "[Address Book Name Service Provider Interface \(NSPI\) Referral Protocol Specification](#)".

[MS-OXBBODY] Microsoft Corporation, "[Best Body Retrieval Algorithm](#)".

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".

[MS-OXCFOLD] Microsoft Corporation, "[Folder Object Protocol Specification](#)".

[MS-OXCFXICS] Microsoft Corporation, "[Bulk Data Transfer Protocol Specification](#)".

[MS-OXCICAL] Microsoft Corporation, "[iCalendar to Appointment Object Conversion Algorithm](#)".

[MS-OXCMAIL] Microsoft Corporation, "[RFC2822 and MIME to E-Mail Object Conversion Algorithm](#)".

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)".

[MS-OXCPERM] Microsoft Corporation, "[Exchange Access and Operation Permissions Protocol Specification](#)".

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol Specification](#)".

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol Specification](#)".

[MS-OXCRPC] Microsoft Corporation, "[Wire Format Protocol Specification](#)".

[MS-OXCSPAM] Microsoft Corporation, "[Spam Confidence Level Protocol Specification](#)".

[MS-OXCSTOR] Microsoft Corporation, "[Store Object Protocol Specification](#)".

[MS-OXCSYNC] Microsoft Corporation, "[Mailbox Synchronization Protocol Specification](#)".

[MS-OXCTABL] Microsoft Corporation, "[Table Object Protocol Specification](#)".

[MS-OXLDAP] Microsoft Corporation, "[Lightweight Directory Access Protocol \(LDAP\) Version 3 Extensions](#)".

[MS-OXMSG] Microsoft Corporation, "[Outlook Item \(.msg\) File Format](#)".

- [MS-OXOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) File Format and Schema](#)".
- [MS-OXOABK] Microsoft Corporation, "[Address Book Object Protocol Specification](#)".
- [MS-OXOABKT] Microsoft Corporation, "[Address Book User Interface Templates Protocol Specification](#)".
- [MS-OXOCAL] Microsoft Corporation, "[Appointment and Meeting Object Protocol Specification](#)".
- [MS-OXOCFG] Microsoft Corporation, "[Configuration Information Protocol Specification](#)".
- [MS-OXOCNTC] Microsoft Corporation, "[Contact Object Protocol Specification](#)".
- [MS-OXODLGT] Microsoft Corporation, "[Delegate Access Configuration Protocol Specification](#)".
- [MS-OXODOC] Microsoft Corporation, "[Document Object Protocol Specification](#)".
- [MS-OXOFLAG] Microsoft Corporation, "[Informational Flagging Protocol Specification](#)".
- [MS-OXOJRNL] Microsoft Corporation, "[Journal Object Protocol Specification](#)".
- [MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)".
- [MS-OXONOTE] Microsoft Corporation, "[Note Object Protocol Specification](#)".
- [MS-OXOPFFB] Microsoft Corporation, "[Public Folder-Based Free/Busy Protocol Specification](#)".
- [MS-OXOPOST] Microsoft Corporation, "[Post Object Protocol Specification](#)".
- [MS-OXORMDR] Microsoft Corporation, "[Reminder Settings Protocol Specification](#)".
- [MS-OXORMMS] Microsoft Corporation, "[Rights-Managed E-Mail Object Protocol Specification](#)".
- [MS-OXORSS] Microsoft Corporation, "[RSS Object Protocol Specification](#)".
- [MS-OXORULE] Microsoft Corporation, "[E-Mail Rules Protocol Specification](#)".
- [MS-OXOSFLD] Microsoft Corporation, "[Special Folders Protocol Specification](#)".
- [MS-OXOSMIME] Microsoft Corporation, "[S/MIME E-Mail Object Algorithm](#)".
- [MS-OXOSMMS] Microsoft Corporation, "[Short Message Service \(SMS\) and Multimedia Messaging Service \(MMS\) Object Protocol Specification](#)".
- [MS-OXOSRCH] Microsoft Corporation, "[Search Folder List Configuration Protocol Specification](#)".
- [MS-OXOTASK] Microsoft Corporation, "[Task-Related Objects Protocol Specification](#)".
- [MS-OXOUUM] Microsoft Corporation, "[Voice Mail and Fax Objects Protocol Specification](#)".
- [MS-OXPFOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) Public Folder Retrieval Protocol Specification](#)".
- [MS-OXPHISH] Microsoft Corporation, "[Phishing Warning Protocol Specification](#)".
- [MS-OXPSVAL] Microsoft Corporation, "[E-Mail Postmark Validation Algorithm](#)".
- [MS-OXRTFCP] Microsoft Corporation, "[Rich Text Format \(RTF\) Compression Algorithm](#)".
- [MS-OXRTFEX] Microsoft Corporation, "[Rich Text Format \(RTF\) Extensions Algorithm](#)".

- [MS-OXSHARE] Microsoft Corporation, "[Sharing Message Object Protocol Specification](#)".
- [MS-OXTNEF] Microsoft Corporation, "[Transport Neutral Encapsulation Format \(TNEF\) Data Algorithm](#)".
- [MS-OXVCARD] Microsoft Corporation, "[vCard to Contact Object Conversion Algorithm](#)".
- [MS-OXWAVLS] Microsoft Corporation, "[Availability Web Service Protocol Specification](#)".
- [MS-WMF] Microsoft Corporation, "[Windows Metafile Format](#)".
- [MS-XWDCAL] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Calendar Support](#)".
- [MS-XWDCNTC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Contacts Support](#)".
- [MS-XWDDOC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Documents Support](#)".
- [MS-XWDEXT] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Core Extensions](#)".
- [MS-XWDFOLD] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Folders Support](#)".
- [MS-XWDMAIL] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for E-Mail Support](#)".
- [MS-XWDSEARCH] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Search](#)".
- [MS-XWDSTRUCTDOC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Structured Documents](#)".
- [MS-XDVSEC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Protocol Security Descriptor Extensions](#)".
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

1.2.2 Informative References

- [MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".
- [MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".
- [MS-OXNSPI] Microsoft Corporation, "[Exchange Server Name Service Provider Interface \(NSPI\) Protocol Specification](#)".
- [MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".
- [RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

1.3 Overview

Each property listing in this document contains a link to the section of the technical specification in the Exchange Server Protocols documentation that acts as the defining reference for the property. The defining reference for each property contains the semantic use and definition of the property, including the property data type. The property information that is included in the defining reference for each property is required to successfully parse property data. As such, this document provides implementers with a single source of navigation to all of the critical property information that is included in the individual Exchange Server Protocols technical specifications.

This document also provides additional information about each property that is helpful to the implementer, such as the functional area where the property is used, a list of all the technical specifications that cite the property, and a list of alternate names by which the canonical property is known within the system. This information is not included in the technical specifications that describe each property, and is unique to this document. It is provided for informational purposes only.

A typical scenario for using this document is when an implementer encounters both **property IDs** and property values with no other identification coming across the wire. The property data type and the semantic definition of the property that are included in the defining reference for each property allow the implementer to correctly parse property values that show up in **ROP buffers**. The parsed values in the ROP buffers include lists of property IDs, which are typically lists of four hexadecimal characters. By searching the information in this document for those four hexadecimal characters, the implementer can quickly name the associated property and navigate to the definition of the individual property in its defining specification.

The following information is provided for each property, as appropriate.

Alternate names: Alternate names are implementation-specific names for properties that are used in source code and non-protocol-related documentation. Information about alternate names is useful when the implementer needs to refer to legacy documentation about a specific canonical property.

Area: The functional area where the property is used. Sections [1.3.1](#), [1.3.2](#), and [1.3.3](#) describe the general functional areas where properties are used. The listing for each property in section [2](#) describes the areas with more varied descriptions so as to provide more insight into property usage.

Canonical name: The name used to refer to the property in the Exchange Server Protocols documentation. The prefix of the canonical name identifies the basic characteristics of a property to the implementer.

The canonical naming structure uses three categories that are denoted by the following prefixes to the canonical property name:

- PidLid prefix: Properties identified by an unsigned 32-bit quantity along with a property set.
- PidName prefix: Properties identified by a string name along with a property set.
- PidTag prefix: Properties identified by an unsigned 16-bit quantity.

Description: A brief description of the contents of the property.

Data type: The property value type, as described in [\[MS-OXCDATA\]](#), that specifies the type of values allowed for the property.

Property ID: An unsigned 16-bit quantity that identifies a **tagged property**. Property IDs are not necessarily unique. With the exception of property IDs in the range from 0x6800 to 0x7BFF (see

section [1.3.3](#)), the combination of property ID and data type are unique. Property IDs in the range from 0x6800 to 0x7BFF are defined by the message class.

Property long ID (LID): An unsigned 32-bit quantity that, along with the **property set**, identifies a **named property**.

Property name: A string that, along with the property set, identifies a named property.

Property set: A **GUID** that identifies a group of properties with a similar purpose.

Defining references: One or more technical specifications that describe the semantics and allowed values for the property.

Consuming references: One or more technical specifications that refer to the property but do not describe semantics and allowed values.

1.3.1 Common Message Classes

Applications set certain required properties corresponding to the object's **message class**. The following table describes several common message classes, the functional area to which each one corresponds, and the specification that describes each one's required and optional properties.

In the following table, an asterisk "*" denotes that any string can appear at that point.

Area name	PidTagMessageClass property values	Specification
Common	IPM.*	[MS-OXCMMSG]
E-mail	IPM.Note, REPORT.*	[MS-OXCMMSG]
Calendar	IPM.Appointment, IPM.Schedule.Meeting.Request, IPM.Schedule.Meeting.Resp.*, IPM.Schedule.Meeting.Canceled, IPM.Schedule.Meeting.Notification	[MS-OXOCAL]
Contact	IPM.Contact, IPM.DistList	[MS-OXOCNTC]
Task	IPM.Task, IPM.TaskRequest.*	[MS-OXOTASK]
Journal	IPM.Activity	[MS-OXOJRNL]
Sticky Note	IPM.StickyNote	[MS-OXONOTE]
Document	IPM.Document.*	[MS-OXODOC]
Post	IPM.Post	[MS-OXOPOST]
RSS Feed	IPM.Post.RSS	[MS-OXORSS]
Rights-managed E-mail	IPM.Note with PidNameContentClass= rpmsg.message	[MS-OXORMMS]

Area name	PidTagMessageClass property values	Specification
S/MIME E-mail	IPM.Note.SMIME, IPM.Note.SMIME.MultipartSigned	[MS-OXOSMIME]
Short Message Service (SMS) / Multimedia Message Service (MMS) Message	IPM.Note.Mobile.SMS, IPM.Note.Mobile.MMS	[MS-OXOSMMS]
Unified Messaging	IPM.Note.Microsoft.Voicemail, IPM.Note.Microsoft.Fax	[MS-OXOUM]
Sharing	IPM.Sharing IPM.Sharing.*	[MS-OXSHARE]

1.3.2 Commonly Used Property Sets

In the property list that forms the main body of this document (section 2), each named property is listed with the GUID that describes its property set. Several of the more common property sets and their functional areas are described in the following table.

Area name	Property set name and GUID value
Common	PS_PUBLIC_STRINGS {00020329-0000-0000-C000-00000000046}
Common	PSETID_Common {00062008-0000-0000-C000-00000000046}
Contact	PSETID_Address {00062004-0000-0000-C000-00000000046}
E-mail	PS_INTERNET_HEADERS {00020386-0000-0000-C000-00000000046}
Calendar	PSETID_Appointment {00062002-0000-0000-C000-00000000046}
Calendar	PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}
Journal	PSETID_Log {0006200A-0000-0000-C000-00000000046}
Messaging	PSETID_Messaging {41F28F13-83F4-4114-A584-EEDB5A6B0BFF}
Sticky note	PSETID_Note {0006200E-0000-0000-C000-00000000046}
RSS feed	PSETID_PostRss {00062041-0000-0000-C000-00000000046}
Task	PSETID_Task {00062003-0000-0000-C000-00000000046}

Area name	Property set name and GUID value
Unified messaging	PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}
Common	PS_MAPI {00020328-0000-0000-C000-000000000046}
Sync	PSETID_AirSync {71035549-0739-4DCB-9163-00F0580DBBDF}
Sharing	PSETID_Sharing {00062040-0000-0000-C000-000000000046}

1.3.3 Property ID Ranges

The 65,536 possible values of the property ID are divided into sub-ranges reserved for various purposes, as described in the following table.

In this context, the term "non-transmittable" refers specifically to transmission via an e-mail transport protocol (such as **SMTP**), and not to any network transport protocol (such as **TCP**):

- Servers do not allow property IDs in ranges specified as non-transmittable to be submitted for transport to another server via an e-mail transport protocol. Property IDs in ranges not specified as non-transmittable are submitted for transport to another server.
- Clients can use properties in ranges described as message class-defined for application-defined purposes. When doing so, applications specify a value for the **PidTagMessageClass** property (section [2.843](#)) that is distinct from any value listed in section [1.3.1](#).
- Clients can use any named property for application-defined purposes. No constraint is placed on the value of the **PidTagMessageClass** property in this case, but the named property's property set is distinct from any value listed in section [1.3.2](#). Note that named properties are always transmittable.
- Clients can use properties in ranges specified as transport-defined, but they cannot define new properties in those ranges.
- Clients can use and define properties in ranges specified as user-defined, but need to avoid conflicts with alternate definitions of the same property ID.

Range minimum	Range maximum	Description
0x0001	0x0BFF	Message object envelope property; reserved
0x0C00	0x0DFF	Recipient property; reserved
0x0E00	0x0FFF	Non-transmittable Message property; reserved
0x1000	0x2FFF	Message content property; reserved
0x3000	0x33FF	Multi-purpose property that can appear on all or most objects; reserved
0x3400	0x35FF	Message store property; reserved

Range minimum	Range maximum	Description
0x3600	0x36FF	Folder and address book container property; reserved
0x3700	0x38FF	Attachment property; reserved
0x3900	0x39FF	Address Book object property; reserved
0x3A00	0x3BFF	Mail user object property; reserved
0x3C00	0x3cff	Distribution list property; reserved
0x3D00	0x3dff	Profile section property; reserved
0x3E00	0x3eff	Status object property; reserved
0x4000	0x57FF	Transport-defined envelope property
0x5800	0x5FFF	Transport-defined recipient property
0x6000	0x65FF	User-defined non-transmittable property
0x6600	0x67FF	Provider-defined internal non-transmittable property
0x6800	0x7BFF	Message class-defined content property
0x7C00	0x7FFF	Message class-defined non-transmittable property
0x8000	0xFFFF	Reserved for mapping to named properties. For more information about the static mapping of NSPI property names to property IDs that occurs in this ID range, see [MS-OXNSPI] .

1.3.4 WebDAV Property Naming

The e-mail server is natively a **Messaging Application Programming Interface (MAPI)** store where the vast majority of properties in it are MAPI properties. The **WebDAV** implementation uses the **Augmented Backus-Naur Form (ABNF)** notation, as described in [\[RFC5234\]](#), as a way to name MAPI properties, allowing **WebDAV clients** to work with these properties directly.

The `http://schemas.microsoft.com/mapi/` namespace is used to directly access MAPI properties on the server. The namespace consists of three sub namespaces: proptag, id, and string. The ABNF notation used to specify the format of these namespaces is described in this section.

1.3.4.1 `http://schemas.microsoft.com/mapi/proptag` Namespace

The `http://schemas.microsoft.com/mapi/proptag` namespace is used to access properties on the server that are identified by a property ID. The implementer can access these properties through WebDAV by appending the hexadecimal property ID value and the hexadecimal **property type** value to the namespace prefix.

```
proptag-specifier = "http://schemas.microsoft.com/mapi/proptag/x" property-id property-type
property-id = 4HEXDIG
property-type = 4HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/proptag/x0037001f (PidTagSubject)
```

1.3.4.2 http://schemas.microsoft.com/mapi/id Namespace

The http://schemas.microsoft.com/mapi/id namespace is used to access named properties on the server that are identified by a property **long ID (LID)**. The implementer can access these properties through WebDAV by appending the property set and the hexadecimal property long ID (LID) value to the namespace prefix.

```
id-specifier = "http://schemas.microsoft.com/mapi/id/" property-set "/x" property-long-id  
property-set = "{" 8HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 12HEXDIG "}"  
property-long-id = 8HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/id/{00062002-0000-0000-C000-000000000046}/x00008213  
(PidLidAppointmentDuration)
```

1.3.4.3 http://schemas.microsoft.com/mapi/string Namespace

The http://schemas.microsoft.com/mapi/string namespace is used to access named properties on the server that are identified by a property name. The implementer can access these properties through WebDAV by appending the property set and the property name to the namespace prefix.

```
string-specifier = "http://schemas.microsoft.com/mapi/string/" property-set "/" property-name  
property-set = "{" 8*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 12*HEXDIG "}"  
property-name = 1*CHAR
```

Example:

```
http://schemas.microsoft.com/mapi/string/{00020329-0000-0000-C000-000000000046}/Subject  
(PidNameSubject)
```

1.4 Relationship to Protocols and Other Structures

This document relies on property data type and error code definitions in [MS-OXCDATA]. For tables and examples that describe property data types, and property and other error codes, see [MS-OXCDATA].

The list of properties and their descriptions included in this document provide context for many of the data structures described in [MS-OXCDATA].

The description of each property contained in this document relies on the technical specification that is cited as its defining reference.

1.5 Applicability Statement

This document provides numeric values used to encode property names, tags, and data types in ROP buffers. It also serves as a convenient index to the object type documents that define how each property is used.

1.6 Versioning and Localization

None.

1.7 Vendor-Extensible Fields

Property ID ranges, as described in section [1.3.3](#), describe how applications choose properties to create new message object types or to add functionality to existing types.

2 Structures

2.1 PidLidAddressBookProviderArrayType

Canonical name: PidLidAddressBookProviderArrayType

Description: Specifies the state of the contact's electronic addresses and represents a set of bit flags.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008029

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.12

Alternate names: dispidABPArrayType

2.2 PidLidAddressBookProviderEmailList

Canonical name: PidLidAddressBookProviderEmailList

Description: Specifies which electronic address properties are set on the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008028

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.11

Alternate names: dispidABPEmailList

2.3 PidLidAddressCountryCode

Canonical name: PidLidAddressCountryCode

Description: Specifies the country code portion of the contact's mailing address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DD

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

Alternate names: dispidAddressCountryCode

2.4 PidLidAgingDontAgeMe

Canonical name: PidLidAgingDontAgeMe

Description: Specifies whether to automatically archive the message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000850E

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.33

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRNLL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMSS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: dispidAgingDontAgeMe

2.5 PidLidAllAttendeesString

Canonical name: PidLidAllAttendeesString

Description: Specifies a list of all the attendees except for the **organizer**, including **resources** and **unsendable attendees**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008238

WebDAV: http://schemas.microsoft.com/mapi/allattendeesstring

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.16

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidAllAttendeesString

2.6 PidLidAllowExternalCheck

Canonical name: PidLidAllowExternalCheck

Description: This property is set to TRUE.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008246

Data type: PtypBoolean, 0x000B

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.5

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidAllowExternCheck

2.7 PidLidAnniversaryEventEntryId

Canonical name: PidLidAnniversaryEventEntryId

Description: Specifies the **EntryID** of the **Appointment object** that represents a contact's anniversary.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804E

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.5.6

Alternate names: dispidAnniversaryEventEID

2.8 PidLidAppointmentAuxiliaryFlags

Canonical name: PidLidAppointmentAuxiliaryFlags

Description: Specifies a bit field that describes the auxiliary state of the object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008207

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.3

Alternate names: dispidApptAuxFlags

2.9 PidLidAppointmentColor

Canonical name: PidLidAppointmentColor

Description: Specifies the color to be used when displaying the **Calendar object**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008214

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining reference:

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: dispidApptColor

2.10 PidLidAppointmentCounterProposal

Canonical name: PidLidAppointmentCounterProposal

Description: Indicates whether a **Meeting Response object** is a **counter proposal**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008257

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.7

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptCounterProposal

2.11 PidLidAppointmentDuration

Canonical name: PidLidAppointmentDuration

Description: Specifies the length of the event, in minutes.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008213

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/apptduration

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.7

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptDuration

2.12 PidLidAppointmentEndDate

Canonical name: PidLidAppointmentEndDate

Description: Indicates the date that the appointment ends.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008211

WebDAV: http://schemas.microsoft.com/mapi/apptenddate

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.3

Alternate names: dispidApptEndDate

2.13 PidLidAppointmentEndTime

Canonical name: PidLidAppointmentEndTime

Description: Indicates the time that the appointment ends.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008210

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptendtime

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.4

Alternate names: dispidApptEndTime

2.14 PidLidAppointmentEndWhole

Canonical name: PidLidAppointmentEndWhole

Description: Specifies the end date and time for the event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820E

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptendwhole

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.6

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptEndWhole

2.15 PidLidAppointmentLastSequence

Canonical name: PidLidAppointmentLastSequence

Description: Indicates to the organizer the last sequence number that was sent to any attendee.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008203

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.2

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptLastSequence

2.16 PidLidAppointmentMessageClass

Canonical name: PidLidAppointmentMessageClass

Description: Indicates the message class of the **Meeting object** to be generated from the **Meeting Request object**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000024

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.6

Alternate names: dispidApptMessageClass

2.17 PidLidAppointmentNotAllowPropose

Canonical name: PidLidAppointmentNotAllowPropose

Description: Indicates whether attendees are not allowed to propose a new date and/or time for the **meeting**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825A

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.26

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptNotAllowPropose

2.18 PidLidAppointmentProposalNumber

Canonical name: PidLidAppointmentProposalNumber

Description: Specifies the number of attendees who have sent counter proposals that have not been accepted or rejected by the organizer.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008259

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.6

Alternate names: dispidApptProposalNum

2.19 PidLidAppointmentProposedDuration

Canonical name: PidLidAppointmentProposedDuration

Description: Indicates the proposed value for the **PidLidAppointmentDuration** property (section [2.11](#)) for a counter proposal.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008256

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.7.5

Alternate names: dispidApptProposedDuration

2.20 PidLidAppointmentProposedEndWhole

Canonical name: PidLidAppointmentProposedEndWhole

Description: Specifies the proposed value for the **PidLidAppointmentEndWhole** property (section [2.14](#)) for a counter proposal.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008251

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.7.4

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptProposedEndWhole

2.21 PidLidAppointmentProposedStartWhole

Canonical name: PidLidAppointmentProposedStartWhole

Description: Specifies the proposed value for the **PidLidAppointmentStartWhole** property (section [2.29](#)) for a counter proposal.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008250

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.7.3

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptProposedStartWhole

2.22 PidLidAppointmentRecur

Canonical name: PidLidAppointmentRecur

Description: Specifies the dates and times when a **recurring series** occurs.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008216

Data type: PtypBinary, 0x0102

WebDAV: http://schemas.microsoft.com/mapi/apptrecur

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.44

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptRecur

2.23 PidLidAppointmentReplyName

Canonical name: PidLidAppointmentReplyName

Description: Specifies the user who last replied to the **meeting request** or meeting update.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008230

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/apptreplyname

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.5

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidApptReplyName, http://schemas.microsoft.com/mapi/apptreplyname

2.24 PidLidAppointmentReplyTime

Canonical name: PidLidAppointmentReplyTime

Description: Specifies the date and time at which the attendee responded to a received meeting request or **Meeting Update object**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008220

Data type: PtypTime, 0x0040

WebDAV: urn:schemas:calendar:replytime, http://schemas.microsoft.com/mapi/apptreplytime

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.3

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidApptReplyTime

2.25 PidLidAppointmentSequence

Canonical name: PidLidAppointmentSequence

Description: Specifies the sequence number of a Meeting object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008201

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/apptsequence

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.1

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptSequence

2.26 PidLidAppointmentSequenceTime

Canonical name: PidLidAppointmentSequenceTime

Description: Indicates the date and time at which the **PidLidAppointmentSequence** property (section [2.25](#)) was last modified.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008202

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.1

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptSeqTime

2.27 PidLidAppointmentStartDate

Canonical name: PidLidAppointmentStartDate

Description: Identifies the date that the appointment starts.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008212

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptstartdate

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.10

Alternate names: dispidApptStartDate

2.28 PidLidAppointmentStartTime

Canonical name: PidLidAppointmentStartTime

Description: Identifies the time that the appointment starts.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820F

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptstarttime

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.11

Alternate names: dispidApptStartTime

2.29 PidLidAppointmentStartWhole

Canonical name: PidLidAppointmentStartWhole

Description: Specifies the start date and time of the appointment.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820D

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptstartwhole

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.5

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptStartWhole

2.30 PidLidAppointmentStateFlags

Canonical name: PidLidAppointmentStateFlags

Description: Specifies a bit field that describes the state of the object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008217

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/apptstateflags

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.10

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptStateFlags

2.31 PidLidAppointmentSubType

Canonical name: PidLidAppointmentSubType

Description: Specifies whether the event is an all-day event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008215

Data type: PtypBoolean, 0x000B

WebDAV: urn:schemas:calendar:alldayevent, http://schemas.microsoft.com/mapi/apptsubtype

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.9

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidApptSubType

2.32 PidLidAppointmentTimeZoneDefinitionEndDisplay

Canonical name: PidLidAppointmentTimeZoneDefinitionEndDisplay

Description: Specifies time zone information that indicates the time zone of the **PidLidAppointmentEndWhole** property (section [2.14](#)).

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825F

Data type: PtypBinary, 0x0102

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.43

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptTZDefEndDisplay

2.33 PidLidAppointmentTimeZoneDefinitionRecur

Canonical name: PidLidAppointmentTimeZoneDefinitionRecur

Description: Specifies time zone information that describes how to convert the meeting date and time on a recurring series to and from **UTC**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008260

Data type: **PtypBinary**, 0x0102

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.41

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#)

Alternate names: dispidApptTZDefRecur

2.34 PidLidAppointmentTimeZoneDefinitionStartDisplay

Canonical name: PidLidAppointmentTimeZoneDefinitionStartDisplay

Description: Specifies time zone information that indicates the time zone of the **PidLidAppointmentStartWhole** property (section [2.29](#)).

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825E

Data type: **PtypBinary**, 0x0102

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.42

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptTZDefStartDisplay

2.35 PidLidAppointmentUnsendableRecipients

Canonical name: PidLidAppointmentUnsendableRecipients

Description: Contains a list of unsendable attendees.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825D

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.25

Alternate names: dispidApptUnsendableRecips

2.36 PidLidAppointmentUpdateTime

Canonical name: PidLidAppointmentUpdateTime

Description: Indicates the time at which the appointment was last updated.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008226

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptupdatetime

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.15

Alternate names: dispidApptUpdateTime

2.37 PidLidAttendeeCriticalChange

Canonical name: PidLidAttendeeCriticalChange

Description: Specifies the date and time at which the **meeting-related object** was sent.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000001

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/attendee_critical_change

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.5.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: LID_ATTENDEE_CRITICAL_CHANGE

2.38 PidLidAutoFillLocation

Canonical name: PidLidAutoFillLocation

Description: Indicates whether the value of the **PidLidLocation** property (section [2.153](#)) is set to the **PidTagDisplayName** property (section [2.734](#)).

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823A

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.8

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidAutoFillLocation

2.39 PidLidAutoLog

Canonical name: PidLidAutoLog

Description: Specifies to the application whether to create a **Journal object** for each action associated with this Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008025

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.19

Alternate names: dispidAutoLog

2.40 PidLidAutoProcessState

Canonical name: PidLidAutoProcessState

Description: Specifies the options used in the automatic processing of e-mail messages.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851A

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.64

Alternate names: dispidSniffState

2.41 PidLidAutoStartCheck

Canonical name: PidLidAutoStartCheck

Description: Specifies whether to automatically start the conferencing application when a reminder for the start of a meeting is executed.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008244

Data type: PtypBoolean, 0x000B

Area: Conferencing

Defining reference:

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidAutoStartCheck

2.42 PidLidBilling

Canonical name: PidLidBilling

Description: Specifies billing information for the contact.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008535

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:billinginformation

Area: General Message Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.24

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXTI\]](#)

Alternate names: dispidBilling

2.43 PidLidBirthdayEventEntryId

Canonical name: PidLidBirthdayEventEntryId

Description: Specifies the EntryId of an optional Appointment object that represents the contact's birthday.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804D

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.5.3

Alternate names: dispidBirthdayEventEID

2.44 PidLidBirthdayLocal

Canonical name: PidLidBirthdayLocal

Description: Specifies the birthday of a contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DE

Data type: PtypTime, 0x0040

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.5.2

Alternate names: dispidApptBirthdayLocal

2.45 PidLidBusinessCardCardPicture

Canonical name: PidLidBusinessCardCardPicture

Description: Contains the image to be used on a business card.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008041

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.7.2

Alternate names: dispidBCCardPicture

2.46 PidLidBusinessCardDisplayDefinition

Canonical name: PidLidBusinessCardDisplayDefinition

Description: Contains user customization details for displaying a contact as a business card.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008040

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.7.1

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidBCDisplayDefinition

2.47 PidLidBusyStatus

Canonical name: PidLidBusyStatus

Description: Specifies the availability of a user for the event described by the object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008205

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/busystatus

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidBusyStatus

2.48 PidLidCalendarType

Canonical name: PidLidCalendarType

Description: Contains the value of the **CalendarType** field from the **PidLidAppointmentRecur** property (section [2.22](#)).

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000001C

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/calendar_type

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.11

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: LID_CALENDAR_TYPE

2.49 PidLidCategories

Canonical name: PidLidCategories

Description: Contains the array of text labels assigned to this message object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property long ID (LID): 0x00009000

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.22

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidCategories

2.50 PidLidCcAttendeesString

Canonical name: PidLidCcAttendeesString

Description: Contains a list of all the sendable attendees who are also **optional attendees**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823C

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.18

Alternate names: dispidCCAttendeesString

2.51 PidLidChangeHighlight

Canonical name: PidLidChangeHighlight

Description: Specifies a bit field that indicates how the Meeting object has changed.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008204

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.2

Consuming reference: [\[MS-OXORMDR\]](#)

Alternate names: dispidChangeHighlight

2.52 PidLidClassification

Canonical name: PidLidClassification

Description: Contains a list of the classification categories to which the associated Message object has been assigned.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B6

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.23

Consuming references: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassification

2.53 PidLidClassificationDescription

Canonical name: PidLidClassificationDescription

Description: Contains a human-readable summary of each of the classification categories included in the **PidLidClassification** property (section [2.53](#)).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B7

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.24

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassDesc

2.54 PidLidClassificationGuid

Canonical name: PidLidClassificationGuid

Description:

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B8

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassGuid

2.55 PidLidClassificationKeep

Canonical name: PidLidClassificationKeep

Description:

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085BA

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassKeep

2.56 PidLidClassified

Canonical name: PidLidClassified

Description: Indicates whether the contents of this message are regarded as classified information.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B5

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.25

Consuming references: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassified

2.57 PidLidCleanGlobalObjectId

Canonical name: PidLidCleanGlobalObjectId

Description: Contains the value of the **PidLidGlobalObjectId** property (section [2.137](#)) for an object that represents an **Exception object** to a recurring series, where the Year, Month, and Day fields are all zero.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000023

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.28

Consuming references: [\[MS-OXCICAL\]](#)

Alternate names: dispidCleanGlobalObjId

2.58 PidLidClientIntent

Canonical name: PidLidClientIntent

Description: Indicates what actions the user has taken on this Meeting object.

Property set: PSETID_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

Property long ID (LID): 0x00000015

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.2.4

Alternate names: dispidClientIntent

2.59 PidLidClipEnd

Canonical name: PidLidClipEnd

Description: Specifies the end date and time of the event in UTC.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008236

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.15

Alternate names: dispidClipEnd

2.60 PidLidClipStart

Canonical name: PidLidClipStart

Description: Specifies the start date and time of the event in UTC.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008235

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.14

Alternate names: dispidClipStart

2.61 PidLidCollaborateDoc

Canonical name: PidLidCollaborateDoc

Description: Specifies the document to be launched when the user joins the meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008247

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.7

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidCollaborateDoc

2.62 PidLidCommonEnd

Canonical name: PidLidCommonEnd

Description: Indicates the end time for the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008517

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.19

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidCommonEnd

2.63 PidLidCommonStart

Canonical name: PidLidCommonStart

Description: Indicates the start time for the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008516

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.18

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidCommonStart

2.64 PidLidCompanies

Canonical name: PidLidCompanies

Description:

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008539

Data type: PtypMultipleString, 0x101F

Area: General Message Properties

Defining reference:

Consuming references: [\[MS-OXOJRNL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidCompanies, http://schemas.microsoft.com/exchange/companies

2.65 PidLidConferencingCheck

Canonical name: PidLidConferencingCheck

Description:

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008240

Data type: PtypBoolean, 0x000B

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidConfCheck

2.66 PidLidConferencingType

Canonical name: PidLidConferencingType

Description: Specifies the type of the meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008241

Data type: PtypInteger32, 0x0003

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.3

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidConfType

2.67 PidLidContactCharacterSet

Canonical name: PidLidContactCharacterSet

Description: Specifies the character set used for a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008023

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.18

Alternate names: dispidContactCharSet

2.68 PidLidContactItemData

Canonical name: PidLidContactItemData

Description: Specifies the visible fields in the application's user interface that are used to help display the contact information.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008007

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.22

Alternate names: dispidContactItemData

2.69 PidLidContactLinkEntry

Canonical name: PidLidContactLinkEntry

Description: Contains the elements of the **PidLidContacts** property (section [2.72](#)).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008585

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.49.1

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidContactLinkEntry

2.70 PidLidContactLinkName

Canonical name: PidLidContactLinkName

Description:

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008586

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.49.3

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidContactLinkName

2.71 PidLidContactLinkSearchKey

Canonical name: PidLidContactLinkSearchKey

Description: Contains the list of SearchKeys for a Contact object linked to by the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008584

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.49.4

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidContactLinkSearchKey

2.72 PidLidContacts

Canonical name: PidLidContacts

Description: Contains the **PidTagDisplayName** property (section [2.734](#)) of each Address Book EntryID referenced in the value of the **PidLidContactLinkEntry** property (section [2.69](#)).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000853A

Data type: PtypMultipleString, 0x101F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.49.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidContacts

2.73 PidLidContactUserField1

Canonical name: PidLidContactUserField1

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804F

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/exchange/extensionattribute1>

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidContactUserField1

2.74 PidLidContactUserField2

Canonical name: PidLidContactUserField2

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008050

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute2

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidContactUserField2

2.75 PidLidContactUserField3

Canonical name: PidLidContactUserField3

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008051

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute3

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidContactUserField3

2.76 PidLidContactUserField4

Canonical name: PidLidContactUserField4

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008052

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute4

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidContactUserField4

2.77 PidLidConversationActionLastAppliedTime

Canonical name: PidLidConversationActionLastAppliedTime

Description: Contains the time, in UTC, that an **E-mail object** was last received in the **conversation**, or the last time that the user modified the **conversation action**, whichever occurs later.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085CA

Data type: PtypTime, 0x0040

Area: Conversation Actions

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.8.1

Alternate names: dispidConvActionLastAppliedTime

2.78 PidLidConversationActionMaxDeliveryTime

Canonical name: PidLidConversationActionMaxDeliveryTime

Description: Contains the maximum value of the **PidTagMessageDeliveryTime** property (section [2.845](#)) of all of the E-mail objects modified in response to the last time that the user changed a conversation action on the client.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C8

Data type: PtypTime, 0x0040

Area: Conversation Actions

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.8.2

Alternate names: dispidConvActionMaxDeliveryTime

2.79 PidLidConversationActionMoveFolderEid

Canonical name: PidLidConversationActionMoveFolderEid

Description: Contains the EntryID for the destination folder.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C6

Data type: PtypBinary, 0x0102

Area: Conversation Actions

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.8.3

Alternate names: dispidConvActionMoveFolderEid

2.80 PidLidConversationActionMoveStoreEid

Canonical name: PidLidConversationActionMoveStoreEid

Description: Contains the EntryID for a move to a folder in a different store.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C7

Data type: PtypBinary, 0x0102

Area: Conversation Actions

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.8.4

Alternate names: dispidConvActionMoveStoreEid

2.81 PidLidConversationActionVersion

Canonical name: PidLidConversationActionVersion

Description: Contains the version of the conversation action **FAI** message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085CB

Data type: PtypInteger32, 0x0003

Area: Conversation Actions

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.8.5

Alternate names: dispidConvActionVersion

2.82 PidLidConversationProcessed

Canonical name: PidLidConversationProcessed

Description:

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C9

Data type: PtypInteger32, 0x0003

Area: Conversation Actions

Defining reference:

Consuming references: [\[MS-OXOCFG\]](#)

Alternate names: dispidConvExLegacyProcessedRand

2.83 PidLidCurrentVersion

Canonical name: PidLidCurrentVersion

Description: Specifies the build number of the client application that sent the message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008552

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.34

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRLN\]](#)

Alternate names: dispidCurrentVersion

2.84 PidLidCurrentVersionName

Canonical name: PidLidCurrentVersionName

Description: Specifies the name of the client application that sent the message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008554

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.35

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRLN\]](#)

Alternate names: dispidCurrentVersionName

2.85 PidLidDayInterval

Canonical name: PidLidDayInterval

Description: Identifies the day interval for the **recurrence pattern**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000011

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/day_interval

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.19

Consuming references: [\[MS-OXOCAL\]](#)

Alternate names: LID_DAY_INTERVAL

2.86 PidLidDayOfMonth

Canonical name: PidLidDayOfMonth

Description: Identifies the day of the month for the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001000

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/dayofmonth

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.20

2.87 PidLidDelegateMail

Canonical name: PidLidDelegateMail

Description: Indicates whether a delegate responded to the meeting request.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000009

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/delegate_mail

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.21

Alternate names: LID_DELEGATE_MAIL

2.88 PidLidDepartment

Canonical name: PidLidDepartment

Description: This property is ignored by the server and is set to an empty string by the client.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008010

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.6.4

Alternate names: dispidDepartment

2.89 PidLidDirectory

Canonical name: PidLidDirectory

Description: Specifies the directory server to be used with Microsoft NetMeeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008242

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidDirectory

2.90 PidLidDistributionListChecksum

Canonical name: PidLidDistributionListChecksum

Description: Specifies the 32-bit **cyclic redundancy check (CRC)** polynomial checksum, as specified in [\[ISO/IEC8802-3\]](#), calculated on the value of the **PidLidDistributionListMembers** property (section [2.91](#)).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804C

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.2.2.3

Alternate names: dispidDLChecksum

2.91 PidLidDistributionListMembers

Canonical name: PidLidDistributionListMembers

Description: Specifies the list of EntryIds of the objects corresponding to the members of the personal distribution list.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008055

Data type: PtypMultipleBinary, 0x1102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.2.2.1

Alternate names: dispidDLMembers

2.92 PidLidDistributionListName

Canonical name: PidLidDistributionListName

Description: Specifies the name of the personal distribution list.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008053

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.2.1.2

Alternate names: dispidDLName

2.93 PidLidDistributionListOneOffMembers

Canonical name: PidLidDistributionListOneOffMembers

Description: Specifies the list of one-off EntryIDs corresponding to the members of the personal distribution list.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008054

Data type: PtypMultipleBinary, 0x1102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.2.2.2

Alternate names: dispidDLOneOffMembers

2.94 PidLidDistributionListStream

Canonical name: PidLidDistributionListStream

Description: Specifies the list of EntryIDs and one-off EntryIDs corresponding to the members of the personal distribution list.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008064

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.2.2.4

Alternate names: dispidDLStream

2.95 PidLidEmail1AddressType

Canonical name: PidLidEmail1AddressType

Description: Specifies the **address type** of an electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008082

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail1AddrType

2.96 PidLidEmail1DisplayName

Canonical name: PidLidEmail1DisplayName

Description: Specifies the user-readable display name for the e-mail address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008080

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail1DisplayName

2.97 PidLidEmail1EmailAddress

Canonical name: PidLidEmail1EmailAddress

Description: Specifies the e-mail address of the contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008083

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail1EmailAddress

2.98 PidLidEmail1OriginalDisplayName

Canonical name: PidLidEmail1OriginalDisplayName

Description: Specifies the SMTP e-mail address that corresponds to the e-mail address for the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008084

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

Alternate names: dispidEmail1OriginalDisplayName

2.99 PidLidEmail1OriginalEntryId

Canonical name: PidLidEmail1OriginalEntryId

Description: Specifies the EntryID of the object corresponding to this electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008085

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

Alternate names: dispidEmail1OriginalEntryID

2.100 PidLidEmail2AddressType

Canonical name: PidLidEmail2AddressType

Description: Specifies the address type of the electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008092

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail2AddrType

2.101 PidLidEmail2DisplayName

Canonical name: PidLidEmail2DisplayName

Description: Specifies the user-readable display name for the e-mail address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008090

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail2DisplayName

2.102 PidLidEmail2EmailAddress

Canonical name: PidLidEmail2EmailAddress

Description: Specifies the e-mail address of the contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008093

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail2EmailAddress

2.103 PidLidEmail2OriginalDisplayName

Canonical name: PidLidEmail2OriginalDisplayName

Description: Specifies the SMTP e-mail address that corresponds to the e-mail address for the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008094

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

Alternate names: dispidEmail2OriginalDisplayName

2.104 PidLidEmail2OriginalEntryId

Canonical name: PidLidEmail2OriginalEntryId

Description: Specifies the EntryID of the object that corresponds to this electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008095

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

Alternate names: dispidEmail2OriginalEntryID

2.105 PidLidEmail3AddressType

Canonical name: PidLidEmail3AddressType

Description: Specifies the address type of the electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail3AddrType

2.106 PidLidEmail3 DisplayName

Canonical name: PidLidEmail3 DisplayName

Description: Specifies the user-readable display name for the e-mail address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A0

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail3DisplayName

2.107 PidLidEmail3EmailAddress

Canonical name: PidLidEmail3EmailAddress

Description: Specifies the e-mail address of the contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail3EmailAddress

2.108 PidLidEmail3OriginalDisplayName

Canonical name: PidLidEmail3OriginalDisplayName

Description: Specifies the SMTP e-mail address that corresponds to the e-mail address for the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

Alternate names: dispidEmail3OriginalDisplayName

2.109 PidLidEmail3OriginalEntryId

Canonical name: PidLidEmail3OriginalEntryId

Description: Specifies the EntryID of the object that corresponds to this electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

Alternate names: dispidEmail3OriginalEntryID

2.110 PidLidEndRecurrenceDate

Canonical name: PidLidEndRecurrenceDate

Description: Identifies the end date of the recurrence range.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000F

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/end_recur_date

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.22

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: LID_END_RECUR_DATE

2.111 PidLidEndRecurrenceTime

Canonical name: PidLidEndRecurrenceTime

Description: Identifies the end time of the recurrence range.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000010

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/end_recur_time

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.23

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: LID_END_RECUR_TIME

2.112 PidLidExceptionReplaceTime

Canonical name: PidLidExceptionReplaceTime

Description: Specifies the date and time, in UTC, within a recurrence pattern that an exception will replace.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008228

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.10.2.5

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidExceptionReplaceTime

2.113 PidLidFax1AddressType

Canonical name: PidLidFax1AddressType

Description: Contains the string value "FAX".

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

Alternate names: dispidFax1AddrType

2.114 PidLidFax1EmailAddress

Canonical name: PidLidFax1EmailAddress

Description: Contains a user-readable display name, followed by the "@" character, followed by a fax number.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

Alternate names: dispidFax1EmailAddress

2.115 PidLidFax1OriginalDisplayName

Canonical name: PidLidFax1OriginalDisplayName

Description: Contains the same value as the **PidTagNormalizedSubject** property (section [2.864](#)).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

Alternate names: dispidFax1OriginalDisplayName

2.116 PidLidFax1OriginalEntryId

Canonical name: PidLidFax1OriginalEntryId

Description: Specifies a one-off EntryID that corresponds to this fax address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

Alternate names: dispidFax1OriginalEntryID

2.117 PidLidFax2AddressType

Canonical name: PidLidFax2AddressType

Description: Contains the string value "FAX".

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

Alternate names: dispidFax2AddrType

2.118 PidLidFax2EmailAddress

Canonical name: PidLidFax2EmailAddress

Description: Contains a user-readable display name, followed by the "@" character, followed by a fax number.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

Alternate names: dispidFax2EmailAddress

2.119 PidLidFax2OriginalDisplayName

Canonical name: PidLidFax2OriginalDisplayName

Description: Contains the same value as the **PidTagNormalizedSubject** property (section [2.864](#)).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C4

Data type: **PtypString**, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

Alternate names: dispidFax2OriginalDisplayName

2.120 PidLidFax2OriginalEntryId

Canonical name: PidLidFax2OriginalEntryId

Description: Specifies a one-off EntryID corresponding to this fax address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C5

Data type: **PtypBinary**, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

Alternate names: dispidFax2OriginalEntryID

2.121 PidLidFax3AddressType

Canonical name: PidLidFax3AddressType

Description: Contains the string value "FAX".

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D2

Data type: **PtypString**, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

Alternate names: dispidFax3AddrType

2.122 PidLidFax3EmailAddress

Canonical name: PidLidFax3EmailAddress

Description: Contains a user-readable display name, followed by the "@" character, followed by a fax number.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

Alternate names: dispidFax3EmailAddress

2.123 PidLidFax3OriginalDisplayName

Canonical name: PidLidFax3OriginalDisplayName

Description: Contains the same value as the **PidTagNormalizedSubject** property (section [2.864](#)).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

Alternate names: dispidFax3OriginalDisplayName

2.124 PidLidFax3OriginalEntryId

Canonical name: PidLidFax3OriginalEntryId

Description: Specifies a one-off EntryID that corresponds to this fax address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

Alternate names: dispidFax3OriginalEntryID

2.125 PidLidFExceptionalAttendees

Canonical name: PidLidFExceptionalAttendees

Description: Indicates that the object is a **Recurring Calendar object** with one or more exceptions, and that at least one of the **Exception Embedded Message objects** has at least one **RecipientRow** structure, as described in [\[MS-OXCDATA\]](#) section 2.8.3.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000822B

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.2.3

Consuming reference: [\[MS-OXORMDR\]](#)

Alternate names: dispidFExceptionalAttendees

2.126 PidLidFExceptionalBody

Canonical name: PidLidFExceptionalBody

Description: Indicates that the Exception Embedded Message object has a body that differs from the Recurring Calendar object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008206

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.10.2.6

Alternate names: dispidFExceptionalBody

2.127 PidLidFileUnder

Canonical name: PidLidFileUnder

Description: Specifies the name under which to file a contact when displaying a list of contacts.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008005

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.1.11

Alternate names: dispidFileUnder

2.128 PidLidFileUnderId

Canonical name: PidLidFileUnderId

Description: Specifies how to generate and recompute the value of the **PidLidFileUnder** property (section [2.127](#)) when other contact name properties change.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008006

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.1.12

Alternate names: dispidFileUnderId

2.129 PidLidFileUnderList

Canonical name: PidLidFileUnderList

Description: Specifies a list of possible values for the **PidLidFileUnderId** property (section [2.128](#)).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008026

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.1.13

Alternate names: dispidFileUnderList

2.130 PidLidFInvited

Canonical name: PidLidFInvited

Description: Indicates whether invitations have been sent for the meeting that this Meeting object represents.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008229

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/finvited

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidFInvited

2.131 PidLidFlagRequest

Canonical name: PidLidFlagRequest

Description: Contains user-specifiable text to be associated with the flag.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008530

Data type: PtypString, 0x001F

WebDAV: urn:schemas:httpmail:messageflag, http://schemas.microsoft.com/mapi/request

Area: Flagging

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.9

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidRequest

2.132 PidLidFlagString

Canonical name: PidLidFlagString

Description: Contains an index identifying one of a set of pre-defined text strings to be associated with the flag.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C0

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.10

Alternate names: dispidFlagStringEnum

2.133 PidLidForwardInstance

Canonical name: PidLidForwardInstance

Description: Indicates whether the Meeting Request object represents an exception to a recurring series, and whether it was forwarded (even when forwarded by the organizer) rather than being an invitation sent by the organizer.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820A

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.3

Alternate names: dispidFwrdInstance

2.134 PidLidForwardNotificationRecipients

Canonical name: PidLidForwardNotificationRecipients

Description: Contains a list of **RecipientRow** structures, as described in [\[MS-OXCDATA\]](#) section 2.8.3, that indicate the recipients of a meeting forward.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008261

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.9.3

Alternate names: dispidForwardNotificationRecipients

2.135 PidLidFOthersAppointment

Canonical name: PidLidFOthersAppointment

Description: Indicates whether the **Calendar folder** from which the meeting was opened is another user's calendar.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000822F

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.26

Alternate names: dispidFOthersAppt, <http://schemas.microsoft.com/mapi/fothersappt>

2.136 PidLidFreeBusyLocation

Canonical name: PidLidFreeBusyLocation

Description: Specifies a **URL** path from which a client can retrieve **free/busy status** information for the contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D8

Data type: PtypString, 0x001F

WebDAV: urn:schemas:calendar:fbusl

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.10

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidFreeBusyLocation

2.137 PidLidGlobalObjectId

Canonical name: PidLidGlobalObjectId

Description: Contains an ID for an object that represents an exception to a recurring series.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000003

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.27

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXWAVLS\]](#)

Alternate names: LID_GLOBAL_OBJID

2.138 PidLidHasPicture

Canonical name: PidLidHasPicture

Description: Specifies whether the attachment has a picture.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008015

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.8.1

Alternate names: dispidHasPicture

2.139 PidLidHomeAddress

Canonical name: PidLidHomeAddress

Description: Specifies the complete address of the contact's home address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000801A

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:homepostaladdress

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidHomeAddress

2.140 PidLidHomeAddressCountryCode

Canonical name: PidLidHomeAddressCountryCode

Description: Specifies the country code portion of the contact's home address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DA

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

Alternate names: dispidHomeAddressCountryCode

2.141 PidLidHtml

Canonical name: PidLidHtml

Description: Specifies the contact's business webpage URL.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802B

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.12

Alternate names: dispidHTML

2.142 PidLidICalendarDayOfWeekMask

Canonical name: PidLidICalendarDayOfWeekMask

Description: Identifies the day of the week for the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001001

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.27

Alternate names: http://schemas.microsoft.com/mapi/dayofweekmask

2.143 PidLidInboundICalStream

Canonical name: PidLidInboundICalStream

Description:

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000827A

Data type: PtypBinary, 0x0102

Area: Calendar

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: InboundICalStream, dispidInboundICalStream

2.144 PidLidInfoPathFormName

Canonical name: PidLidInfoPathFormName

Description: Contains the name of the form associated with this message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x85B1

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.27

Consuming reference: [\[MS-OXCMAIL\]](#)

2.145 PidLidInstantMessagingAddress

Canonical name: PidLidInstantMessagingAddress

Description: Specifies the contact's instant messaging address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008062

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.6

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidInstMsg

2.146 PidLidIntendedBusyStatus

Canonical name: PidLidIntendedBusyStatus

Description: Contains the value of the **PidLidBusyStatus** property (section 2.47) on the Meeting object in the organizer's **calendar** at the time that the Meeting Request object or Meeting Update object was sent.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008224

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/intendedbusystatus

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidIntendedBusyStatus

2.147 PidLidInternetAccountName

Canonical name: PidLidInternetAccountName

Description: Specifies the user-visible e-mail account name through which the e-mail message is sent.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008580

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.53

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidInetAcctName

2.148 PidLidInternetAccountStamp

Canonical name: PidLidInternetAccountStamp

Description: Specifies the e-mail account ID through which the e-mail message is sent.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008581

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.54

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidInetAcctStamp

2.149 PidLidIsException

Canonical name: PidLidIsException

Description: Indicates whether the object represents an exception (including an **orphan instance**).

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000A

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/is_exception

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.35

Consuming references: [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: LID_IS_EXCEPTION

2.150 PidLidIsRecurring

Canonical name: PidLidIsRecurring

Description: Specifies whether the object is associated with a recurring series.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000005

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/is_recurring

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.13

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: LID_IS_RECURRING

2.151 PidLidIsSilent

Canonical name: PidLidIsSilent

Description: Indicates whether the user did not include any text in the body of the Meeting Response object.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000004

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/is_silent

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.7.7

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: LID_IS_SILENT

2.152 PidLidLinkedTaskItems

Canonical name: PidLidLinkedTaskItems

Description: Indicates whether the user did not include any text in the body of the Meeting Response object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820C

Data type: PtypMultipleBinary, 0x1102

Area: Tasks

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.47

Alternate names: dispidLinkedTaskItems

2.153 PidLidLocation

Canonical name: PidLidLocation

Description: Specifies the location of the event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008208

Data type: PtypString, 0x001F

WebDAV: urn:schemas:calendar:location

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidLocation

2.154 PidLidLogDocumentPosted

Canonical name: PidLidLogDocumentPosted

Description: Indicates whether the document was sent by e-mail or posted to a server folder during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008711

Data type: PtypBoolean, 0x000B

Area: Journal

Defining reference: [\[MS-OXOJRNRL\]](#) section 2.2.1.10

Alternate names: dispidLogDocPosted

2.155 PidLidLogDocumentPrinted

Canonical name: PidLidLogDocumentPrinted

Description: Indicates whether the document was printed during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000870E

Data type: PtypBoolean, 0x000B

Area: Journal

Defining reference: [\[MS-OXOJRNRL\]](#) section 2.2.1.7

Alternate names: dispidLogDocPrinted

2.156 PidLidLogDocumentRouted

Canonical name: PidLidLogDocumentRouted

Description: Indicates whether the document was sent to a routing recipient during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008710

Data type: PtypBoolean, 0x000B

Area: Journal

Defining reference: [\[MS-OXOJRNRL\]](#) section 2.2.1.9

Alternate names: dispidLogDocRouted

2.157 PidLidLogDocumentSaved

Canonical name: PidLidLogDocumentSaved

Description: Indicates whether the document was saved during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000870F

Data type: PtypBoolean, 0x000B

Area: Journal

Defining reference: [\[MS-OXOJRNRL\]](#) section 2.2.1.8

Alternate names: dispidLogDocSaved

2.158 PidLidLogDuration

Canonical name: PidLidLogDuration

Description: Contains the duration, in minutes, of the activity.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008707

Data type: PtypInteger32, 0x0003

Area: Journal

Defining reference: [\[MS-OXOJRNRL\]](#) section 2.2.1.5

Alternate names: dispidLogDuration

2.159 PidLidLogEnd

Canonical name: PidLidLogEnd

Description: Contains the time, in UTC, at which the activity ended.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008708

Data type: PtypTime, 0x0040

Area: Journal

Defining reference: [\[MS-OXOJRNRL\]](#) section 2.2.1.4

Alternate names: dispidLogEnd

2.160 PidLidLogFlags

Canonical name: PidLidLogFlags

Description: Contains metadata about the Journal object.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000870C

Data type: PtypInteger32, 0x0003

Area: Journal

Defining reference: [\[MS-OXOJRN\]](#) section 2.2.1.6

Alternate names: dispidLogFlags

2.161 PidLidLogStart

Canonical name: PidLidLogStart

Description: Contains the time, in UTC, at which the activity began.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008706

Data type: PtypTime, 0x0040

Area: Journal

Defining reference: [\[MS-OXOJRN\]](#) section 2.2.1.3

Alternate names: dispidLogStart

2.162 PidLidLogType

Canonical name: PidLidLogType

Description: Briefly describes the journal activity that is being recorded.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008700

Data type: PtypString, 0x001F

Area: Journal

Defining reference: [\[MS-OXOJRN\]](#) section 2.2.1.1

Alternate names: dispidLogType

2.163 PidLidLogTypeDesc

Canonical name: PidLidLogTypeDesc

Description: Contains an expanded description of the journal activity that is being recorded.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008712

Data type: PtypString, 0x001F

Area: Journal

Defining reference: [\[MS-OXOJRN\]](#) section 2.2.1.2

Alternate names: dispidLogTypeDesc

2.164 PidLidMeetingType

Canonical name: PidLidMeetingType

Description: Indicates the type of Meeting Request object or Meeting Update object.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000026

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.5

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidMeetingType

2.165 PidLidMeetingWorkspaceUrl

Canonical name: PidLidMeetingWorkspaceUrl

Description: Specifies the URL of the **Meeting Workspace** that is associated with a Calendar object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008209

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/meetingworkspaceurl

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.48

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidMWSURL

2.166 PidLidMonthInterval

Canonical name: PidLidMonthInterval

Description: Indicates the monthly interval of the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000013

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/month_interval

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.33

Alternate names: LID_MONTH_INTERVAL

2.167 PidLidMonthOfYear

Canonical name: PidLidMonthOfYear

Description: Indicates the month of the year in which the appointment or meeting occurs.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001006

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/monthofyear

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.34

2.168 PidLidMonthOfYearMask

Canonical name: PidLidMonthOfYearMask

Description: Indicates the month of the year in which the appointment or meeting occurs.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000017

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/moy_mask

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.35

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: LID_MOY_MASK

2.169 PidLidNetShowUrl

Canonical name: PidLidNetShowUrl

Description: Specifies the URL to be launched when the user joins the meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008248

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.8

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidNetShowURL

2.170 PidLidNoEndDateFlag

Canonical name: PidLidNoEndDateFlag

Description: Indicates whether the recurrence pattern has an end date.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000100B

Data type: PtypBoolean, 0x000B

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.36

Alternate names: http://schemas.microsoft.com/mapi/fnoenddate

2.171 PidLidNonSendableBcc

Canonical name: PidLidNonSendableBcc

Description: Contains a list of all of the unsendable attendees who are also resources.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008538

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/nonsendablebcc

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.21

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendableBCC

2.172 PidLidNonSendableCc

Canonical name: PidLidNonSendableCc

Description: Contains a list of all of the unsendable attendees who are also optional attendees.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008537

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/nonsendablecc

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.20

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendableCC

2.173 PidLidNonSendableTo

Canonical name: PidLidNonSendableTo

Description: Contains a list of all of the unsendable attendees who are also required attendees.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008536

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/mapi/nonsendableto>

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.19

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendableTo

2.174 PidLidNonSendBccTrackStatus

Canonical name: PidLidNonSendBccTrackStatus

Description: Contains the value from the response table.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008545

Data type: PtypMultipleInteger32, 0x1003

WebDAV: <http://schemas.microsoft.com/mapi/nonsendbcctrackstatus>

Area: General Message Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.24

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendBccTrackStatus

2.175 PidLidNonSendCcTrackStatus

Canonical name: PidLidNonSendCcTrackStatus

Description: Contains the value from the response table.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008544

Data type: PtypMultipleInteger32, 0x1003

WebDAV: http://schemas.microsoft.com/mapi/nonsendccctrackstatus

Area: General Message Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.23

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendCcTrackStatus

2.176 PidLidNonSendToTrackStatus

Canonical name: PidLidNonSendToTrackStatus

Description: Contains the value from the response table.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008543

Data type: PtypMultipleInteger32, 0x1003

WebDAV: http://schemas.microsoft.com/mapi/nonsendtotracksstatus

Area: General Message Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.22

Consuming references: [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendToTrackStatus

2.177 PidLidNoteColor

Canonical name: PidLidNoteColor

Description: Specifies the suggested background color of the **Note object**.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B00

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [\[MS-OXONOTE\]](#) section 2.2.1.1

Alternate names: dispidNoteColor

2.178 PidLidNoteHeight

Canonical name: PidLidNoteHeight

Description: Specifies the height of the visible message window in pixels.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B03

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [\[MS-OXONOTE\]](#) section 2.2.1.3

Alternate names: dispidNoteHeight

2.179 PidLidNoteWidth

Canonical name: PidLidNoteWidth

Description: Specifies the width of the visible message window in pixels.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B02

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [\[MS-OXONOTE\]](#) section 2.2.1.2

Alternate names: dispidNoteWidth

2.180 PidLidNoteX

Canonical name: PidLidNoteX

Description: Specifies the distance, in pixels, from the left edge of the screen that a user interface displays a Note object.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B04

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [\[MS-OXONOTE\]](#) section 2.2.1.4

Alternate names: dispidNoteX

2.181 PidLidNoteY

Canonical name: PidLidNoteY

Description: Specifies the distance, in pixels, from the top edge of the screen that a user interface displays a Note object.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B05

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [\[MS-OXONOTE\]](#) section 2.2.1.5

Alternate names: dispidNoteY

2.182 PidLidOccurrences

Canonical name: PidLidOccurrences

Description: Indicates the number of occurrences in the recurring appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001005

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/occurrences

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.43

2.183 PidLidOldLocation

Canonical name: PidLidOldLocation

Description: Indicates the original value of the **PidLidLocation** property (section [2.153](#)) before a meeting update.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000028

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.7

Alternate names: dispidOldLocation

2.184 PidLidOldRecurrenceType

Canonical name: PidLidOldRecurrenceType

Description: Indicates the recurrence pattern for the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000018

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/recur_type

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.44

Alternate names: LID_RECUR_TYPE

2.185 PidLidOldWhenEndWhole

Canonical name: PidLidOldWhenEndWhole

Description: Indicates the original value of the **PidLidAppointmentEndWhole** property (section [2.14](#)) before a meeting update.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000002A

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.9

Alternate names: dispidOldWhenEndWhole

2.186 PidLidOldWhenStartWhole

Canonical name: PidLidOldWhenStartWhole

Description: Indicates the original value of the **PidLidAppointmentStartWhole** property (section [2.29](#)) before a meeting update.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000029

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.8

Alternate names: dispidOldWhenStartWhole

2.187 PidLidOnlinePassword

Canonical name: PidLidOnlinePassword

Description: Specifies the password for a meeting on which the **PidLidConferencingType** property (section [2.66](#)) has the value 0x00000002.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008249

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.9

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidOnlinePassword

2.188 PidLidOptionalAttendees

Canonical name: PidLidOptionalAttendees

Description: Specifies optional attendees.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000007

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/optional_attendees

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.45

Alternate names: LID_OPTIONAL_ATTENDEES

2.189 PidLidOrganizerAlias

Canonical name: PidLidOrganizerAlias

Description: Specifies the e-mail address of the organizer.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008243

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.6

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidOrgAlias

2.190 PidLidOriginalStoreEntryId

Canonical name: PidLidOriginalStoreEntryId

Description: Specifies the EntryID of the delegator's store.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008237

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.9

Alternate names: dispidOrigStoreEid, <http://schemas.microsoft.com/mapi/origstoreeid>

2.191 PidLidOtherAddress

Canonical name: PidLidOtherAddress

Description: Specifies the complete address of the contact's other address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000801C

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:otherpostaladdress

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidOtherAddress

2.192 PidLidOtherAddressCountryCode

Canonical name: PidLidOtherAddressCountryCode

Description: Specifies the country code portion of the contact's other address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DC

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

Alternate names: dispidOtherAddressCountryCode

2.193 PidLidOwnerCriticalChange

Canonical name: PidLidOwnerCriticalChange

Description: Specifies the date and time at which a Meeting Request object was sent by the organizer.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000001A

Data type: PtypTime, 0x0040

WebDAV: urn:schemas:calendar:dtstamp,
http://schemas.microsoft.com/mapi/owner_critical_change

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.34

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: LID_OWNER_CRITICAL_CHANGE

2.194 PidLidOwnerName

Canonical name: PidLidOwnerName

Description: Indicates the name of the owner of the **mailbox**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000822E

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/ownername

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.47

Alternate names: dispidOwnerName

2.195 PidLidPercentComplete

Canonical name: PidLidPercentComplete

Description: Indicates whether a time-flagged Message object is complete.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008102

Data type: PtypFloating64, 0x0005

Area: Tasks

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.2.2

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidPercentComplete

2.196 PidLidPostalAddressId

Canonical name: PidLidPostalAddressId

Description: Specifies which physical address is the mailing address for this contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008022

Data type: PtypInteger32, 0x0003

WebDAV: urn:schemas:contacts:mailingaddressid

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.9

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidPostalAddressId

2.197 PidLidPostRssChannel

Canonical name: PidLidPostRssChannel

Description: Contains the contents of the title field from the **XML** of the Atom feed or RSS channel.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008904

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.5

Alternate names: dispidPostRssChannel

2.198 PidLidPostRssChannelLink

Canonical name: PidLidPostRssChannelLink

Description: Contains the URL of the RSS or Atom feed from which the XML file came.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008900

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.1

Alternate names: dispidPostRssChannelLink

2.199 PidLidPostRssItemGuid

Canonical name: PidLidPostRssItemGuid

Description: Contains a unique identifier for the RSS object.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008903

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.4

Alternate names: dispidPostRssItemGuid

2.200 PidLidPostRssItemHash

Canonical name: PidLidPostRssItemHash

Description: Contains a hash of the feed XML computed by using an implementation-dependent algorithm.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008902

Data type: PtypInteger32, 0x0003

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.3

Alternate names: dispidPostRssItemHash

2.201 PidLidPostRssItemLink

Canonical name: PidLidPostRssItemLink

Description: Contains the URL of the link from an RSS or Atom item.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008901

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.2

Alternate names: dispidPostRssItemLink

2.202 PidLidPostRssItemXml

Canonical name: PidLidPostRssItemXml

Description: Contains the item element and all of its sub-elements from an RSS feed, or the entry element and all of its sub-elements from an Atom feed.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008905

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.6

Alternate names: dispidPostRssItemXml

2.203 PidLidPostRssSubscription

Canonical name: PidLidPostRssSubscription

Description: Contains the user's preferred name for the RSS or Atom subscription.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008906

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.7

Alternate names: dispidPostRssSubscription

2.204 PidLidPrivate

Canonical name: PidLidPrivate

Description: Indicates whether the end user wishes for this Message object to be hidden from other users who have access to the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008506

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.15

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidPrivate

2.205 PidLidPromptSendUpdate

Canonical name: PidLidPromptSendUpdate

Description: Indicates that the Meeting Response object was out-of-date when it was received.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008045

Data type: PtypBoolean, 0x000B

Area: Meeting Response

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.7.8

Alternate names: dispidPromptSendUpdate

2.206 PidLidRecurrenceDuration

Canonical name: PidLidRecurrenceDuration

Description: Identifies the length, in minutes, of the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000100D

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/recurduration

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.48

2.207 PidLidRecurrencePattern

Canonical name: PidLidRecurrencePattern

Description: Specifies a description of the recurrence pattern of the Calendar object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008232

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/recurpattern

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.46

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidRecurPattern

2.208 PidLidRecurrenceType

Canonical name: PidLidRecurrenceType

Description: Specifies the recurrence type of the recurring series.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008231

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/recurtype

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.45

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidRecurType

2.209 PidLidRecurring

Canonical name: PidLidRecurring

Description: Specifies whether the object represents a recurring series.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008223

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/recurring

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.12

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidRecurring

2.210 PidLidReferenceEntryId

Canonical name: PidLidReferenceEntryId

Description: Specifies the value of the EntryID of the Contact object unless the Contact object is a copy of an earlier original.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085BD

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.1

Alternate names: dispidReferenceEID

2.211 PidLidReferredBy

Canonical name: PidLidReferredBy

Description: Specifies the name of the person who referred the contact to the user.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000800E

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:referredby

Area: Contact Properties

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.5

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidReferredBy

2.212 PidLidReminderDelta

Canonical name: PidLidReminderDelta

Description: Specifies the interval, in minutes, between the time at which the reminder first becomes overdue and the start time of the Calendar object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008501

Data type: PtypInteger32, 0x0003

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.3

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMMS\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

Alternate names: dispidReminderDelta, <http://schemas.microsoft.com/mapi/reminderdelta>

2.213 PidLidReminderFileParameter

Canonical name: PidLidReminderFileParameter

Description: Specifies the filename of the sound that a client is to play when the **reminder** for that object becomes overdue.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851F

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/mapi/reminderfileparam>

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.7

Consuming reference: [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidReminderFileParam

2.214 PidLidReminderOverride

Canonical name: PidLidReminderOverride

Description: Specifies whether the client is to respect the current values of the **PidLidReminderPlaySound** property (section 2.215) and the **PidLidReminderFileParameter** property (section 2.213), or use the default values for those properties.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851C

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/reminderoverride

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.5

Consuming reference: [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidReminderOverride

2.215 PidLidReminderPlaySound

Canonical name: PidLidReminderPlaySound

Description: Specifies whether the client is to play a sound when the reminder becomes overdue.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851E

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/reminderplaysound

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.6

Consuming reference: [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidReminderPlaySound

2.216 PidLidReminderSet

Canonical name: PidLidReminderSet

Description: Specifies whether a reminder is set on the object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008503

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/reminderset

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.1

Consuming references: [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOPOST\]](#)

Alternate names: dispidReminderSet

2.217 PidLidReminderSignalTime

Canonical name: PidLidReminderSignalTime

Description: Specifies the point in time when a reminder transitions from pending to overdue.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008560

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/remindernexttime>

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidReminderNextTime

2.218 PidLidReminderTime

Canonical name: PidLidReminderTime

Description: Specifies the initial **signal time** for non-Calendar objects.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008502

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/remindertime>

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidReminderTime

2.219 PidLidReminderTimeDate

Canonical name: PidLidReminderTimeDate

Description: Indicates the time and date of the reminder for the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008505

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/remindertimedate

Area: Reminders

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.59

Alternate names: dispidReminderTimeDate

2.220 PidLidReminderTimeTime

Canonical name: PidLidReminderTimeTime

Description: Indicates the time of the reminder for the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008504

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/remindertimetetime

Area: Reminders

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.60

Consuming references: [\[MS-OXONOTE\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

Alternate names: dispidReminderTimeTime

2.221 PidLidReminderType

Canonical name: PidLidReminderType

Description: This property is not set and, if set, is ignored.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851D

Data type: PtypInteger32, 0x0003

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.9

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidReminderType, http://schemas.microsoft.com/mapi/remindertype

2.222 PidLidRemoteStatus

Canonical name: PidLidRemoteStatus

Description: Indicates the remote status of the calendar item.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008511

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/remotestatus

Area: Run-time configuration

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.62

Alternate names: dispidRemoteStatus

2.223 PidLidRequiredAttendees

Canonical name: PidLidRequiredAttendees

Description: Identifies required attendees for the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000006

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/required_attendees

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.63

Consuming references: [\[MS-OXOCAL\]](#)

Alternate names: LID_REQUIRED_ATTENDEES

2.224 PidLidResourceAttendees

Canonical name: PidLidResourceAttendees

Description: Identifies resource attendees for the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000008

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/resource_attendees

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.64

Consuming references: [\[MS-OXOCAL\]](#)

Alternate names: LID_RESOURCE_ATTENDEES

2.225 PidLidResponseStatus

Canonical name: PidLidResponseStatus

Description: Specifies the response status of an attendee.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008218

Data type: PtypInteger32, 0x0003

WebDAV: urn:schemas:calendar:attendeestatus,
http://schemas.microsoft.com/mapi/responsestatus

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.11

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidResponseStatus

2.226 PidLidServerProcessed

Canonical name: PidLidServerProcessed

Description: Indicates whether the Meeting Request Object or Meeting Update Object has been processed.

Property set: PSETID_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

Property long ID (LID): 0x000085CC

Data type: PtypBoolean, 0x000B

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.5.4

Alternate names: dispidExchangeProcessed

2.227 PidLidServerProcessingActions

Canonical name: PidLidServerProcessingActions

Description: Indicates what processing actions have been taken on this Meeting Request Object or Meeting Update Object.

Property set: PSETID_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

Property long ID (LID): 0x000085CD

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.5.5

Alternate names: dispidExchangeProcessingAction

2.228 PidLidSharingAnonymity

Canonical name: PidLidSharingAnonymity

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A19

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingAnonymity

2.229 PidLidSharingBindingEntryId

Canonical name: PidLidSharingBindingEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2D

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingBindingEid

2.230 PidLidSharingBrowseUrl

Canonical name: PidLidSharingBrowseUrl

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A51

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingBrowseUrl

2.231 PidLidSharingCapabilities

Canonical name: PidLidSharingCapabilities

Description: Indicates that the Message object relates to a **special folder**.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A17

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.1

Alternate names: dispidSharingCaps

2.232 PidLidSharingConfigurationUrl

Canonical name: PidLidSharingConfigurationUrl

Description: Contains a zero-length string.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A24

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.3

Alternate names: dispidSharingConfigUrl

2.233 PidLidSharingDataRangeEnd

Canonical name: PidLidSharingDataRangeEnd

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A45

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingDataRangeEnd

2.234 PidLidSharingDataRangeStart

Canonical name: PidLidSharingDataRangeStart

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A44

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingDataRangeStart

2.235 PidLidSharingDetail

Canonical name: PidLidSharingDetail

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2B

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingDetail

2.236 PidLidSharingExtensionXml

Canonical name: PidLidSharingExtensionXml

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A21

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingExtXml

2.237 PidLidSharingFilter

Canonical name: PidLidSharingFilter

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A13

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingFilter

2.238 PidLidSharingFlags

Canonical name: PidLidSharingFlags

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0A

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingFlags

2.239 PidLidSharingFlavor

Canonical name: PidLidSharingFlavor

Description: Indicates the type of Sharing Message object.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A18

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.5

Alternate names: dispidSharingFlavor

2.240 PidLidSharingFolderEntryId

Canonical name: PidLidSharingFolderEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A15

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingFolderEid

2.241 PidLidSharingIndexEntryId

Canonical name: PidLidSharingIndexEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2E

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingIndexEid

2.242 PidLidSharingInitiatorEntryId

Canonical name: PidLidSharingInitiatorEntryId

Description: Contains the value of the **PidTagEntryId** property (section [2.741](#)) for the Address Book object of the currently logged-on user.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A09

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.7

Alternate names: dispidSharingInitiatorEid

2.243 PidLidSharingInitiatorName

Canonical name: PidLidSharingInitiatorName

Description: Contains the value of the **PidTagDisplayName** property (section [2.734](#)) from the Address Book object identified by the **PidLidSharingInitiatorEntryId** property (section [2.242](#)).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A07

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.8

Alternate names: dispidSharingInitiatorName

2.244 PidLidSharingInitiatorSmtip

Canonical name: PidLidSharingInitiatorSmtip

Description: Contains the value of the **PidTagSmtipAddress** property (section [2.1072](#)) from the Address Book object identified by the **PidLidSharingInitiatorEntryId** property (section [2.242](#)).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A08

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.9

Alternate names: dispidSharingInitiatorSmtip

2.245 PidLidSharingInstanceGuid

Canonical name: PidLidSharingInstanceGuid

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1C

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingInstanceGuid

2.246 PidLidSharingLastAutoSyncTime

Canonical name: PidLidSharingLastAutoSyncTime

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A55

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingLastAutoSync

2.247 PidLidSharingLastSyncTime

Canonical name: PidLidSharingLastSyncTime

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1F

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingLastSync

2.248 PidLidSharingLocalComment

Canonical name: PidLidSharingLocalComment

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4D

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingLocalComment

2.249 PidLidSharingLocalLastModificationTime

Canonical name: PidLidSharingLocalLastModificationTime

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A23

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingLocalLastMod

2.250 PidLidSharingLocalName

Canonical name: PidLidSharingLocalName

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0F

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingLocalName

2.251 PidLidSharingLocalPath

Canonical name: PidLidSharingLocalPath

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0E

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingLocalPath

2.252 PidLidSharingLocalStoreUid

Canonical name: PidLidSharingLocalStoreUid

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A49

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingLocalStoreUid

2.253 PidLidSharingLocalType

Canonical name: PidLidSharingLocalType

Description: Contains the value of the **PidTagContainerClass** property (section [2.701](#)) of the folder being shared.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A14

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.10

Alternate names: dispidSharingLocalType

2.254 PidLidSharingLocalUid

Canonical name: PidLidSharingLocalUid

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A10

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingLocalUid

2.255 PidLidSharingOriginalMessageEntryId

Canonical name: PidLidSharingOriginalMessageEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A29

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingOriginalMessageEid

2.256 PidLidSharingParentBindingEntryId

Canonical name: PidLidSharingParentBindingEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A5C

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingParentBindingEid

2.257 PidLidSharingParticipants

Canonical name: PidLidSharingParticipants

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1E

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingParticipants

2.258 PidLidSharingPermissions

Canonical name: PidLidSharingPermissions

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1B

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingPermissions

2.259 PidLidSharingProviderExtension

Canonical name: PidLidSharingProviderExtension

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0B

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingProviderExtension

2.260 PidLidSharingProviderGuid

Canonical name: PidLidSharingProviderGuid

Description: Contains the value "%xAE.F0.06.00.00.00.00.00.C0.00.00.00.00.00.00.46".

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A01

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.12

Alternate names: dispidSharingProviderGuid

2.261 PidLidSharingProviderName

Canonical name: PidLidSharingProviderName

Description: Contains a user-displayable name of the sharing provider identified by the **PidLidSharingProviderGuid** property (section [2.260](#)).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A02

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.14

Alternate names: dispidSharingProviderName

2.262 PidLidSharingProviderUrl

Canonical name: PidLidSharingProviderUrl

Description: Contains a URL related to the sharing provider identified by the **PidLidSharingProviderGuid** property (section [2.260](#)).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A03

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.16

Alternate names: dispidSharingProviderUrl

2.263 PidLidSharingRangeEnd

Canonical name: PidLidSharingRangeEnd

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A47

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingRangeEnd

2.264 PidLidSharingRangeStart

Canonical name: PidLidSharingRangeStart

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A46

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingRangeStart

2.265 PidLidSharingReciprocation

Canonical name: PidLidSharingReciprocation

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1A

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingReciprocation

2.266 PidLidSharingRemoteByteSize

Canonical name: PidLidSharingRemoteByteSize

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4B

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Consuming reference: [MS-OXSHARE]

Alternate names: dispidSharingRemoteByteSize

2.267 PidLidSharingRemoteComment

Canonical name: PidLidSharingRemoteComment

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2F

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingRemoteComment

2.268 PidLidSharingRemoteCrc

Canonical name: PidLidSharingRemoteCrc

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4C

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingRemoteCrc

2.269 PidLidSharingRemoteLastModificationTime

Canonical name: PidLidSharingRemoteLastModificationTime

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A22

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingRemoteLastMod

2.270 PidLidSharingRemoteMessageCount

Canonical name: PidLidSharingRemoteMessageCount

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4F

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingRemoteMsgCount

2.271 PidLidSharingRemoteName

Canonical name: PidLidSharingRemoteName

Description: Contains the value of the **PidTagDisplayName** property (section [2.734](#)) on the folder being shared.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A05

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.4.1

Alternate names: dispidSharingRemoteName

2.272 PidLidSharingRemotePass

Canonical name: PidLidSharingRemotePass

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0D

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingRemotePass

2.273 PidLidSharingRemotePath

Canonical name: PidLidSharingRemotePath

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A04

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingRemotePath

2.274 PidLidSharingRemoteStoreUid

Canonical name: PidLidSharingRemoteStoreUid

Description: Contains a hexadecimal string representation of the value of the **PidTagStoreEntryId** property (section [2.1080](#)) on the folder being shared.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A48

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.4.3

Alternate names: dispidSharingRemoteStoreUid

2.275 PidLidSharingRemoteType

Canonical name: PidLidSharingRemoteType

Description: Contains the same value as the **PidLidSharingLocalType** property (section [2.253](#)).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1D

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.4.5

Alternate names: dispidSharingRemoteType

2.276 PidLidSharingRemoteUid

Canonical name: PidLidSharingRemoteUid

Description: Contains the EntryID of the folder being shared.

Property set: PSTID_Sharing {00062040-0000-0000-C000-00000000046}

Property long ID (LID): 0x00008A06

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.4.7

Alternate names: dispidSharingRemoteUid

2.277 PidLidSharingRemoteUser

Canonical name: PidLidSharingRemoteUser

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-00000000046}

Property long ID (LID): 0x00008A0C

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingRemoteUser

2.278 PidLidSharingRemoteVersion

Canonical name: PidLidSharingRemoteVersion

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-00000000046}

Property long ID (LID): 0x00008A5B

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingRemoteVersion

2.279 PidLidSharingResponseTime

Canonical name: PidLidSharingResponseTime

Description: Contains the time at which the recipient of the sharing request sent a sharing response.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A28

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.3.1

Alternate names: dispidSharingResponseTime

2.280 PidLidSharingResponseType

Canonical name: PidLidSharingResponseType

Description: Contains the type of response with which the recipient of the sharing request responded.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A27

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.3.2

Alternate names: dispidSharingResponseType

2.281 PidLidSharingRoamLog

Canonical name: PidLidSharingRoamLog

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4E

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingRoamLog

2.282 PidLidSharingStart

Canonical name: PidLidSharingStart

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A25

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingStart

2.283 PidLidSharingStatus

Canonical name: PidLidSharingStatus

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A00

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingStatus

2.284 PidLidSharingStop

Canonical name: PidLidSharingStop

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A26

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingStop

2.285 PidLidSharingSyncFlags

Canonical name: PidLidSharingSyncFlags

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A60

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingSyncFlags

2.286 PidLidSharingSyncInterval

Canonical name: PidLidSharingSyncInterval

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2A

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingSyncInterval

2.287 PidLidSharingTimeToLive

Canonical name: PidLidSharingTimeToLive

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2C

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingTimeToLive

2.288 PidLidSharingTimeToLiveAuto

Canonical name: PidLidSharingTimeToLiveAuto

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A56

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingTimeToLiveAuto

2.289 PidLidSharingWorkingHoursDays

Canonical name: PidLidSharingWorkingHoursDays

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A42

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingWorkingHoursDays

2.290 PidLidSharingWorkingHoursEnd

Canonical name: PidLidSharingWorkingHoursEnd

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A41

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingWorkingHoursEnd

2.291 PidLidSharingWorkingHoursStart

Canonical name: PidLidSharingWorkingHoursStart

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A40

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingWorkingHoursStart

2.292 PidLidSharingWorkingHoursTimeZone

Canonical name: PidLidSharingWorkingHoursTimeZone

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A43

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

Alternate names: dispidSharingWorkingHoursTZ

2.293 PidLidSideEffects

Canonical name: PidLidSideEffects

Description: Specifies how a Message object is handled by the client in relation to certain user interface actions by the user, such as deleting a message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008510

Data type: PtypInteger32, 0x0003

Area: Run-time configuration

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.16

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMMS\]](#), [\[MS-OXOJRNLL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidSideEffects

2.294 PidLidSingleBodyICal

Canonical name: PidLidSingleBodyICal

Description: Indicates that the original MIME message contained a single MIME part.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000827B

Data type: PtypBoolean, 0x000B

Area: Calendar

Defining reference: [\[MS-OXCICAL\]](#) section 2.2.2

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: IsSingleBodyICal, dispidIsSingleBodyICal

2.295 PidLidSmartNoAttach

Canonical name: PidLidSmartNoAttach

Description: Indicates whether the Message object has no end-user visible attachments.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008514

Data type: PtypBoolean, 0x000B

Area: Run-time configuration

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.14

Alternate names: dispidSmartNoAttach

2.296 PidLidSpamOriginalFolder

Canonical name: PidLidSpamOriginalFolder

Description: Specifies which folder a message was in before it was filtered into the Junk E-mail folder.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000859C

Data type: PtypBinary, 0x0102

Area: Spam

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.1.1

Alternate names: dispidSpamOriginalFolder

2.297 PidLidStartRecurrenceDate

Canonical name: PidLidStartRecurrenceDate

Description: Identifies the start date of the recurrence pattern.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000D

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/start_recur_date

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.66

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: LID_START_RECUR_DATE

2.298 PidLidStartRecurrenceTime

Canonical name: PidLidStartRecurrenceTime

Description: Identifies the start time of the recurrence pattern.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000E

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/start_recur_time

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.67

Consuming references: [\[MS-OXOCAL\]](#), [\[MS-OXCICAL\]](#)

Alternate names: LID_START_RECUR_TIME

2.299 PidLidTaskAcceptanceState

Canonical name: PidLidTaskAcceptanceState

Description: Indicates the acceptance state of the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000812A

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.30

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOPOST\]](#)

Alternate names: dispidTaskDelegValue

2.300 PidLidTaskAccepted

Canonical name: PidLidTaskAccepted

Description: Indicates whether a task assignee has replied to a **task request** for this **Task object**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008108

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.7

Consuming reference: [\[MS-OXOSFLD\]](#)

Alternate names: dispidTaskAccepted

2.301 PidLidTaskActualEffort

Canonical name: PidLidTaskActualEffort

Description: Indicates the number of minutes that the user actually spent working on a task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008110

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.11

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskActualEffort

2.302 PidLidTaskAssigner

Canonical name: PidLidTaskAssigner

Description: Specifies the name of the user that last assigned the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008121

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.24

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskDelegator

2.303 PidLidTaskAssigners

Canonical name: PidLidTaskAssigners

Description: Contains a stack of entries, each of which represents a task assigner.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008117

Data type: PtypBinary, 0x0102

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.16

Alternate names: dispidTaskMyDelegators

2.304 PidLidTaskComplete

Canonical name: PidLidTaskComplete

Description: Indicates that the task is complete.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811C

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.20

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskComplete

2.305 PidLidTaskCustomFlags

Canonical name: PidLidTaskCustomFlags

Description: The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008139

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.33

Alternate names: dispidTaskCustomFlags

2.306 PidLidTaskDateCompleted

Canonical name: PidLidTaskDateCompleted

Description: Specifies the date when the user completed work on the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000810F

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.9

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#)

Alternate names: dispidTaskDateCompleted

2.307 PidLidTaskDeadOccurrence

Canonical name: PidLidTaskDeadOccurrence

Description: Indicates whether new occurrences remain to be generated.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008109

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.8

Alternate names: dispidTaskDeadOccur

2.308 PidLidTaskDueDate

Canonical name: PidLidTaskDueDate

Description: Specifies the date by which the user expects work on the task to be complete.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008105

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.5

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidTaskDueDate

2.309 PidLidTaskEstimatedEffort

Canonical name: PidLidTaskEstimatedEffort

Description: Indicates the number of minutes that the user expects to work on a task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008111

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.12

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLL\]](#), [\[MS-OXOPOST\]](#)

Alternate names: dispidTaskEstimatedEffort

2.310 PidLidTaskFCreator

Canonical name: PidLidTaskFCreator

Description: Indicates that the Task object was originally created by the action of the current user or user agent instead of by the processing of a task request.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811E

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.21

Alternate names: dispidTaskFCreator

2.311 PidLidTaskFFixOffline

Canonical name: PidLidTaskFFixOffline

Description: Indicates the accuracy of the **PidLidTaskOwner** property (section [2.322](#)).

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000812C

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.31

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskFFixOffline

2.312 PidLidTaskFRecurring

Canonical name: PidLidTaskFRecurring

Description: Indicates whether the task includes a recurrence pattern.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008126

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.28

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskFRecur

2.313 PidLidTaskGlobalId

Canonical name: PidLidTaskGlobalId

Description: Contains a unique GUID for this task, which is used to locate an existing task upon receipt of a task response or task update.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008519

Data type: PtypBinary, 0x0102

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.32

Alternate names: dispidTaskGlobalObjId

2.314 PidLidTaskHistory

Canonical name: PidLidTaskHistory

Description: Indicates the type of change that was last made to the Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811A

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.18

Alternate names: dispidTaskHistory

2.315 PidLidTaskLastDelegate

Canonical name: PidLidTaskLastDelegate

Description: Contains the name of the user who most recently assigned the task, or the user to whom it was most recently assigned.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008125

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.27

Alternate names: dispidTaskLastDelegate

2.316 PidLidTaskLastUpdate

Canonical name: PidLidTaskLastUpdate

Description: Contains the date and time of the most recent change made to the Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008115

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.10

Alternate names: dispidTaskLastUpdate

2.317 PidLidTaskLastUser

Canonical name: PidLidTaskLastUser

Description: Contains the name of the most recent user to have been the owner of the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008122

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.25

Alternate names: dispidTaskLastUser

2.318 PidLidTaskMode

Canonical name: PidLidTaskMode

Description: Specifies the assignment status of the embedded Task object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008518

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.3.2

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMMS\]](#)

Alternate names: dispidTaskMode

2.319 PidLidTaskMultipleRecipients

Canonical name: PidLidTaskMultipleRecipients

Description: Provides optimization hints about the recipients of a Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008120

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.23

Alternate names: dispidTaskMultRecips

2.320 PidLidTaskNoCompute

Canonical name: PidLidTaskNoCompute

Description: Not used. The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008124

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.35

Consuming reference: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskNoCompute

2.321 PidLidTaskOrdinal

Canonical name: PidLidTaskOrdinal

Description: Provides an aid to custom sorting of Task objects.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008123

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.26

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskOrdinal

2.322 PidLidTaskOwner

Canonical name: PidLidTaskOwner

Description: Contains the name of the owner of the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811F

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.22

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskOwner

2.323 PidLidTaskOwnership

Canonical name: PidLidTaskOwnership

Description: Indicates the role of the current user relative to the Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008129

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.29

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRLN\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskOwnership

2.324 PidLidTaskRecurrence

Canonical name: PidLidTaskRecurrence

Description: Contains a **RecurrencePattern** structure that provides information about **recurring tasks**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008116

Data type: PtypBinary, 0x0102

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.15

Consuming references: [\[MS-OXORMDR\]](#)

Alternate names: dispidTaskRecur

2.325 PidLidTaskResetReminder

Canonical name: PidLidTaskResetReminder

Description: Indicates whether future **instances** of recurring tasks need reminders, even though the value of the **PidLidReminderSet** property (section [2.216](#)) is 0x00.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008107

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.6

Consuming references: [\[MS-OXORMDR\]](#)

Alternate names: dispidTaskResetReminder

2.326 PidLidTaskRole

Canonical name: PidLidTaskRole

Description: Not used. The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008127

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.34

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskRole

2.327 PidLidTaskStartDate

Canonical name: PidLidTaskStartDate

Description: Specifies the date on which the user expects work on the task to begin.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008104

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.4

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidTaskStartDate

2.328 PidLidTaskState

Canonical name: PidLidTaskState

Description: Indicates the current assignment state of the Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008113

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.14

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskState

2.329 PidLidTaskStatus

Canonical name: PidLidTaskStatus

Description: Specifies the status of a task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008101

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.2

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD1\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

Alternate names: dispidTaskStatus

2.330 PidLidTaskStatusOnComplete

Canonical name: PidLidTaskStatusOnComplete

Description: Indicates whether the task assignee has been requested to send an e-mail message update upon completion of the assigned task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008119

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.17

Alternate names: dispidTaskSOC

2.331 PidLidTaskUpdates

Canonical name: PidLidTaskUpdates

Description: Indicates whether the task assignee has been requested to send a task update when the assigned Task object changes.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811B

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.19

Alternate names: dispidTaskUpdates

2.332 PidLidTaskVersion

Canonical name: PidLidTaskVersion

Description: Indicates which copy is the latest update of a Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008112

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.13

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskVersion

2.333 PidLidTeamTask

Canonical name: PidLidTeamTask

Description: This property is set by the client but is ignored by the server.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008103

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.36

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTeamTask

2.334 PidLidTimeZone

Canonical name: PidLidTimeZone

Description: Specifies information about the time zone of a recurring meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000C

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/time_zone

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.5.6

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: LID_TIME_ZONE

2.335 PidLidTimeZoneDescription

Canonical name: PidLidTimeZoneDescription

Description: Specifies a human-readable description of the time zone that is represented by the data in the **PidLidTimeZoneStruct** property (section [2.336](#)).

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008234

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/timezonedesc

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.40

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidTimeZoneDesc

2.336 PidLidTimeZoneStruct

Canonical name: PidLidTimeZoneStruct

Description: Specifies time zone information for a recurring meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008233

Data type: PtypBinary, 0x0102

WebDAV: http://schemas.microsoft.com/mapi/timezonestruct

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.39

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidTimeZoneStruct

2.337 PidLidToAttendeesString

Canonical name: PidLidToAttendeesString

Description: Contains a list of all of the sendable attendees who are also required attendees.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823B

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.17

Alternate names: dispidToAttendeesString

2.338 PidLidToDoOrdinalDate

Canonical name: PidLidToDoOrdinalDate

Description: Contains the current time, in UTC, which is used to determine the sort order of objects in a consolidated to-do list.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085A0

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.13

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: dispidToDoOrdinalDate

2.339 PidLidToDoSubOrdinal

Canonical name: PidLidToDoSubOrdinal

Description: Contains the numerals 0 through 9 that are used to break a tie when the **PidLidToDoOrdinalDate** property (section [2.338](#)) is used to perform a sort of objects.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085A1

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.14

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: dispidToDoSubOrdinal

2.340 PidLidToDoTitle

Canonical name: PidLidToDoTitle

Description: Contains user-specifiable text to identify this Message object in a consolidated to-do list.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085A4

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.12

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#)

Alternate names: dispidToDoTitle

2.341 PidLidTrustRecipientHighlights

Canonical name: PidLidTrustRecipientHighlights

Description:

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823E

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference:

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: dispidTrustRecipHighlights

2.342 PidLidUseTnef

Canonical name: PidLidUseTnef

Description: Specifies whether **Transport Neutral Encapsulation Format (TNEF)** is to be included on a message when the message is converted from TNEF to **MIME** or SMTP format.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008582

Data type: PtypBoolean, 0x000B

Area: Run-time configuration

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.57

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: dispidUseTNEF

2.343 PidLidValidFlagStringProof

Canonical name: PidLidValidFlagStringProof

Description: Contains the value of the **PidTagMessageDeliveryTime** property (section [2.845](#)) when modifying the **PidLidFlagRequest** property (section [2.131](#)).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085BF

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.11

Consuming references: [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidValidFlagStringProof

2.344 PidLidVerbResponse

Canonical name: PidLidVerbResponse

Description: Specifies the voting option that a respondent has selected.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008524

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.66

Alternate names: dispidVerbResponse

2.345 PidLidVerbStream

Canonical name: PidLidVerbStream

Description: Specifies what voting responses the user can make in response to the message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008520

Data type: PtypBinary, 0x0102

Area: Run-time configuration

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.65

Alternate names: dispidVerbStream

2.346 PidLidWeddingAnniversaryLocal

Canonical name: PidLidWeddingAnniversaryLocal

Description: Specifies the wedding anniversary of the contact, at 0:00 in the client's local time zone, and is saved without any time zone conversions.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DF

Data type: PtypTime, 0x0040

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.5.5

Alternate names: dispidApptAnniversaryLocal

2.347 PidLidWeekInterval

Canonical name: PidLidWeekInterval

Description: Identifies the number of weeks that occur between each meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000012

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/week_interval

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.71

Consuming references: [\[MS-OXOCAL\]](#)

Alternate names: LID_WEEK_INTERVAL

2.348 PidLidWhere

Canonical name: PidLidWhere

Description: Contains the value of the **PidLidLocation** property (section [2.153](#)) from the associated Meeting object.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000002

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/where

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.5.3

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: LID_WHERE

2.349 PidLidWorkAddress

Canonical name: PidLidWorkAddress

Description: Specifies the complete address of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-00000000046}

Property long ID (LID): 0x0000801B

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:workaddress

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddress

2.350 PidLidWorkAddressCity

Canonical name: PidLidWorkAddressCity

Description: Specifies the city or locality portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-00000000046}

Property long ID (LID): 0x00008046

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:l

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.2

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressCity

2.351 PidLidWorkAddressCountry

Canonical name: PidLidWorkAddressCountry

Description: Specifies the country or region portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-00000000046}

Property long ID (LID): 0x00008049

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:co

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.5

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressCountry

2.352 PidLidWorkAddressCountryCode

Canonical name: PidLidWorkAddressCountryCode

Description: Specifies the country code portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DB

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

Alternate names: dispidWorkAddressCountryCode

2.353 PidLidWorkAddressPostalCode

Canonical name: PidLidWorkAddressPostalCode

Description: Specifies the postal code (ZIP code) portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008048

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:postalcode

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.4

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressPostalCode

2.354 PidLidWorkAddressPostOfficeBox

Canonical name: PidLidWorkAddressPostOfficeBox

Description: Specifies the post office box portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C00-000000000046}

Property long ID (LID): 0x0000804A

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:postofficebox

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.7

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressPostOfficeBox

2.355 PidLidWorkAddressState

Canonical name: PidLidWorkAddressState

Description: Specifies the state or province portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-00000000046}

Property long ID (LID): 0x00008047

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:st

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.3

Consuming references: [\[MS-XWDCNTC\]](#)

Alternate names: dispidWorkAddressState

2.356 PidLidWorkAddressStreet

Canonical name: PidLidWorkAddressStreet

Description: Specifies the street portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-00000000046}

Property long ID (LID): 0x00008045

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:street

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.1

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressStreet

2.357 PidLidYearInterval

Canonical name: PidLidYearInterval

Description: Indicates the yearly interval of the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000014

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/year_interval

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.73

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: LID_YEAR_INTERVAL

2.358 PidLidYomiCompanyName

Canonical name: PidLidYomiCompanyName

Description: Specifies the phonetic pronunciation of the contact's company name.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802E

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/yomiorganization

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.6.8

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: dispidYomiCompanyName

2.359 PidLidYomiFirstName

Canonical name: PidLidYomiFirstName

Description: Specifies the phonetic pronunciation of the contact's given name.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802C

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/yomifirstname

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.1.9

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: dispidYomiFirstName

2.360 PidLidYomiLastName

Canonical name: PidLidYomiLastName

Description: Specifies the phonetic pronunciation of the contact's surname.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802D

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/yomilastname

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.1.10

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: dispidYomiLastName

2.361 PidNameAcceptLanguage

Canonical name: PidNameAcceptLanguage

Description: Contains the value of the MIME Accept-Language header.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Accept-Language

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.42

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: AcceptLanguage

2.362 PidNameApplicationName

Canonical name: PidNameApplicationName

Description: Specifies the application used to open the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: AppName

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.9

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#NameOfApplication

2.363 PidNameApprovalAllowedDecisionMakers

Canonical name: PidNameApprovalAllowedDecisionMakers

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-Approval-Allowed-Decision-Makers

Data type: PtypString, 0x001F

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMSExchangeOrganizationDecisionMakers

2.364 PidNameApprovalRequestor

Canonical name: PidNameApprovalRequestor

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-Approval-Requestor

Data type: PtypString, 0x001F

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMSExchangeOrganizationApprovalRequestor

2.365 PidNameApproved

Canonical name: PidNameApproved

Description: Specifies the address of the moderator that approved and posted a message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Approved

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.1

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:approved

2.366 PidNameAttachmentMacContentType

Canonical name: PidNameAttachmentMacContentType

Description: Contains the Content-Type of the Mac attachment.

Property set: PSETID_Attachment {96357f7f-59e1-47d0-99a7-46515c183b54}

Property name: AttachmentMacContentType

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.26

Consuming reference: [\[MS-OXCMAIL\]](#)

2.367 PidNameAttachmentMacInfo

Canonical name: PidNameAttachmentMacInfo

Description: Contains the headers and resource fork data associated with the Mac attachment.

Property set: PSETID_Attachment {96357f7f-59e1-47d0-99a7-46515c183b54}

Property name: AttachmentMacInfo

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.26

Consuming reference: [\[MS-OXCMAIL\]](#)

2.368 PidNameAudioNotes

Canonical name: PidNameAudioNotes

Description: Contains textual annotations to a voice message after it has been delivered to the user's mailbox.

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: UMAudioNotes

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.1.4

Alternate names: UMAudioNotes

2.369 PidNameAuthenticatedAs

Canonical name: PidNameAuthenticatedAs

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-AuthAs

Data type: PtypString, 0x001F

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchOrganizationAuthAs

2.370 PidNameAuthenticatedDomain

Canonical name: PidNameAuthenticatedDomain

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-AuthDomain

Data type: PtypString, 0x001F

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchOrganizationAuthDomain

2.371 PidNameAuthenticatedMechanism

Canonical name: PidNameAuthenticatedMechanism

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-AuthMechanism

Data type: PtypString, 0x001F

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchOrganizationAuthMechanism

2.372 PidNameAuthenticatedSource

Canonical name: PidNameAuthenticatedSource

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-AuthSource

Data type: PtypString, 0x001F

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchOrganizationAuthSource

2.373 PidNameAuthor

Canonical name: PidNameAuthor

Description: Specifies the author of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Author

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.3

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Author

2.374 PidNameAutomaticSpeechRecognitionData

Canonical name: PidNameAutomaticSpeechRecognitionData

Description: Contains an unprotected voice message.

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: AsrData

Data type: PtypBinary, 0x0102

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.1.5

2.375 PidNameBcc

Canonical name: PidNameBcc

Description: Specifies the blind carbon copy addressees of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Bcc

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.2

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:bcc

2.376 PidNameByteCount

Canonical name: PidNameByteCount

Description: Specifies the size, in bytes, of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: ByteCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.22

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Bytes

2.377 PidNameCalendarAttendeeRole

Canonical name: PidNameCalendarAttendeeRole

Description: Specifies the role of the attendee.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:attendeerole

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.7

Alternate names: urn:schemas:calendar:attendeerole

2.378 PidNameCalendarBusystatus

Canonical name: PidNameCalendarBusystatus

Description: Specifies whether the attendee is busy at the time of an appointment on their calendar.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:busystatus

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.8

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:busystatus

2.379 PidNameCalendarContact

Canonical name: PidNameCalendarContact

Description: Identifies the name of a contact who is an attendee of a meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:contact

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.9

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:contact

2.380 PidNameCalendarContactUrl

Canonical name: PidNameCalendarContactUrl

Description: Identifies the URL where you can access contact information in **HTML** format.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:contacturl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.10

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:contacturl

2.381 PidNameCalendarCreated

Canonical name: PidNameCalendarCreated

Description: Identifies the date and time, in UTC, that the organizer created the appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:created

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.11

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:created

2.382 PidNameCalendarDescriptionUrl

Canonical name: PidNameCalendarDescriptionUrl

Description: Specifies the URL of a resource that contains a description of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:descriptionurl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.12

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:descriptionurl

2.383 PidNameCalendarDuration

Canonical name: PidNameCalendarDuration

Description: Identifies the duration, in seconds, of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:duration

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.13

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:duration

2.384 PidNameCalendarExceptionDate

Canonical name: PidNameCalendarExceptionDate

Description: Identifies a list of dates that are exceptions to a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:exdate

Data type: PtypMultipleTime, 0x1040

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.14

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:exdate

2.385 PidNameCalendarExceptionRule

Canonical name: PidNameCalendarExceptionRule

Description: Specifies an exception rule for a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:exrule

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.15

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:exrule

2.386 PidNameCalendarGeoLatitude

Canonical name: PidNameCalendarGeoLatitude

Description: Specifies the geographical latitude of the location of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:geolatitude

Data type: PtypFloating64, 0x0005

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.16

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:geolatitude

2.387 PidNameCalendarGeoLongitude

Canonical name: PidNameCalendarGeoLongitude

Description: Specifies the geographical longitude of the location of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:geolongitude

Data type: PtypFloating64, 0x0005

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.17

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:geolongitude

2.388 PidNameCalendarInstanceType

Canonical name: PidNameCalendarInstanceType

Description: Specifies the type of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:instancetype

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.18

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:instancetype

2.389 PidNameCalendarIsOrganizer

Canonical name: PidNameCalendarIsOrganizer

Description: Specifies whether an attendee is the organizer of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:isorganizer

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.19

Alternate names: urn:schemas:calendar:isorganizer

2.390 PidNameCalendarLastModified

Canonical name: PidNameCalendarLastModified

Description: Specifies the date and time, in UTC, when an appointment was last modified.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:lastmodified

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.20

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:lastmodified

2.391 PidNameCalendarLocationUrl

Canonical name: PidNameCalendarLocationUrl

Description: Specifies a URL with location information in HTML format.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:locationurl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.21

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:locationurl

2.392 PidNameCalendarMeetingStatus

Canonical name: PidNameCalendarMeetingStatus

Description: Specifies the status of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:meetingstatus

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.22

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:meetingstatus

2.393 PidNameCalendarMethod

Canonical name: PidNameCalendarMethod

Description: Specifies the iCalendar method that is associated with an Appointment object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:method

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.23

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:method

2.394 PidNameCalendarProductId

Canonical name: PidNameCalendarProductId

Description: Identifies the product that created the iCalendar-formatted stream.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:prodid

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.24

Alternate names: urn:schemas:calendar:prodid

2.395 PidNameCalendarRecurrenceIdRange

Canonical name: PidNameCalendarRecurrenceIdRange

Description: Specifies which instances of a recurring appointment are being referred to.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:recurrenceidrange

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.25

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:recurrenceidrange

2.396 PidNameCalendarReminderOffset

Canonical name: PidNameCalendarReminderOffset

Description: Identifies the number of seconds before an appointment starts that a reminder is to be displayed.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:reminderoffset

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.26

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:reminderoffset

2.397 PidNameCalendarResources

Canonical name: PidNameCalendarResources

Description: Identifies a list of resources, such as rooms and video equipment, that are available for an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:resources

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.27

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:resources

2.398 PidNameCalendarRsvp

Canonical name: PidNameCalendarRsvp

Description: Specifies whether the organizer of an appointment or meeting requested a response.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:rsvp

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.28

Alternate names: urn:schemas:calendar:rsvp

2.399 PidNameCalendarSequence

Canonical name: PidNameCalendarSequence

Description: Specifies the sequence number of a version of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:sequence

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.29

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:sequence

2.400 PidNameCalendarTimeZone

Canonical name: PidNameCalendarTimeZone

Description: Specifies the time zone of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:timezone

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.30

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:timezone

2.401 PidNameCalendarTimeZoneId

Canonical name: PidNameCalendarTimeZoneId

Description: Specifies the time zone identifier of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:timezoneid

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.31

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:timezoneid

2.402 PidNameCalendarTransparent

Canonical name: PidNameCalendarTransparent

Description: Specifies whether an appointment or meeting is visible to busy time searches.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:transparent

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.32

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:transparent

2.403 PidNameCalendarUid

Canonical name: PidNameCalendarUid

Description: Specifies the unique identifier of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:uid

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.33

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:uid

2.404 PidNameCalendarVersion

Canonical name: PidNameCalendarVersion

Description: Identifies the version of the iCalendar specification that is required to correctly interpret an iCalendar object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:version

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.34

Alternate names: urn:schemas:calendar:version

2.405 PidNameCategory

Canonical name: PidNameCategory

Description: Specifies the category of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Category

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.18

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Category

2.406 PidNameCc

Canonical name: PidNameCc

Description: Specifies the carbon copy addressees of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Cc

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.3

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:cc

2.407 PidNameCharacterCount

Canonical name: PidNameCharacterCount

Description: Specifies the character count of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: CharCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.16

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Characters

2.408 PidNameComments

Canonical name: PidNameComments

Description: Specifies the comments of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Comments

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.5

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Comments

2.409 PidNameCompany

Canonical name: PidNameCompany

Description: Specifies the company for which the file was created.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Company

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.21

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Company

2.410 PidNameContactsAlternateRecipient

Canonical name: PidNameContactsAlternateRecipient

Description: Specifies a secondary e-mail address of the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:alternaterecipient

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.13

Alternate names: urn:schemas:contacts:alternaterecipient

2.411 PidNameContactsCountry

Canonical name: PidNameContactsCountry

Description: Specifies the country/region code for the contact's work address.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:c

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.14

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:c

2.412 PidNameContactsEmail1

Canonical name: PidNameContactsEmail1

Description: Specifies the primary address of the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:email1

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.15

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:email1

2.413 PidNameContactsEmail2

Canonical name: PidNameContactsEmail2

Description: Specifies a secondary e-mail address of the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:email2

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.16

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:email2

2.414 PidNameContactsEmail3

Canonical name: PidNameContactsEmail3

Description: Specifies a third e-mail address of the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:email3

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.17

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:email3

2.415 PidNameContactsFileAs

Canonical name: PidNameContactsFileAs

Description: Specifies the contact information in the format in which it is to be displayed.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:fileas

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.18

Alternate names: urn:schemas:contacts:fileas

2.416 PidNameContactsFileasId

Canonical name: PidNameContactsFileasId

Description: Specifies a numeric value that determines how the contact information is displayed.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:fileasid

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.19

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:fileasid

2.417 PidNameContactsHomeLatitude

Canonical name: PidNameContactsHomeLatitude

Description: Specifies the latitude of the contact's home address.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:homelatitude

Data type: PtypFloating64, 0x0005

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.20

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:homelatitude

2.418 PidNameContactsHomeLongitude

Canonical name: PidNameContactsHomeLongitude

Description: Specifies the longitude of the contact's home address.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:homelongitude

Data type: PtypFloating64, 0x0005

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.21

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:homelongitude

2.419 PidNameContactsHomeTimeZone

Canonical name: PidNameContactsHomeTimeZone

Description: Specifies the time zone of the contact's home address.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:hometimezone

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.22

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:hometimezone

2.420 PidNameContactsMapUrl

Canonical name: PidNameContactsMapUrl

Description: Specifies the map URL for the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:mapurl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.23

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:mapurl

2.421 PidNameContactsOtherCountryCode

Canonical name: PidNameContactsOtherCountryCode

Description: Specifies an alternative, two-letter country/region code for the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:othercountrycode

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.24

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:othercountrycode

2.422 PidNameContactsOtherPager

Canonical name: PidNameContactsOtherPager

Description: Specifies a pager telephone number for the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:otherpager

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.25

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:otherpager

2.423 PidNameContactsOtherTimeZone

Canonical name: PidNameContactsOtherTimeZone

Description: Specifies an alternate time zone for the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:othertimezone

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.26

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:othertimezone

2.424 PidNameContactsProxyAddresses

Canonical name: PidNameContactsProxyAddresses

Description: Specifies one or more of the contact's e-mail addresses.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:proxyaddresses

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.27

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:proxyaddresses

2.425 PidNameContactsSecretaryUrl

Canonical name: PidNameContactsSecretaryUrl

Description: Specifies the URL to the contact's secretary.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:secretaryurl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.28

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:secretaryurl

2.426 PidNameContactsSourceUrl

Canonical name: PidNameContactsSourceUrl

Description: Specifies the URL of the source from which the contact's information was obtained.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:sourceurl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.29

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:sourceurl

2.427 PidNameContentBase

Canonical name: PidNameContentBase

Description: Specifies the value of the MIME Content-Base header, which defines the base URI for resolving relative URLs contained within the message body.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Base

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.41

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: BodyContentBase

2.428 PidNameContentClass

Canonical name: PidNameContentClass

Description: Indicates the intent of an e-mail message based on the context of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Class

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6.1

Consuming references: [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOUM\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDSTRUCTDOC\]](#)

Alternate names: DAV:contentclassDAV:contentclass, urn:schemas:mailheader:content-class

2.429 PidNameContentDisposition

Canonical name: PidNameContentDisposition

Description: Specifies the intended disposition of the **body part**.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Disposition

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.6

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-disposition

2.430 PidNameContentID

Canonical name: PidNameContentID

Description: Specifies a unique identifier for the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-ID

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.7

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-id

2.431 PidNameContentLanguage

Canonical name: PidNameContentLanguage

Description: Specifies the language identifier for the text content of the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Language

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.8

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-language

2.432 PidNameContentLocation

Canonical name: PidNameContentLocation

Description: Specifies the **Uniform Resource Identifier (URI)** that corresponds to the content of the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Location

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.9

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-location

2.433 PidNameContentTransferEncoding

Canonical name: PidNameContentTransferEncoding

Description: Specifies the encoding mechanism used to encode the content of the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Transfer-Encoding

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.10

Alternate names: urn:schemas:mailheader:content-transfer-encoding

2.434 PidNameContentType

Canonical name: PidNameContentType

Description: Specifies the type of the body part's content.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Type

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.11

Consuming reference: [\[MS-OXCMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-type

2.435 PidNameControl

Canonical name: PidNameControl

Description: Specifies a Usenet control command.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-00000000046}

Property name: Control

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.12

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:control

2.436 PidNameCreateDateTimeReadOnly

Canonical name: PidNameCreateDateTimeReadOnly

Description: Specifies the time, in UTC, that the file was first created.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-00000000046}

Property name: CreateDtmRo

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.12

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Created

2.437 PidNameCrossReference

Canonical name: PidNameCrossReference

Description: Contains the name of the host (with **domains** omitted) and a white-space-separated list of colon-separated pairs of newsgroup names and message numbers.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-00000000046}

Property name: Xref

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.51

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:xref

2.438 PidNameDavGetContentType

Canonical name: PidNameDavGetContentType

Description: Specifies the type of the Message object's content.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:getcontenttype

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.1.3

2.439 PidNameDavId

Canonical name: PidNameDavId

Description: Specifies a unique ID for the calendar item.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:id

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.1.2

Consuming reference: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:id

2.440 PidNameDavIsCollection

Canonical name: PidNameDavIsCollection

Description: Indicates whether a Calendar object is a collection.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:iscollection

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.1.3

Consuming references: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:iscollection

2.441 PidNameDavIsStructuredDocument

Canonical name: PidNameDavIsStructuredDocument

Description: Indicates whether a Calendar object is a structured document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:isstructureddocument

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.1.4

Consuming references: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:isstructureddocument

2.442 PidNameDavParentName

Canonical name: PidNameDavParentName

Description: Specifies the name of the Folder object that contains the Calendar object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:parentname

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.1.5

Consuming references: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:parentname

2.443 PidNameDav ResourceType

Canonical name: PidNameDavResourceType

Description: Specifies that the **Folder object** is a search folder.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:resourcetype

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDSEARCH\]](#) section 2.2.3.3

Consuming references: [\[MS-XWDEXT\]](#), [\[MS-XWDSTRUCTDOC\]](#)

Alternate names: DAV:resourcetype

2.444 PidNameDavSearchRequest

Canonical name: PidNameDavSearchRequest

Description: Indicates the search that the search folder performs.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:searchrequest

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDSEARCH\]](#) section 2.2.3.1

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: DAV:searchrequest

2.445 PidNameDavSearchType

Canonical name: PidNameDavSearchType

Description: Indicates the type of search that the search folder performs.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:searchtype

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDSEARCH\]](#) section 2.2.3.2

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: DAV:searchtype

2.446 PidNameDavUid

Canonical name: PidNameDavUid

Description: Specifies the unique identifier for an item.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:uid

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.1.6

Consuming references: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:uid

2.447 PidNameDisposition

Canonical name: PidNameDisposition

Description: Specifies the Mail Delivery Notification (MDN) status for the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Disposition

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.14

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:disposition

2.448 PidNameDispositionNotificationTo

Canonical name: PidNameDispositionNotificationTo

Description: Specifies the destination to which disposition notifications should be sent.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Disposition-Notification-To

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.15

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:disposition-notification-to

2.449 PidNameDistribution

Canonical name: PidNameDistribution

Description: Contains a comma-separated list, similar to the Newsgroups header field, which is intended to restrict the distribution of a message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Distribution

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.16

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:distribution

2.450 PidNameDocumentParts

Canonical name: PidNameDocumentParts

Description: Specifies the title of each part of the document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DocParts

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.29

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#PartTitles

2.451 PidNameEditTime

Canonical name: PidNameEditTime

Description: Specifies the time that the file was last edited.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: EditTime

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.10

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#TotalTime

2.452 PidNameExchangeIntendedBusyStatus

Canonical name: PidNameExchangeIntendedBusyStatus

Description: Specifies the busy status of the user during an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/intendedbusystatus

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.1

Alternate names: http://schemas.microsoft.com/exchange/intendedbusystatus

2.453 PidNameExchangeJunkEmailMoveStamp

Canonical name: PidNameExchangeJunkEmailMoveStamp

Description: Indicates that the message is not to be processed by a **spam filter**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/junkemailmovestamp

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.1.2

Consuming reference: [\[MS-OXORSS\]](#)

Alternate names: http://schemas.microsoft.com/exchange/junkemailmovestamp

2.454 PidNameExchangeModifyExceptionStructure

Canonical name: PidNameExchangeModifyExceptionStructure

Description: Specifies a structure that modifies an exception to the recurrence.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/modifyexceptionstruct

Data type: PtypBinary, 0x0102

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.2

Alternate names: http://schemas.microsoft.com/exchange/modifyexceptionstruct

2.455 PidNameExchangeNoModifyExceptions

Canonical name: PidNameExchangeNoModifyExceptions

Description: Indicates whether exceptions to a recurring appointment can be modified.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/nomodifyexceptions

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.3

Alternate names: http://schemas.microsoft.com/exchange/nomodifyexceptions

2.456 PidNameExchangePatternEnd

Canonical name: PidNameExchangePatternEnd

Description: Identifies the maximum time when an instance of a recurring appointment ends.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/patternend

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.4

Alternate names: http://schemas.microsoft.com/exchange/patternend

2.457 PidNameExchangePatternStart

Canonical name: PidNameExchangePatternStart

Description: Identifies the absolute minimum time when an instance of a recurring appointment starts.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/patternstart

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.5

Alternate names: http://schemas.microsoft.com/exchange/patternstart

2.458 PidNameExchangePublicFolderEmailAddress

Canonical name: PidNameExchangePublicFolderEmailAddress

Description:

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/publicfolderemailaddress

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDFOLD\]](#) section 2.2.7

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: http://schemas.microsoft.com/exchange/publicfolderemailaddress

2.459 PidNameExchangeReminderInterval

Canonical name: PidNameExchangeReminderInterval

Description: Identifies the time, in seconds, between reminders.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/reminderinterval

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.6

Consuming reference: [MS-XWDCAL]

Alternate names: http://schemas.microsoft.com/exchange/reminderinterval

2.460 PidNameExchDatabaseSchema

Canonical name: PidNameExchDatabaseSchema

Description: Specifies an array of URLs that identifies other folders within the same store that contain schema definition items.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas-microsoft-com:exch-data:baseschema

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.5.1

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas-microsoft-com:exch-data:baseschema

2.461 PidNameExchDataExpectedContentClass

Canonical name: PidNameExchDataExpectedContentClass

Description: Specifies an array of names that indicates the expected content **classes** of items within a folder.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas-microsoft-com:exch-data:expected-content-class

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.5.2

Consuming references: [\[MS-XWDEXT\]](#), [\[MS-XWDSEARCH\]](#)

Alternate names: urn:schemas-microsoft-com:exch-data:expected-content-class

2.462 PidNameExchDataSchemaCollectionReference

Canonical name: PidNameExchDataSchemaCollectionReference

Description: Specifies an array of names that indicates the expected content classes of items within a folder.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas-microsoft-com:exch-data:schema-collection-ref

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.5.3

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas-microsoft-com:exch-data:schema-collection-ref

2.463 PidNameExpires

Canonical name: PidNameExpires

Description: This property specifies the date on which the message expires.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Expires

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.17

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:expires

2.464 PidNameExpiryDate

Canonical name: PidNameExpiryDate

Description: This property specifies the expiry date of a message in an e-mail header.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Expiry-Date

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.18

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:expiry-date

2.465 PidNameFollowupTo

Canonical name: PidNameFollowupTo

Description: This property specifies the newsgroups to which follow-up messages are to be posted.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Followup-To

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.19

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:followup-to

2.466 PidNameFrom

Canonical name: PidNameFrom

Description: Specifies the SMTP e-mail **alias** of the organizer of an appointment or meeting.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: From

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.35

Consuming reference: [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:calendar:organizer

2.467 PidNameHeadingPairs

Canonical name: PidNameHeadingPairs

Description: Specifies which group of headings are indented in the document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: HeadingPairs

Data type: PtypBinary, 0x0102

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.30

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#HeadingPairs

2.468 PidNameHiddenCount

Canonical name: PidNameHiddenCount

Description: Specifies the hidden value of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: HiddenCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.27

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#HiddenSlides

2.469 PidNameHttpmailCalendar

Canonical name: PidNameHttpmailCalendar

Description: Specifies the URL for the Calendar folder for a particular user.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:calendar

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.3.1

Alternate names: urn:schemas:httpmail:calendar

2.470 PidNameHttpmailCc

Canonical name: PidNameHttpmailCc

Description: Specifies the **carbon copy (Cc) recipients** of the message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:cc

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.2

Alternate names: urn:schemas:httpmail:cc

2.471 PidNameHttpmailContacts

Canonical name: PidNameHttpmailContacts

Description:

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:contacts

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.4.1

Alternate names: urn:schemas:httpmail:contacts

2.472 PidNameHttpmailContentMediaType

Canonical name: PidNameHttpmailContentMediaType

Description: Specifies the content media type for the body part.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:content-media-type

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.3

Alternate names: urn:schemas:httpmail:content-media-type

2.473 PidNameHttpmailFrom

Canonical name: PidNameHttpmailFrom

Description: Specifies the person from whom the message was sent.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:from

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.8

Alternate names: urn:schemas:httpmail:from

2.474 PidNameHttpmailFromEmail

Canonical name: PidNameHttpmailFromEmail

Description: Specifies the e-mail address from which the message was sent.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:fromemail

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.9

Alternate names: urn:schemas:httpmail:fromemail

2.475 PidNameHttpmailHtmlDescription

Canonical name: PidNameHttpmailHtmlDescription

Description: Specifies the HTML content of the message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:htmldescription

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.3.2

Consuming references: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:httpmail:htmldescription

2.476 PidNameHttpmailOutbox

Canonical name: PidNameHttpmailOutbox

Description:

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:outbox

Data type: PtypString, 0x001F

Area: Common

Defining reference:

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:httpmail:outbox

2.477 PidNameHttpmailSendMessage

Canonical name: PidNameHttpmailSendMessage

Description: Specifies the e-mail submission URI to which outgoing e-mail is submitted.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:sendmsg

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.3.3

Consuming reference: [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:httpmail:sendmsg

2.478 PidNameHttpmailSubmitted

Canonical name: PidNameHttpmailSubmitted

Description: Specifies whether a message has been submitted to the **Outbox folder**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:submitted

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.20

Alternate names: urn:schemas:httpmail:submitted

2.479 PidNameHttpmailTo

Canonical name: PidNameHttpmailTo

Description: Specifies the principle (To) message addressees.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:to

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.23

Alternate names: urn:schemas:httpmail:to

2.480 PidNameICalendarRecurrenceDate

Canonical name: PidNameICalendarRecurrenceDate

Description: Identifies an array of instances of a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:rdate

Data type: PtypMultipleTime, 0x1040

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.36

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:rdate

2.481 PidNameICalendarRecurrenceRule

Canonical name: PidNameICalendarRecurrenceRule

Description: Specifies the rule for the pattern that defines a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:rrule

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.37

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:rrule

2.482 PidNameImportance

Canonical name: PidNameImportance

Description: Indicates the level of importance for a message as either low, normal, or high.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Importance

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.13

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:importance

2.483 PidNameInReplyTo

Canonical name: PidNameInReplyTo

Description: Specifies the message to which another message is a reply.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: In-Reply-To

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.22

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:in-reply-to

2.484 PidNameInternetComment

Canonical name: PidNameInternetComment

Description: Contains a comment about the purpose or content of the folder.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-00000000046}

Property name: Comment

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.4

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:comment

2.485 PidNameInternetKeywords

Canonical name: PidNameInternetKeywords

Description: Specifies the key words for the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-00000000046}

Property name: Keywords

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.23

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:keywords

2.486 PidNameInternetSubject

Canonical name: PidNameInternetSubject

Description: Specifies the subject of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-00000000046}

Property name: Subject

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.4.1

Consuming reference: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:subject

2.487 PidNameKeywords

Canonical name: PidNameKeywords

Description: Contains keywords or categories for the Message object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Keywords

Data type: PtypMultipleString, 0x101F

Area: General Message Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.17

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXONOTE\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Keywords,
http://schemas.microsoft.com/exchange/keywords-utf8

2.488 PidNameLastAuthor

Canonical name: PidNameLastAuthor

Description: Specifies the most recent author of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LastAuthor

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.7

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#LastAuthor

2.489 PidNameLastPrinted

Canonical name: PidNameLastPrinted

Description: Specifies the time, in UTC, that the file was last printed.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LastPrinted

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.11

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#LastPrinted

2.490 PidNameLastSaveDateTime

Canonical name: PidNameLastSaveDateTime

Description: Specifies the time, in UTC, that the file was last saved.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LastSaveDtm

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.13

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#LastSaved

2.491 PidNameLineCount

Canonical name: PidNameLineCount

Description: Specifies the number of lines in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LineCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.23

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Lines

2.492 PidNameLines

Canonical name: PidNameLines

Description: Specifies the number of lines in the body of a newsgroup message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Lines

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.24

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:lines

2.493 PidNameLinksDirty

Canonical name: PidNameLinksDirty

Description: Indicates whether the links in the document are up-to-date.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LinksDirty

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.31

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#LinksUpToDate

2.494 PidNameLocationUrl

Canonical name: PidNameLocationUrl

Description:

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:locationurl

Data type: PtypString, 0x001F

Area: Calendar

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: urn:schemas:calendar:locationurl, LocationUrl

2.495 PidNameMailSubmissionUri

Canonical name: PidNameMailSubmissionUri

Description: Specifies the URI that is used for e-mail submissions.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: MAIL:submissionuri

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.4.1

2.496 PidNameManager

Canonical name: PidNameManager

Description: Specifies the manager of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Manager

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.20

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Manager

2.497 PidNameMessageId

Canonical name: PidNameMessageId

Description: Specifies a unique identifier for the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Message-ID

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.25

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:message-id

2.498 PidNameMimeType

Canonical name: PidNameMimeType

Description: Specifies the version of Multipurpose Internet Mail Extensions (MIME) that is used to format the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Mime-Version

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.26

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:mime-version

2.499 PidNameMultimediaClipCount

Canonical name: PidNameMultimediaClipCount

Description: Specifies the number of multimedia clips in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: MMClipCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.28

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#MultimediaClips

2.500 PidNameNewsgroups

Canonical name: PidNameNewsgroups

Description: Specifies the newsgroup addressees for the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Newsgroups

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.27

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:newsgroups

2.501 PidNameNntpPostingHost

Canonical name: PidNameNntpPostingHost

Description: Specifies the initial host to which the USENET feed was posted.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: NNTP-Posting-Host

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.28

Alternate names: urn:schemas:mailheader:nntp-posting-host

2.502 PidNameNoteCount

Canonical name: PidNameNoteCount

Description: Specifies the number of notes in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: NoteCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.26

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Notes

2.503 PidNameOMSAccountGuid

Canonical name: PidNameOMSAccountGuid

Description: Contains the GUID of the **SMS** account used to deliver the message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSAccountGuid

Data type: PtypString, 0x001F

Area: SMS

Defining reference: [\[MS-OXOSMMS\]](#) section 2.2.1.1

2.504 PidNameOMSMobileModel

Canonical name: PidNameOMSMobileModel

Description: Indicates the model of the mobile device used to send the SMS or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSMobileModel

Data type: PtypString, 0x001F

Area: SMS

Defining reference: [\[MS-OXOSMMS\]](#) section 2.2.1.6

2.505 PidNameOMSScheduleTime

Canonical name: PidNameOMSScheduleTime

Description: Contains the time, in UTC, at which the client requested that the service provider send the SMS or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSScheduleTime

Data type: PtypTime, 0x0040

Area: SMS

Defining reference: [\[MS-OXOSMMS\]](#) section 2.2.1.2

2.506 PidNameOMSServiceType

Canonical name: PidNameOMSServiceType

Description: Contains the type of service used to send an SMS or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSServiceType

Data type: PtypInteger32, 0x0003

Area: SMS

Defining reference: [\[MS-OXOSMMS\]](#) section 2.2.1.3

2.507 PidNameOMSSourceType

Canonical name: PidNameOMSSourceType

Description: Contains the source of an SMS or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSSourceType

Data type: PtypInteger32, 0x0003

Area: SMS

Defining reference: [\[MS-OXOSMMS\]](#) section 2.2.1.4

2.508 PidNameOrganization

Canonical name: PidNameOrganization

Description: Specifies the organization to which the sender belongs.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Organization

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.29

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:organization

2.509 PidNameOriginalRecipient

Canonical name: PidNameOriginalRecipient

Description: Specifies the e-mail address of an original recipient of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Original-Recipient

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.30

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:original-recipient

2.510 PidNameOriginalSpamConfidenceLevel

Canonical name: PidNameOriginalSpamConfidenceLevel

Description:

Property set: PSETID_Messaging {41F28F13-83F4-4114-A584-EEDB5A6B0BFF}

Property name: OriginalScl

Data type: PtypInteger32, 0x0003

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: OriginalScl

2.511 PidNameOutlookProtectionRuleOverridden

Canonical name: PidNameOutlookProtectionRuleOverridden

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-Outlook-Protection-Rule-Overridden

Data type: PtypString, 0x001F

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMSEmailProtectionRuleOverridden

2.512 PidNameOutlookProtectionRuleTimestamp

Canonical name: PidNameOutlookProtectionRuleTimestamp

Description:

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-Organization-Outlook-Protection-Rule-Config-Timestamp

Data type: PtypString, 0x001F

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMSEmailProtectionRuleConfigTimestamp

2.513 PidNameOutlookProtectionRuleVersion

Canonical name: PidNameOutlookProtectionRuleVersion

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-Outlook-Protection-Rule-Addin-Version

Data type: PtypString, 0x001F

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMSEmailProtectionRuleVersion

2.514 PidNamePageCount

Canonical name: PidNamePageCount

Description: Specifies the page count of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: PageCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.14

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Pages

2.515 PidNameParagraphCount

Canonical name: PidNameParagraphCount

Description: Specifies the number of paragraphs in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: ParCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.24

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Paragraphs

2.516 PidNamePath

Canonical name: PidNamePath

Description: Specifies the list of **Network News Transfer Protocol (NNTP)** hosts through which this message was relayed before arriving at the current host.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Path

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.31

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:path

2.517 PidNamePhishingStamp

Canonical name: PidNamePhishingStamp

Description: Indicates whether a message is likely to be **phishing**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/outlook/phishingstamp

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Defining reference: [\[MS-OXPHISH\]](#) section 2.2.1.1

2.518 PidNamePostingVersion

Canonical name: PidNamePostingVersion

Description: Identifies the software that is used to post the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Posting-Version

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.32

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:posting-version

2.519 PidNamePresentationFormat

Canonical name: PidNamePresentationFormat

Description: Specifies the presentation format of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: PresFormat

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.19

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#PresentationFormat

2.520 PidNamePriority

Canonical name: PidNamePriority

Description: Specifies the priority of a message or appointment.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Priority

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.33

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:priority

2.521 PidNameQuarantineOriginalSender

Canonical name: PidNameQuarantineOriginalSender

Description:

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: quarantine-original-sender

Data type: PtypString, 0x001F

Area: Common

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

2.522 PidNameReceived

Canonical name: PidNameReceived

Description: Specifies the SMTP host received headers for a message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Received

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.34

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:received

2.523 PidNameReferences

Canonical name: PidNameReferences

Description: Specifies the USENET header used to correlate replies with their original messages.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: References

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.35

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:references

2.524 PidNameRelayVersion

Canonical name: PidNameRelayVersion

Description: Specifies the version of the program responsible for transmitting an item over the immediate link.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Relay-Version

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.36

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:relay-version

2.525 PidNameReplyBy

Canonical name: PidNameReplyBy

Description: Indicates when there should be a reply to a message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Reply-By

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.37

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:reply-by

2.526 PidNameReplyTo

Canonical name: PidNameReplyTo

Description: Specifies the address to which replies are to be sent.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Reply-To

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.38

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:reply-to

2.527 PidNameReturnPath

Canonical name: PidNameReturnPath

Description: Specifies the address of the message originator.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Return-Path

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.39

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:return-path

2.528 PidNameReturnReceiptTo

Canonical name: PidNameReturnReceiptTo

Description: Specifies the address to which return receipts are to be sent.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Return-Receipt-To

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.40

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:return-receipt-to

2.529 PidNameRevisionNumber

Canonical name: PidNameRevisionNumber

Description: Specifies the revision number of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: RevNumber

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.8

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Revision

2.530 PidNameRightsManagementLicense

Canonical name: PidNameRightsManagementLicense

Description: Specifies the value used to cache the **Use License** for the **rights-managed e-mail message**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DRMLicense

Data type: PtypMultipleBinary, 0x1102

Area: Secure Messaging Properties

Defining reference: [\[MS-OXORMMS\]](#) section 2.2.1.1

2.531 PidNameRightsProtectMessage

Canonical name: PidNameRightsProtectMessage

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-RightsProtectMessage

Data type: PtypString, 0x001F

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchangeOrganizationRightsProtectMessage

2.532 PidNameScale

Canonical name: PidNameScale

Description: Indicates whether the image is to be scaled or cropped.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Scale

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.32

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#ScaleCrop

2.533 PidNameSecurity

Canonical name: PidNameSecurity

Description: Specifies the security level of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Security

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.17

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Security

2.534 PidNameSender

Canonical name: PidNameSender

Description: Specifies the sender of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Sender

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.41

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:sender

2.535 PidNameSensitivity

Canonical name: PidNameSensitivity

Description: Specifies the sensitivity of the message or appointment.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Sensitivity

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.42

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:sensitivity

2.536 PidNameSlideCount

Canonical name: PidNameSlideCount

Description: Specifies the number of slides in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: SlideCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.25

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Slides

2.537 PidNameSubject

Canonical name: PidNameSubject

Description: Specifies the subject of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Subject

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.2

Consuming reference: [\[MS-XWDDOC\]](#), [\[MS-OXOCAL\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Subject

2.538 PidNameSummary

Canonical name: PidNameSummary

Description: Contains a summary of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Summary

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.44

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:summary

2.539 PidNameTemplate

Canonical name: PidNameTemplate

Description: Specifies the template of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Template

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.6

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Template

2.540 PidNameThreadIndex

Canonical name: PidNameThreadIndex

Description: Identifies a particular conversation thread.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Thread-Index

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.45

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:thread-index

2.541 PidNameThreadTopic

Canonical name: PidNameThreadTopic

Description: Specifies the topic of a discussion thread.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Thread-Topic

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.46

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:thread-topic

2.542 PidNameThumbnail

Canonical name: PidNameThumbnail

Description: Specifies the data representing the thumbnail image of the document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Thumbnail

Data type: PtypBinary, 0x0102

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.33

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#ThumbNail

2.543 PidNameTitle

Canonical name: PidNameTitle

Description: Specifies the title of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Title

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.1

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Title

2.544 PidNameTo

Canonical name: PidNameTo

Description: Specifies the principal message addressees.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: To

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.47

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:to

2.545 PidNameWordCount

Canonical name: PidNameWordCount

Description: Specifies the word count of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: WordCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.15

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Words

2.546 PidNameXCallId

Canonical name: PidNameXCallId

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-CallID

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

2.547 PidNameXFaxNumberOfPages

Canonical name: PidNameXFaxNumberOfPages

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-FaxNumberOfPages

Data type: PtypInteger16, 0x0002

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

2.548 PidNameXMailer

Canonical name: PidNameXMailer

Description: Specifies the name of the software used to send the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Mailer

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.48

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:x-mailer

2.549 PidNameXMessageCompleted

Canonical name: PidNameXMessageCompleted

Description: Contains the header for message flag completion.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Message-Completed

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.49

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:x-message-completed

2.550 PidNameXMessageFlag

Canonical name: PidNameXMessageFlag

Description: Specifies message **flags** that indicate special characteristics of a particular message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Message-Flag

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.50

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:x-message-flag

2.551 PidNameXRequireProtectedPlayOnPhone

Canonical name: PidNameXRequireProtectedPlayOnPhone

Description: Indicates that the client only renders the message on a phone.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-RequireProtectedPlayOnPhone

Data type: PtypBoolean, 0x000B

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.2

2.552 PidNameXSenderTelephoneNumber

Canonical name: PidNameXSenderTelephoneNumber

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-CallingTelephoneNumber

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

2.553 PidNameXSharingBrowseUrl

Canonical name: PidNameXSharingBrowseUrl

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Browse-Url

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

2.554 PidNameXSharingCapabilities

Canonical name: PidNameXSharingCapabilities

Description: Contains a string representation of the value of the **PidLidSharingCapabilities** property (section [2.231](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-00000000046}

Property name: X-Sharing-Capabilities

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.2

2.555 PidNameXSharingConfigUrl

Canonical name: PidNameXSharingConfigUrl

Description: Contains the same value as the **PidLidSharingConfigurationUrl** property (section [2.232](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-00000000046}

Property name: X-Sharing-Config-Url

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.4

2.556 PidNameXSharingExendedCaps

Canonical name: PidNameXSharingExendedCaps

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-00000000046}

Property name: X-Sharing-Exended-Caps

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

2.557 PidNameXSharingFlavor

Canonical name: PidNameXSharingFlavor

Description: Contains a hexadecimal string representation of the value of the **PidLidSharingFlavor** property (section [2.239](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-00000000046}

Property name: X-Sharing-Flavor

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.6

2.558 PidNameXSharingInstanceId

Canonical name: PidNameXSharingInstanceId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Instance-Guid

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

2.559 PidNameXSharingLocalType

Canonical name: PidNameXSharingLocalType

Description: Contains the same value as the **PidLidSharingLocalType** property (section [2.253](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Local-Type

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.11

2.560 PidNameXSharingProviderGuid

Canonical name: PidNameXSharingProviderGuid

Description: Contains the hexadecimal string representation of the value of the **PidLidSharingProviderGuid** property (section [2.260](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Provider-Guid

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.13

2.561 PidNameXSharingProviderName

Canonical name: PidNameXSharingProviderName

Description: Contains the same value as the **PidLidSharingProviderName** property (section [2.261](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Provider-Name

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.15

2.562 PidNameXSharingProviderUrl

Canonical name: PidNameXSharingProviderUrl

Description: Contains the same value as the **PidLidSharingProviderUrl** property (section [2.262](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Provider-Url

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.17

2.563 PidNameXSharingRemoteName

Canonical name: PidNameXSharingRemoteName

Description: Contains the same value as the **PidLidSharingRemoteName** property (section [2.271](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Name

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.4.2

2.564 PidNameXSharingRemotePath

Canonical name: PidNameXSharingRemotePath

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Path

Data type: **PtypString**, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5

2.565 PidNameXSharingRemoteStoreUid

Canonical name: PidNameXSharingRemoteStoreUid

Description: Contains the same value as the **PidLidSharingRemoteStoreUid** property (section [2.276](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Store-Uid

Data type: **PtypString**, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.4.4

2.566 PidNameXSharingRemoteType

Canonical name: PidNameXSharingRemoteType

Description: Contains the same value as the **PidLidSharingRemoteType** property (section [2.275](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Type

Data type: **PtypString**, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.4.6

2.567 PidNameXSharingRemoteUid

Canonical name: PidNameXSharingRemoteUid

Description: Contains the same value as the **PidLidSharingRemoteUid** property (section [2.276](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Uid

Data type: **PtypString**, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.4.8

2.568 PidNameXUnifiedMessagingPartnerAssignedId

Canonical name: PidNameXUnifiedMessagingPartnerAssignedId

Description:

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-UM-PartnerAssignedID

Data type: **PtypString**, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsexchangeUMPartnerAssignedID

2.569 PidNameXUnifiedMessagingPartnerContent

Canonical name: PidNameXUnifiedMessagingPartnerContent

Description:

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-UM-PartnerContent

Data type: **PtypString**, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsexchangeUMPartnerContent

2.570 PidNameXUnifiedMessagingPartnerContext

Canonical name: PidNameXUnifiedMessagingPartnerContext

Description:

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-UM-PartnerContext

Data type: **PtypString**, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsexchangeUMPartnerContext

2.571 PidNameXUnifiedMessagingPartnerStatus

Canonical name: PidNameXUnifiedMessagingPartnerStatus

Description:

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-UM-PartnerStatus

Data type: **PtypString**, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchangeUMPartnerStatus

2.572 PidNameXUnsent

Canonical name: PidNameXUnsent

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Unsent

Data type: **PtypString**, 0x001F

Area: E-mail

Defining reference:

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:x-unsent

2.573 PidNameXVoiceMessageAttachmentOrder

Canonical name: PidNameXVoiceMessageAttachmentOrder

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-AttachmentOrder

Data type: **PtypString**, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

2.574 PidNameXVoiceMessageDuration

Canonical name: PidNameXVoiceMessageDuration

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-VoiceMessageDuration

Data type: PtypInteger16, 0x0002

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

2.575 PidNameXVoiceMessageSenderName

Canonical name: PidNameXVoiceMessageSenderName

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-VoiceMessageSenderName

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

2.576 PidTagAccess

Canonical name: PidTagAccess

Description: Indicates the operations available to the client for the object.

Property ID: 0x0FF4

Data type: PtypInteger32, 0x0003

Area: Access Control Properties

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.1.1

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSP\]](#), [MS-OXCPRPT], [\[MS-OXOJRNL\]](#)

Alternate names: PR_ACCESS, ptagAccess

2.577 PidTagAccessControlListData

Canonical name: PidTagAccessControlListData

Description: Contains a **permissions** list for a folder.

Property ID: 0x3FE0

Data type: **PtypBinary**, 0x0102

Area: Access Control Properties

Defining reference: [\[MS-OXCPERM\]](#) section 2.2.1.3

Consuming references: [\[MS-OXCOLD\]](#)

Alternate names: PR_ACL_DATA, ptagACLDATA

2.578 PidTagAccessLevel

Canonical name: PidTagAccessLevel

Description: Indicates the client's access level to the object.

Property ID: 0x0FF7

Data type: **PtypInteger32**, 0x0003

Area: Access Control Properties

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.1.2

Consuming references: [\[MS-OXCOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMMSG\]](#)

Alternate names: PR_ACCESS_LEVEL, ptagAccessLevel

2.579 PidTagAccount

Canonical name: PidTagAccount

Description: Contains the Address Book object's alias, which is an alternative name by which the object can be identified.

Property ID: 0x3A00

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.11

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOABI\]](#), [\[MS-OXOMSG\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_ACCOUNT, PR_ACCOUNT_A, PR_ACCOUNT_W,
urn:schemas:contacts:account

2.580 PidTagAdditionalRenEntryIds

Canonical name: PidTagAdditionalRenEntryIds

Description: Contains the indexed entry IDs for several special folders related to conflicts, sync issues, local failures, server failures, junk e-mail and **spam**.

Property ID: 0x36D8

Data type: **PtypMultipleBinary**, 0x1102

Area: Outlook Application

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.4

Consuming references: [\[MS-OXCSPAM\]](#), [\[MS-OXPHISH\]](#)

Alternate names: PR_ADDITIONAL_RN_ENTRYIDS, ptagAdditionalRenEntryIds

2.581 PidTagAdditionalRenEntryIdsEx

Canonical name: PidTagAdditionalRenEntryIdsEx

Description: Contains an array of blocks that contain the EntryIDs for folders related to RSS feed folders, and the Tracked Mail Processing folder, To-Do Search folder, and Conversation Action Settings folder.

Property ID: 0x36D9

Data type: **PtypBinary**, 0x0102

Area: Outlook Application

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.5

Alternate names: PR_ADDITIONAL_RN_ENTRYIDS_EX, ptagAdditionalRenEntryIdsEx

2.582 PidTagAddressBookAuthorizedSenders

Canonical name: PidTagAddressBookAuthorizedSenders

Description: Indicates whether delivery restrictions exist for a recipient.

Property ID: 0x8CD8

Data type: **PtypObject**, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.84

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_AUTH_ORIG

2.583 PidTagAddressBookContainerId

Canonical name: PidTagAddressBookContainerId

Description: Contains the ID of a container on an NSPI server.

Property ID: 0xFFFFD

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.2.3

Consuming references: [\[MS-NSPI\]](#)

Alternate names: PR_EMS_AB_CONTAINERID

2.584 PidTagAddressBookDeliveryContentLength

Canonical name: PidTagAddressBookDeliveryContentLength

Description: Specifies the maximum size of a message that a recipient can receive.

Property ID: 0x806A

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.27

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_DELIV_CONT_LENGTH

2.585 PidTagAddressBookDisplayNamePrintable

Canonical name: PidTagAddressBookDisplayNamePrintable

Description: Contains the printable string version of the display name.

Property ID: 0x39FF

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.30

Consuming reference: [MS-OXCMSG], [\[MS-OXOAB\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_EMS_AB_DISPLAY_NAME_PRINTABLE,
PR_EMS_AB_DISPLAY_NAME_PRINTABLE_A, PR_EMS_AB_DISPLAY_NAME_PRINTABLE_W,
PR_7BIT_DISPLAY_NAME, PR_7BIT_DISPLAY_NAME_A, PR_7BIT_DISPLAY_NAME_W,
ptagSimpleDisplayName

2.586 PidTagAddressBookDisplayTypeExtended

Canonical name: PidTagAddressBookDisplayTypeExtended

Description: Contains a value that indicates how to display an Address Book object in a table or as a recipient on a message.

Property ID: 0x8C93

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.35

Alternate names: PR_EMS_AB_DISPLAY_TYPE_EX

2.587 PidTagAddressBookDistributionListExternalMemberCount

Canonical name: PidTagAddressBookDistributionListExternalMemberCount

Description: Contains the number of external recipients in the distribution list.

Property ID: 0x8CE3

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.30

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_DL_EXTERNAL_MEMBER_COUNT

2.588 PidTagAddressBookDistributionListMemberCount

Canonical name: PidTagAddressBookDistributionListMemberCount

Description: Contains the total number of recipients in the distribution list.

Property ID: 0x8CE2

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.29

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_DL_TOTAL_MEMBER_COUNT

2.589 PidTagAddressBookDistributionListMemberSubmitAccepted

Canonical name: PidTagAddressBookDistributionListMemberSubmitAccepted

Description: Indicates that delivery restrictions exist for a recipient.

Property ID: 0x8073

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.86

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_DL_MEM_SUBMIT_PERMS_BL_O

2.590 PidTagAddressBookDistributionListMemberSubmitRejected

Canonical name: PidTagAddressBookDistributionListMemberSubmitRejected

Description: Indicates that delivery restrictions exist for a recipient.

Property ID: 0x8CDA

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.87

Consuming references: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_DL_MEM_SUBMIT_PERMS

2.591 PidTagAddressBookDistributionListRejectMessagesFromDLMembers

Canonical name: PidTagAddressBookDistributionListRejectMessagesFromDLMembers

Description: Indicates that delivery restrictions exist for a recipient.

Property ID: 0x8CDB

Data type: PtypObject, 0x000D

Area: Address book

Defining reference: [\[MS-OXOAB\]](#) section 2.9.2.2

Alternate names: PR_EMS_AB_DL_MEM_REJECT_PERMS

2.592 PidTagAddressBookEntryId

Canonical name: PidTagAddressBookEntryId

Description: Contains the name-service EntryID of a directory object that refers to a **public folder**.

Property ID: 0x663B

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [\[MS-OXCFO\]](#) section 2.2.2.2.1.4

Alternate names: PR_ADDRESS_BOOK_ENTRYID, ptagAddressBookEntryId

2.593 PidTagAddressBookExtensionAttribute1

Canonical name: PidTagAddressBookExtensionAttribute1

Description: Contains information to be added to **display templates**.

Property ID: 0x802D

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_1,
PR_EMS_AB_EXTENSION_ATTRIBUTE_1_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_1_W

2.594 PidTagAddressBookExtensionAttribute15

Canonical name: PidTagAddressBookExtensionAttribute15

Description: Contains information to be added to display templates.

Property ID: 0x8C61

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_15,
PR_EMS_AB_EXTENSION_ATTRIBUTE_15_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_15_W

2.595 PidTagAddressBookFolderPathname

Canonical name: PidTagAddressBookFolderPathname

Description: This property is deprecated and is to be ignored.

Property ID: 0x8004

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.6.4

Alternate names: PR_EMS_AB_FOLDER_PATHNAME, PR_EMS_AB_FOLDER_PATHNAME_A,
PR_EMS_AB_FOLDER_PATHNAME_W

2.596 PidTagAddressBookHierarchicalChildDepartments

Canonical name: PidTagAddressBookHierarchicalChildDepartments

Description: Contains the child departments in a hierarchy of departments.

Property ID: 0x8C9A

Data type: **PtypEmbeddedTable**, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.8.1

Alternate names: PR_EMS_AB_HAB_CHILD_DEPARTMENTS

2.597 PidTagAddressBookHierarchicalDepartmentMembers

Canonical name: PidTagAddressBookHierarchicalDepartmentMembers

Description: Contains all of the mail users that belong to this department.

Property ID: 0x8C97

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.8.3

Alternate names: PR_EMS_AB_HAB_DEPARTMENT_MEMBERS

2.598 PidTagAddressBookHierarchicalIsHierarchicalGroup

Canonical name: PidTagAddressBookHierarchicalIsHierarchicalGroup

Description: Indicates whether the distribution list represents a **departmental group**.

Property ID: 0x8CDD

Data type: PtypBoolean, 0x000B

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.6.5

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_HAB_IS_HIERARCHICAL_GROUP,
PR_EMS_AB_IS_ORGANIZATIONAL

2.599 PidTagAddressBookHierarchicalParentDepartment

Canonical name: PidTagAddressBookHierarchicalParentDepartment

Description: Contains all of the departments to which this department is a child.

Property ID: 0x8C99

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.8.2

Alternate names: PR_EMS_AB_HAB_PARENT_DEPARTMENT

2.600 PidTagAddressBookHierarchicalRootDepartment

Canonical name: PidTagAddressBookHierarchicalRootDepartment

Description: Contains the **DN** of the root departmental group in the department hierarchy for the organization.

Property ID: 0x8C98

Data type: **PtypString8**, 0x001E

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.7.2

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_HAB_ROOT_DEPARTMENT

2.601 PidTagAddressBookHierarchicalShowInDepartments

Canonical name: PidTagAddressBookHierarchicalShowInDepartments

Description: Lists all Department objects of which the mail user is a member.

Property ID: 0x8C94

Data type: **PtypEmbeddedTable**, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.5.6

Alternate names: PR_EMS_AB_HAB_SHOW_IN_DEPARTMENTS

2.602 PidTagAddressBookHomeMessageDatabase

Canonical name: PidTagAddressBookHomeMessageDatabase

Description: Contains the DN expressed in the **X500 DN** format.

Property ID: 0x8006

Data type: **PtypString8**, 0x001E

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.67

Consuming references: [\[MS-OXABREF\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_EMS_AB_HOME_MDB, PR_EMS_AB_HOME_MDB_A,
PR_EMS_AB_HOME_MDB_W

2.603 PidTagAddressBookIsMaster

Canonical name: PidTagAddressBookIsMaster

Description: Contains a Boolean value of TRUE if it is possible to create Address Book objects in that container, and FALSE otherwise.

Property ID: 0xFFFFB

Data type: PtypBoolean, 0x000B

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.2.4

Consuming reference: [\[MS-NSPI\]](#)

Alternate names: PR_EMS_AB_IS_MASTER

2.604 PidTagAddressBookIsMemberOfDistributionList

Canonical name: PidTagAddressBookIsMemberOfDistributionList

Description: List all of the distribution lists for which this object is a member.

Property ID: 0x8008

Data type: PtypString8, 0x001E

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.5.3

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_IS_MEMBER_OF_DL, PR_EMS_AB_IS_MEMBER_OF_DL_A, PR_EMS_AB_IS_MEMBER_OF_DL_W

2.605 PidTagAddressBookManageDistributionList

Canonical name: PidTagAddressBookManageDistributionList

Description: Contains information for use in display templates for distribution lists.

Property ID: 0x6704

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.10.2

Consuming reference: [\[MS-OXOABKT\]](#)

Alternate names: PR_EMS_AB_MANAGE_DL

2.606 PidTagAddressBookManager

Canonical name: PidTagAddressBookManager

Description: Contains one row that references the mail user's manager.

Property ID: 0x8005

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.5.1

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_MANAGER, PR_EMS_AB_MANAGER_A, PR_EMS_AB_MANAGER_W

2.607 PidTagAddressBookManagerDistinguishedName

Canonical name: PidTagAddressBookManagerDistinguishedName

Description: Contains the **distinguished name (DN)** of the mail user's manager.

Property ID: 0x8005

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.13

Alternate names: PR_EMS_AB_MANAGER_T

2.608 PidTagAddressBookMember

Canonical name: PidTagAddressBookMember

Description: Contains the members of the distribution list.

Property ID: 0x8009

Data type: PtypMultipleString8, 0x101E

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.6.1

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_MEMBER, PR_EMS_AB_MEMBER_A, PR_EMS_AB_MEMBER_W

2.609 PidTagAddressBookMessageId

Canonical name: PidTagAddressBookMessageId

Description: Contains the Short-term Message ID (MID) ([\[MS-OXCDATA\]](#) section 2.2.1.2) of the first message in the local site's **offline address book** public folder.

Property ID: 0x674F

Data type: PtypInteger64, 0x0014

Area: ProviderDefinedNonTransmittable

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.2

Alternate names: ptagAddrbookMID

2.610 PidTagAddressBookModerationEnabled

Canonical name: PidTagAddressBookModerationEnabled

Description: Indicates whether moderation is enabled for the mail user of the distribution list.

Property ID: 0x8CB5

Data type: **PtypBoolean**, 0x000B

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.28

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_ENABLE_MODERATION

2.611 PidTagAddressBookNetworkAddress

Canonical name: PidTagAddressBookNetworkAddress

Description: Contains a list of names by which a server is known to the various transports in use by the network.

Property ID: 0x8170

Data type: **PtypMultipleString**, 0x101F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.68

Alternate names: PR_EMS_AB_NETWORK_ADDRESS, PR_EMS_AB_NETWORK_ADDRESS_A, PR_EMS_AB_NETWORK_ADDRESS_W

2.612 PidTagAddressBookObjectDistinguishedName

Canonical name: PidTagAddressBookObjectDistinguishedName

Description: Contains the distinguished name (DN) of the Address Book object.

Property ID: 0x803C

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.15

Consuming reference: [\[MS-NSPI\]](#)

Alternate names: PR_EMS_AB_OBJ_DIST_NAME, PR_EMS_AB_OBJ_DIST_NAME_A, PR_EMS_AB_OBJ_DIST_NAME_W

2.613 PidTagAddressBookObjectGuid

Canonical name: PidTagAddressBookObjectGuid

Description: Contains a GUID that identifies an Address Book object.

Property ID: 0x8C6D

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.25

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_OBJECT_GUID

2.614 PidTagAddressBookOrganizationalUnitRootDistinguishedName

Canonical name: PidTagAddressBookOrganizationalUnitRootDistinguishedName

Description: Contains the distinguished name (DN) of the Organization object of the mail user's organization.

Property ID: 0x8CA8

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.81

Alternate names: PR_EMS_AB_ORG_UNIT_ROOT_DN, msExchOURoot

2.615 PidTagAddressBookOwner

Canonical name: PidTagAddressBookOwner

Description: Contains one row that references the distribution list's owner.

Property ID: 0x800C

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.6.2

Alternate names: PR_EMS_AB_OWNER_O

2.616 PidTagAddressBookOwnerBackLink

Canonical name: PidTagAddressBookOwnerBackLink

Description: Contains a list of the distribution lists owned by a mail user.

Property ID: 0x8024

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.5.4

Alternate names: PR_EMS_AB_OWNER_BL_O

2.617 PidTagAddressBookParentEntryId

Canonical name: PidTagAddressBookParentEntryId

Description: Contains the EntryID of the parent container in a hierarchy of address book containers.

Property ID: 0xFFFFC

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.2.5

Consuming reference: [\[MS-NSPI\]](#)

Alternate names: PR_EMS_AB_PARENT_ENTRYID

2.618 PidTagAddressBookPhoneticCompanyName

Canonical name: PidTagAddressBookPhoneticCompanyName

Description: Contains the phonetic representation of the **PidTagCompanyName** property (section [2.697](#)).

Property ID: 0x8C91

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.16

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_PHONETIC_COMPANY_NAME,
PR_EMS_AB_PHONETIC_COMPANY_NAME_A, PR_EMS_AB_PHONETIC_COMPANY_NAME_W

2.619 PidTagAddressBookPhoneticDepartmentName

Canonical name: PidTagAddressBookPhoneticDepartmentName

Description: Contains the phonetic representation of the **PidTagDepartmentName** property (section [2.730](#)).

Property ID: 0x8C90

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.17

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_PHONETIC_DEPARTMENT_NAME,
PR_EMS_AB_PHONETIC_DEPARTMENT_NAME_A, PR_EMS_AB_PHONETIC_DEPARTMENT_NAME_W

2.620 PidTagAddressBookPhoneticDisplayName

Canonical name: PidTagAddressBookPhoneticDisplayName

Description: Contains the phonetic representation of the **PidTagDisplayName** property (section [2.734](#)).

Property ID: 0x8C92

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.9

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_PHONETIC_DISPLAY_NAME,
PR_EMS_AB_PHONETIC_DISPLAY_NAME_A, PR_EMS_AB_PHONETIC_DISPLAY_NAME_W

2.621 PidTagAddressBookPhoneticGivenName

Canonical name: PidTagAddressBookPhoneticGivenName

Description: Contains the phonetic representation of the **PidTagGivenName** property (section [2.771](#)).

Property ID: 0x8C8E

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.14

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_PHONETIC_GIVEN_NAME,
PR_EMS_AB_PHONETIC_GIVEN_NAME_A, PR_EMS_AB_PHONETIC_GIVEN_NAME_W

2.622 PidTagAddressBookPhoneticSurname

Canonical name: PidTagAddressBookPhoneticSurname

Description: Contains the phonetic representation of the **PidTagSurname** property (section [2.1088](#)).

Property ID: 0x8C8F

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.15

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_PHONETIC_SURNAME, PR_EMS_AB_PHONETIC_SURNAME_A, PR_EMS_AB_PHONETIC_SURNAME_W

2.623 PidTagAddressBookProxyAddresses

Canonical name: PidTagAddressBookProxyAddresses

Description: Contains alternate e-mail addresses for the Address Book object.

Property ID: 0x800F

Data type: PtypMultipleString, 0x101F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.23

Consuming references: [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_EMS_AB_PROXY_ADDRESSES, PR_EMS_AB_PROXY_ADDRESSES_A, PR_EMS_AB_PROXY_ADDRESSES_W

2.624 PidTagAddressBookPublicDelegates

Canonical name: PidTagAddressBookPublicDelegates

Description: Contains a list of mail users who are allowed to send e-mail on behalf of the mailbox owner.

Property ID: 0x8015

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.5.5

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_EMS_AB_PUBLIC_DELEGATES, PR_EMS_AB_PUBLIC_DELEGATES_A, PR_EMS_AB_PUBLIC_DELEGATES_W

2.625 PidTagAddressBookReports

Canonical name: PidTagAddressBookReports

Description: Lists all a mail user's direct reports.

Property ID: 0x800E

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.5.2

Alternate names: PR_EMS_AB_REPORTS, PR_EMS_AB_REPORTS_A, PR_EMS_AB_REPORTS_W

2.626 PidTagAddressBookRoomCapacity

Canonical name: PidTagAddressBookRoomCapacity

Description: Contains the maximum occupancy of the room.

Property ID: 0x0807

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.9.1

Alternate names: PR_EMS_AB_ROOM_CAPACITY

2.627 PidTagAddressBookRoomContainers

Canonical name: PidTagAddressBookRoomContainers

Description: Contains a list of DNs that represent the address book containers that hold **Resource objects**, such as conference rooms and equipment.

Property ID: 0x8C96

Data type: PtypMultipleString, 0x101F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.7.1

Alternate names: PR_EMS_AB_ROOM_CONTAINERS, PR_EMS_AB_ROOM_CONTAINERS_A, PR_EMS_AB_ROOM_CONTAINERS_W

2.628 PidTagAddressBookRoomDescription

Canonical name: PidTagAddressBookRoomDescription

Description: Contains a description of the Resource object.

Property ID: 0x0809

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.9.2

Alternate names: PR_EMS_AB_ROOM_DESCRIPTION, PR_EMS_AB_ROOM_DESCRIPTION_A, PR_EMS_AB_ROOM_DESCRIPTION_W

2.629 PidTagAddressBookSenderHintTranslations

Canonical name: PidTagAddressBookSenderHintTranslations

Description: Contains the **locale** ID and translations of the default **mail tip**.

Property ID: 0x8CAC

Data type: **PtypMultipleString**, 0x101F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.26

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_DL_SENDER_HINT_TRANSLATIONS_W

2.630 PidTagAddressBookSeniorityIndex

Canonical name: PidTagAddressBookSeniorityIndex

Description: Contains a signed integer that specifies the seniority order of Address Book objects that represent members of a department and are referenced by a Department object or departmental group, with larger values specifying members that are more senior.

Property ID: 0x8CA0

Data type: **PtypInteger32**, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.24

Consuming reference: [\[MS-OXOAB\]](#) **Alternate names:** PR_EMS_AB_HAB_SENIORITY_INDEX, PR_EMS_AB_SENIORITY_INDEX

2.631 PidTagAddressBookTargetAddress

Canonical name: PidTagAddressBookTargetAddress

Description: Contains the foreign system e-mail address of an Address Book object.

Property ID: 0x8011

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.22

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_TARGET_ADDRESS, PR_EMS_AB_TARGET_ADDRESS_A, PR_EMS_AB_TARGET_ADDRESS_W

2.632 PidTagAddressBookUnauthorizedSenders

Canonical name: PidTagAddressBookUnauthorizedSenders

Description: Indicates whether delivery restrictions exist for this recipient.

Property ID: 0x8CD9

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.85

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_UNAUTH_ORIG

2.633 PidTagAddressBookX509Certificate

Canonical name: PidTagAddressBookX509Certificate

Description: Contains the ASN_1 DER encoded X.509 certificates for the mail user.

Property ID: 0x8C6A

Data type: PtypMultipleBinary, 0x1102

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.66

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_X509_CERT

2.634 PidTagAddressType

Canonical name: PidTagAddressType

Description: Contains the Message object's e-mail address type.

Property ID: 0x3002

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.13

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXPVAL\]](#)

Alternate names: PR_ADDRTYPE, PR_ADDRTYPE_A, ptagAddrType, PR_ADDRTYPE_W

2.635 PidTagAlternateRecipientAllowed

Canonical name: PidTagAlternateRecipientAllowed

Description: Specifies whether the sender permits the message to be auto-forwarded.

Property ID: 0x0002

Data type: PtypBoolean, 0x000B

Area: Address Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.36

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ALTERNATE_RECIPIENT_ALLOWED, ptagAlternateRecipientAllowed

2.636 PidTagAnr

Canonical name: PidTagAnr

Description: Contains a filter value used in **ambiguous name resolution**.

Property ID: 0x360C

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.10.1

Alternate names: PR_ANR, PR_ANR_A, PR_ANR_W

2.637 PidTagArchiveDate

Canonical name: PidTagArchiveDate

Property ID: 0x301F

Data type: PtypTime, 0x0040

Area: Archive

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.50.8

Alternate names: PR_ARCHIVE_DATE, ptagArchiveDate

2.638 PidTagArchivePeriod

Canonical name: PidTagArchivePeriod

Property ID: 0x301E

Data type: PtypInteger32, 0x0003

Area: Archive

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.50.7

Alternate names: PR_ARCHIVE_PERIOD, ptagArchivePeriod

2.639 PidTagArchiveTag

Canonical name: PidTagArchiveTag

Property ID: 0x3018

Data type: PtypBinary, 0x0102

Area: Archive

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.50.1

Alternate names: PR_ARCHIVE_TAG, ptagArchiveTag

2.640 PidTagAssistant

Canonical name: PidTagAssistant

Description: Contains the name of the mail user's administrative assistant.

Property ID: 0x3A30

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.11

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ASSISTANT, PR_ASSISTANT_A, PR_ASSISTANT_W,
urn:schemas:contacts:secretarycn

2.641 PidTagAssistantTelephoneNumber

Canonical name: PidTagAssistantTelephoneNumber

Description: Contains the telephone number of the mail user's administrative assistant.

Property ID: 0x3A2E

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.57

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ASSISTANT_TELEPHONE_NUMBER,
PR_ASSISTANT_TELEPHONE_NUMBER_A, PR_ASSISTANT_TELEPHONE_NUMBER_W,
urn:schemas:contacts:secretaryphone

2.642 PidTagAssociated

Canonical name: PidTagAssociated

Description: Specifies whether the message being synchronized is an FAI message.

Property ID: 0x67AA

Data type: PtypBoolean, 0x000B

Area: Sync

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.5

Alternate names: ptagAssociated

2.643 PidTagAttachAdditionalInformation

Canonical name: PidTagAttachAdditionalInformation

Description: Contains attachment encoding information.

Property ID: 0x370F

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.21

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_ATTACH_ADDITIONAL_INFO

2.644 PidTagAttachContentBase

Canonical name: PidTagAttachContentBase

Description: Contains the base of a relative URI.

Property ID: 0x3711

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.26

Consuming reference: [\[MS-OXCMAIL\]](#) **Alternate names:** PR_ATTACH_CONTENT_BASE, PR_ATTACH_CONTENT_BASE_A, PR_ATTACH_CONTENT_BASE_W

2.645 PidTagAttachContentId

Canonical name: PidTagAttachContentId

Description: Contains a content identifier unique to the Message object that matches a corresponding "cid:" URI scheme reference in the HTML body of the Message object.

Property ID: 0x3712

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.26

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMSS\]](#), [\[MS-OXOSMMS\]](#)

Alternate names: PR_ATTACH_CONTENT_ID, PR_ATTACH_CONTENT_ID_A, PR_ATTACH_CONTENT_ID_W

2.646 PidTagAttachContentLocation

Canonical name: PidTagAttachContentLocation

Description: Contains a relative or full URI that matches a corresponding reference in the HTML body of a Message object.

Property ID: 0x3713

Data type: **PtypString**, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.26

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXORMMSS\]](#)

Alternate names: PR_ATTACH_CONTENT_LOCATION, PR_ATTACH_CONTENT_LOCATION_A, PR_ATTACH_CONTENT_LOCATION_W

2.647 PidTagAttachDataBinary

Canonical name: PidTagAttachDataBinary

Description: Contains the contents of the file to be attached.

Property ID: 0x3701

Data type: **PtypBinary**, 0x0102

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.7

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMSS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_ATTACH_DATA_BIN, ptagAttachDataBin

2.648 PidTagAttachDataObject

Canonical name: PidTagAttachDataObject

Description: Contains the binary representation of the **Attachment object** in an application-specific format.

Property ID: 0x3701

Data type: **PtypObject**, 0x000D

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.8

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOCAL\]](#)

Alternate names: PR_ATTACH_DATA_OBJ, ptagAttachDataObj

2.649 PidTagAttachEncoding

Canonical name: PidTagAttachEncoding

Description: Contains encoding information about the Attachment object.

Property ID: 0x3702

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.20

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTACH_ENCODING

2.650 PidTagAttachExtension

Canonical name: PidTagAttachExtension

Description: Contains a file name extension that indicates the document type of an attachment.

Property ID: 0x3703

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.12

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_EXTENSION, PR_ATTACH_EXTENSION_A, PR_ATTACH_EXTENSION_W

2.651 PidTagAttachFilename

Canonical name: PidTagAttachFilename

Description: Contains the [8.3 name](#) of the **PidTagAttachLongFilename** property (section [2.653](#)).

Property ID: 0x3704

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.11

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMSS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_FILENAME, PR_ATTACH_FILENAME_A, ptagAttachFilename, PR_ATTACH_FILENAME_W

2.652 PidTagAttachFlags

Canonical name: PidTagAttachFlags

Description: Indicates which body formats might reference this attachment when rendering data.

Property ID: 0x3714

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.18

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_FLAGS

2.653 PidTagAttachLongFilename

Canonical name: PidTagAttachLongFilename

Description: Contains the full filename and extension of the Attachment object.

Property ID: 0x3707

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.10

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMSS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOUM\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_LONG_FILENAME, PR_ATTACH_LONG_FILENAME_A, PR_ATTACH_LONG_FILENAME_W, urn:schemas:httpmail:attachmentfilename

2.654 PidTagAttachLongPathname

Canonical name: PidTagAttachLongPathname

Description: Contains the fully-qualified path and file name with extension.

Property ID: 0x370D

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.13

Consuming reference: [\[MS-OXORMMMS\]](#)

Alternate names: PR_ATTACH_LONG_PATHNAME, PR_ATTACH_LONG_PATHNAME_A, ptagAttachLongPathname, PR_ATTACH_LONG_PATHNAME_W

2.655 PidTagAttachmentContactPhoto

Canonical name: PidTagAttachmentContactPhoto

Description: Indicates that a contact photo attachment is attached to a Contact object.

Property ID: 0x7FFF

Data type: PtypBoolean, 0x000B

Area: Message Attachment Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.8

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_ATTACHMENT_CONTACTPHOTO

2.656 PidTagAttachmentFlags

Canonical name: PidTagAttachmentFlags

Description: Indicates special handling for an Attachment object.

Property ID: 0x7FFD

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.23

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: PR_ATTACHMENT_FLAGS, ptagAttachmentFlags

2.657 PidTagAttachmentHidden

Canonical name: PidTagAttachmentHidden

Description: Indicates whether an Attachment object is hidden from the end user.

Property ID: 0x7FFE

Data type: PtypBoolean, 0x000B

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.24

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

Alternate names: PR_ATTACHMENT_HIDDEN

2.658 PidTagAttachmentLinkId

Canonical name: PidTagAttachmentLinkId

Description: Contains the type of Message object to which this attachment is linked.

Property ID: 0x7FFA

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.22

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_ATTACHMENT_LINKID, ptagAttachmentLinkId

2.659 PidTagAttachMethod

Canonical name: PidTagAttachMethod

Description: Represents the way the contents of an attachment are accessed.

Property ID: 0x3705

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.9

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_METHOD, ptagAttachMethod

2.660 PidTagAttachMimeType

Canonical name: PidTagAttachMimeType

Description: Contains a content-type MIME header.

Property ID: 0x370E

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.26

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMSS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMSS\]](#), [\[MS-OXOUM\]](#)

Alternate names: PR_ATTACH_MIME_TAG, PR_ATTACH_MIME_TAG_A, PR_ATTACH_MIME_TAG_W

2.661 PidTagAttachNumber

Canonical name: PidTagAttachNumber

Description: Identifies the Attachment object within its Message object.

Property ID: 0x0E21

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.6

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXRTFEX\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_NUM, ptagAttachNum

2.662 PidTagAttachPathname

Canonical name: PidTagAttachPathname

Description: Contains the 8.3 name of the **PidTagAttachLongPathname** property (section [2.654](#)).

Property ID: 0x3708

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.14

Consuming reference: [\[MS-OXORMMSS\]](#)

Alternate names: PR_ATTACH_PATHNAME, PR_ATTACH_PATHNAME_A, ptagAttachPathname, PR_ATTACH_PATHNAME_W

2.663 PidTagAttachPayloadClass

Canonical name: PidTagAttachPayloadClass

Description: Contains the class name of an object that can display the contents of the message.

Property ID: 0x371A

Data type: PtypString, 0x001F

Area: Outlook Application

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.26

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_ATTACH_PAYLOAD_CLASS, PR_ATTACH_PAYLOAD_CLASS_A, PR_ATTACH_PAYLOAD_CLASS_W, ptagAttachPayloadClass

2.664 PidTagAttachPayloadProviderGuidString

Canonical name: PidTagAttachPayloadProviderGuidString

Description: Contains the GUID of the software component that can display the contents of the message.

Property ID: 0x3719

Data type: PtypString, 0x001F

Area: Outlook Application

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.26

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_ATTACH_PAYLOAD_PROV_GUID_STR, PR_ATTACH_PAYLOAD_PROV_GUID_STR_A, PR_ATTACH_PAYLOAD_PROV_GUID_STR_W

2.665 PidTagAttachRendering

Canonical name: PidTagAttachRendering

Description: Contains a Windows Metafile, as specified in [\[MS-WMF\]](#), for the Attachment object.

Property ID: 0x3709

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.17

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTACH_RENDERING, ptagAttachRendering

2.666 PidTagAttachSize

Canonical name: PidTagAttachSize

Description: Contains the size, in bytes, consumed by the Attachment object on the server.

Property ID: 0x0E20

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.5

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_SIZE, ptagAttachSize

2.667 PidTagAttachTag

Canonical name: PidTagAttachTag

Description: Contains the identifier information for the application that supplied the Attachment object's data.

Property ID: 0x370A

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.15

Consuming references: [\[MS-OXORMMSS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTACH_TAG

2.668 PidTagAttachTransportName

Canonical name: PidTagAttachTransportName

Description: Contains the name of an attachment file, modified so that it can be correlated with TNEF messages.

Property ID: 0x370C

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.19

Consuming reference: [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTACH_TRANSPORT_NAME, PR_ATTACH_TRANSPORT_NAME_A, PR_ATTACH_TRANSPORT_NAME_W

2.669 PidTagAttributeHidden

Canonical name: PidTagAttributeHidden

Description: Specifies the hide or show status of a folder.

Property ID: 0x10F4

Data type: PtypBoolean, 0x000B

Area: Access Control Properties

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.1

Consuming references: [\[MS-OXOSFLD\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ATTR_HIDDEN, ptagAttrHidden, DAV:ishidden

2.670 PidTagAttributeReadOnly

Canonical name: PidTagAttributeReadOnly

Description:

Property ID: 0x10F6

Data type: PtypBoolean, 0x000B

Area: Access Control Properties

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.1.8

Consuming references: [\[MS-OXTNEF\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ATTR_READONLY, ptagAttrReadonly, DAV:isreadonly

2.671 PidTagAutoForwarded

Canonical name: PidTagAutoForwarded

Description:

Property ID: 0x0005

Data type: PtypBoolean, 0x000B

Area: General Report Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.20

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_AUTO_FORWARDED, ptagAutoForwarded

2.672 PidTagAutoForwardComment

Canonical name: PidTagAutoForwardComment

Description: Contains text included in an automatically-generated message.

Property ID: 0x0004

Data type: PtypString, 0x001F

Area: General Report Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.21

Alternate names: PR_AUTO_FORWARD_COMMENT, PR_AUTO_FORWARD_COMMENT_A, PR_AUTO_FORWARD_COMMENT_W

2.673 PidTagAutoResponseSuppress

Canonical name: PidTagAutoResponseSuppress

Description: Specifies whether a client or server application should forego sending automated replies in response to this message.

Property ID: 0x3FDF

Data type: PtypInteger32, 0x0003

Area: E-mail

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.68

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_AUTO_RESPONSE_SUPPRESS, ptagAutoResponseSuppress

2.674 PidTagBirthday

Canonical name: PidTagBirthday

Description: Contains the date of the mail user's birthday at midnight.

Property ID: 0x3A42

Data type: PtypTime, 0x0040

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.79

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BIRTHDAY, urn:schemas:contacts:bday

2.675 PidTagBlockStatus

Canonical name: PidTagBlockStatus

Description: Indicates the user's preference for viewing external content (such as links to images on an **HTTP** server) in the message body.

Property ID: 0x1096

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.1

Alternate names: PR_BLOCK_STATUS, ptagBlockStatus

2.676 PidTagBody

Canonical name: PidTagBody

Description: Contains message body text in **plain text** format.

Property ID: 0x1000

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.1

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMSS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BODY, PR_BODY_A, ptagBody, PR_BODY_W,
urn:schemas:httpmail:textdescription

2.677 PidTagBodyContentId

Canonical name: PidTagBodyContentId

Description: Contains a GUID that corresponds to the current message body.

Property ID: 0x1015

Data type: **PtypString**, 0x001F

Area: Exchange

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.7

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_BODY_CONTENT_ID, PR_BODY_CONTENT_ID_A, PR_BODY_CONTENT_ID_W

2.678 PidTagBodyContentLocation

Canonical name: PidTagBodyContentLocation

Description: Contains a globally unique Uniform Resource Identifier (URI) that serves as a label for the current message body.

Property ID: 0x1014

Data type: **PtypString**, 0x001F

Area: MIME Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.8

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_BODY_CONTENT_LOCATION, PR_BODY_CONTENT_LOCATION_A,
PR_BODY_CONTENT_LOCATION_W

2.679 PidTagBodyHtml

Canonical name: PidTagBodyHtml

Property ID: 0x1013

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.3

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMMS\]](#), [\[MS-OXRTFEX\]](#)

Alternate names: PR_BODY_HTML, PR_BODY_HTML_A, ptagBodyHtml, PR_BODY_HTML_W

2.680 PidTagBusiness2TelephoneNumber

Canonical name: PidTagBusiness2TelephoneNumber

Description: Contains a secondary telephone number at the mail user's place of business.

Property ID: 0x3A1B

Data type: **PtypString**, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.40

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: "PR_BUSINESS2_TELEPHONE_NUMBER,
PR_BUSINESS2_TELEPHONE_NUMBER_A, PR_BUSINESS2_TELEPHONE_NUMBER_W,
PR_OFFICE2_TELEPHONE_NUMBER, urn:schemas:contacts:telephonenumber2

2.681 PidTagBusiness2Telephones

Canonical name: PidTagBusiness2Telephones

Description: Contains secondary telephone numbers at the mail user's place of business.

Property ID: 0x3A1B

Data type: **PtypMultipleString**, 0x101F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.41

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_BUSINESS2_TELEPHONE_NUMBER_A_MV

2.682 PidTagBusinessFaxNumber

Canonical name: PidTagBusinessFaxNumber

Description: Contains the telephone number of the mail user's business fax machine.

Property ID: 0x3A24

Data type: **PtypString**, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.51

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BUSINESS_FAX_NUMBER, PR_BUSINESS_FAX_NUMBER_A,
PR_BUSINESS_FAX_NUMBER_W, urn:schemas:contacts:facsimiletelephonenumber

2.683 PidTagBusinessHomePage

Canonical name: PidTagBusinessHomePage

Description: Contains the URL of the mail user's business home page.

Property ID: 0x3A51

Data type: **PtypString**, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.78

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BUSINESS_HOME_PAGE, PR_BUSINESS_HOME_PAGE_A,
PR_BUSINESS_HOME_PAGE_W,
urn:schemas:contacts:businesshomepageurn:schemas:contacts:businesshomepage

2.684 PidTagBusinessTelephoneNumber

Canonical name: PidTagBusinessTelephoneNumber

Description: Contains the primary telephone number of the mail user's place of business.

Property ID: 0x3A08

Data type: **PtypString**, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.38

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BUSINESS_TELEPHONE_NUMBER, PR_BUSINESS_TELEPHONE_NUMBER_A,
PR_BUSINESS_TELEPHONE_NUMBER_W, PR_OFFICE_TELEPHONE_NUMBER,
urn:schemas:contacts:telephoneNumber

2.685 PidTagCallbackTelephoneNumber

Canonical name: PidTagCallbackTelephoneNumber

Description: Contains a telephone number to reach the mail user.

Property ID: 0x3A02

Data type: **PtypString**, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.44

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CALLBACK_TELEPHONE_NUMBER, PR_CALLBACK_TELEPHONE_NUMBER_A, PR_CALLBACK_TELEPHONE_NUMBER_W, urn:schemas:contacts:callbackphone

2.686 PidTagCallId

Canonical name: PidTagCallId

Description:

Property ID: 0x6806

Data type: **PtypString**, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaCallID

2.687 PidTagCarTelephoneNumber

Canonical name: PidTagCarTelephoneNumber

Description: Contains the mail user's car telephone number.

Property ID: 0x3A1E

Data type: **PtypString**, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.47

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CAR_TELEPHONE_NUMBER, PR_CAR_TELEPHONE_NUMBER_A, PR_CAR_TELEPHONE_NUMBER_W, urn:schemas:contacts:othermobile

2.688 PidTagCdoRecurrenceid

Canonical name: PidTagCdoRecurrenceid

Description:

Property ID: 0x10C5

Data type: PtypTime, 0x0040

Area: Exchange

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.38

Alternate names: PR_CDO_RECURRENCEID, urn:schemas:calendar:recurrenceid

2.689 PidTagChangeKey

Canonical name: PidTagChangeKey

Description: Contains a structure that identifies the last change to the object.

Property ID: 0x65E2

Data type: PtypBinary, 0x0102

Area: History Properties

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.7

Consuming references: [\[MS-OXCOLD\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXCSYNC\]](#)

Alternate names: PR_CHANGE_KEY

2.690 PidTagChangeNumber

Canonical name: PidTagChangeNumber

Description: Contains a structure that identifies the last change to the message or folder that is currently being synchronized.

Property ID: 0x67A4

Data type: PtypInteger64, 0x0014

Area: Sync

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.3

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: ptagCn

2.691 PidTagChildrensNames

Canonical name: PidTagChildrensNames

Description:

Property ID: 0x3A58

Data type: PtypMultipleString, 0x101F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.17

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CHILDRENS_NAMES, PR_CHILDRENS_NAMES_A, PR_CHILDRENS_NAMES_W, urn:schemas:contacts:childrensnames

2.692 PidTagClientActions

Canonical name: PidTagClientActions

Property ID: 0x6645

Data type: PtypBinary, 0x0102

Area: Server-side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.6.6

Alternate names: PR_CLIENT_ACTIONS, ptagClientActions

2.693 PidTagClientSubmitTime

Canonical name: PidTagClientSubmitTime

Description: Contains the current time, in UTC, when the e-mail message is submitted.

Property ID: 0x0039

Data type: PtypTime, 0x0040

Area: Message Time Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.11

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_CLIENT_SUBMIT_TIME, urn:schemas:httpmail:date, http://schemas.microsoft.com/exchange/date-iso

2.694 PidTagCodePageId

Canonical name: PidTagCodePageId

Description: Contains the identifier for the client code page used for **Unicode to double-byte character set (DBCS)** string conversion.

Property ID: 0x66C3

Data type: PtypInteger32, 0x0003

Area: Exchange Profile Configuration

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Alternate names: PR_CODE_PAGE_ID, ptagCodePageId

2.695 PidTagComment

Canonical name: PidTagComment

Description: Contains a comment about the purpose or content of the Address Book object.

Property ID: 0x3004

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.2

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_COMMENT, PR_COMMENT_A, ptagComment, PR_COMMENT_W,
DAV:comment, http://schemas.microsoft.com/exchange/summary-utf8

2.696 PidTagCompanyMainTelephoneNumber

Canonical name: PidTagCompanyMainTelephoneNumber

Description: Contains the main telephone number of the mail user's company.

Property ID: 0x3A57

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.53

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_COMPANY_MAIN_PHONE_NUMBER,
PR_COMPANY_MAIN_PHONE_NUMBER_A, PR_COMPANY_MAIN_PHONE_NUMBER_W,
urn:schemas:contacts:organizationmainphone

2.697 PidTagCompanyName

Canonical name: PidTagCompanyName

Description: Contains the mail user's company name.

Property ID: 0x3A16

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.10

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#)

Alternate names: PR_COMPANY_NAME, PR_COMPANY_NAME_A, PR_COMPANY_NAME_W,
urn:schemas:contacts:o

2.698 PidTagComputerNetworkName

Canonical name: PidTagComputerNetworkName

Description: Contains the name of the mail user's computer network.

Property ID: 0x3A49

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.74

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_COMPUTER_NETWORK_NAME, PR_COMPUTER_NETWORK_NAME_A, PR_COMPUTER_NETWORK_NAME_W, urn:schemas:contacts:computernetworkname

2.699 PidTagConflictEntryId

Canonical name: PidTagConflictEntryId

Description: Contains the EntryID of the conflict resolve message.

Property ID: 0x3FF0

Data type: PtypBinary, 0x0102

Area: ICS

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.4.2

Alternate names: PR_CONFLICT_ENTRYID, ptagConflictEntryId

2.700 PidTagConflictItems

Canonical name: PidTagConflictItems

Description: Contains the EntryIDs of messages that won or lost in the conflict resolution involving this message.

Property ID: 0x1098

Data type: PtypMultipleBinary, 0x1102

Area: ICS

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.4.3

Consuming reference: [\[MS-OXCSYNC\]](#)

Alternate names: PR_CONFLICT_ITEMS

2.701 PidTagContainerClass

Canonical name: PidTagContainerClass

Description: Contains a string value that describes the type of Message object that a folder contains.

Property ID: 0x3613

Data type: PtypString, 0x001F

Area: Container Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.11.1

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDFOLD\]](#)

Alternate names: PR_CONTAINER_CLASS, PR_CONTAINER_CLASS_A, ptagContainerClass, PR_CONTAINER_CLASS_W, <http://schemas.microsoft.com/exchange/outlookfolderclass> <http://schemas.microsoft.com/exchange/outlookfolderclass>

2.702 PidTagContainerContents

Canonical name: PidTagContainerContents

Description: Always empty. An NSPI server defines this value for distribution lists and it is not present for other objects.

Property ID: 0x360F

Data type: PtypEmbeddedTable, 0x000D

Area: Container Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.6.3

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

Alternate names: PR_CONTAINER_CONTENTS, ptagContainerContents

2.703 PidTagContainerFlags

Canonical name: PidTagContainerFlags

Description: Contains a bitmask of flags that describe capabilities of an address book container.

Property ID: 0x3600

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.2.1

Consuming reference: [\[MS-NSPI\]](#)

Alternate names: PR_CONTAINER_FLAGS

2.704 PidTagContainerHierarchy

Canonical name: PidTagContainerHierarchy

Description: Identifies all of the subfolders of the current folder.

Property ID: 0x360E

Data type: **PtypObject**, 0x000D

Area: Container Properties

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

Alternate names: PR_CONTAINER_HIERARCHY, ptagContainerHierarchy

2.705 PidTagContentCount

Canonical name: PidTagContentCount

Description: Specifies the number of rows under the header row.

Property ID: 0x3602

Data type: **PtypInteger32**, 0x0003

Area: Folder Properties

Defining reference: [\[MS-OXCOLD\]](#) section 2.2.2.2.1.1

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CONTENT_COUNT, ptagContentCount, DAV:visiblecount

2.706 PidTagContentFilterPhishingConfidenceLevel

Canonical name: PidTagContentFilterPhishingConfidenceLevel

Description:

Property ID: 0x4084

Data type: **PtypInteger32**, 0x0003

Area: Secure Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ContentFilterPcl, PR_CONTENT_FILTER_PCL

2.707 PidTagContentFilterSpamConfidenceLevel

Canonical name: PidTagContentFilterSpamConfidenceLevel

Description: Indicates a confidence level that the message is spam.

Property ID: 0x4076

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.1.3

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_CONTENT_FILTER_SCL, ptagContentFilterSCL

2.708 PidTagContentUnreadCount

Canonical name: PidTagContentUnreadCount

Description: Specifies the number of rows under the header row that have the **PidTagRead** property (section [2.931](#)) set to FALSE.

Property ID: 0x3603

Data type: PtypInteger32, 0x0003

Area: Folder Properties

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.2

Consuming references: [\[MS-OXCTABL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CONTENT_UNREAD, ptagContentUnread, urn:schemas:httpmail:unreadcount

2.709 PidTagConversationId

Canonical name: PidTagConversationId

Description: Contains a computed value derived from other Conversation-related properties.

Property ID: 0x3013

Data type: PtypBinary, 0x0102

Area: Conversations

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.2

Consuming references: [\[MS-OXGLOS\]](#), [\[MS-OXOCFG\]](#)

Alternate names: PR_CONVERSATION_ID

2.710 PidTagConversationIndex

Canonical name: PidTagConversationIndex

Description: Indicates the relative position of this message within a conversation thread.

Property ID: 0x0071

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.3

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [MS-OXOMSG], [\[MS-OXOPOST\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCAL\]](#)

Alternate names: PR_CONVERSATION_INDEX, ptagConversationIndex

2.711 PidTagConversationIndexTracking

Canonical name: PidTagConversationIndexTracking

Description: Indicates whether the GUID portion of the **PidTagConversationIndex** property (section [2.710](#)) is to be used to compute the **PidTagConversationId** property (section [2.709](#)).

Property ID: 0x3016

Data type: PtypBoolean, 0x000B

Area: Conversations

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.4

Alternate names: PR_CONVERSATION_INDEX_TRACKING

2.712 PidTagConversationTopic

Canonical name: PidTagConversationTopic

Description: Contains an unchanging copy of the original subject.

Property ID: 0x0070

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.5

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_CONVERSATION_TOPIC, PR_CONVERSATION_TOPIC_A, ptagConversationTopic, PR_CONVERSATION_TOPIC_W, urn:schemas:httpmail:thread-topic

2.713 PidTagCountry

Canonical name: PidTagCountry

Description: Contains the name of the mail user's country/region.

Property ID: 0x3A26

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.24

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_COUNTRY, PR_COUNTRY_A, PR_COUNTRY_W,
PR_BUSINESS_ADDRESS_COUNTRY, PR_BUSINESS_ADDRESS_COUNTRY_A,
PR_BUSINESS_ADDRESS_COUNTRY_W, urn:schemas:contacts:mailingcountry

2.714 PidTagCreationTime

Canonical name: PidTagCreationTime

Description: Contains the time, in UTC, that the object was created.

Property ID: 0x3007

Data type: PtypTime, 0x0040

Area: Message Time Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.3

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMMS\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CREATION_TIME, ptagCreationTime, DAV:creationdate

2.715 PidTagCreatorEntryId

Canonical name: PidTagCreatorEntryId

Description: Specifies the original author of the message according to their Address Book EntryID.

Property ID: 0x3FF9

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.31

Consuming reference: [MS-OXCMSG], [\[MS-OXTNEF\]](#)

Alternate names: PR_CREATOR_ENTRYID, ptagCreatorEntryId

2.716 PidTagCreatorName

Canonical name: PidTagCreatorName

Description: Contains the name of a Message object.

Property ID: 0x3FF8

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_CREATOR_NAME, PR_CREATOR_NAME_A, ptagCreatorName, PR_CREATOR_NAME_W

2.717 PidTagCustomerId

Canonical name: PidTagCustomerId

Description: Contains the mail user's customer identification number.

Property ID: 0x3A4A

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.75

Consuming references: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CUSTOMER_ID, PR_CUSTOMER_ID_A, PR_CUSTOMER_ID_W, urn:schemas:contacts:customerid

2.718 PidTagDamBackPatched

Canonical name: PidTagDamBackPatched

Description: Indicates whether the **Deferred Action Message (DAM)** was updated by the server.

Property ID: 0x6647

Data type: PtypBoolean, 0x000B

Area: Server-side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.6.2

Alternate names: PR_DAM_BACK_PATCHED, ptagDamBackPatched

2.719 PidTagDamOriginalEntryId

Canonical name: PidTagDamOriginalEntryId

Description: Contains the EntryID of the delivered message that the client has to process.

Property ID: 0x6646

Data type: PtypBinary, 0x0102

Area: Server-side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.6.3

Alternate names: PR_DAM_ORIGINAL_ENTRYID

2.720 PidTagDefaultPostMessageClass

Canonical name: PidTagDefaultPostMessageClass

Description: Contains the message class of the object.

Property ID: 0x36E5

Data type: PtypString, 0x001F

Area: MapiContainer

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.11.2

Alternate names: PR_DEF_POST_MSGCLASS

2.721 PidTagDeferredActionMessageOriginalEntryId

Canonical name: PidTagDeferredActionMessageOriginalEntryId

Description: Contains the server EntryID for the DAM.

Property ID: 0x6741

Data type: PtypServerId, 0x00FB

Area: Server-side Rules Properties

Defining reference: [\[MS-OXORULE\]](#)

Alternate names: PR_DAM_ORIG_MSG_SVREID, ptagDamOrgMsgSvrEID

2.722 PidTagDeferredDeliveryTime

Canonical name: PidTagDeferredDeliveryTime

Description: Contains the date and time, in UTC, at which the sender prefers that the message be delivered.

Property ID: 0x000F

Data type: PtypTime, 0x0040

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.6

Alternate names: PR_DEFERRED_DELIVERY_TIME, ptagDeferredDeliveryTime, <http://schemas.microsoft.com/exchange/deferred-delivery-iso>

2.723 PidTagDeferredSendNumber

Canonical name: PidTagDeferredSendNumber

Description: Contains a number used in the calculation of how long to defer sending a message.

Property ID: 0x3FEB

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.2

Alternate names: PR_DEFERRED_SEND_NUMBER

2.724 PidTagDeferredSendTime

Canonical name: PidTagDeferredSendTime

Description: Contains the amount of time after which a client would like to defer sending the message.

Property ID: 0x3FEF

Data type: PtypTime, 0x0040

Area: MapiStatus

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.4

Alternate names: PR_DEFERRED_SEND_TIME, ptagDeferredSendTime

2.725 PidTagDeferredSendUnits

Canonical name: PidTagDeferredSendUnits

Description: Specifies the unit of time used as a multiplier with the **PidTagDeferredSendNumber** property (section [2.723](#)) value.

Property ID: 0x3FEC

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.3

Alternate names: PR_DEFERRED_SEND_UNITS

2.726 PidTagDelegatedByRule

Canonical name: PidTagDelegatedByRule

Description: Specifies whether the message was forwarded due to the triggering of a delegate forward rule.

Property ID: 0x3FE3

Data type: PtypBoolean, 0x000B

Area: MapiStatus

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.76

Consuming references: [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_DELEGATED_BY_RULE

2.727 PidTagDelegateFlags

Canonical name: PidTagDelegateFlags

Description:

Property ID: 0x686B

Data type: PtypMultipleInteger32, 0x1003

Area: MessageClassDefinedTransmittable

Defining reference: [\[MS-OXODLGT\]](#) section 2.2.2.2.6

Alternate names: PR_DELEGATE_FLAGS, ptagDelegateFlags

2.728 PidTagDeleteAfterSubmit

Canonical name: PidTagDeleteAfterSubmit

Description: Indicates that the original message is to be deleted after it is sent.

Property ID: 0x0E01

Data type: PtypBoolean, 0x000B

Area: MapiNonTransmittable

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.8

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCSTORI\]](#), [\[MS-OXODOC\]](#)

Alternate names: PR_DELETE_AFTER_SUBMIT, ptagDeleteAfterSubmit

2.729 PidTagDeletedOn

Canonical name: PidTagDeletedOn

Description: Specifies the time, in UTC, when the item or folder was **soft deleted**.

Property ID: 0x668F

Data type: PtypTime, 0x0040

Area: ExchangeFolder

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.3

Alternate names: PR_DELETED_ON, ptagDeletedOn, urn:schemas:httpmail:deletedon

2.730 PidTagDepartmentName

Canonical name: PidTagDepartmentName

Description: Contains a name for the department in which the mail user works.

Property ID: 0x3A18

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.9

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#) [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_DEPARTMENT_NAME, PR_DEPARTMENT_NAME_A, PR_DEPARTMENT_NAME_W, urn:schemas:contacts:department

2.731 PidTagDepth

Canonical name: PidTagDepth

Description: Specifies the number of nested categories in which a given row is contained.

Property ID: 0x3005

Data type: PtypInteger32, 0x0003

Area: MapiCommon

Defining reference: [\[MS-OXCTABL\]](#) section 2.2.1.4

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#)

Alternate names: PR_DEPTH, ptagDepth

2.732 PidTagDisplayBcc

Canonical name: PidTagDisplayBcc

Description: Contains a list of **blind carbon copy (Bcc) recipient** display names.

Property ID: 0x0E02

Data type: PtypString, 0x001F

Area: Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.7

Consuming reference: [\[MS-OXCMSG\]](#)

Alternate names: PR_DISPLAY_BCC, PR_DISPLAY_BCC_A, ptagDisplayBcc, PR_DISPLAY_BCC_W, urn:schemas:httpmail:displaybcc

2.733 PidTagDisplayCc

Canonical name: PidTagDisplayCc

Description: Contains a list of carbon copy (Cc) recipient display names.

Property ID: 0x0E03

Data type: PtypString, 0x001F

Area: Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.8

Consuming references: [\[MS-OXCMSG\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_DISPLAY_CC, PR_DISPLAY_CC_A, ptagDisplayCc, PR_DISPLAY_CC_W, urn:schemas:httpmail:displaycc

2.734 PidTagDisplayName

Canonical name: PidTagDisplayName

Description: Contains the display name of the folder.

Property ID: 0x3001

Data type: PtypString, 0x001F

Area: MapiCommon

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.3

Consuming references: [\[MS-OXCMSG\]](#), [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOAB1\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRP1\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDVSEC\]](#)

Alternate names: PR_DISPLAY_NAME, PR_DISPLAY_NAME_A, ptagDisplayName, PR_DISPLAY_NAME_W, urn:schemas:contacts:cn

2.735 PidTagDisplayNamePrefix

Canonical name: PidTagDisplayNamePrefix

Description: Contains the mail user's honorific title.

Property ID: 0x3A45

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.4

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_DISPLAY_NAME_PREFIX, PR_DISPLAY_NAME_PREFIX_A, PR_DISPLAY_NAME_PREFIX_W, urn:schemas:contacts:personaltitle

2.736 PidTagDisplayTo

Canonical name: PidTagDisplayTo

Description: Contains a list of the **primary recipient** display names, separated by semicolons, when an e-mail message has primary recipients.

Property ID: 0x0E04

Data type: PtypString, 0x001F

Area: Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.9

Consuming references: [\[MS-OXCMSG\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_DISPLAY_TO, PR_DISPLAY_TO_A, ptagDisplayTo, PR_DISPLAY_TO_W

2.737 PidTagDisplayType

Canonical name: PidTagDisplayType

Description: Contains an integer value that indicates how to display an Address Book object in a table or as an addressee on a message.

Property ID: 0x3900

Data type: PtypInteger32, 0x0003

Area: MapiAddressBook

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.11

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_DISPLAY_TYPE, ptagDisplayType

2.738 PidTagDisplayTypeEx

Canonical name: PidTagDisplayTypeEx

Description: Contains an integer value that indicates how to display an Address Book object in a table or as a recipient on a message.

Property ID: 0x3905

Data type: PtypInteger32, 0x0003

Area: MapiAddressBook

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.12

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_DISPLAY_TYPE_EX

2.739 PidTagEmailAddress

Canonical name: PidTagEmailAddress

Description: Contains the Message object's e-mail address.

Property ID: 0x3003

Data type: PtypString, 0x001F

Area: MapiCommon

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.14

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXPSVAL\]](#)

Alternate names: PR_EMAIL_ADDRESS, PR_EMAIL_ADDRESS_A, PR_EMAIL_ADDRESS_W

2.740 PidTagEndDate

Canonical name: PidTagEndDate

Description: Contains the value of the **PidLidAppointmentEndWhole** property (section [2.14](#)).

Property ID: 0x0061

Data type: PtypTime, 0x0040

Area: MapiEnvelope Property set

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.31

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

Alternate names: PR_END_DATE, http://schemas.microsoft.com/mapi/end_date

2.741 PidTagEntryId

Canonical name: PidTagEntryId

Description: Contains the information to identify many different types of **messaging objects**.

Property ID: 0x0FFF

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXCPERM\]](#) section 2.2.1.4

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXWAVLS\]](#), [\[MS-OXOCFG\]](#)

Alternate names: PR_ENTRYID, ptagEntryId

2.742 PidTagExceptionEndTime

Canonical name: PidTagExceptionEndTime

Description: Contains the start date and time of the exception in the local time zone of the computer when the exception is created.

Property ID: 0x7FFC

Data type: PtypTime, 0x0040

Area: MessageClassDefinedNonTransmittable

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.10.1.5

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_EXCEPTION_ENDTIME, ptagExceptionEndTime

2.743 PidTagExceptionReplaceTime

Canonical name: PidTagExceptionReplaceTime

Description: Indicates the original date and time, in UTC, at which the instance in the recurrence pattern would have occurred if it were not an exception.

Property ID: 0x7FF9

Data type: PtypTime, 0x0040

Area: MessageClassDefinedNonTransmittable

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.10.1.6

Alternate names: PR_EXCEPTION_REPLACETIME

2.744 PidTagExceptionStartTime

Canonical name: PidTagExceptionStartTime

Description: Contains the end date and time of the exception in the local time zone of the computer when the exception is created.

Property ID: 0x7FFB

Data type: PtypTime, 0x0040

Area: MessageClassDefinedNonTransmittable

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.10.1.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_EXCEPTION_STARTTIME, ptagExceptionStartTime

2.745 PidTagExchangeNTSecurityDescriptor

Canonical name: PidTagExchangeNTSecurityDescriptor

Description: Contains the calculated security descriptor for the item.

Property ID: 0x0E84

Data type: PtypBinary, 0x0102

Area: Calendar Document

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.8

Consuming references: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: http://schemas.microsoft.com/exchange/ntsecuritydescriptor, http://schemas.microsoft.com/exchange/ntsecuritydescriptor

2.746 PidTagExpiryNumber

Canonical name: PidTagExpiryNumber

Description: Contains an integer value that is used along with the **PidTagExpiryUnits** property (section [2.748](#)) to define the expiry send time.

Property ID: 0x3FED

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.5

Alternate names: PR_EXPIRY_NUMBER

2.747 PidTagExpiryTime

Canonical name: PidTagExpiryTime

Description: Contains the time, in UTC, after which a client wants to receive an expiry event if the message arrives late.

Property ID: 0x0015

Data type: PtypTime, 0x0040

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.7

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_EXPIRY_TIME, ptagExpiryTime, urn:schemas:httpmail:expiry-date, http://schemas.microsoft.com/exchange/expiry-date-iso

2.748 PidTagExpiryUnits

Canonical name: PidTagExpiryUnits

Description: Contains the unit of time that the value of the **PidTagExpiryNumber** property (section [2.746](#)) multiplies.

Property ID: 0x3FEE

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.6

Alternate names: PR_EXPIRY_UNITS

2.749 PidTagExtendedFolderFlags

Canonical name: PidTagExtendedFolderFlags

Description: Contains encoded sub-properties for a folder.

Property ID: 0x36DA

Data type: PtypBinary, 0x0102

Area: MapiContainer

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.2.1.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#)

Alternate names: PR_EXTENDED_FOLDER_FLAGS, ptagExtendedFolderFlags

2.750 PidTagExtendedRuleMessageActions

Canonical name: PidTagExtendedRuleMessageActions

Description: Contains action information about named properties used in the rule.

Property ID: 0x0E99

Data type: PtypBinary, 0x0102

Area: Rules

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.9

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: PR_EXTENDED_RULE_MSG_ACTIONS

2.751 PidTagExtendedRuleMessageCondition

Canonical name: PidTagExtendedRuleMessageCondition

Description: Contains condition information about named properties used in the rule.

Property ID: 0x0E9A

Data type: PtypBinary, 0x0102

Area: Rules

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.10

Consuming references: [\[MS-OXCPRPT\]](#), [\[MS-OXCSPAM\]](#)

Alternate names: PR_EXTENDED_RULE_MSG_CONDITION

2.752 PidTagExtendedRuleSizeLimit

Canonical name: PidTagExtendedRuleSizeLimit

Description: Contains the maximum size, in bytes, that the user is allowed to accumulate for a single extended rule.

Property ID: 0x0E9B

Data type: PtypInteger32, 0x0003

Area: Rules

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Consuming Reference: [\[MS-OXORULE\]](#)

Alternate names: PR_EXTENDED_RULE_SIZE_LIMIT

2.753 PidTagFaxNumberOfPages

Canonical name: PidTagFaxNumberOfPages

Description: Contains the number of pages in a Fax object.

Property ID: 0x6804

Data type: PtypInteger32, 0x0003

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaFaxNumberOfPages

2.754 PidTagFlagCompleteTime

Canonical name: PidTagFlagCompleteTime

Description: Specifies the date and time, in UTC, that the Message object was flagged as complete.

Property ID: 0x1091

Data type: PtypTime, 0x0040

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.3

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_FLAG_COMPLETE_TIME, ptagFlagCompleteTime, urn:schemas:httpmail:flagcompleted

2.755 PidTagFlagStatus

Canonical name: PidTagFlagStatus

Description: Specifies the flag state of the Message object.

Property ID: 0x1090

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.1

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_FLAG_STATUS, ptagFlagStatus

2.756 PidTagFlatUrlName

Canonical name: PidTagFlatUrlName

Description: Contains a unique identifier for an item across the store.

Property ID: 0x670E

Data type: PtypString, 0x001F

Area: ExchangeAdministrative

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.9

Consuming references: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_FLAT_URL_NAME, PR_FLAT_URL_NAME_A, PR_FLAT_URL_NAME_W, ptagFlatURLName, http://schemas.microsoft.com/exchange/permanenturl

2.757 PidTagFolderAssociatedContents

Canonical name: PidTagFolderAssociatedContents

Description: Identifies all FAI messages in the current folder.

Property ID: 0x3610

Data type: PtypObject, 0x000D

Area: MapiContainer

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

Alternate names: PR_FOLDER_ASSOCIATED_CONTENTS

2.758 PidTagFolderId

Canonical name: PidTagFolderId

Description: Contains the Folder ID (FID) ([\[MS-OXCDATA\]](#) section 2.2.1.1) of the folder.

Property ID: 0x6748

Data type: PtypInteger64, 0x0014

Area: ID Properties

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.5

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

Alternate names: ptagFID

2.759 PidTagFolderType

Canonical name: PidTagFolderType

Description: Specifies the type of a folder that includes the **Root folder**, Generic folder, and Search folder.

Property ID: 0x3601

Data type: PtypInteger32, 0x0003

Area: MapiContainer

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_FOLDER_TYPE, ptagFolderType

2.760 PidTagFollowupIcon

Canonical name: PidTagFollowupIcon

Description: Specifies the flag color of the Message object.

Property ID: 0x1095

Data type: PtypInteger32, 0x0003

Area: RenMessageFolder

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.2

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_FOLLOWUP_ICON, ptagFollowupIcon

2.761 PidTagFreeBusyCountMonths

Canonical name: PidTagFreeBusyCountMonths

Description: Contains an integer value used to calculate the start and end dates of the range of free/busy data to be published to the public folders.

Property ID: 0x6869

Data type: PtypInteger32, 0x0003

Area: MessageClassDefinedTransmittable

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.12.1

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: PR_FREEBUSY_COUNT_MONTHS

2.762 PidTagFreeBusyEntryIds

Canonical name: PidTagFreeBusyEntryIds

Description: Contains EntryIDs of the Delegate Information object, the free/busy message of the logged on user, and the folder with the **PidTagDisplayName** property (section [2.734](#)) value of "Freebusy Data".

Property ID: 0x36E4

Data type: PtypMultipleBinary, 0x1102

Area: MapiContainer

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.2.1

Consuming references: [\[MS-OXODLGT\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_FREEBUSY_ENTRYIDS, ptagFreeBusyEntryIds

2.763 PidTagFreeBusyMessageEmailAddress

Canonical name: PidTagFreeBusyMessageEmailAddress

Description: Specifies the e-mail address of the user to whom this free/busy message applies.

Property ID: 0x6849

Data type: PtypString, 0x001F

Area: MessageClassDefinedTransmittable

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.12

Alternate names: PR_FREEBUSY_EMA

2.764 PidTagFreeBusyPublishEnd

Canonical name: PidTagFreeBusyPublishEnd

Description: Specifies the end time, in UTC, of the publishing range.

Property ID: 0x6848

Data type: PtypInteger32, 0x0003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.10

Alternate names: PR_FREEBUSY_PUBLISH_END

2.765 PidTagFreeBusyPublishStart

Canonical name: PidTagFreeBusyPublishStart

Description: Specifies the start time, in UTC, of the publishing range.

Property ID: 0x6847

Data type: PtypInteger32, 0x0003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.9

Alternate names: PR_FREEBUSY_PUBLISH_START

2.766 PidTagFreeBusyRangeTimestamp

Canonical name: PidTagFreeBusyRangeTimestamp

Description: Specifies the time, in UTC, that the data was published.

Property ID: 0x6868

Data type: PtypTime, 0x0040

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.11

Alternate names: PR_FREEBUSY_RANGE_TIMESTAMP

2.767 PidTagFtpSite

Canonical name: PidTagFtpSite

Description: Contains the mail user's **File Transfer Protocol (FTP)** site address.

Property ID: 0x3A4C

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.76

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_FTP_SITE, PR_FTP_SITE_A, PR_FTP_SITE_W, urn:schemas:contacts:ftpsite

2.768 PidTagGatewayNeedsToRefresh

Canonical name: PidTagGatewayNeedsToRefresh

Description: This property is deprecated and SHOULD NOT be used.

Property ID: 0x6846

Data type: **PtypBoolean**, 0x000B

Area: MessageClassDefinedTransmittable

Defining reference: [\[MS-OXOPFB\]](#) section 2.2.1.4.1

Alternate names: PR_GATEWAY_NEEDS_TO_REFRESH

2.769 PidTagGender

Canonical name: PidTagGender

Description: Contains a value that represents the mail user's gender.

Property ID: 0x3A4D

Data type: **PtypInteger16**, 0x0002

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.73

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_GENDER, urn:schemas:contacts:gender

2.770 PidTagGeneration

Canonical name: PidTagGeneration

Description: Contains a generational abbreviation that follows the full name of the mail user.

Property ID: 0x3A05

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.6

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_GENERATION, PR_GENERATION_A, PR_GENERATION_W,
urn:schemas:contacts:namesuffix

2.771 PidTagGivenName

Canonical name: PidTagGivenName

Description: Contains the mail user's given name.

Property ID: 0x3A06

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.2

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_GIVEN_NAME, PR_GIVEN_NAME_A, PR_GIVEN_NAME_W,
urn:schemas:contacts:givenName

2.772 PidTagGovernmentIdNumber

Canonical name: PidTagGovernmentIdNumber

Description: Contains a government identifier for the mail user.

Property ID: 0x3A07

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.59

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_GOVERNMENT_ID_NUMBER, PR_GOVERNMENT_ID_NUMBER_A,
PR_GOVERNMENT_ID_NUMBER_W, urn:schemas:contacts:governmentid

2.773 PidTagHasAttachments

Canonical name: PidTagHasAttachments

Description: Indicates whether the Message object contains at least one attachment.

Property ID: 0x0E1B

Data type: **PtypBoolean**, 0x000B

Area: Message Attachment Properties Property set

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HASATTACH, ptagHasAttach, urn:schemas:httpmail:hasattachment

2.774 PidTagHasDeferredActionMessages

Canonical name: PidTagHasDeferredActionMessages

Description: Indicates whether a Message object has a deferred action message associated with it.

Property ID: 0x3FEA

Data type: PtypBoolean, 0x000B

Area: Rules

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.5.1

Alternate names: PR_HAS_DAMS, ptagHasDAMs

2.775 PidTagHasNamedProperties

Canonical name: PidTagHasNamedProperties

Description: Indicates whether the Message object has a named property.

Property ID: 0x664A

Data type: PtypBoolean, 0x000B

Area: ExchangeMessageReadOnly

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.39

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: PR_HAS_NAMED_PROPERTIES, ptagHasNamedProperties

2.776 PidTagHasRules

Canonical name: PidTagHasRules

Description: Indicates whether a Folder object has rules.

Property ID: 0x663A

Data type: PtypBoolean, 0x000B

Area: ExchangeFolder

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.4.1

Alternate names: PR_HAS_RULES, ptagHasRules

2.777 PidTagHierarchyChangeNumber

Canonical name: PidTagHierarchyChangeNumber

Description: Contains a number that monotonically increases every time a subfolder is added to, or deleted from, this folder.

Property ID: 0x663E

Data type: PtypInteger32, 0x0003

Area: ExchangeFolder

Defining reference: [\[MS-OXCOLD\]](#) section 2.2.2.2.1.6

Alternate names: PR_HIERARCHY_CHANGE_NUM

2.778 PidTagHobbies

Canonical name: PidTagHobbies

Description: Contains the names of the mail user's hobbies.

Property ID: 0x3A43

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.69

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOBBIES, PR_HOBBIES_A, PR_HOBBIES_W, urn:schemas:contacts:hobbies

2.779 PidTagHome2TelephoneNumber

Canonical name: PidTagHome2TelephoneNumber

Description: Contains a secondary telephone number at the mail user's home.

Property ID: 0x3A2F

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.42

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME2_TELEPHONE_NUMBER, PR_HOME2_TELEPHONE_NUMBER_A, PR_HOME2_TELEPHONE_NUMBER_W, urn:schemas:contacts:homephone2

2.780 PidTagHome2Telephones

Canonical name: PidTagHome2Telephones

Description: Contains secondary telephone numbers at the mail user's home.

Property ID: 0x3A2F

Data type: PtypMultipleString, 0x101F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.43

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_HOME2_TELEPHONE_NUMBER_A_MV

2.781 PidTagHomeAddressCity

Canonical name: PidTagHomeAddressCity

Description: Contains the name of the mail user's home locality, such as the town or city.

Property ID: 0x3A59

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.27

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_CITY, PR_HOME_ADDRESS_CITY_A, PR_HOME_ADDRESS_CITY_W, urn:schemas:contacts:homeCity

2.782 PidTagHomeAddressCountry

Canonical name: PidTagHomeAddressCountry

Description: Contains the name of the mail user's home country/region.

Property ID: 0x3A5A

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.30

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_COUNTRY, PR_HOME_ADDRESS_COUNTRY_A, PR_HOME_ADDRESS_COUNTRY_W, urn:schemas:contacts:homeCountry

2.783 PidTagHomeAddressPostalCode

Canonical name: PidTagHomeAddressPostalCode

Description: Contains the postal code for the mail user's home postal address.

Property ID: 0x3A5B

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.29

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_POSTAL_CODE, PR_HOME_ADDRESS_POSTAL_CODE_A, PR_HOME_ADDRESS_POSTAL_CODE_W, urn:schemas:contacts:homePostalCode

2.784 PidTagHomeAddressPostOfficeBox

Canonical name: PidTagHomeAddressPostOfficeBox

Description: Contains the number or identifier of the mail user's home post office box.

Property ID: 0x3A5E

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.26

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_POST_OFFICE_BOX, PR_HOME_ADDRESS_POST_OFFICE_BOX_A, PR_HOME_ADDRESS_POST_OFFICE_BOX_W, urn:schemas:contacts:homepostofficebox

2.785 PidTagHomeAddressStateOrProvince

Canonical name: PidTagHomeAddressStateOrProvince

Description: Contains the name of the mail user's home state or province.

Property ID: 0x3A5C

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.28

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_STATE_OR_PROVINCE, PR_HOME_ADDRESS_STATE_OR_PROVINCE_A, PR_HOME_ADDRESS_STATE_OR_PROVINCE_W, urn:schemas:contacts:homeState

2.786 PidTagHomeAddressStreet

Canonical name: PidTagHomeAddressStreet

Description: Contains the mail user's home street address.

Property ID: 0x3A5D

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.25

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_STREET, PR_HOME_ADDRESS_STREET_A, PR_HOME_ADDRESS_STREET_W, urn:schemas:contacts:homeStreet

2.787 PidTagHomeFaxNumber

Canonical name: PidTagHomeFaxNumber

Description: Contains the telephone number of the mail user's home fax machine.

Property ID: 0x3A25

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.52

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_FAX_NUMBER, PR_HOME_FAX_NUMBER_A, PR_HOME_FAX_NUMBER_W, urn:schemas:contacts:homefax

2.788 PidTagHomeTelephoneNumber

Canonical name: PidTagHomeTelephoneNumber

Description: Contains the primary telephone number of the mail user's home.

Property ID: 0x3A09

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.39

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_TELEPHONE_NUMBER, PR_HOME_TELEPHONE_NUMBER_A, PR_HOME_TELEPHONE_NUMBER_W, urn:schemas:contacts:homePhone

2.789 PidTagHtml

Canonical name: PidTagHtml

Description: Contains message body text in HTML format.

Property ID: 0x1013

Data type: **PtypBinary**, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.9

Consuming references: [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#)

Alternate names: PR_HTML, ptagHtml

2.790 PidTagICalendarEndTime

Canonical name: PidTagICalendarEndTime

Description: Contains the date and time, in UTC, when an appointment or meeting ends.

Property ID: 0x10C4

Data type: **PtypTime**, 0x0040

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.39

Consuming Reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:dtend

2.791 PidTagICalendarReminderNextTime

Canonical name: PidTagICalendarReminderNextTime

Description: Contains the date and time, in UTC, for the activation of the next reminder.

Property ID: 0x10CA

Data type: **PtypTime**, 0x0040

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.40

Alternate names: urn:schemas:calendar:remindernexttime

2.792 PidTagICalendarStartTime

Canonical name: PidTagICalendarStartTime

Description: Contains the date and time, in UTC, when the appointment or meeting starts.

Property ID: 0x10C3

Data type: **PtypTime**, 0x0040

Area: Calendar Property set

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.41

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:dtstart

2.793 PidTagIconIndex

Canonical name: PidTagIconIndex

Description: Specifies which icon is to be used by a user interface when displaying a group of Note objects.

Property ID: 0x1080

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.10

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ICON_INDEX, ptagIconIndex

2.794 PidTagImportance

Canonical name: PidTagImportance

Description: Indicates the level of importance assigned by the end user to the Message object.

Property ID: 0x0017

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.11

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_IMPORTANCE, ptagImportance, urn:schemas:httpmail:importance, http://schemas.microsoft.com/exchange/importance-long, http://schemas.microsoft.com/exchange/x-priority-long

2.795 PidTagInConflict

Canonical name: PidTagInConflict

Description: Specifies whether the attachment represents an alternate replica.

Property ID: 0x666C

Data type: PtypBoolean, 0x000B

Area: Conflict Note

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.4.4

Alternate names: PR_IN_CONFLICT, ptagInConflict

2.796 PidTagInitialDetailsPane

Canonical name: PidTagInitialDetailsPane

Description: Indicates which page of a display template to display first.

Property ID: 0x3F08

Data type: PtypInteger32, 0x0003

Area: MAPI Display Tables

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.33

Consuming Reference: [\[MS-NSPI\]](#)

Alternate names: PR_INITIAL_DETAILS_PANE

2.797 PidTagInitials

Canonical name: PidTagInitials

Description: Contains the initials for parts of the full name of the mail user.

Property ID: 0x3A0A

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.5

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_INITIALS, PR_INITIALS_A, PR_INITIALS_W, urn:schemas:contacts:initials

2.798 PidTagInReplyToId

Canonical name: PidTagInReplyToId

Description: Contains the value of the original message's **PidTagInternetMessageId** property (section [2.805](#)) value.

Property ID: 0x1042

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.13

Consuming Reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_IN_REPLY_TO_ID, PR_IN_REPLY_TO_ID_A, PR_IN_REPLY_TO_ID_W

2.799 PidTagInstanceKey

Canonical name: PidTagInstanceKey

Description: Contains an object on an NSPI server.

Property ID: 0x0FF6

Data type: **PtypBinary**, 0x0102

Area: Table Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.6

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABKT\]](#)

Alternate names: PR_INSTANCE_KEY, ptagInstanceKey

2.800 PidTagInstanceNum

Canonical name: PidTagInstanceNum

Description: Contains an identifier for a single instance of a row in the table.

Property ID: 0x674E

Data type: **PtypInteger32**, 0x0003

Area: ProviderDefinedNonTransmittable

Defining reference: [\[MS-OXCTABL\]](#) section 2.2.1.2

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: ptagInstanceNum

2.801 PidTagInstID

Canonical name: PidTagInstID

Description: Contains an identifier for all instances of a row in the table.

Property ID: 0x674D

Data type: **PtypInteger64**, 0x0014

Area: ProviderDefinedNonTransmittable

Defining reference: [\[MS-OXCTABL\]](#) section 2.2.1.1

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: ptagInstID

2.802 PidTagInternetArticleNumber

Canonical name: PidTagInternetArticleNumber

Description:

Property ID: 0x0E23

Data type: PtypInteger32, 0x0003

Area: MIME Properties

Defining reference:

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: PR_INTERNET_ARTICLE_NUMBER

2.803 PidTagInternetCodepage

Canonical name: PidTagInternetCodepage

Description: Indicates the code page used for the **PidTagBody** property (section [2.676](#)) or the **PidTagBodyHtml** property (section [2.679](#)).

Property ID: 0x3FDE

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.6

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_INTERNET_CPID, ptagInternetCpid

2.804 PidTagInternetMailOverrideFormat

Canonical name: PidTagInternetMailOverrideFormat

Description: Indicates the encoding method and HTML inclusion for attachments.

Property ID: 0x5902

Data type: PtypInteger32, 0x0003

Area: MIME Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.11

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

Alternate names: PR_INETMAIL_OVERRIDE_FORMAT, ptagInetMailOverrideFormat

2.805 PidTagInternetMessageId

Canonical name: PidTagInternetMessageId

Description: Corresponds to the **message-id** field.

Property ID: 0x1035

Data type: PtypString, 0x001F

Area: MIME Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.12

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_INTERNET_MESSAGE_ID, PR_INTERNET_MESSAGE_ID_A,
PR_INTERNET_MESSAGE_ID_W

2.806 PidTagInternetReferences

Canonical name: PidTagInternetReferences

Description: Contains a list of message IDs that specify the messages to which this reply is related.

Property ID: 0x1039

Data type: PtypString, 0x001F

Area: MIME Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.26

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_INTERNET_REFERENCES, PR_INTERNET_REFERENCES_A,
PR_INTERNET_REFERENCES_W

2.807 PidTagIpmAppointmentEntryId

Canonical name: PidTagIpmAppointmentEntryId

Description: Contains the EntryID of the Calendar folder.

Property ID: 0x36D0

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Consuming references: [\[MS-OXODLGT\]](#)

Alternate names: PR_IPM_APPOINTMENT_ENTRYID

2.808 PidTagIpmContactEntryId

Canonical name: PidTagIpmContactEntryId

Description: Contains the EntryID of the Contacts folder.

Property ID: 0x36D1

Data type: **PtypBinary**, 0x0102

Area: Folder Properties

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Consuming references: [\[MS-OXODLGT\]](#)

Alternate names: PR_IPM_CONTACT_ENTRYID

2.809 PidTagIpmDraftsEntryId

Canonical name: PidTagIpmDraftsEntryId

Description: Contains the EntryID of the Drafts folder.

Property ID: 0x36D7

Data type: **PtypBinary**, 0x0102

Area: Folder Properties

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Alternate names: PR_IPM_DRAFTS_ENTRYID

2.810 PidTagIpmJournalEntryId

Canonical name: PidTagIpmJournalEntryId

Description: Contains the EntryID of the Journal folder.

Property ID: 0x36D2

Data type: **PtypBinary**, 0x0102

Area: Folder Properties

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Consuming references: [\[MS-OXODLGT\]](#)

Alternate names: PR_IPM_JOURNAL_ENTRYID

2.811 PidTagIpmNoteEntryId

Canonical name: PidTagIpmNoteEntryId

Description: Contains the EntryID of the Notes folder.

Property ID: 0x36D3

Data type: **PtypBinary**, 0x0102

Area: Folder Properties

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Consuming references: [\[MS-OXODLGT\]](#)

Alternate names: PR_IPM_NOTE_ENTRYID

2.812 PidTagIpmTaskEntryId

Canonical name: PidTagIpmTaskEntryId

Description: Contains the EntryID of the Tasks folder.

Property ID: 0x36D4

Data type: **PtypBinary**, 0x0102

Area: Folder Properties

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Consuming references: [\[MS-OXODLGT\]](#)

Alternate names: PR_IPM_TASK_ENTRYID

2.813 PidTagIsdnNumber

Canonical name: PidTagIsdnNumber

Description: Contains the mail user's **Integrated Services Digital Network (ISDN)** telephone number.

Property ID: 0x3A2D

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.56

Consuming references: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ISDN_NUMBER, PR_ISDN_NUMBER_A, PR_ISDN_NUMBER_W,
urn:schemas:contacts:internationalisdnnumber

2.814 PidTagJunkAddRecipientsToSafeSendersList

Canonical name: PidTagJunkAddRecipientsToSafeSendersList

Description: Indicates whether e-mail recipients are to be added to the safe senders list.

Property ID: 0x6103

Data type: PtypInteger32, 0x0003

Area: Spam

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.2.1

Alternate names: PR_JUNK_ADD_RECIPS_TO_SSL

2.815 PidTagJunkIncludeContacts

Canonical name: PidTagJunkIncludeContacts

Description: Indicates whether e-mail addresses of the contacts in the Contacts folder are treated in a special way with respect to the spam filter.

Property ID: 0x6100

Data type: PtypInteger32, 0x0003

Area: Spam

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.2.2

Alternate names: PR_JUNK_INCLUDE_CONTACTS

2.816 PidTagJunkPermanentlyDelete

Canonical name: PidTagJunkPermanentlyDelete

Description: Indicates whether messages identified as spam can be permanently deleted.

Property ID: 0x6102

Data type: PtypInteger32, 0x0003

Area: Spam

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.2.3

Alternate names: PR_JUNK_PERMANENTLY_DELETE

2.817 PidTagJunkPhishingEnableLinks

Canonical name: PidTagJunkPhishingEnableLinks

Description: Indicated whether the phishing stamp on a message is to be ignored.

Property ID: 0x6107

Data type: PtypBoolean, 0x000B

Area: Spam

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.2.4

Consuming reference: [\[MS-OXPHISH\]](#)

Alternate names: PR_JUNK_PHISHING_ENABLE_LINKS

2.818 PidTagJunkThreshold

Canonical name: PidTagJunkThreshold

Description: Indicates how aggressively incoming e-mail is to be sent to the Junk E-mail folder.

Property ID: 0x6101

Data type: PtypInteger32, 0x0003

Area: Spam

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.2.5

Alternate names: PR_JUNK_THRESHOLD

2.819 PidTagKeyword

Canonical name: PidTagKeyword

Description: Contains a keyword that identifies the mail user to the mail user's system administrator.

Property ID: 0x3A0B

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.58

Alternate names: PR_KEYWORD, PR_KEYWORD_A, PR_KEYWORD_W

2.820 PidTagLanguage

Canonical name: PidTagLanguage

Description: Contains a value that indicates the language in which the messaging user is writing messages.

Property ID: 0x3A0C

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.61

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_LANGUAGE, PR_LANGUAGE_A, PR_LANGUAGE_W,
urn:schemas:contacts:language

2.821 PidTagLastModificationTime

Canonical name: PidTagLastModificationTime

Description: Contains the time, in UTC, of the last modification to the object.

Property ID: 0x3008

Data type: PtypTime, 0x0040

Area: Message Time Properties **Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.2

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCSYNC\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS1\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_LAST_MODIFICATION_TIME, ptagLastModificationTime, urn:schemas:calendar:lastmodifiedtime, DAV:getlastmodified

2.822 PidTagLastModifierEntryId

Canonical name: PidTagLastModifierEntryId

Description: Specifies the Address Book EntryID of the last user to modify the contents of the message.

Property ID: 0x3FFB

Data type: PtypBinary, 0x0102

Area: History Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.32

Consuming reference: [\[MS-OXTNEF\]](#)

Alternate names: PR_LAST_MODIFIER_ENTRYID, ptagLastModifierEntryId

2.823 PidTagLastModifierName

Canonical name: PidTagLastModifierName

Description: Contains the name of the last mail user to change the Message object.

Property ID: 0x3FFA

Data type: PtypString, 0x001F

Area: History Properties

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.1.5

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_LAST_MODIFIER_NAME, PR_LAST_MODIFIER_NAME_A, ptagLastModifierName, PR_LAST_MODIFIER_NAME_W

2.824 PidTagLastVerbExecuted

Canonical name: PidTagLastVerbExecuted

Description: Specifies the last verb executed for the message item to which it is related.

Property ID: 0x1081

Data type: PtypInteger32, 0x0003

Area: History Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.14

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: PR_LAST_VERB_EXECUTED, ptagLastVerbExecuted

2.825 PidTagLastVerbExecutionTime

Canonical name: PidTagLastVerbExecutionTime

Description: Contains the date and time, in UTC, during which the operation represented in the **PidTagLastVerbExecuted** property (section [2.824](#)) took place.

Property ID: 0x1082

Data type: PtypTime, 0x0040

Area: History Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.15

Consuming Reference: [\[MS-OXCICAL\]](#)

Alternate names: PR_LAST_VERB_EXECUTION_TIME, ptagLastVerbExecutionTime

2.826 PidTagListHelp

Canonical name: PidTagListHelp

Description: Contains a URI that provides detailed help information for the mailing list from which an e-mail message was sent.

Property ID: 0x1043

Data type: PtypString, 0x001F

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.73

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_LIST_HELP, PR_LIST_HELP_A, PR_LIST_HELP_W

2.827 PidTagListSubscribe

Canonical name: PidTagListSubscribe

Description: Contains the URI that subscribes a recipient (2) to a message's associated mailing list.

Property ID: 0x1044

Data type: PtypString, 0x001F

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.74

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_LIST_SUBSCRIBE, PR_LIST_SUBSCRIBE_A, PR_LIST_SUBSCRIBE_W

2.828 PidTagListUnsubscribe

Canonical name: PidTagListUnsubscribe

Description: Contains the URI that unsubscribes a recipient (2) from a message's associated mailing list.

Property ID: 0x1045

Data type: **PtypString**, 0x001F

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.75

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_LIST_UNSUBSCRIBE, PR_LIST_UNSUBSCRIBE_A, PR_LIST_UNSUBSCRIBE_W

2.829 PidTagLocalCommitTime

Canonical name: PidTagLocalCommitTime

Description: Contains the time, in UTC, that a **RopCreateMessage** remote operation (ROP) ([\[MS-OXCROPS\]](#) section 2.2.6.2) was processed.

Property ID: 0x6709

Data type: **PtypTime**, 0x0040

Area: Server

Defining reference:

Consuming Reference: [\[MS-OXCMMSG\]](#)

Alternate names: PR_LOCAL_COMMIT_TIME, ptagLocalCommitTime

2.830 PidTagLocaleId

Canonical name: PidTagLocaleId

Description: Contains the **Logon object** LocaleID.

Property ID: 0x66A1

Data type: **PtypInteger32**, 0x0003

Area: Miscellaneous Properties

Defining reference:

Consuming references: [\[MS-OXCMSG\]](#), [\[MS-OXCSTOR\]](#)

Alternate names: PR_LOCALE_ID, ptagLocaleId

2.831 PidTagLocality

Canonical name: PidTagLocality

Description: Contains the name of the mail user's locality, such as the town or city.

Property ID: 0x3A27

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.21

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_LOCALITY, PR_LOCALITY_A, PR_LOCALITY_W,
PR_BUSINESS_ADDRESS_LOCALITY, PR_BUSINESS_ADDRESS_LOCALITY_A,
PR_BUSINESS_ADDRESS_LOCALITY_W, urn:schemas:contacts:mailingcity

2.832 PidTagLocation

Canonical name: PidTagLocation

Description: Contains the location of the mail user.

Property ID: 0x3A0D

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.62

Consuming references: [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_LOCATION, PR_LOCATION_A, PR_LOCATION_W,
urn:schemas:contacts:location

2.833 PidTagMailboxOwnerEntryId

Canonical name: PidTagMailboxOwnerEntryId

Description: Contains the EntryID in the **Global Address List (GAL)** of the owner of the mailbox.

Property ID: 0x661B

Data type: **PtypBinary**, 0x0102

Area: Message Store Properties

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Consuming references: [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: PR_MAILBOX_OWNER_ENTRYID, ptagMailboxOwnerEntryId

2.834 PidTagMailboxOwnerName

Canonical name: PidTagMailboxOwnerName

Description: Contains the display name of the owner of the mailbox.

Property ID: 0x661C

Data type: **PtypString**, 0x001F

Area: Message Store Properties

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: PR_MAILBOX_OWNER_NAME, PR_MAILBOX_OWNER_NAME_A, ptagMailboxOwnerName, PR_MAILBOX_OWNER_NAME_W

2.835 PidTagManagerName

Canonical name: PidTagManagerName

Description: Contains the name of the mail user's manager.

Property ID: 0x3A4E

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.12

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MANAGER_NAME, PR_MANAGER_NAME_A, PR_MANAGER_NAME_W, urn:schemas:contacts:manager

2.836 PidTagMappingSignature

Canonical name: PidTagMappingSignature

Description: A 16-byte constant that is present on all Address Book objects, but is not present on objects in an offline address book.

Property ID: 0x0FF8

Data type: **PtypBinary**, 0x0102

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.32

Consuming reference: [\[MS-NSPI\]](#)

Alternate names: PR_MAPPING_SIGNATURE, ptagMappingSignature

2.837 PidTagMaximumSubmitMessageSize

Canonical name: PidTagMaximumSubmitMessageSize

Description: Maximum size, in kilobytes, of a message that a user is allowed to submit for transmission to another user.

Property ID: 0x666D

Data type: PtypInteger32, 0x0003

Area: Message Store Properties

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Alternate names: PR_MAX_SUBMIT_MESSAGE_SIZE

2.838 PidTagMemberId

Canonical name: PidTagMemberId

Description: Contains a unique identifier that the messaging server generates for each user.

Property ID: 0x6671

Data type: PtypInteger64, 0x0014

Area: Access Control Properties

Defining reference: [\[MS-OXCPERM\]](#) section 2.2.1.5

Alternate names: PR_MEMBER_ID, ptagMemberId

2.839 PidTagMemberName

Canonical name: PidTagMemberName

Description: Contains the user-readable name of the user.

Property ID: 0x6672

Data type: PtypString, 0x001F

Area: Access Control Properties

Defining reference: [\[MS-OXCPERM\]](#) section 2.2.1.6

Alternate names: PR_MEMBER_NAME, PR_MEMBER_NAME_A, ptagMemberName, PR_MEMBER_NAME_W

2.840 PidTagMemberRights

Canonical name: PidTagMemberRights

Description: Contains the permissions for the specified user.

Property ID: 0x6673

Data type: PtypInteger32, 0x0003

Area: Access Control Properties

Defining reference: [\[MS-OXCPERM\]](#) section 2.2.1.7

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_MEMBER_RIGHTS, ptagMemberRights

2.841 PidTagMessageAttachments

Canonical name: PidTagMessageAttachments

Description: Identifies all attachments to the current message.

Property ID: 0x0E13

Data type: PtypObject, 0x000D

Area: Message Attachment Properties

Defining reference:

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#)

Alternate names: PR_MESSAGE_ATTACHMENTS, ptagMessageAttachments

2.842 PidTagMessageCcMe

Canonical name: PidTagMessageCcMe

Description: Indicates that the receiving mailbox owner is a carbon copy (Cc) recipient of this e-mail message.

Property ID: 0x0058

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.18

Consuming reference: [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_CC_ME, ptagMessageCcMe

2.843 PidTagMessageClass

Canonical name: PidTagMessageClass

Description: Denotes the specific type of the Message object.

Property ID: 0x001A

Data type: PtypString, 0x001F

Area: Common Property set

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.3

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXBODY\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCSYNC\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOUML\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MESSAGE_CLASS, PR_MESSAGE_CLASS_A, ptagMessageClass, PR_MESSAGE_CLASS_W, <http://schemas.microsoft.com/exchange/outlookmessageclass>

2.844 PidTagMessageCodepage

Canonical name: PidTagMessageCodepage

Description: Specifies the code page used to encode the **non-Unicode** string properties on this Message object.

Property ID: 0x3FFD

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.4

Consuming references: [\[MS-OXTNEF\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXPFOAB\]](#)

Alternate names: PR_MESSAGE_CODEPAGE

2.845 PidTagMessageDeliveryTime

Canonical name: PidTagMessageDeliveryTime

Description: Contains the posting date of the item or entry.

Property ID: 0x0E06

Data type: PtypTime, 0x0040

Area: Message Time Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.9

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORSS\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_MESSAGE_DELIVERY_TIME, urn:schemas:httpmail:datereceived

2.846 PidTagMessageEditorFormat

Canonical name: PidTagMessageEditorFormat

Description: Specifies the format that an e-mail editor can use for editing the **message body**.

Property ID: 0x5909

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.69

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MSG_EDITOR_FORMAT, ptagMsgEditorFormat

2.847 PidTagMessageFlags

Canonical name: PidTagMessageFlags

Description: Specifies the status of the Message object.

Property ID: 0x0E07

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.6

Consuming references: [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#) [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMMS\]](#)

Alternate names: PR_MESSAGE_FLAGS, ptagMessageFlags

2.848 PidTagMessageHandlingSystemCommonName

Canonical name: PidTagMessageHandlingSystemCommonName

Description: Contains the **common name** of a messaging user for use in a message header.

Property ID: 0x3A0F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.60

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MHS_COMMON_NAME, PR_MHS_COMMON_NAME_A, PR_MHS_COMMON_NAME_W, urn:schemas:contacts:dn

2.849 PidTagMessageLocaleId

Canonical name: PidTagMessageLocaleId

Description: Contains the Windows Locale ID of the end-user who created this message.

Property ID: 0x3FF1

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.5

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_LOCALE_ID

2.850 PidTagMessageRecipientMe

Canonical name: PidTagMessageRecipientMe

Description: Indicates that the receiving mailbox owner is a primary or a carbon copy (Cc) recipient of this e-mail message.

Property ID: 0x0059

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.19

Consuming Reference: [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_RECIP_ME, ptagMessageRecipMe

2.851 PidTagMessageRecipients

Canonical name: PidTagMessageRecipients

Description: Identifies all of the recipients of the current message.

Property ID: 0x0E12

Data type: PtypObject, 0x000D

Area: Address Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.47

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_RECIPIENTS, ptagMessageRecipients

2.852 PidTagMessageSize

Canonical name: PidTagMessageSize

Description: Contains the size, in bytes, consumed by the Message object on the server.

Property ID: 0x0E08

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXCOLD\]](#) section 2.2.2.2.1.7

Consuming references: [\[MS-OXCSTOR\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXPFOAB\]](#)

Alternate names: PR_MESSAGE_SIZE, ptagMessageSize

2.853 PidTagMessageSizeExtended

Canonical name: PidTagMessageSizeExtended

Description: Specifies the 64-bit version of the **PidTagNormalMessageSize** property (section [2.865](#)).

Property ID: 0x0E08

Data type: PtypInteger64, 0x0014

Area: General Message Properties

Defining reference: [\[MS-OXCOLD\]](#) section 2.2.2.2.1.8

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: PR_MESSAGE_SIZE_EXTENDED, ptagMessageSizeExtended

2.854 PidTagMessageStatus

Canonical name: PidTagMessageStatus

Description: Specifies the status of a message in a **contents table**.

Property ID: 0x0E17

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.8

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCSYNC\]](#)

Alternate names: PR_MSG_STATUS, ptagMsgStatus

2.855 PidTagMessageSubmissionId

Canonical name: PidTagMessageSubmissionId

Description: Contains a message identifier assigned by a message transfer agent.

Property ID: 0x0047

Data type: PtypBinary, 0x0102

Area: Email

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.70

Consuming references: [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_SUBMISSION_ID, ptagMessageSubmissionId

2.856 PidTagMessageToMe

Canonical name: PidTagMessageToMe

Description: Indicates that the receiving mailbox owner is one of the primary recipients of this e-mail message.

Property ID: 0x0057

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.17

Consuming reference: [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_TO_ME, ptagMessageToMe

2.857 PidTagMid

Canonical name: PidTagMid

Description: Contains a value that contains the MID of the message currently being synchronized.

Property ID: 0x674A

Data type: PtypInteger64, 0x0014

Area: ID Properties

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.1

Consuming references: [\[MS-OXCMMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: ptagMID, <http://schemas.microsoft.com/exchange/mid>

2.858 PidTagMiddleName

Canonical name: PidTagMiddleName

Description: Specifies the middle name(s) of the contact.

Property ID: 0x3A44

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.1.5

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MIDDLE_NAME, PR_MIDDLE_NAME_A, PR_MIDDLE_NAME_W,
urn:schemas:contacts:middlename

2.859 PidTagMimeSkeleton

Canonical name: PidTagMimeSkeleton

Description: Contains the top-level MIME message headers, all MIME message body part headers, and body part content that is not already converted to message object properties, including attachments.

Property ID: 0x64F0

Data type: PtypBinary, 0x0102

Area: MIME properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.28

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagMimeSkeleton

2.860 PidTagMobileTelephoneNumber

Canonical name: PidTagMobileTelephoneNumber

Description: Contains the mail user's cellular telephone number.

Property ID: 0x3A1C

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.45

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MOBILE_TELEPHONE_NUMBER, PR_MOBILE_TELEPHONE_NUMBER_A, PR_MOBILE_TELEPHONE_NUMBER_W, urn:schemas:contacts:mobile

2.861 PidTagNativeBody

Canonical name: PidTagNativeBody

Description: Indicates the best available format for storing the message body.

Property ID: 0x1016

Data type: PtypInteger32, 0x0003

Area: BestBody

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.2

Consuming Reference: [\[MS-OXBODY\]](#)

Alternate names: PR_NATIVE_BODY_INFO, ptagNativeBodyInfo

2.862 PidTagNextSendAcct

Canonical name: PidTagNextSendAcct

Description: Specifies the server that a client is currently attempting to use to send e-mail.

Property ID: 0x0E29

Data type: PtypString, 0x001F

Area: Outlook Application

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.56

Consuming Reference: [\[MS-OXCICAL\]](#)

Alternate names: PR_NEXT_SEND_ACCT

2.863 PidTagNickname

Canonical name: PidTagNickname

Description: Contains the mail user's nickname.

Property ID: 0x3A4F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.3

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_NICKNAME, PR_NICKNAME_A, PR_NICKNAME_W,
urn:schemas:contacts:nickname

2.864 PidTagNormalizedSubject

Canonical name: PidTagNormalizedSubject

Description: Contains the normalized subject of the message.

Property ID: 0x0E1D

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.10

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_NORMALIZED SUBJECT, PR_NORMALIZED SUBJECT_A, pttagNormalizedSubject, PR_NORMALIZED SUBJECT_W, urn:schemas:httpmail:normalizedsubject

2.865 PidTagNormalMessageSize

Canonical name: PidTagNormalMessageSize

Description: Contains the aggregate size of Message objects in a folder.

Property ID: 0x66B3

Data type: PtypInteger32, 0x0003

Area: Server

Defining reference: [\[MS-XWDFOLD\]](#) section 2.2.6

Consuming references: [\[MS-XWDEXT\]](#)

Alternate names: PR_NORMAL_MESSAGE_SIZE, <http://schemas.microsoft.com/exchange/foldersize>

2.866 PidTagObjectType

Canonical name: PidTagObjectType

Description: Indicates the type of **Server object**.

Property ID: 0x0FFE

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.1.7

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_OBJECT_TYPE, ptagObjectType

2.867 PidTagOfficeLocation

Canonical name: PidTagOfficeLocation

Description: Contains the mail user's office location.

Property ID: 0x3A19

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.8

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OFFICE_LOCATION, PR_OFFICE_LOCATION_A, PR_OFFICE_LOCATION_W, urn:schemas:contacts:roomnumber

2.868 PidTagOfflineAddressBookContainerGuid

Canonical name: PidTagOfflineAddressBookContainerGuid

Description: A string formatted GUID that represents the **address list** container object.

Property ID: 0x6802

Data type: PtypString8, 0x001E

Area: Offline Address Book Properties

Defining reference: [\[MS-OXOAB\]](#) section 2.9.2.1

Consuming reference: [\[MS-OXPFOAB\]](#)

Alternate names: PR_OAB_CONTAINER_GUID, PR_OAB_CONTAINER_GUID_W

2.869 PidTagOfflineAddressBookDistinguishedName

Canonical name: PidTagOfflineAddressBookDistinguishedName

Description: Contains the distinguished name (DN) (1) of the address list that is contained in the OAB message.

Property ID: 0x6804

Data type: PtypString8, 0x001E

Area: Offline Address Book Properties

Defining reference: [\[MS-OXOAB\]](#) section 2.9.2.1

Consuming reference: [\[MS-OXPFOAB\]](#)

Alternate names: PR_OAB_DN, PR_OAB_DN_W

2.870 PidTagOfflineAddressBookMessageClass

Canonical name: PidTagOfflineAddressBookMessageClass

Description: Contains the message class for full OAB messages.

Property ID: 0x6803

Data type: PtypInteger32, 0x0003

Area: Offline Address Book Properties

Defining reference: [\[MS-OXPFOAB\]](#) section 2.2.2.1.1

Alternate names: PR_OAB_MESSAGE_CLASS

2.871 PidTagOfflineAddressBookName

Canonical name: PidTagOfflineAddressBookName

Description: Contains the display name of the address list.

Property ID: 0x6800

Data type: PtypString, 0x001F

Area: Offline Address Book Properties

Defining reference: [\[MS-OXOAB\]](#) section 2.9.2.1

Consuming Reference: [\[MS-OXPFOAB\]](#)

Alternate names: PR_OAB_NAME, PR_OAB_NAME_W

2.872 PidTagOfflineAddressBookSequence

Canonical name: PidTagOfflineAddressBookSequence

Description: Contains the sequence number of the OAB.

Property ID: 0x6801

Data type: PtypInteger32, 0x0003

Area: Offline Address Book Properties

Defining reference: [\[MS-OXOAB\]](#) section 2.9.2.1

Consuming reference: [\[MS-OXPFOAB\]](#)

Alternate names: PR_OAB_SEQUENCE

2.873 PidTagOfflineAddressBookTruncatedProperties

Canonical name: PidTagOfflineAddressBookTruncatedProperties

Description: Contains a list of the property tags that have been truncated or limited by the server.

Property ID: 0x6805

Data type: PtypMultipleInteger32, 0x1003

Area: Offline Address Book Properties

Defining reference: [\[MS-OXOAB\]](#) section 2.9.2.2

Alternate names: PR_OAB_TRUNCATED_PROPS

2.874 PidTagOrdinalMost

Canonical name: PidTagOrdinalMost

Description: Contains a positive number whose negative is less than or equal to the value of the PidLidTaskOrdinal property (section [2.321](#)) of all of the Task objects in the folder.

Property ID: 0x36E2

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.1.1

Alternate names: PR_ORDINAL_MOST

2.875 PidTagOrganizationalIdNumber

Canonical name: PidTagOrganizationalIdNumber

Description: Contains an identifier for the mail user used within the mail user's organization.

Property ID: 0x3A10

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.63

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ORGANIZATIONAL_ID_NUMBER, PR_ORGANIZATIONAL_ID_NUMBER_A, PR_ORGANIZATIONAL_ID_NUMBER_W, urn:schemas:contacts:employeenumber

2.876 PidTagOriginalDeliveryTime

Canonical name: PidTagOriginalDeliveryTime

Description: Contains the delivery time, in UTC, from the original message.

Property ID: 0x0055

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.2

Alternate names: PR_ORIGINAL_DELIVERY_TIME, ptagOriginalDeliveryTime

2.877 PidTagOriginalDisplayBcc

Canonical name: PidTagOriginalDisplayBcc

Description: Contains the value of the **PidTagDisplayBcc** property (section [2.732](#)) from the original message.

Property ID: 0x0072

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.5

Alternate names: PR_ORIGINAL_DISPLAY_BCC, PR_ORIGINAL_DISPLAY_BCC_A, ptagOriginalDisplayBcc, PR_ORIGINAL_DISPLAY_BCC_W, <http://schemas.microsoft.com/exchange/originaldisplaybcc>

2.878 PidTagOriginalDisplayCc

Canonical name: PidTagOriginalDisplayCc

Description: Contains the value of the **PidTagDisplayCc** property (section [2.733](#)) from the original message.

Property ID: 0x0073

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.4

Alternate names: PR_ORIGINAL_DISPLAY_CC, PR_ORIGINAL_DISPLAY_CC_A, ptagOriginalDisplayCc, PR_ORIGINAL_DISPLAY_CC_W, <http://schemas.microsoft.com/exchange/originaldisplaycc>, http://schemas.microsoft.com/mapi/original_display_cc

2.879 PidTagOriginalDisplayTo

Canonical name: PidTagOriginalDisplayTo

Description: Contains the value of the **PidTagDisplayTo** property (section [2.736](#)) from the original message.

Property ID: 0x0074

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.3

Alternate names: PR_ORIGINAL_DISPLAY_TO, PR_ORIGINAL_DISPLAY_TO_A, ptagOriginalDisplayTo, PR_ORIGINAL_DISPLAY_TO_W, http://schemas.microsoft.com/exchange/originaldisplayto, http://schemas.microsoft.com/mapi/original_display_to

2.880 PidTagOriginalEntryId

Canonical name: PidTagOriginalEntryId

Description: Contains the original EntryID of an object.

Property ID: 0x3A12

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.9

Alternate names: PR_ORIGINAL_ENTRYID, ptagOriginalEntryId

2.881 PidTagOriginalMessageClass

Canonical name: PidTagOriginalMessageClass

Property ID: 0x004B

Data type: PtypString, 0x001F

Area: Secure Messaging Properties

Defining reference:

Consuming reference: [\[MS-OXTNEF\]](#)

Alternate names: PR_ORIG_MESSAGE_CLASS, PR_ORIG_MESSAGE_CLASS_A, PR_ORIG_MESSAGE_CLASS_W

2.882 PidTagOriginalMessageId

Canonical name: PidTagOriginalMessageId

Description:

Property ID: 0x1046

Data type: PtypString, 0x001F

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagOriginalInternetMessageID, OriginalMessageId

2.883 PidTagOriginalSenderAddressType

Canonical name: PidTagOriginalSenderAddressType

Description: Contains the value of the original message sender's **PidTagSenderAddressType** property (section [2.1052](#)).

Property ID: 0x0066

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.6

Alternate names: PR_ORIGINAL_SENDER_ADDRTYPE, PR_ORIGINAL_SENDER_ADDRTYPE_A, ptagOriginalSenderAddrType, PR_ORIGINAL_SENDER_ADDRTYPE_W

2.884 PidTagOriginalSenderEmailAddress

Canonical name: PidTagOriginalSenderEmailAddress

Description: Contains the value of the original message sender's **PidTagSenderEmailAddress** property (section [2.1053](#)).

Property ID: 0x0067

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.7

Alternate names: PR_ORIGINAL_SENDER_EMAIL_ADDRESS, PR_ORIGINAL_SENDER_EMAIL_ADDRESS_A, PR_ORIGINAL_SENDER_EMAIL_ADDRESS_W

2.885 PidTagOriginalSenderEntryId

Canonical name: PidTagOriginalSenderEntryId

Description: Contains an address book EntryID that is set on delivery report messages.

Property ID: 0x005B

Data type: **PtypBinary**, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.8

Alternate names: PR_ORIGINAL_SENDER_ENTRYID, ptagOriginalSenderEntryId

2.886 PidTagOriginalSenderName

Canonical name: PidTagOriginalSenderName

Description: Contains the value of the original message sender's **PidTagSenderName** property (section [2.1057](#)), and is set on delivery report messages.

Property ID: 0x005A

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.9

Alternate names: PR_ORIGINAL_SENDER_NAME, PR_ORIGINAL_SENDER_NAME_A, ptagOriginalSenderName, PR_ORIGINAL_SENDER_NAME_W, http://schemas.microsoft.com/exchange/originalsendername

2.887 PidTagOriginalSenderSearchKey

Canonical name: PidTagOriginalSenderSearchKey

Description: Contains an address book search key set on the original e-mail message.

Property ID: 0x005C

Data type: **PtypBinary**, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.10

Alternate names: PR_ORIGINAL_SENDER_SEARCH_KEY, ptagOriginalSenderSearchKey

2.888 PidTagOriginalSensitivity

Canonical name: PidTagOriginalSensitivity

Description: Contains the sensitivity value of the original e-mail message.

Property ID: 0x002E

Data type: **PtypInteger32**, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.22

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: PR_ORIGINAL_SENSITIVITY, ptagOriginalSensitivity

2.889 PidTagOriginalSentRepresentingAddressType

Canonical name: PidTagOriginalSentRepresentingAddressType

Description: Contains the address type of the end user who is represented by the original e-mail message sender.

Property ID: 0x0068

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.11

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE,
PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE_A, ptagOriginalSentRepresentingAddrType,
PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE_W

2.890 PidTagOriginalSentRepresentingEmailAddress

Canonical name: PidTagOriginalSentRepresentingEmailAddress

Description: Contains the e-mail address of the end user who is represented by the original e-mail message sender.

Property ID: 0x0069

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.12

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS,
PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS_A,
PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS_W

2.891 PidTagOriginalSentRepresentingEntryId

Canonical name: PidTagOriginalSentRepresentingEntryId

Description: Identifies an address book EntryID that contains the entry identifier of the end user who is represented by the original message sender.

Property ID: 0x005E

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.13

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_ENTRYID,
ptagOriginalSentRepresentingEntryId

2.892 PidTagOriginalSentRepresentingName

Canonical name: PidTagOriginalSentRepresentingName

Description: Contains the display name of the end user who is represented by the original e-mail message sender.

Property ID: 0x005D

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.14

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_NAME,
PR_ORIGINAL_SENT_REPRESENTING_NAME_A, ptagOriginalSentRepresentingName,
PR_ORIGINAL_SENT_REPRESENTING_NAME_W

2.893 PidTagOriginalSentRepresentingSearchKey

Canonical name: PidTagOriginalSentRepresentingSearchKey

Description: Identifies an address book search key that contains the SearchKey of the end user who is represented by the original message sender.

Property ID: 0x005F

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.15

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_SEARCH_KEY,
ptagOriginalSentRepresentingSearchKey

2.894 PidTagOriginalSubject

Canonical name: PidTagOriginalSubject

Description: Specifies the subject of the original message.

Property ID: 0x0049

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.16

Consuming reference: [\[MS-OXCSYNC\]](#)

Alternate names: PR_ORIGINAL SUBJECT, PR_ORIGINAL SUBJECT_A, ptagOriginalSubject,
PR_ORIGINAL SUBJECT_W, http://schemas.microsoft.com/exchange/originalsubject,
http://schemas.microsoft.com/mapi/original_subject

2.895 PidTagOriginalSubmitTime

Canonical name: PidTagOriginalSubmitTime

Description: Specifies the original e-mail message's submission date and time, in UTC.

Property ID: 0x004E

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.17

Alternate names: PR_ORIGINAL_SUBMIT_TIME, ptagOriginalSubmitTime,
http://schemas.microsoft.com/exchange/originaldate,
http://schemas.microsoft.com/mapi/original_submit_time

2.896 PidTagOriginatorDeliveryReportRequested

Canonical name: PidTagOriginatorDeliveryReportRequested

Description: Indicates whether an e-mail sender requests an e-mail **delivery receipt** from the messaging system.

Property ID: 0x0023

Data type: PtypBoolean, 0x000B

Area: MIME Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.20

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASKI\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ORIGINATOR_DELIVERY_REPORT_REQUESTED,
http://schemas.microsoft.com/exchange/deliveryreportrequested

2.897 PidTagOriginatorNonDeliveryReportRequested

Canonical name: PidTagOriginatorNonDeliveryReportRequested

Description: Specifies whether an e-mail sender requests suppression of nondelivery receipts.

Property ID: 0x0C08

Data type: PtypBoolean, 0x000B

Area: MIME Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.21

Alternate names: PR_ORIGINATOR_NON_DELIVERY_REPORT_REQUESTED

2.898 PidTagOtherAddressCity

Canonical name: PidTagOtherAddressCity

Description: Contains the name of the mail user's other locality, such as the town or city.

Property ID: 0x3A5F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.33

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_CITY, PR_OTHER_ADDRESS_CITY_A, PR_OTHER_ADDRESS_CITY_W, urn:schemas:contacts:othercity

2.899 PidTagOtherAddressCountry

Canonical name: PidTagOtherAddressCountry

Description: Contains the name of the mail user's other country/region.

Property ID: 0x3A60

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.36

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_OTHER_ADDRESS_COUNTRY, PR_OTHER_ADDRESS_COUNTRY_A, PR_OTHER_ADDRESS_COUNTRY_W, urn:schemas:contacts:othercountry

2.900 PidTagOtherAddressPostalCode

Canonical name: PidTagOtherAddressPostalCode

Description: Contains the postal code for the mail user's other postal address.

Property ID: 0x3A61

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.35

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_POSTAL_CODE, PR_OTHER_ADDRESS_POSTAL_CODE_A, PR_OTHER_ADDRESS_POSTAL_CODE_W, urn:schemas:contacts:otherpostalcode

2.901 PidTagOtherAddressPostOfficeBox

Canonical name: PidTagOtherAddressPostOfficeBox

Description: Contains the number or identifier of the mail user's other post office box.

Property ID: 0x3A64

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.32

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_POST_OFFICE_BOX,
PR_OTHER_ADDRESS_POST_OFFICE_BOX_A, PR_OTHER_ADDRESS_POST_OFFICE_BOX_W,
urn:schemas:contacts:otherpostofficebox

2.902 PidTagOtherAddressStateOrProvince

Canonical name: PidTagOtherAddressStateOrProvince

Description: Contains the name of the mail user's other state or province.

Property ID: 0x3A62

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.34

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_STATE_OR_PROVINCE,
PR_OTHER_ADDRESS_STATE_OR_PROVINCE_A, PR_OTHER_ADDRESS_STATE_OR_PROVINCE_W,
urn:schemas:contacts:otherstate

2.903 PidTagOtherAddressStreet

Canonical name: PidTagOtherAddressStreet

Description: Contains the mail user's other street address.

Property ID: 0x3A63

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.31

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_STREET, PR_OTHER_ADDRESS_STREET_A,
PR_OTHER_ADDRESS_STREET_W, urn:schemas:contacts:otherstreet

2.904 PidTagOtherTelephoneNumber

Canonical name: PidTagOtherTelephoneNumber

Description: Contains an alternate telephone number for the mail user.

Property ID: 0x3A1F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.48

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_TELEPHONE_NUMBER, PR_OTHER_TELEPHONE_NUMBER_A, PR_OTHER_TELEPHONE_NUMBER_W, urn:schemas:contacts:otherTelephone

2.905 PidTagOutOfOfficeState

Canonical name: PidTagOutOfOfficeState

Description: Indicates whether the user is **OOF**.

Property ID: 0x661D

Data type: PtypBoolean, 0x000B

Area: Message Store Properties

Defining reference:

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: PR_OOF_STATE, ptagOOFState

2.906 PidTagOwnerAppointmentId

Canonical name: PidTagOwnerAppointmentId

Description: Specifies a quasi-unique value among all of the Calendar objects in a user's mailbox.

Property ID: 0x0062

Data type: PtypInteger32, 0x0003

Area: Appointment

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.29

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

Alternate names: PR_OWNER_APPT_ID, http://schemas.microsoft.com/mapi/owner_appt_id

2.907 PidTagPagerTelephoneNumber

Canonical name: PidTagPagerTelephoneNumber

Description: Contains the mail user's pager telephone number.

Property ID: 0x3A21

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.49

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PAGER_TELEPHONE_NUMBER, PR_PAGER_TELEPHONE_NUMBER_A, PR_PAGER_TELEPHONE_NUMBER_W, urn:schemas:contacts:pager

2.908 PidTagParentEntryId

Canonical name: PidTagParentEntryId

Description: Contains the EntryID of the folder where messages reside.

Property ID: 0x0E09

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXPFOAB\]](#) section 2.2.1.8

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_PARENT_ENTRYID, ptagParentEntryId

2.909 PidTagParentFolderId

Canonical name: PidTagParentFolderId

Description: Contains a value that contains the Folder ID (FID), as specified in [\[MS-OXCDATA\]](#) section 2.2.1.1, that identifies the parent folder of the messaging object being synchronized.

Property ID: 0x6749

Data type: PtypInteger64, 0x0014

Area: ID Properties

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.4

Alternate names: ptagParentFID

2.910 PidTagParentKey

Canonical name: PidTagParentKey

Description: Contains the search key that is used to correlate the original message and the reports about the original message.

Property ID: 0x0025

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.18

Alternate names: PR_PARENT_KEY, ptagParentKey

2.911 PidTagParentSourceKey

Canonical name: PidTagParentSourceKey

Description: Contains a value on a folder that contains the **PidTagSourceKey** property (section [2.1074](#)) of the parent folder.

Property ID: 0x65E1

Data type: PtypBinary, 0x0102

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.6

Consuming reference: [\[MS-OXCSYNC\]](#)

Alternate names: PR_PARENT_SOURCE_KEY

2.912 PidTagPersonalHomePage

Canonical name: PidTagPersonalHomePage

Description: Contains the URL of the mail user's personal home page.

Property ID: 0x3A50

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.77

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PERSONAL_HOME_PAGE, PR_PERSONAL_HOME_PAGE_A, PR_PERSONAL_HOME_PAGE_W, urn:schemas:contacts:personalHomePage

2.913 PidTagPolicyTag

Canonical name: PidTagPolicyTag

Description: Specifies the GUID of a **retention tag**.

Property ID: 0x3019

Data type: PtypBinary, 0x0102

Area: Archive

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.50.2

Alternate names: PR_POLICY_TAG, ptagPolicyTag

2.914 PidTagPostalAddress

Canonical name: PidTagPostalAddress

Description: Contains the mail user's postal address.

Property ID: 0x3A15

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.18

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_POSTAL_ADDRESS, PR_POSTAL_ADDRESS_A, PR_POSTAL_ADDRESS_W, urn:schemas:contacts:mailingpostaladdress

2.915 PidTagPostalCode

Canonical name: PidTagPostalCode

Description: Contains the postal code for the mail user's postal address.

Property ID: 0x3A2A

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.23

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_POSTAL_CODE, PR_POSTAL_CODE_A, PR_POSTAL_CODE_W, PR_BUSINESS_ADDRESS_POSTAL_CODE, PR_BUSINESS_ADDRESS_POSTAL_CODE_A, PR_BUSINESS_ADDRESS_POSTAL_CODE_W, urn:schemas:contacts:mailingpostalcode

2.916 PidTagPostOfficeBox

Canonical name: PidTagPostOfficeBox

Description: Contains the number or identifier of the mail user's post office box.

Property ID: 0x3A2B

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.20

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_POST_OFFICE_BOX, PR_POST_OFFICE_BOX_A, PR_POST_OFFICE_BOX_W, PR_BUSINESS_ADDRESS_POST_OFFICE_BOX, PR_BUSINESS_ADDRESS_POST_OFFICE_BOX_A, PR_BUSINESS_ADDRESS_POST_OFFICE_BOX_W, urn:schemas:contacts:mailingpostofficebox

2.917 PidTagPredecessorChangeList

Canonical name: PidTagPredecessorChangeList

Description: Contains a value that contains a serialized representation of a **PredecessorChangeList** structure.

Property ID: 0x65E3

Data type: **PtypBinary**, 0x0102

Area: Sync

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.8

Consuming reference: [\[MS-OXCSYNC\]](#)

Alternate names: PR_PREDECESSOR_CHANGE_LIST

2.918 PidTagPrimaryFaxNumber

Canonical name: PidTagPrimaryFaxNumber

Description: Contains the telephone number of the mail user's primary fax machine.

Property ID: 0x3A23

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.50

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PRIMARY_FAX_NUMBER, PR_PRIMARY_FAX_NUMBER_A, PR_PRIMARY_FAX_NUMBER_W, urn:schemas:contacts:otherfax

2.919 PidTagPrimarySendAccount

Canonical name: PidTagPrimarySendAccount

Description: Specifies the first server that a client is to use to send the e-mail with.

Property ID: 0x0E28

Data type: PtypString, 0x001F

Area: MapiNonTransmittable

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.55

Alternate names: PR_PRIMARY_SEND_ACCT

2.920 PidTagPrimaryTelephoneNumber

Canonical name: PidTagPrimaryTelephoneNumber

Description: Contains the mail user's primary telephone number.

Property ID: 0x3A1A

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.37

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-NSPI\]](#)

Alternate names: PR_PRIMARY_TELEPHONE_NUMBER, PR_PRIMARY_TELEPHONE_NUMBER_A, PR_PRIMARY_TELEPHONE_NUMBER_W

2.921 PidTagPriority

Canonical name: PidTagPriority

Description: Indicates the client's request for the priority with which the message is to be sent by the messaging system.

Property ID: 0x0026

Data type: PtypInteger32, 0x0003

Area: E-mail

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.12

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOJRNL\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PRIORITY, ptagPriority, urn:schemas:httpmail:priority, urn:schemas:httpmail:priority

2.922 PidTagProcessed

Canonical name: PidTagProcessed

Description: Indicates whether a client has already processed a received task communication.

Property ID: 0x7D01

Data type: PtypBoolean, 0x000B

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.5.7

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOTASK\]](#)

Alternate names: PR_PROCESSED

2.923 PidTagProfession

Canonical name: PidTagProfession

Description: Contains the name of the mail user's line of business.

Property ID: 0x3A46

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.70

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PROFESSION, PR_PROFESSION_A, PR_PROFESSION_W, urn:schemas:contacts:profession

2.924 PidTagProhibitReceiveQuota

Canonical name: PidTagProhibitReceiveQuota

Description: Maximum size, in kilobytes, that a user is allowed to accumulate in their mailbox before no further e-mail will be delivered to their mailbox.

Property ID: 0x666A

Data type: PtypInteger32, 0x0003

Area: Exchange Administrative

Defining reference:

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: PR_PROHIBIT_RECEIVE_QUOTA, ptagProhibitReceiveQuota

2.925 PidTagProhibitSendQuota

Canonical name: PidTagProhibitSendQuota

Description: Maximum size, in kilobytes, that a user is allowed to accumulate in their mailbox before the user can no longer send any more e-mail.

Property ID: 0x666E

Data type: PtypInteger32, 0x0003

Area: ExchangeAdministrative

Defining reference:

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: PR_PROHIBIT_SEND_QUOTA, ptagProhibitSendQuota

2.926 PidTagProviderSubmitTime

Canonical name: PidTagProviderSubmitTime

Description:

Property ID: 0x0048

Data type: PtypTime, 0x0040

Area: E-mail

Defining reference:

Consuming reference: [\[MS-OXOMSG\]](#)

Alternate names: PR_PROVIDER_SUBMIT_TIME

2.927 PidTagPublicFolderAdministrativeDescription

Canonical name: PidTagPublicFolderAdministrativeDescription

Description: Contains a text description of a public folder.

Property ID: 0x671C

Data type: **PtypString**, 0x001F

Area: Folder Properties

Defining reference: [\[MS-XWDFOLD\]](#) section 2.2.4

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: http://schemas.microsoft.com/exchange/adminfolderdescription

2.928 PidTagPublicFolderProxy

Canonical name: PidTagPublicFolderProxy

Description: Contains the **base64 encoding** of the ObjectGUID for a mail-enabled public folder.

Property ID: 0x671D

Data type: **PtypBinary**, 0x0102

Area: Folder Properties

Defining reference: [\[MS-XWDFOLD\]](#) section 2.2.5

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: http://schemas.microsoft.com/exchange/folderproxy

2.929 PidTagPurportedSenderDomain

Canonical name: PidTagPurportedSenderDomain

Description: Contains the domain responsible for transmitting the current message.

Property ID: 0x4083

Data type: **PtypString**, 0x001F

Area: TransportEnvelope

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.43

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_PURPORTED_SENDER_DOMAIN

2.930 PidTagRadioTelephoneNumber

Canonical name: PidTagRadioTelephoneNumber

Description: Contains the mail user's radio telephone number.

Property ID: 0x3A1D

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.46

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_RADIO_TELEPHONE_NUMBER, PR_RADIO_TELEPHONE_NUMBER_A, PR_RADIO_TELEPHONE_NUMBER_W

2.931 PidTagRead

Canonical name: PidTagRead

Description: Indicates whether a message has been read.

Property ID: 0x0E69

Data type: PtypBoolean, 0x000B

Area: MapiNonTransmittable Property set

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.16

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_READ, ptagRead, urn:schemas:httpmail:read

2.932 PidTagReadReceiptAddressType

Canonical name: PidTagReadReceiptAddressType

Description: Contains the address type of the end user to whom a **read receipt** is directed.

Property ID: 0x4029

Data type: PtypString, 0x001F

Area: Transport Envelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.24

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagReadReceiptAddrType, ReadReceiptAddrType

2.933 PidTagReadReceiptEmailAddress

Canonical name: PidTagReadReceiptEmailAddress

Description: Contains the e-mail address of the end user to whom a read receipt is directed.

Property ID: 0x402A

Data type: PtypString, 0x001F

Area: Transport Envelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.25

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagReadReceiptEmailAddr, ReadReceiptEmailAddress

2.934 PidTagReadReceiptEntryId

Canonical name: PidTagReadReceiptEntryId

Description: Contains an address book EntryID.

Property ID: 0x0046

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.26

Alternate names: PR_READ_RECEIPT_ENTRYID, ptagReadReceiptEntryId

2.935 PidTagReadReceiptName

Canonical name: PidTagReadReceiptName

Description: Contains the **display name** for the end user to whom a read receipt is directed.

Property ID: 0x402B

Data type: PtypString, 0x001F

Area: Transport Envelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.27

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagReadReceiptDisplayName, ReadReceiptDisplayName

2.936 PidTagReadReceiptRequested

Canonical name: PidTagReadReceiptRequested

Description: Specifies whether the e-mail sender requests a read receipt from all recipients when this e-mail message is read or opened.

Property ID: 0x0029

Data type: PtypBoolean, 0x000B

Area: E-mail

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.28

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMSS\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#)

Alternate names: PR_READ_RECEIPT_REQUESTED, ptagReadReceiptRequested, <http://schemas.microsoft.com/exchange/readreceiptrequested>

2.937 PidTagReadReceiptSearchKey

Canonical name: PidTagReadReceiptSearchKey

Description: Contains an address book search key.

Property ID: 0x0053

Data type: **PtypBinary**, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.28

Alternate names: PR_READ_RECEIPT_SEARCH_KEY, ptagReadReceiptSearchKey

2.938 PidTagReceivedByAddressType

Canonical name: PidTagReceivedByAddressType

Description: Contains the e-mail message receiver's e-mail address type.

Property ID: 0x0075

Data type: **PtypString**, 0x001F

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.29

Alternate names: PR_RECEIVED_BY_ADDRTYPE, PR_RECEIVED_BY_ADDRTYPE_A, ptagReceivedByAddrType, PR_RECEIVED_BY_ADDRTYPE_W

2.939 PidTagReceivedByEmailAddress

Canonical name: PidTagReceivedByEmailAddress

Description: Contains the e-mail message receiver's e-mail address.

Property ID: 0x0076

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.30

Alternate names: PR_RECEIVED_BY_EMAIL_ADDRESS, PR_RECEIVED_BY_EMAIL_ADDRESS_A, PR_RECEIVED_BY_EMAIL_ADDRESS_W

2.940 PidTagReceivedByEntryId

Canonical name: PidTagReceivedByEntryId

Description: Contains the address book EntryID of the mailbox receiving the E-mail object.

Property ID: 0x003F

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.31

Alternate names: PR_RECEIVED_BY_ENTRYID

2.941 PidTagReceivedByFlags

Canonical name: PidTagReceivedByFlags

Description:

Property ID: 0x401B

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: ptagRcvdByFlags

2.942 PidTagReceivedByName

Canonical name: PidTagReceivedByName

Description: Contains the e-mail message receiver's display name.

Property ID: 0x0040

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.32

Alternate names: PR_RECEIVED_BY_NAME, PR_RECEIVED_BY_NAME_A,
PR_RECEIVED_BY_NAME_W

2.943 PidTagReceivedBySearchKey

Canonical name: PidTagReceivedBySearchKey

Description: Identifies an address book search key that contains a binary-comparable key that is used to identify correlated objects for a search.

Property ID: 0x0051

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.33

Alternate names: PR_RECEIVED_BY_SEARCH_KEY

2.944 PidTagReceivedRepresentingAddressType

Canonical name: PidTagReceivedRepresentingAddressType

Description: Contains the e-mail address type for the end user represented by the receiving mailbox owner.

Property ID: 0x0077

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.23

Alternate names: PR_RCVD REPRESENTING_ADDRTYPE,
PR_RCVD REPRESENTING_ADDRTYPE_A, ptagRcvdRepresentingAddrType,
PR_RCVD REPRESENTING_ADDRTYPE_W

2.945 PidTagReceivedRepresentingEmailAddress

Canonical name: PidTagReceivedRepresentingEmailAddress

Description: Contains the e-mail address for the end user represented by the receiving mailbox owner.

Property ID: 0x0078

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.24

Alternate names: PR_RCVD REPRESENTING_EMAIL_ADDRESS,
PR_RCVD REPRESENTING_EMAIL_ADDRESS_A, PR_RCVD REPRESENTING_EMAIL_ADDRESS_W

2.946 PidTagReceivedRepresentingEntryId

Canonical name: PidTagReceivedRepresentingEntryId

Description: Contains an address book EntryID that identifies the end user represented by the receiving mailbox owner.

Property ID: 0x0043

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.25

Alternate names: PR_RCVD REPRESENTING_ENTRYID, ptagRcvdRepresentingEntryId

2.947 PidTagReceivedRepresentingFlags

Canonical name: PidTagReceivedRepresentingFlags

Description:

Property ID: 0x401C

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: ptagRcvdRepresentingFlags

2.948 PidTagReceivedRepresentingName

Canonical name: PidTagReceivedRepresentingName

Description: Contains the display name for the end user represented by the receiving mailbox owner.

Property ID: 0x0044

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.26

Alternate names: PR_RCVD REPRESENTING_NAME, PR_RCVD REPRESENTING_NAME_A, ptagRcvdRepresentingName, PR_RCVD REPRESENTING_NAME_W

2.949 PidTagReceivedRepresentingSearchKey

Canonical name: PidTagReceivedRepresentingSearchKey

Description: Identifies an address book search key that contains a binary-comparable key of the end user represented by the receiving mailbox owner.

Property ID: 0x0052

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.27

Alternate names: PR_RCVD REPRESENTING_SEARCH_KEY, ptagRcvdRepresentingSearchKey

2.950 PidTagRecipientDisplayName

Canonical name: PidTagRecipientDisplayName

Description:

Property ID: 0x5FF6

Data type: **PtypString**, 0x001F

Area: TransportRecipient

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_DISPLAY_NAME, PR_RECIPIENT_DISPLAY_NAME_W

2.951 PidTagRecipientEntryId

Canonical name: PidTagRecipientEntryId

Description:

Property ID: 0x5FF7

Data type: **PtypBinary**, 0x0102

Area: ID Properties

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_ENTRYID, ptagRecipientEntryId

2.952 PidTagRecipientFlags

Canonical name: PidTagRecipientFlags

Description: Specifies a bit field that describes the recipient status.

Property ID: 0x5FFD

Data type: **PtypInteger32**, 0x0003

Area: TransportRecipient

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.10.1

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_FLAGS

2.953 PidTagRecipientOrder

Canonical name: PidTagRecipientOrder

Description: Specifies the location of the current recipient in the recipients table.

Property ID: 0x5FDF

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.40

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_ORDER, ptagRecipientOrder

2.954 PidTagRecipientProposed

Canonical name: PidTagRecipientProposed

Description: Indicates that the attendee proposed a new date and/or time.

Property ID: 0x5FE1

Data type: PtypBoolean, 0x000B

Area: TransportRecipient

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.10.4

Alternate names: PR_RECIPIENT_PROPOSED, ptagRecipientProposed

2.955 PidTagRecipientProposedEndTime

Canonical name: PidTagRecipientProposedEndTime

Description: Indicates the meeting end time requested by the attendee in a counter-proposal.

Property ID: 0x5FE4

Data type: PtypTime, 0x0040

Area: TransportRecipient

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.10.6

Alternate names: PR_RECIPIENT_PROPOSEDENDTIME, ptagRecipientProposedEndTime

2.956 PidTagRecipientProposedStartTime

Canonical name: PidTagRecipientProposedStartTime

Description: Indicates the meeting start time requested by the attendee in a counter-proposal.

Property ID: 0x5FE3

Data type: PtypTime, 0x0040

Area: TransportRecipient

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.10.5

Alternate names: PR_RECIPIENT_PROPOSEDSTARTTIME, ptagRecipientProposedStartTime

2.957 PidTagRecipientReassignmentProhibited

Canonical name: PidTagRecipientReassignmentProhibited

Description: Specifies whether adding additional or different recipients is prohibited for the e-mail message when forwarding the e-mail message.

Property ID: 0x002B

Data type: PtypBoolean, 0x000B

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.34

Alternate names: PR_RECIPIENT_REASSIGNMENT_PROHIBITED, ptagRecipientReassignmentProhibited

2.958 PidTagRecipientResourceState

Canonical name: PidTagRecipientResourceState

Description:

Property ID: 0x5FDE

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_RECIPIENT_RESOURCESTATE

2.959 PidTagRecipientTrackStatus

Canonical name: PidTagRecipientTrackStatus

Description: Indicates the response status that is returned by the attendee.

Property ID: 0x5FFF

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.10.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_TRACKSTATUS, ptagRecipientTrackStatus

2.960 PidTagRecipientTrackStatusTime

Canonical name: PidTagRecipientTrackStatusTime

Description: Indicates the date and time at which the attendee responded.

Property ID: 0x5FFB

Data type: PtypTime, 0x0040

Area: TransportRecipient

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.10.3

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: PR_RECIPIENT_TRACKSTATUS_TIME, ptagRecipientTrackStatusTime

2.961 PidTagRecipientType

Canonical name: PidTagRecipientType

Description: Represents the recipient type of a recipient on the message.

Property ID: 0x0C15

Data type: PtypInteger32, 0x0003

Area: MapiRecipient

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.1

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCMMSG\]](#)

Alternate names: PR_RECIPIENT_TYPE, ptagRecipientType

2.962 PidTagRecordKey

Canonical name: PidTagRecordKey

Description: Contains a unique binary-comparable identifier for a specific object.

Property ID: 0x0FF9

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.1.8

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_RECORD_KEY, ptagRecordKey

2.963 PidTagReferredByName

Canonical name: PidTagReferredByName

Description: Contains the name of the mail user's referral.

Property ID: 0x3A47

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.71

Consuming reference: [\[MS-OXOCNTC\]](#)

Alternate names: PR_REFERRED_BY_NAME, PR_REFERRED_BY_NAME_A, PR_REFERRED_BY_NAME_W

2.964 PidTagRemindersOnlineEntryId

Canonical name: PidTagRemindersOnlineEntryId

Description: Contains an EntryID for the Reminders folder.

Property ID: 0x36D5

Data type: PtypBinary, 0x0102

Area: MapiContainer

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Alternate names: PR_Rem_Online_EntryId, ptagRemOnlineEntryId

2.965 PidTagRemoteMessageTransferAgent

Canonical name: PidTagRemoteMessageTransferAgent

Description:

Property ID: 0x0C21

Data type: PtypString, 0x001F

Area: Transport Envelope

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagDsnRemoteMta, PR_DSN_REMOTE_MTA, RemoteMta

2.966 PidTagRenderingPosition

Canonical name: PidTagRenderingPosition

Description: Represents an offset, in rendered characters, to use when rendering an attachment within the main message text.

Property ID: 0x370B

Data type: PtypInteger32, 0x0003

Area: MapiAttachment

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.16

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#), , [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_RENDERING_POSITION, ptagRenderingPosition

2.967 PidTagReplyRecipientEntries

Canonical name: PidTagReplyRecipientEntries

Description: Identifies a **FlatEntryList** ([\[MS-OXCDATA\]](#) section 2.3.3) of address book EntryIDs for recipients that are to receive a reply.

Property ID: 0x004F

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.35

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_REPLY_RECIPIENT_ENTRIES, ptagReplyRecipientEntries, <http://schemas.microsoft.com/exchange/reply-to-base64>

2.968 PidTagReplyRecipientNames

Canonical name: PidTagReplyRecipientNames

Description: Contains a list of display names for recipients that are to receive a reply.

Property ID: 0x0050

Data type: PtypString, 0x001F

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.36

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_REPLY_RECIPIENT_NAMES, PR_REPLY_RECIPIENT_NAMES_A, ptagReplyRecipientNames, PR_REPLY_RECIPIENT_NAMES_W

2.969 PidTagReplyRequested

Canonical name: PidTagReplyRequested

Description: Indicates whether a reply is requested to a Message object.

Property ID: 0x0C17

Data type: PtypBoolean, 0x000B

Area: MapiRecipient

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.37

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [MS-OXOMSG], [\[MS-OXORMDR\]](#)

Alternate names: PR_REPLY_REQUESTED, ptagReplyRequested

2.970 PidTagReplyTemplateId

Canonical name: PidTagReplyTemplateId

Description: Contains the value of the GUID that points to a Reply template.

Property ID: 0x65C2

Data type: PtypBinary, 0x0102

Area: Rules

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.5.2

Alternate names: PR_REPLY_TEMPLATE_ID, ptagReplyTemplateId

2.971 PidTagReplyTime

Canonical name: PidTagReplyTime

Description: Specifies the time, in UTC, that the sender has designated for an associated work item to be due.

Property ID: 0x0030

Data type: PtypTime, 0x0040

Area: MapiEnvelope

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.3.1

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_REPLY_TIME, urn:schemas:httpmail:reply-by, http://schemas.microsoft.com/exchange/reply-by-iso

2.972 PidTagReportEntryId

Canonical name: PidTagReportEntryId

Description: Specifies whether a reply to the e-mail message is requested by the e-mail message's sender.

Property ID: 0x0045

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.37

Alternate names: PR_REPORT_ENTRYID, ptagReportEntryId

2.973 PidTagReportingMessageTransferAgent

Canonical name: PidTagReportingMessageTransferAgent

Description:

Property ID: 0x6820

Data type: PtypString, 0x001F

Area: Transport Envelope

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagDsnReportingMta, ReportingMta

2.974 PidTagReportName

Canonical name: PidTagReportName

Description: Contains the display name for the entity (usually a server agent) that generated the report message.

Property ID: 0x003A

Data type: PtypString, 0x001F

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.20

Alternate names: PR_REPORT_NAME, PR_REPORT_NAME_A, PR_REPORT_NAME_W

2.975 PidTagReportSearchKey

Canonical name: PidTagReportSearchKey

Description: Contains an address book search key representing the entity (usually a server agent) that generated the report message.

Property ID: 0x0054

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.21

Alternate names: PR_REPORT_SEARCH_KEY, ptagReportSearchKey

2.976 PidTagReportTag

Canonical name: PidTagReportTag

Description: Contains the data that is used to correlate the report and the original message.

Property ID: 0x0031

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.22

Alternate names: PR_REPORT_TAG, ptagReportTag

2.977 PidTagReportText

Canonical name: PidTagReportText

Description: Contains the optional text for a report message.

Property ID: 0x1001

Data type: PtypString, 0x001F

Area: MapiMessage

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.23

Alternate names: PR_REPORT_TEXT, PR_REPORT_TEXT_A, ptagReportText, PR_REPORT_TEXT_W

2.978 PidTagReportTime

Canonical name: PidTagReportTime

Description: Indicates the last time that the contact list that is controlled by the **PidTagJunkIncludeContacts** property (section [2.815](#)) was updated.

Property ID: 0x0032

Data type: PtypTime, 0x0040

Area: MapiEnvelope Property set

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.2.6

Alternate names: PR_REPORT_TIME, ptagReportTime,
<http://schemas.microsoft.com/exchange/reporttime>

2.979 PidTagResolveMethod

Canonical name: PidTagResolveMethod

Description: Specifies how to resolve any conflicts with the message.

Property ID: 0x3FE7

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.4.1

Alternate names: PR_RESOLVE_METHOD, ptagResolveMethod

2.980 PidTagResponseRequested

Canonical name: PidTagResponseRequested

Description: Indicates whether a response is requested to a Message object.

Property ID: 0x0063

Data type: PtypBoolean, 0x000B

Area: MapiEnvelope Property set

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.38

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_RESPONSE_REQUESTED, urn:schemas:calendar:responserequested, http://schemas.microsoft.com/mapi/response_requested

2.981 PidTagResponsibility

Canonical name: PidTagResponsibility

Description: Specifies whether another mail agent has ensured that the message will be delivered.

Property ID: 0x0E0F

Data type: PtypBoolean, 0x000B

Area: MapiNonTransmittable

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.37

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: PR_RESPONSIBILITY, ptagResponsibility

2.982 PidTagRetentionDate

Canonical name: PidTagRetentionDate

Description: Specifies the date, in UTC, after which a Message object is expired by the server.

Property ID: 0x301C

Data type: PtypTime, 0x0040

Area: Archive

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.50.5

Alternate names: PR_RETENTION_DATE, ptagRetentionDate

2.983 PidTagRetentionFlags

Canonical name: PidTagRetentionFlags

Description: Contains flags that specify the status or nature of an item's retention tag or archive tag.

Property ID: 0x301D

Data type: PtypInteger32, 0x0003

Area: Archive

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.50.6

Alternate names: PR_RETENTION_FLAGS, ptagRetentionFlags

2.984 PidTagRetentionPeriod

Canonical name: PidTagRetentionPeriod

Description: Specifies the number of days that a Message object can remain unarchived.

Property ID: 0x301A

Data type: PtypInteger32, 0x0003

Area: Archive

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.50.3

Alternate names: PR_RETENTION_PERIOD, ptagRetentionPeriod

2.985 PidTagRights

Canonical name: PidTagRights

Description: Specifies a user's folder permissions.

Property ID: 0x6639

Data type: PtypInteger32, 0x0003

Area: ExchangeFolder

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.5

Consuming reference: [\[MS-OXCPERM\]](#)

Alternate names: PR_RIGHTS, ptagRights

2.986 PidTagRoamingDatatypes

Canonical name: PidTagRoamingDatatypes

Description: Contains a bitmask that indicates which stream properties exist on the message.

Property ID: 0x7C06

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.2.1

Alternate names: PR_ROAMING_DATATYPES

2.987 PidTagRoamingDictionary

Canonical name: PidTagRoamingDictionary

Description: Contains a dictionary stream, as specified in [\[MS-OXOCFG\]](#) section 2.2.5.1.

Property ID: 0x7C07

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.2.2

Alternate names: PR_ROAMING_DICTIONARY

2.988 PidTagRoamingXmlStream

Canonical name: PidTagRoamingXmlStream

Description: Contains an XML stream, as specified in [\[MS-OXOCFG\]](#) section 2.2.5.2.

Property ID: 0x7C08

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.2.3

Alternate names: PR_ROAMING_XMLSTREAM

2.989 PidTagRowid

Canonical name: PidTagRowid

Description: Contains a unique identifier for a recipient (2) in a message's recipient table.

Property ID: 0x3000

Data type: PtypInteger32, 0x0003

Area: MapiCommon

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.38

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: PR_ROWID, ptagRowId

2.990 PidTagRowType

Canonical name: PidTagRowType

Description: Identifies the type of the row.

Property ID: 0x0FF5

Data type: PtypInteger32, 0x0003

Area: MapiNonTransmittable

Defining reference: [\[MS-OXCTABL\]](#) section 2.2.1.3

Alternate names: PR_ROW_TYPE, ptagRowType

2.991 PidTagRtfCompressed

Canonical name: PidTagRtfCompressed

Description: Contains message body text in compressed **RTF** format.

Property ID: 0x1009

Data type: PtypBinary, 0x0102

Area: E-mail

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.48.4

Consuming references: [\[MS-OXB BODY\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFCP\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_RTF_COMPRESSED, ptagRTFCompressed

2.992 PidTagRtfInSync

Canonical name: PidTagRtfInSync

Description: Indicates whether the **PidTagBody** property (section [2.676](#)) and the **PidTagRtfCompressed** property (section [2.991](#)) contain the same text (ignoring formatting).

Property ID: 0x0E1F

Data type: PtypBoolean, 0x000B

Area: E-mail

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.48.5

Consuming references: [\[MS-OXBBODY\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#)

Alternate names: PR_RTF_IN_SYNC, ptagRTFInSync

2.993 PidTagRuleActionNumber

Canonical name: PidTagRuleActionNumber

Description: Contains the index of a rule action that failed.

Property ID: 0x6650

Data type: PtypInteger32, 0x0003

Area: ExchangeMessageReadOnly

Defining reference: [\[MS-OXORULE\]](#) section 2.2.7.4

Alternate names: PR_RULE_ACTION_NUMBER, ptagRuleActionNumber

2.994 PidTagRuleActions

Canonical name: PidTagRuleActions

Description: Contains the set of actions associated with the rule.

Property ID: 0x6680

Data type: PtypRuleAction, 0x00FE

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.2.10

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_ACTIONS, ptagRuleActions

2.995 PidTagRuleActionType

Canonical name: PidTagRuleActionType

Description: Contains the **ActionType** ([\[MS-OXORULE\]](#) section 2.2.5.1.1) of a rule that failed.

Property ID: 0x6649

Data type: PtypInteger32, 0x0003

Area: ExchangeMessageReadOnly

Defining reference: [\[MS-OXORULE\]](#) section 2.2.7.3

Alternate names: PR_RULE_ACTION_TYPE, ptagRuleActionType

2.996 PidTagRuleCondition

Canonical name: PidTagRuleCondition

Description: Defines the conditions under which a rule's action is to be executed.

Property ID: 0x6679

Data type: PtypRestriction, 0x00FD

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.2.9

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_CONDITION, ptagRuleCondition

2.997 PidTagRuleError

Canonical name: PidTagRuleError

Description: Contains the error code that indicates the cause of an error encountered during the execution of the rule.

Property ID: 0x6648

Data type: PtypInteger32, 0x0003

Area: ExchangeMessageReadOnly

Defining reference: [\[MS-OXORULE\]](#) section 2.2.7.2

Alternate names: PR_RULE_ERROR, ptagRuleError

2.998 PidTagRuleFolderEntryId

Canonical name: PidTagRuleFolderEntryId

Description: Contains the EntryID of the folder where the rule that triggered the generation of a DAM is stored.

Property ID: 0x6651

Data type: PtypBinary, 0x0102

Area: ExchangeMessageReadOnly

Defining reference: [\[MS-OXORULE\]](#) section 2.2.6.5

Alternate names: PR_RULE_FOLDER_ENTRYID, ptagRuleFolderEntryId

2.999 PidTagRuleId

Canonical name: PidTagRuleId

Description: Specifies a unique identifier that is generated by the messaging server for each rule when the rule is first created.

Property ID: 0x6674

Data type: PtypInteger64, 0x0014

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.2.1

Alternate names: PR_RULE_ID, ptagRuleId

2.1000 PidTagRuleIds

Canonical name: PidTagRuleIds

Description: Contains a buffer that is obtained by concatenating the **PidTagRuleId** property (section [2.999](#)) values from all of the rules contributing actions that are contained in the **PidTagClientActions** property (section [2.692](#)).

Property ID: 0x6675

Data type: PtypBinary, 0x0102

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.6.7

Alternate names: PR_RULE_IDS, ptagRuleIds

2.1001 PidTagRuleLevel

Canonical name: PidTagRuleLevel

Description: Contains 0x00000000. This property is not used.

Property ID: 0x6683

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.2.6

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_LEVEL, ptagRuleLevel

2.1002 PidTagRuleMessageLevel

Canonical name: PidTagRuleMessageLevel

Description: Contains 0x00000000. Set on the FAI message.

Property ID: 0x65ED

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.6

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: PR_RULE_MSG_LEVEL, ptagRuleMsgLevel

2.1003 PidTagRuleMessageName

Canonical name: PidTagRuleMessageName

Description: Specifies the name of the rule. Set on the FAI message.

Property ID: 0x65EC

Data type: PtypString, 0x001F

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.1

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: ptagRuleMsgName

2.1004 PidTagRuleMessageProvider

Canonical name: PidTagRuleMessageProvider

Description: Identifies the client application that owns the rule. Set on the FAI message.

Property ID: 0x65EB

Data type: PtypString, 0x001F

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.7

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: ptagRuleMsgProvider

2.1005 PidTagRuleMessageProviderData

Canonical name: PidTagRuleMessageProviderData

Description: Contains opaque data set by the client for the exclusive use of the client. Set on the FAI message.

Property ID: 0x65EE

Data type: PtypBinary, 0x0102

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.8

Alternate names: PR_RULE_MSG_PROVIDER_DATA, ptagRuleMsgProviderData

2.1006 PidTagRuleMessageSequence

Canonical name: PidTagRuleMessageSequence

Description: Contains a value used to determine the order in which rules are evaluated and executed. Set on the FAI message.

Property ID: 0x65F3

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.3

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: PR_RULE_MSG_SEQUENCE, ptagRuleMsgSequence

2.1007 PidTagRuleMessageState

Canonical name: PidTagRuleMessageState

Description: Contains flags that specify the state of the rule. Set on the FAI message.

Property ID: 0x65E9

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.4

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: PR_RULE_MSG_STATE, ptagRuleMsgState

2.1008 PidTagRuleMessageUserFlags

Canonical name: PidTagRuleMessageUserFlags

Description: Contains an opaque property that the client sets for the exclusive use of the client. Set on the FIA message.

Property ID: 0x65EA

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.5

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: PR_RULE_MSG_USER_FLAGS, ptagRuleMsgUserFlags

2.1009 PidTagRuleName

Canonical name: PidTagRuleName

Description: Specifies the name of the rule.

Property ID: 0x6682

Data type: **PtypString**, 0x001F

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.2.4

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_NAME, PR_RULE_NAME_A, ptagRuleName, PR_RULE_NAME_W

2.1010 PidTagRuleProvider

Canonical name: PidTagRuleProvider

Description: Contains opaque data set by the client for the exclusive use of the client.

Property ID: 0x6681

Data type: **PtypString**, 0x001F

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.2.5

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_PROVIDER, ptagRuleProvider, PR_RULE_PROVIDER_W

2.1011 PidTagRuleProviderData

Canonical name: PidTagRuleProviderData

Description: Contains opaque data set by the client for the exclusive use of the client.

Property ID: 0x6684

Data type: **PtypBinary**, 0x0102

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.2.8

Alternate names: PR_RULE_PROVIDER_DATA, ptagRuleProviderData

2.1012 PidTagRuleSequence

Canonical name: PidTagRuleSequence

Description: Contains a value used to determine the order in which rules are evaluated and executed.

Property ID: 0x6676

Data type: **PtypInteger32**, 0x0003

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.2.2

Consuming references: [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_SEQUENCE, ptagRuleSequence

2.1013 PidTagRuleState

Canonical name: PidTagRuleState

Description: Contains flags that specify the state of the rule.

Property ID: 0x6677

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.2.3

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_STATE, ptagRuleState

2.1014 PidTagRuleUserFlags

Canonical name: PidTagRuleUserFlags

Description: Contains an opaque property that the client sets for the exclusive use of the client.

Property ID: 0x6678

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.2.7

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_USER_FLAGS, ptagRuleUserFlags

2.1015 PidTagRwRulesStream

Canonical name: PidTagRwRulesStream

Description: Contains additional rule data that is opaque to the server.

Property ID: 0x6802

Data type: PtypBinary, 0x0102

Area: Message Class Defined Transmittable

Defining reference:

Consuming reference: [\[MS-OXORULE\]](#)

Alternate names: PR_RW_RULES_STREAM

2.1016 PidTagScheduleInfoAppointmentTombstone

Canonical name: PidTagScheduleInfoAppointmentTombstone

Description: Contains a list of tombstones, where each tombstone represents a Meeting object that has been declined.

Property ID: 0x686A

Data type: PtypBinary, 0x0102

Area: Free/Busy Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.12.5

Alternate names: PR_SCHDINFO_APPT_TOMBSTONE

2.1017 PidTagScheduleInfoAutoAcceptAppointments

Canonical name: PidTagScheduleInfoAutoAcceptAppointments

Description: Indicates whether a client or server is to automatically respond to all meeting requests for the attendee or resource.

Property ID: 0x686D

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.12.2

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_AUTO_ACCEPT_APPTS

2.1018 PidTagScheduleInfoDelegateEntryIds

Canonical name: PidTagScheduleInfoDelegateEntryIds

Description: Specifies the EntryIDs of the delegates.

Property ID: 0x6845

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

Defining reference: [\[MS-OXODLGT\]](#) section 2.2.2.2.5

Alternate names: PR_SCHDINFO_DELEGATE_ENTRYIDS

2.1019 PidTagScheduleInfoDelegateNames

Canonical name: PidTagScheduleInfoDelegateNames

Description: Specifies the names of the delegates.

Property ID: 0x6844

Data type: PtypMultipleString, 0x101F

Area: Free/Busy Properties

Defining reference: [\[MS-OXODLGT\]](#) section 2.2.2.2.3

Consuming reference: [\[MS-OXMSG\]](#)

Alternate names: PR_SCHDINFO_DELEGATE_NAMES

2.1020 PidTagScheduleInfoDelegateNamesW

Canonical name: PidTagScheduleInfoDelegateNamesW

Description: Specifies the names of the delegates in Unicode.

Property ID: 0x684A

Data type: PtypMultipleString, 0x101F

Area: Free/Busy Properties

Defining reference: [\[MS-OXODLGT\]](#) section 2.2.2.2.4

Alternate names: PR_SCHDINFO_DELEGATE_NAMES_W, ptagDelegateNames

2.1021 PidTagScheduleInfoDelegatorWantsCopy

Canonical name: PidTagScheduleInfoDelegatorWantsCopy

Description: Indicates whether the delegator wants to receive copies of the meeting-related objects that are sent to the delegate.

Property ID: 0x6842

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [\[MS-OXODLGT\]](#) section 2.2.2.2.1

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_BOSS_WANTS_COPY

2.1022 PidTagScheduleInfoDelegatorWantsInfo

Canonical name: PidTagScheduleInfoDelegatorWantsInfo

Description: Indicates whether the delegator wants to receive informational updates.

Property ID: 0x684B

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [\[MS-OXODLGT\]](#) section 2.2.2.2.2

Consuming references: [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_BOSS_WANTS_INFO

2.1023 PidTagScheduleInfoDisallowOverlappingAppts

Canonical name: PidTagScheduleInfoDisallowOverlappingAppts

Description: Indicates whether a client or server, when automatically responding to meeting requests, is to decline Meeting Request objects that overlap with previously scheduled events.

Property ID: 0x686F

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.12.4

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_DISALLOW_OVERLAPPING_APPTS

2.1024 PidTagScheduleInfoDisallowRecurringAppts

Canonical name: PidTagScheduleInfoDisallowRecurringAppts

Description: Indicates whether a client or server, when automatically responding to meeting requests, is to decline Meeting Request objects that represent a recurring series.

Property ID: 0x686E

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.12.3

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_DISALLOW_RECURRING_APPTS

2.1025 PidTagScheduleInfoDontMailDelegates

Canonical name: PidTagScheduleInfoDontMailDelegates

Description:

Property ID: 0x6843

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference:

Consuming references: [\[MS-OXOPFFB\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_SCHDINFO_DONT_MAIL_DELEGATES

2.1026 PidTagScheduleInfoFreeBusy

Canonical name: PidTagScheduleInfoFreeBusy

Description: This property is deprecated and is not to be used.

Property ID: 0x686C

Data type: **PtypBinary**, 0x0102

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.4.3

Alternate names: PR_SCHDINFO_FREEBUSY

2.1027 PidTagScheduleInfoFreeBusyAway

Canonical name: PidTagScheduleInfoFreeBusyAway

Description: Specifies the times for which the free/busy status is set a value of **OOF**.

Property ID: 0x6856

Data type: **PtypMultipleBinary**, 0x1102

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.6

Alternate names: PR_SCHDINFO_FREEBUSY_OOF

2.1028 PidTagScheduleInfoFreeBusyBusy

Canonical name: PidTagScheduleInfoFreeBusyBusy

Description: Specifies the blocks of time for which the free/busy status is set to a value of **busy**.

Property ID: 0x6854

Data type: **PtypMultipleBinary**, 0x1102

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.4

Alternate names: PR_SCHDINFO_FREEBUSY_BUSY

2.1029 PidTagScheduleInfoFreeBusyMerged

Canonical name: PidTagScheduleInfoFreeBusyMerged

Description: Specifies the months for which free/busy data of type **busy** or **OOF** is present in the free/busy message.

Property ID: 0x6850

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.8

Alternate names: PR_SCHDINFO_FREEBUSY_MERGED

2.1030 PidTagScheduleInfoFreeBusyTentative

Canonical name: PidTagScheduleInfoFreeBusyTentative

Description: Specifies the blocks of times for which the free/busy status is set to a value of **tentative**.

Property ID: 0x6852

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.2

Alternate names: PR_SCHDINFO_FREEBUSY_TENTATIVE

2.1031 PidTagScheduleInfoMonthsAway

Canonical name: PidTagScheduleInfoMonthsAway

Description: Specifies the months for which free/busy data of type **OOF** is present in the free/busy message.

Property ID: 0x6855

Data type: PtypMultipleInteger32, 0x1003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.5

Alternate names: PR_SCHDINFO_MONTHS_OOF

2.1032 PidTagScheduleInfoMonthsBusy

Canonical name: PidTagScheduleInfoMonthsBusy

Description: Specifies the months for which free/busy data of type **busy** is present in the free/busy message.

Property ID: 0x6853

Data type: PtypMultipleInteger32, 0x1003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.3

Consuming reference: [\[MS-OXMSG\]](#)

Alternate names: PR_SCHDINFO_MONTHS_BUSY

2.1033 PidTagScheduleInfoMonthsMerged

Canonical name: PidTagScheduleInfoMonthsMerged

Description: Specifies the months for which free/busy data of type **busy** or **OOF** is present in the free/busy message.

Property ID: 0x684F

Data type: PtypMultipleInteger32, 0x1003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.7

Alternate names: PR_SCHDINFO_MONTHS_MERGED

2.1034 PidTagScheduleInfoMonthsTentative

Canonical name: PidTagScheduleInfoMonthsTentative

Description: Specifies the months for which free/busy data of type **tentative** is present in the free/busy message.

Property ID: 0x6851

Data type: PtypMultipleInteger32, 0x1003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.1

Alternate names: PR_SCHDINFO_MONTHS_TENTATIVE

2.1035 PidTagScheduleInfoResourceType

Canonical name: PidTagScheduleInfoResourceType

Description: Set to 0x00000000 when sending and is ignored on receipt.

Property ID: 0x6841

Data type: PtypInteger32, 0x0003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.4.2

Alternate names: PR_SCHDINFO_RESOURCE_TYPE

2.1036 PidTagSchedulePlusFreeBusyEntryId

Canonical name: PidTagSchedulePlusFreeBusyEntryId

Description: Contains the EntryID of the folder named "SCHEDULE+ FREE BUSY" under the non-IPM subtree of the public folder store.

Property ID: 0x6622

Data type: PtypBinary, 0x0102

Area: ExchangeMessageStore

Defining reference: [\[MS-OXOPFFB\]](#) section 3.1.1.1.1

Alternate names: PR_SPLUS_FREE_BUSY_ENTRYID

2.1037 PidTagScriptData

Canonical name: PidTagScriptData

Description: Contains a series of instructions that can be executed to format an address and the data that is needed to execute those instructions.

Property ID: 0x0004

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [\[MS-OXOABKT\]](#) section 2.2.2

Alternate names: PR_EMS_SCRIPT_BLOB

2.1038 PidTagSearchFolderDefinition

Canonical name: PidTagSearchFolderDefinition

Description: Specifies the search criteria and search options.

Property ID: 0x6845

Data type: PtypBinary, 0x0102

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.8

Alternate names: PR_WB_SF_DEFINITION

2.1039 PidTagSearchFolderEfpFlags

Canonical name: PidTagSearchFolderEfpFlags

Description: Specifies flags that control how a folder is displayed.

Property ID: 0x6848

Data type: PtypInteger32, 0x0003

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.7

Alternate names: PR_WB_SF_EFP_FLAGS

2.1040 PidTagSearchFolderExpiration

Canonical name: PidTagSearchFolderExpiration

Description: Contains the time, in UTC, at which the search folder container will be stale and has to be updated or recreated.

Property ID: 0x683A

Data type: PtypInteger32, 0x0003

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.5

Alternate names: PR_WB_SF_EXPIRATION

2.1041 PidTagSearchFolderId

Canonical name: PidTagSearchFolderId

Description: Contains a GUID that identifies the search folder.

Property ID: 0x6842

Data type: PtypBinary, 0x0102

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.1

Consuming reference: [\[MS-OXOCFG\]](#)

Alternate names: PR_WB_SF_ID

2.1042 PidTagSearchFolderLastUsed

Canonical name: PidTagSearchFolderLastUsed

Description: Contains the last time, in UTC, that the folder was accessed.

Property ID: 0x6834

Data type: PtypInteger32, 0x0003

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.4

Alternate names: PR_WB_SF_LAST_USED

2.1043 PidTagSearchFolderReCreateInfo

Canonical name: PidTagSearchFolderReCreateInfo

Description: This property is not to be used.

Property ID: 0x6844

Data type: PtypBinary, 0x0102

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.9

Alternate names: PR_WB_SF_RECREATE_INFO

2.1044 PidTagSearchFolderStorageType

Canonical name: PidTagSearchFolderStorageType

Description: Contains flags that specify the binary large object (BLOB) data that appears in the **PidTagSearchFolderDefinition** (section [2.1038](#)) property.

Property ID: 0x6846

Data type: PtypInteger32, 0x0003

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.6

Alternate names: PR_WB_SF_STORAGE_TYPE

2.1045 PidTagSearchFolderTag

Canonical name: PidTagSearchFolderTag

Description: Contains the value of the **SearchFolderTag** sub-property of the **PidTagExtendedFolderFlags** (section [2.749](#)) property of the search folder container.

Property ID: 0x6847

Data type: PtypInteger32, 0x0003

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.3

Alternate names: PR_WB_SF_TAG

2.1046 PidTagSearchFolderTemplateId

Canonical name: PidTagSearchFolderTemplateId

Description: Contains the ID of the template that is being used for the search.

Property ID: 0x6841

Data type: PtypInteger32, 0x0003

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.2

Alternate names: PR_WB_SF_TEMPLATE_ID

2.1047 PidTagSearchKey

Canonical name: PidTagSearchKey

Description: Contains a unique binary-comparable key that identifies an object for a search.

Property ID: 0x300B

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.1.9

Consuming references: [\[MS-OXCFOLD1\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SEARCH_KEY, ptagSearchKey

2.1048 PidTagSecureSubmitFlags

Canonical name: PidTagSecureSubmitFlags

Description:

Property ID: 0x65C6

Data type: PtypInteger32, 0x0003

Area: Exchange

Defining reference:

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: PR_SECURE_SUBMIT_FLAGS, ptagSecureSubmitFlags

2.1049 PidTagSecurityDescriptor

Canonical name: PidTagSecurityDescriptor

Description: Contains security attributes.

Property ID: 0x0E27

Data type: PtypBinary, 0x0102

Area: Access Control Properties

Defining reference:

Consuming reference: [\[MS-OXCMMSG\]](#)

Alternate names: PR_NT_SECURITY_DESCRIPTOR

2.1050 PidTagSecurityDescriptorAsXml

Canonical name: PidTagSecurityDescriptorAsXml

Description: Contains security attributes in XML.

Property ID: 0x0E6A

Data type: PtypString, 0x001F

Area: Access Control Properties

Defining reference: [\[MS-XWDVSEC\]](#) section 2.2.2

Consuming reference: [\[MS-OXCPERM\]](#)

Alternate names: PR_NT_SECURITY_DESCRIPTOR_AS_XML,
PR_NT_SECURITY_DESCRIPTOR_AS_XML_A, PR_NT_SECURITY_DESCRIPTOR_AS_XML_W,
<http://schemas.microsoft.com/exchange/security/descriptor>

2.1051 PidTagSelectable

Canonical name: PidTagSelectable

Description:

Property ID: 0x3609

Data type: PtypBoolean, 0x000B

Area: AB Container

Defining reference:

Consuming reference: [\[MS-OXOABKT\]](#)

Alternate names: PR_SELECTABLE

2.1052 PidTagSenderAddressType

Canonical name: PidTagSenderAddressType

Description: Contains the sending mailbox owner's e-mail address type.

Property ID: 0x0C1E

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.40

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOPOST\]](#)

Alternate names: PR_SENDER_ADDRTYPE, PR_SENDER_ADDRTYPE_A, ptagSenderAddrType, PR_SENDER_ADDRTYPE_W

2.1053 PidTagSenderEmailAddress

Canonical name: PidTagSenderEmailAddress

Description: Contains the sending mailbox owner's e-mail address.

Property ID: 0x0C1F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.41

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENDER_EMAIL_ADDRESS, PR_SENDER_EMAIL_ADDRESS_A, PR_SENDER_EMAIL_ADDRESS_W

2.1054 PidTagSenderEntryId

Canonical name: PidTagSenderEntryId

Description: Identifies an address book EntryID that contains the sending mailbox owner's address book EntryID.

Property ID: 0x0C19

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.42

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENDER_ENTRYID, ptagSenderEntryId

2.1055 PidTagSenderFlags

Canonical name: PidTagSenderFlags

Description:

Property ID: 0x4019

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: ptagSenderFlags

2.1056 PidTagSenderIdStatus

Canonical name: PidTagSenderIdStatus

Description: Reports the results of a Sender-ID check.

Property ID: 0x4079

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.71

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_SENDER_ID_STATUS

2.1057 PidTagSenderName

Canonical name: PidTagSenderName

Description: Contains the sending mailbox owner's display name.

Property ID: 0x0C1A

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.43

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_SENDER_NAME, PR_SENDER_NAME_A, ptagSenderName, PR_SENDER_NAME_W, urn:schemas:httpmail:sendername, http://schemas.microsoft.com/exchange/sender-name-utf8

2.1058 PidTagSenderSearchKey

Canonical name: PidTagSenderSearchKey

Description: Identifies an address book search key.

Property ID: 0x0C1D

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.44

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#)

Alternate names: PR_SENDER_SEARCH_KEY, ptagSenderSearchKey

2.1059 PidTagSenderSmtpAddress

Canonical name: PidTagSenderSmtpAddress

Description: Contains the SMTP e-mail address format of the e-mail address of the sending mailbox owner.

Property ID: 0x5D01

Data type: **PtypString**, 0x001F

Area: Mail

Defining reference: [\[MS-OXOMSG\]](#) section [2.2.1.47](#)

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: SenderSmtpAddress, ptagSenderSmtpAddress

2.1060 PidTagSenderTelephoneNumber

Canonical name: PidTagSenderTelephoneNumber

Description: Contains the telephone number of the caller associated with a voice mail message.

Property ID: 0x6802

Data type: **PtypString**, 0x001F

Area: Unified Messaging

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.72

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXOUM\]](#)

Alternate names: InternalSchemaSenderTelephoneNumber

2.1061 PidTagSendInternetEncoding

Canonical name: PidTagSendInternetEncoding

Description: Contains a bitmask of message encoding preferences for e-mail sent to an e-mail-enabled entity that is represented by this Address Book object.

Property ID: 0x3A71

Data type: **PtypInteger32**, 0x0003

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.19

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_SEND_INTERNET_ENCODING, ptagSendInternetEncoding

2.1062 PidTagSendRichInfo

Canonical name: PidTagSendRichInfo

Description: Indicates whether the e-mail-enabled entity represented by the Address Book object can receive all message content, including Rich Text Format (RTF) and other embedded objects.

Property ID: 0x3A40

Data type: PtypBoolean, 0x000B

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.18

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_SEND_RICH_INFO, ptagSendRichInfo

2.1063 PidTagSensitivity

Canonical name: PidTagSensitivity

Description: Indicates the sender's assessment of the sensitivity of the Message object.

Property ID: 0x0036

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.13

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXVCARD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMSS\]](#)

Alternate names: PR_SENSITIVITY, ptagSensitivity,
http://schemas.microsoft.com/exchange/sensitivity-long,
http://schemas.microsoft.com/exchange/sensitivity

2.1064 PidTagSentMailSvrEID

Canonical name: PidTagSentMailSvrEID

Description: Contains an EntryID that represents the **Sent Items folder** for the message.

Property ID: 0x6740

Data type: PtypServerId, 0x00FB

Area: ProviderDefinedNonTransmittable

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.10

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: ptagSentMailSvrEID

2.1065 PidTagSentRepresentingAddressType

Canonical name: PidTagSentRepresentingAddressType

Description: Contains an e-mail address type.

Property ID: 0x0064

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.46

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENT_REPRESENTING_ADDRTYPE, PR_SENT_REPRESENTING_ADDRTYPE_A, ptagSentRepresentingAddrType, PR_SENT_REPRESENTING_ADDRTYPE_W

2.1066 PidTagSentRepresentingEmailAddress

Canonical name: PidTagSentRepresentingEmailAddress

Description: Contains an e-mail address for the end user who is represented by the sending mailbox owner.

Property ID: 0x0065

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.47

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENT_REPRESENTING_EMAIL_ADDRESS, PR_SENT_REPRESENTING_EMAIL_ADDRESS_A, PR_SENT_REPRESENTING_EMAIL_ADDRESS_W

2.1067 PidTagSentRepresentingEntryId

Canonical name: PidTagSentRepresentingEntryId

Description: Contains the identifier of the end user who is represented by the sending mailbox owner.

Property ID: 0x0041

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.48

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENT_REPRESENTING_ENTRYID, ptagSentRepresentingEntryId

2.1068 PidTagSentRepresentingFlags

Canonical name: PidTagSentRepresentingFlags

Description:

Property ID: 0x401A

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: ptagSentRepresentingFlags

2.1069 PidTagSentRepresentingName

Canonical name: PidTagSentRepresentingName

Description: Contains the display name for the end user who is represented by the sending mailbox owner.

Property ID: 0x0042

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.49

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_SENT_REPRESENTING_NAME, PR_SENT_REPRESENTING_NAME_A, ptagSentRepresentingName, PR_SENT_REPRESENTING_NAME_W, urn:schemas:httpmail:fromname, http://schemas.microsoft.com/exchange/from-name-utf8

2.1070 PidTagSentRepresentingSearchKey

Canonical name: PidTagSentRepresentingSearchKey

Description: Contains a binary-comparable key that represents the end user who is represented by the sending mailbox owner.

Property ID: 0x003B

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.50

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

Alternate names: PR_SENT_REPRESENTING_SEARCH_KEY, ptagSentRepresentingSearchKey

2.1071 PidTagSessionInitiationProtocolUri

Canonical name: PidTagSessionInitiationProtocolUri

Description:

Property ID: 0x5FE5

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagRecipientSipUri, SipUri

2.1072 PidTagSmtpAddress

Canonical name: PidTagSmtpAddress

Description: Contains the Message object's SMTP address.

Property ID: 0x39FE

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.21

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXSHARE\]](#)

Alternate names: PR_SMTP_ADDRESS, PR_SMTP_ADDRESS_A, PR_SMTP_ADDRESS_W

2.1073 PidTagSortLocaleId

Canonical name: PidTagSortLocaleId

Description: Contains the locale identifier.

Property ID: 0x6705

Data type: PtypInteger32, 0x0003

Area: ExchangeAdministrative

Defining reference: [\[MS-OXPFOAB\]](#) section 2.2.1.5

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: PR_SORT_LOCALE_ID, ptagSortLocaleId

2.1074 PidTagSourceKey

Canonical name: PidTagSourceKey

Description: Contains a value that contains an internal global identifier (GID) for this folder or message.

Property ID: 0x65E0

Data type: PtypBinary, 0x0102

Area: Sync

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.5

Alternate names: PR_SOURCE_KEY

2.1075 PidTagSpokenName

Canonical name: PidTagSpokenName

Description: Contains a recording of the mail user's name pronunciation.

Property ID: 0x8CC2

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.83

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_UM_SPOKEN_NAME

2.1076 PidTagSpouseName

Canonical name: PidTagSpouseName

Description: Contains the name of the mail user's spouse/partner.

Property ID: 0x3A48

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.72

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SPOUSE_NAME, PR_SPOUSE_NAME_A, PR_SPOUSE_NAME_W,
urn:schemas:contacts:spousecn

2.1077 PidTagStartDate

Canonical name: PidTagStartDate

Description: Contains the value of the **PidLidAppointmentStartWhole** property (section [2.29](#)).

Property ID: 0x0060

Data type: **PtypTime**, 0x0040

Area: MapiEnvelope

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.30

Consuming references: [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#),

Alternate names: PR_START_DATE, http://schemas.microsoft.com/mapi/start_date

2.1078 PidTagStartDateEtc

Canonical name: PidTagStartDateEtc

Description: Contains the default retention period, and the start date from which the Message object's age is calculated.

Property ID: 0x301B

Data type: **PtypBinary**, 0x0102

Area: Archive

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.50.4

Alternate names: PR_START_DATE_ETC, ptagStartDateEtc

2.1079 PidTagStateOrProvince

Canonical name: PidTagStateOrProvince

Description: Contains the name of the mail user's state or province.

Property ID: 0x3A28

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.22

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_STATE_OR_PROVINCE, PR_STATE_OR_PROVINCE_A,
PR_STATE_OR_PROVINCE_W, PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE,
PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE_A,
PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE_W, urn:schemas:contacts:mailingstate

2.1080 PidTagStoreEntryId

Canonical name: PidTagStoreEntryId

Description: Contains the unique EntryID of the message store where an object resides.

Property ID: 0x0FFB

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.44

Consuming references: [\[MS-OXOFLAG\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXOCFG\]](#)

Alternate names: PR_STORE_ENTRYID, ptagStoreEntryId

2.1081 PidTagStoreState

Canonical name: PidTagStoreState

Description: Indicates whether a mailbox has any active Search folders.

Property ID: 0x340E

Data type: PtypInteger32, 0x0003

Area: MapiMessageStore

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Alternate names: PR_STORE_STATE

2.1082 PidTagStoreSupportMask

Canonical name: PidTagStoreSupportMask

Description: Indicates whether string properties within the .msg file are Unicode-encoded.

Property ID: 0x340D

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [\[MS-OXMSG\]](#) section 2.1.1.1

Alternate names: PR_STORE_SUPPORT_MASK, ptagStoreSupportMask

2.1083 PidTagStreetAddress

Canonical name: PidTagStreetAddress

Description: Contains the mail user's street address.

Property ID: 0x3A29

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.19

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_STREET_ADDRESS, PR_STREET_ADDRESS_A, PR_STREET_ADDRESS_W, PR_BUSINESS_ADDRESS_STREET, PR_BUSINESS_ADDRESS_STREET_A, PR_BUSINESS_ADDRESS_STREET_W, urn:schemas:contacts:mailingstreet

2.1084 PidTagSubfolder

Canonical name: PidTagSubfolder

Description: Indicates whether the resource is a folder as displayed to end users.

Property ID: 0x6708

Data type: PtypBoolean, 0x000B

Area: ExchangeAdministrative Property set

Defining reference: [\[MS-XWDFOLD\]](#) section 2.2.1

Consuming references: [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SUBFOLDER, ptagSubfolder, DAV:isfolder

2.1085 PidTagSubfolders

Canonical name: PidTagSubfolders

Description: Specifies whether a folder has subfolders.

Property ID: 0x360A

Data type: PtypBoolean, 0x000B

Area: MapiContainer

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.9

Consuming references: [\[MS-XWDFOLD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SUBFOLDERS, ptagSubFolders, DAV:hassubs

2.1086 PidTagSubject

Canonical name: PidTagSubject

Description: Contains the subject of the e-mail message.

Property ID: 0x0037

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.46

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORULE\]](#), [\[MS-OXPVAL\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR SUBJECT, PR SUBJECT_A, ptagSubject, PR SUBJECT_W, urn:schemas:httpmail:subject, http://schemas.microsoft.com/exchange/subject-utf8

2.1087 PidTagSubjectPrefix

Canonical name: PidTagSubjectPrefix

Description: Contains the prefix for the subject of the message.

Property ID: 0x003D

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.9

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR SUBJECT_PREFIX, PR SUBJECT_PREFIX_A, ptagSubjectPrefix, PR SUBJECT_PREFIX_W

2.1088 PidTagSurname

Canonical name: PidTagSurname

Description: Contains the mail user's family name.

Property ID: 0x3A11

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.1

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR SURNAME, PR SURNAME_A, PR SURNAME_W, urn:schemas:contacts:sn

2.1089 PidTagSwappedToDoData

Canonical name: PidTagSwappedToDoData

Description: Contains a secondary flag storage location when sender flags or sender reminders are supported.

Property ID: 0x0E2D

Data type: **PtypBinary**, 0x0102

Area: MapiNonTransmittable

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.7

Consuming reference: [\[MS-OXORMDR\]](#)

Alternate names: PR_SWAPPED_TODO_DATA, ptagSwappedTodoData

2.1090 PidTagSwappedToDoStore

Canonical name: PidTagSwappedToDoStore

Description: Contains the value of the **PidTagStoreEntryId** property (section [2.1080](#)) of the message when the value of the **PidTagSwappedToDoData** property (section [2.1089](#)) is set.

Property ID: 0x0E2C

Data type: **PtypBinary**, 0x0102

Area: MapiNonTransmittable

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.8

Consuming reference: [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_SWAPPED_TODO_STORE, ptagSwappedTodoStore

2.1091 PidTagTargetEntryId

Canonical name: PidTagTargetEntryId

Description: Contains the message ID of a Message object being submitted for optimization ([\[MS-OXOMSG\]](#) section 3.2.4.4).

Property ID: 0x3010

Data type: **PtypBinary**, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.67

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCRPC\]](#),

Alternate names: PR_TARGET_ENTRYID, ptagTargetEntryId

2.1092 PidTagTelecommunicationsDeviceForDeafTelephoneNumber

Canonical name: PidTagTelecommunicationsDeviceForDeafTelephoneNumber

Description: Contains the mail user's telecommunication device for the deaf (TTY/TDD) telephone number.

Property ID: 0x3A4B

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.54

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_TTYTDD_PHONE_NUMBER, PR_TTYTDD_PHONE_NUMBER_A, PR_TTYTDD_PHONE_NUMBER_W, urn:schemas:contacts:ttytddphone

2.1093 PidTagTelexNumber

Canonical name: PidTagTelexNumber

Description: Contains the mail user's telex number.

Property ID: 0x3A2C

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.55

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_TELEX_NUMBER, PR_TELEX_NUMBER_A, PR_TELEX_NUMBER_W, urn:schemas:contacts:telexnumber

2.1094 PidTagTemplateData

Canonical name: PidTagTemplateData

Description:

Property ID: 0x0001

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference:

Consuming reference: [\[MS-OXOABKT\]](#)

Alternate names: PR_EMS_TEMPLATE_BLOB

2.1095 PidTagTemplateid

Canonical name: PidTagTemplateid

Description: Contains the value of the **PidTagEntryId** property (section [2.741](#)), expressed as a **Permanent Entry ID** format.

Property ID: 0x3902

Data type: PtypBinary, 0x0102

Area: MapiAddressBook

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.3

Alternate names: PR_TEMPLATEID

2.1096 PidTagTemporaryDefaultDocument

Canonical name: PidTagTemporaryDefaultDocument

Description: Indicates the relative URI of the default document contained in the structured document.

Property ID: 0x3F20

Data type: PtypString, 0x001F

Area: Structured Documents

Defining reference: [\[MS-XWDSTRUCTDOC\]](#) section 2.2.1.1

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: DAV:defaultdocument

2.1097 PidTagTextAttachmentCharset

Canonical name: PidTagTextAttachmentCharset

Description: Specifies the character set of an attachment received via MIME with the content-type of text.

Property ID: 0x371B

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.25

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagTextAttachmentCharset

2.1098 PidTagThumbnailPhoto

Canonical name: PidTagThumbnailPhoto

Description: Contains the mail user's photo in .jpg format.

Property ID: 0x8C9E

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.82

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_THUMBNAIL_PHOTO

2.1099 PidTagTitle

Canonical name: PidTagTitle

Description: Contains the mail user's job title.

Property ID: 0x3A17

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.7

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_TITLE, PR_TITLE_A, PR_TITLE_W, urn:schemas:contacts:title

2.1100 PidTagTnefCorrelationKey

Canonical name: PidTagTnefCorrelationKey

Description: Contains a value that correlates a Transport Neutral Encapsulation Format (TNEF) attachment with a message.

Property ID: 0x007F

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.29

Consuming reference: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_TNEF_CORRELATION_KEY

2.1101 PidTagToDoItemFlags

Canonical name: PidTagToDoItemFlags

Description: Contains flags associated with objects.

Property ID: 0x0E2B

Data type: PtypInteger32, 0x0003

Area: MapiNonTransmittable

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.6

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_TODO_ITEM_FLAGS, ptagToDoItemFlags

2.1102 PidTagTransmittableDisplayName

Canonical name: PidTagTransmittableDisplayName

Description: Contains an Address Book object's display name that is transmitted with the message.

Property ID: 0x3A20

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.8

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_TRANSMITTABLE_DISPLAY_NAME, PR_TRANSMITTABLE_DISPLAY_NAME_A, ptagTransmittableDisplayName, PR_TRANSMITTABLE_DISPLAY_NAME_W

2.1103 PidTagTransportMessageHeaders

Canonical name: PidTagTransportMessageHeaders

Description: Contains transport-specific message envelope information for e-mail.

Property ID: 0x007D

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.52

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#)

Alternate names: PR_TRANSPORT_MESSAGE_HEADERS, PR_TRANSPORT_MESSAGE_HEADERS_A, PR_TRANSPORT_MESSAGE_HEADERS_W

2.1104 PidTagTrustSender

Canonical name: PidTagTrustSender

Description: Specifies whether the associated message was delivered through a trusted transport channel.

Property ID: 0x0E79

Data type: PtypInteger32, 0x0003

Area: MapiNonTransmittable

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.45

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_TRUST_SENDER, ptagTrustSender

2.1105 PidTagUrlCompName

Canonical name: PidTagUrlCompName

Description: Contains the composite URL name.

Property ID: 0x10F3

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.1.2

Consuming references: [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_URL_COMP_NAME, PR_URL_COMP_NAME_A, PR_URL_COMP_NAME_W, ptagURLCompName

2.1106 PidTagUrlCompNameSet

Canonical name: PidTagUrlCompNameSet

Description:

Property ID: 0x0E62

Data type: **PtypBoolean**, 0x000B

Area: ID Properties

Defining reference:

Consuming reference: [\[MS-OXCMSG\]](#)

Alternate names: ptagURLCompNameSet

2.1107 PidTagUrlName

Canonical name: PidTagUrlName

Description: Contains the URL of an object.

Property ID: 0x6707

Data type: **PtypString**, 0x001F

Area: ExchangeAdministrative

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.1.4

Consuming references: [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_URL_NAME, PR_URL_NAME_A, PR_URL_NAME_W, ptagURLName, DAV:href

2.1108 PidTagUserCertificate

Canonical name: PidTagUserCertificate

Description: Contains an ASN.1 authentication certificate for a messaging user.

Property ID: 0x3A22

Data type: PtypBinary, 0x0102

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.64

Consuming references: [\[MS-OXOAB\]](#), [\[MS-XWDCNTC\]](#)

Alternate names: PR_USER_CERTIFICATE, ptagUserCertificate,
urn:schemas:contacts:usercertificate

2.1109 PidTagUserEntryId

Canonical name: PidTagUserEntryId

Description: Address book EntryID of the user logged on to the public folders.

Property ID: 0x6619

Data type: PtypBinary, 0x0102

Area: ExchangeMessageStore

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Alternate names: PR_USER_ENTRYID, ptagUserEntryId

2.1110 PidTagUserX509Certificate

Canonical name: PidTagUserX509Certificate

Description: Contains a list of certificates for the mail user.

Property ID: 0x3A70

Data type: PtypMultipleBinary, 0x1102

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.66

Consuming references: [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_USER_X509_CERTIFICATE

2.1111 PidTagViewDescriptorBinary

Canonical name: PidTagViewDescriptorBinary

Description: Contains view definitions.

Property ID: 0x7001

Data type: PtypBinary, 0x0102

Area: MessageClassDefinedTransmittable

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.6.1

Alternate names: PR_VD_BINARY

2.1112 PidTagViewDescriptorName

Canonical name: PidTagViewDescriptorName

Description:

Property ID: 0x7006

Data type: PtypString, 0x001F

Area: MessageClassDefinedTransmittable

Defining reference:

Consuming reference: [\[MS-OXOCFG\]](#)

Alternate names: PR_VD_NAME, PR_VD_NAME_W

2.1113 PidTagViewDescriptorStrings

Canonical name: PidTagViewDescriptorStrings

Description: Contains view definitions in string format.

Property ID: 0x7002

Data type: PtypString, 0x001F

Area: MessageClassDefinedTransmittable

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.6.2

Alternate names: PR_VD_STRINGS, PR_VD_STRINGS_W

2.1114 PidTagViewDescriptorVersion

Canonical name: PidTagViewDescriptorVersion

Description: Contains the View Descriptor version.

Property ID: 0x7007

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference:

Consuming reference: [\[MS-OXOCFG\]](#)

Alternate names: PR_VD_VERSION

2.1115 PidTagVoiceMessageAttachmentOrder

Canonical name: PidTagVoiceMessageAttachmentOrder

Description: Contains a list of file names for the audio file attachments that are to be played as part of a message.

Property ID: 0x6805

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference:

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXOUM\]](#)

Alternate names: InternalSchemaVoiceMessageAttachmentOrder

2.1116 PidTagVoiceMessageDuration

Canonical name: PidTagVoiceMessageDuration

Description:

Property ID: 0x6801

Data type: PtypInteger32, 0x0003

Area: Unified Messaging

Defining reference:

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXOUM\]](#)

Alternate names: InternalSchemaVoiceMessageDuration

2.1117 PidTagVoiceMessageSenderName

Canonical name: PidTagVoiceMessageSenderName

Description:

Property ID: 0x6803

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference:

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXOUM\]](#)

Alternate names: InternalSchemaVoiceMessageSenderName

2.1118 PidTagWeddingAnniversary

Canonical name: PidTagWeddingAnniversary

Description: Contains the date of the mail user's wedding anniversary.

Property ID: 0x3A41

Data type: PtypTime, 0x0040

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.80

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_WEDDING_ANNIVERSARY, urn:schemas:contacts:weddinganniversary

2.1119 PidTagWlinkAddressBookEID

Canonical name: PidTagWlinkAddressBookEID

Description: Specifies the value of the **PidTagEntryId** property (section [2.741](#)) of the user to whom the folder belongs.

Property ID: 0x6854

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.16

Alternate names: PR_WLINK_ABEID

2.1120 PidTagWlinkAddressBookStoreEID

Canonical name: PidTagWlinkAddressBookStoreEID

Description: Specifies the value of the **PidTagStoreEntryId** property (section [2.1080](#)) of the current user (not the owner of the folder).

Property ID: 0x6891

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.17

Alternate names: PR_WLINK_AB_EXSTOREEID

2.1121 PidTagWlinkCalendarColor

Canonical name: PidTagWlinkCalendarColor

Description: Specifies the background color of the calendar.

Property ID: 0x6853

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.15

Alternate names: PR_WLINK_CALENDAR_COLOR

2.1122 PidTagWlinkClientID

Canonical name: PidTagWlinkClientID

Description: Specifies the Client ID that allows the client to determine whether the shortcut was created on the current machine/user via an equality test.

Property ID: 0x6890

Data type: PttypGuid, 0x0048

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.18

Alternate names: PR_WLINK_CLIENTID

2.1123 PidTagWlinkEntryId

Canonical name: PidTagWlinkEntryId

Description: Specifies the EntryID of the folder pointed to by the shortcut.

Property ID: 0x684C

Data type: PttypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.8

Alternate names: PR_WLINK_ENTRYID

2.1124 PidTagWlinkFlags

Canonical name: PidTagWlinkFlags

Description: Specifies conditions associated with the shortcut.

Property ID: 0x684A

Data type: PttypInteger32, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.6

Alternate names: PR_WLINK_FLAGS

2.1125 PidTagWlinkFolderType

Canonical name: PidTagWlinkFolderType

Description: Specifies the type of folder pointed to by the shortcut.

Property ID: 0x684F

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.11

Alternate names: PR_WLINK_FOLDER_TYPE

2.1126 PidTagWlinkGroupClSID

Canonical name: PidTagWlinkGroupClSID

Description: Specifies the value of the **PidTagWlinkGroupHeaderID** property (section [2.1126](#)) of the group header associated with the shortcut.

Property ID: 0x6850

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.12

Alternate names: PR_WLINK_GROUP_CLSID

2.1127 PidTagWlinkGroupHeaderID

Canonical name: PidTagWlinkGroupHeaderID

Description: Specifies the ID of the **navigation shortcut** that groups other navigation shortcuts.

Property ID: 0x6842

Data type: PtypGuid, 0x0048

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.3

Alternate names:

2.1128 PidTagWlinkGroupName

Canonical name: PidTagWlinkGroupName

Description: Specifies the value of the **PidTagNormalizedSubject** (section [2.864](#)) of the group header associated with the shortcut.

Property ID: 0x6851

Data type: PtypString, 0x001F

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.13

Alternate names: PR_WLINK_GROUP_NAME

2.1129 PidTagWlinkOrdinal

Canonical name: PidTagWlinkOrdinal

Description: Specifies a variable-length binary property to be used to sort shortcuts lexicographically.

Property ID: 0x684B

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.7

Alternate names: PR_WLINK_ORDINAL

2.1130 PidTagWlinkRecordKey

Canonical name: PidTagWlinkRecordKey

Description: Specifies the value of **PidTagRecordKey** property (section [2.962](#)) of the folder pointed to by the shortcut.

Property ID: 0x684D

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.9

Alternate names: PR_WLINK_RECKEY

2.1131 PidTagWlinkROGroupType

Canonical name: PidTagWlinkROGroupType

Description: Specifies the type of **group header**.

Property ID: 0x6892

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.19

Alternate names: PR_WLINK_RO_GROUP_TYPE

2.1132 PidTagWlinkSaveStamp

Canonical name: PidTagWlinkSaveStamp

Description: Specifies an integer that allows a client to identify with a high probability whether the navigation shortcut was saved by the current client session.

Property ID: 0x6847

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.4

Alternate names:

2.1133 PidTagWlinkSection

Canonical name: PidTagWlinkSection

Description: Specifies the section where the shortcut should be grouped.

Property ID: 0x6852

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.14

Alternate names: PR_WLINK_SECTION

2.1134 PidTagWlinkStoreEntryId

Canonical name: PidTagWlinkStoreEntryId

Description: Specifies the value of the **PidTagStoreEntryId** property (section [2.1080](#)) of the folder pointed to by the shortcut.

Property ID: 0x684E

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.10

Alternate names: PR_WLINK_STORE_ENTRYID

2.1135 PidTagWlinkType

Canonical name: PidTagWlinkType

Description: Specifies the type of navigation shortcut.

Property ID: 0x6849

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.5

Alternate names: PR_WLINK_TYPE

3 Structure Examples

None.

4 Security Considerations

There are no security considerations unique to this specification.

5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2003
- Microsoft® Exchange Server 2007
- Microsoft® Exchange Server 2010
- Microsoft® Office Outlook® 2003
- Microsoft® Office Outlook® 2007
- Microsoft® Outlook® 2010

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

6 Change Tracking

This section identifies changes that were made to the [MS-OXPROPS] protocol document between the August 2011 and October 2011 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major chang e (Y or N)	Change type
1 Introduction	Clarified the role of this document and highlighted the value that it provides to implementers.	N	Content updated .
1.1 Glossary	Changed glossary term from "permissions list" to "permissions".	N	Content updated .
1.1 Glossary	Added the "Messaging Application Programming Interface (MAPI)" glossary term.	N	Content updated .
1.1 Glossary	Added the "Integrated Services Digital Network (ISDN)" glossary term.	N	Content updated .
1.3 Overview	Clarified the purpose of this document, provided a typical scenario for using it, and added helpful information about the types of property information in this document.	Y	Content updated .
2.41 PidLidAutoStartCheck	Revised the description for clarity.	N	Content updated .
2.49 PidLidCategories	Removed [MS-OXCMAIL] from the list of consuming references.	N	Content updated .

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.52 PidLidClassification	Updated the property description.	N	Content updated .
2.125 PidLidFExceptionalAttendees	Added a link to describe a RecipientRow structure.	N	Content updated .
2.134 PidLidForwardNotificationRecipients	Added a link to describe a RecipientRow structure.	N	Content updated .
2.159 PidLidLogEnd	Added UTC time designation.	N	Content updated .
2.161 PidLidLogStart	Added UTC time designation.	N	Content updated .
2.162 PidLidLogType	Added a descriptor for the type of activity being recorded in the log.	N	Content updated .
2.163 PidLidLogTypeDesc	Revised the description of the contents of the property.	N	Content updated .
2.201 PidLidPostRssItemLink	Revised the description to include links from both RSS or Atom items.	N	Content updated .
2.203 PidLidPostRssSubscription	Revised the description to include both RSS or Atom subscriptions.	N	Content updated .
2.228 PidLidSharingAnonymity	Added Description and Defining reference to PidLidSharingAnonymity section. Deleted Consuming reference.	N	Content updated .
2.229 PidLidSharingBindingEntryId	Added Description and Defining reference to PidLidSharingBindingEntryId section. Deleted Consuming reference.	N	Content updated .
2.230 PidLidSharingBrowseUrl	Added Description and Defining reference to PidLidSharingBrowseUrl section. Deleted Consuming reference.	N	Content updated .
2.233 PidLidSharingDataRangeEnd	Added Description and Defining reference to PidLidSharingDataRangeEnd section. Deleted Consuming reference.	N	Content updated .
2.235 PidLidSharingDetail	Added Description and Defining reference to PidLidSharingDetail section. Deleted Consuming reference.	N	Content updated .

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.237 PidLidSharingFilter	Added Description and Defining reference to PidLidSharingFilter section. Deleted Consuming reference.	N	Content updated .
2.238 PidLidSharingFlags	Added Description and Defining reference to PidLidSharingFlags section. Deleted Consuming reference.	N	Content updated .
2.240 PidLidSharingFolderEntryId	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingFolderEntryId section.	N	Content updated .
2.241 PidLidSharingIndexEntryId	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingIndexEntryId section.	N	Content updated .
2.245 PidLidSharingInstanceGuid	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingInstanceGuid section.	N	Content updated .
2.246 PidLidSharingLastAutoSyncTime	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingLastAutoSyncTime section.	N	Content updated .
2.247 PidLidSharingLastSyncTime	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingLastSyncTime section.	N	Content updated .
2.248 PidLidSharingLocalComment	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingLocalComment section.	N	Content updated .
2.249 PidLidSharingLocalLastModificationTime	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingLocalLastModificationTime section.	N	Content updated .
2.250 PidLidSharingLocalName	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingLocalName section.	N	Content updated .
2.251 PidLidSharingLocalPath	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingLocalPath section.	N	Content updated .
2.252 PidLidSharingLocalStoreUid	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingLocalStoreUid section.	N	Content updated .
2.254 PidLidSharingLocalUid	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingLocalUid section.	N	Content updated .
2.255 PidLidSharingOriginalMessageEntryId	Added Description and Defining reference, and deleted Consuming reference, in the	N	Content updated

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
	PidLidSharingOriginalMessageEntryId section.		.
2.256 PidLidSharingParentBindingEntryId	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingParentBindingEntryId section.	N	Content updated .
2.257 PidLidSharingParticipants	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingParticipants section.	N	Content updated .
2.258 PidLidSharingPermissions	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingPermissions section.	N	Content updated .
2.259 PidLidSharingProviderExtension	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingProviderExtension section.	N	Content updated .
2.263 PidLidSharingRangeEnd	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingRangeEnd section.	N	Content updated .
2.264 PidLidSharingRangeStart	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingRangeStart section.	N	Content updated .
2.265 PidLidSharingReciprocation	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingReciprocation section.	N	Content updated .
2.266 PidLidSharingRemoteByteSize	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingRemoteByteSize section.	N	Content updated .
2.267 PidLidSharingRemoteComment	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingRemoteComment section.	N	Content updated .
2.268 PidLidSharingRemoteCrc	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingRemoteCrc section.	N	Content updated .
2.269 PidLidSharingRemoteLastModificationTime	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingRemoteLastModificationTime section.	N	Content updated .
2.270 PidLidSharingRemoteMessageCount	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingRemoteMessageCount section.	N	Content updated .
2.272 PidLidSharingRemotePass	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingRemotePass section.	N	Content updated .

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.273 PidLidSharingRemotePath	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingRemotePath section.	N	Content updated .
2.277 PidLidSharingRemoteUser	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingRemoteUser section.	N	Content updated .
2.278 PidLidSharingRemoteVersion	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingRemoteVersion section.	N	Content updated .
2.281 PidLidSharingRoamLog	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingRoamLog section.	N	Content updated .
2.282 PidLidSharingStart	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingStart section.	N	Content updated .
2.283 PidLidSharingStatus	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingStatus section.	N	Content updated .
2.284 PidLidSharingStop	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingStop section.	N	Content updated .
2.285 PidLidSharingSyncFlags	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingSyncFlags section.	N	Content updated .
2.286 PidLidSharingSyncInterval	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingSyncInterval section.	N	Content updated .
2.287 PidLidSharingTimeToLive	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingTimeToLive section.	N	Content updated .
2.288 PidLidSharingTimeToLiveAuto	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingTimeToLiveAuto section.	N	Content updated .
2.289 PidLidSharingWorkingHoursDays	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingWorkingHoursDays section.	N	Content updated .
2.290 PidLidSharingWorkingHoursEnd	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingWorkingHoursEnd section.	N	Content updated .
2.291 PidLidSharingWorkingHoursStart	Added Description and Defining reference, and deleted Consuming reference, in the PidLidSharingWorkingHoursStart section.	N	Content updated .

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.292 PidLidSharingWorkingHoursTimeZone	Added property description and defining reference. Removed consuming reference.	N	Content updated .
2.318 PidLidTaskMode	Changed the defining reference to [MS-OXOTASK] section 2.2.3.2.	N	Content updated .
2.381 PidNameCalendarCreated	Added UTC time designation.	N	Content updated .
2.390 PidNameCalendarLastModified	Added UTC time designation.	N	Content updated .
2.436 PidNameCreateDateTimeReadOnly	Added UTC time designation.	N	Content updated .
2.489 PidNameLastPrinted	Added UTC time designation.	N	Content updated .
2.490 PidNameLastSaveDateTime	Added UTC time designation.	N	Content updated .
2.505 PidNameOMSScheduleTime	Added UTC time designation.	N	Content updated .
2.553 PidNameXSharingBrowseUrl	Added Description and Defining reference, and deleted Consuming reference, in the PidNameXSharingBrowseUrl section.	N	Content updated .
2.556 PidNameXSharingExendedCaps	Added Description and Defining reference, and deleted Consuming reference, in the PidNameXSharingExendedCaps section.	N	Content updated .
2.558 PidNameXSharingInstanceId	Added Description and Defining reference, and deleted Consuming reference, in the PidNameXSharingInstanceId section.	N	Content updated .
2.564 PidNameXSharingRemotePath	Added Description and Defining reference, and deleted Consuming reference, in the PidNameXSharingRemotePath section.	N	Content updated .
2.602 PidTagAddressBookHomeMessageDatabase	Updated the description of the property.	N	Content updated .
2.609 PidTagAddressBookMessageId	Updated the description of the property.	N	Content updated .

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.633 PidTagAddressBookX509Certificate	Updated the description of the property.	N	Content updated .
2.674 PidTagBirthday	Updated the description of the property.	N	Content updated .
2.689 PidTagChangeKey	Updated the description of the property.	N	Content updated .
2.690 PidTagChangeNumber	Updated the description of the property.	N	Content updated .
2.694 PidTagCodePageId	Added description and defining reference for the property.	N	Content updated .
2.699 PidTagConflictEntryId	Added property description and defining reference. Removed consuming reference.	N	Content updated .
2.700 PidTagConflictItems	Added property description and defining reference. Removed consuming reference.	N	Content updated .
2.701 PidTagContainerClass	Updated the description of the property to include the type value contained in the property.	N	Content updated .
2.729 PidTagDeletedOn	Added UTC time designation.	N	Content updated .
2.734 PidTagDisplayName	Updated the property description.	N	Content updated .
2.737 PidTagDisplayType	Updated the property description to include "integer value".	N	Content updated .
2.738 PidTagDisplayTypeEx	Updated the property description to include "integer value".	N	Content updated .
2.743 PidTagExceptionReplaceTime	Updated the property description to include the UTC time descriptor.	N	Content updated .
2.746 PidTagExpiryNumber	Updated the description to increase usability.	N	Content updated .

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.747 PidTagExpiryTime	Added UTC time designation.	N	Content updated .
2.748 PidTagExpiryUnits	Updated the description to increase usability.	N	Content updated .
2.761 PidTagFreeBusyCountMonths	Updated the description to include the type of value.	N	Content updated .
2.764 PidTagFreeBusyPublishEnd	Updated the property description to include the UTC time descriptor.	N	Content updated .
2.790 PidTagICalendarEndTime	Updated the property description to include the UTC time descriptor.	N	Content updated .
2.791 PidTagICalendarReminderNextTime	Updated the property description to include the UTC time descriptor.	N	Content updated .
2.792 PidTagICalendarStartTime	Updated the property description to include the UTC time descriptor.	N	Content updated .
2.795 PidTagInConflict	Added property description and defining reference. Removed consuming reference.	N	Content updated .
2.823 PidTagLastModifierName	Updated the description to enhance clarity.	N	Content updated .
2.829 PidTagLocalCommitTime	Updated the description with the UTC time descriptor, and link to the ROP reference.	N	Content updated .
2.832 PidTagLocation	Updated the description to enhance clarity.	N	Content updated .
2.833 PidTagMailboxOwnerEntryId	Updated the description to enhance clarity.	N	Content updated .
2.834 PidTagMailboxOwnerName	Updated the description to enhance clarity.	N	Content updated .
2.865 PidTagNormalMessageSize	Added the property description.	N	Content updated .

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.869 PidTagOfflineAddressBookDistinguishedName	Revised the description for clarity.	N	Content updated .
2.876 PidTagOriginalDeliveryTime	Updated the property description to include the UTC time descriptor.	N	Content updated .
2.880 PidTagOriginalEntryId	Added property description and defining reference.	N	Content updated .
2.885 PidTagOriginalSenderEntryId	Revised to enhance clarity.	N	Content updated .
2.895 PidTagOriginalSubmitTime	Updated the property description to include the UTC time descriptor.	N	Content updated .
2.924 PidTagProhibitReceiveQuota	Revised description to increase clarity.	N	Content updated .
2.925 PidTagProhibitSendQuota	Revised description to increase clarity.	N	Content updated .
2.940 PidTagReceivedByEntryId	Revised description to increase clarity.	N	Content updated .
2.967 PidTagReplyRecipientEntries	Revised description to increase clarity.	N	Content updated .
2.971 PidTagReplyTime	Revised description to increase clarity.	N	Content updated .
2.991 PidTagRtfCompressed	Updated the description of the property to denote that it contains text in a compressed RTF format.	N	Content updated .
2.995 PidTagRule ActionType	Revised description to increase clarity.	N	Content updated .
2.1023 PidTagScheduleInfoDisallowOverlappingAppts	Revised description to increase clarity.	N	Content updated .
2.1024 PidTagScheduleInfoDisallowRecurringAppts	Revised description to increase clarity.	N	Content updated .

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.1026 PidTagScheduleInfoFreeBusy	Revised description to increase clarity.	N	Content updated .
2.1027 PidTagScheduleInfoFreeBusyAway	Revised description to increase clarity.	N	Content updated .
2.1028 PidTagScheduleInfoFreeBusyBusy	Revised description to increase clarity.	N	Content updated .
2.1030 PidTagScheduleInfoFreeBusyTentative	Revised description to increase clarity.	N	Content updated .
2.1040 PidTagSearchFolderExpiration	Revised description to increase clarity.	N	Content updated .
2.1042 PidTagSearchFolderLastUsed	Revised description to increase clarity.	N	Content updated .
2.1043 PidTagSearchFolderReCreateInfo	Revised description to increase clarity.	N	Content updated .
2.1062 PidTagSendRichInfo	Revised description to increase clarity.	N	Content updated .
2.1067 PidTagSentRepresentingEntryId	Revised description to increase clarity.	N	Content updated .
2.1070 PidTagSentRepresentingSearchKey	Revised description to increase clarity.	N	Content updated .
2.1082 PidTagStoreSupportMask	Revised description to increase clarity.	N	Content updated .
2.1087 PidTagSubjectPrefix	Removed [MS-OXCMSG] from the list of consuming references.	N	Content updated .
2.1091 PidTagTargetEntryId	Revised description to increase clarity.	N	Content updated .
2.1118 PidTagWeddingAnniversary	Revised description to increase clarity.	N	Content updated .

Section	Tracking number (if applicable) and description	Major chang e (Y or N)	Change type
	Removed the "PidTagChangeNotificationGuid" section from the "Structures" section.	Y	Content removed.
	Removed the following sections from the "Structures" section: "PidTagRtfSyncBodyCrc", "PidTagRtfSyncBodyTag", "PidTagRtfSyncPrefixCount", "PidTagRtfSyncTrailingCount".	Y	Content removed.
	Removed the following sections from the "Structures" section: "PidTagSenderSimpleDisplayName", "PidTagSentRepresentingSimpleDisplayName", ", "PidTagAttributeSystem", "PidTagCreatorSimpleDisplayName".	Y	Content removed.
	Removed the following sections from the Structures section: "PidTagImapCachedMsgsize", "PidTagLastModifierSimpleDisplayName", "PidTagReceivedRepresentingSimpleDisplayName", "PidTagRtfSyncBodyCount".	Y	Content removed.

7 Index

A

[Applicability](#) 37

[Vendor-extensible fields](#) 37
[Versioning](#) 37

C

[Change tracking](#) 410

E

[Examples](#) 407

F

[Fields - vendor-extensible](#) 37

G

[Glossary](#) 25

I

[Implementer - security considerations](#) 408

[Informative references](#) 30

[Introduction](#) 25

L

[Localization](#) 37

N

[Normative references](#) 28

O

[Overview \(synopsis\)](#) 31

P

[Product behavior](#) 409

R

References

[informative](#) 30

[normative](#) 28

[Relationship to protocols and other structures](#) 36

S

[Security - implementer considerations](#) 408

T

[Tracking changes](#) 410

V