

[MS-OXWSGNI]:

Nonindexable Item Web Service Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **License Programs.** To see all of the protocols in scope under a specific license program and the associated patents, visit the [Patent Map](#).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

Support. For questions and support, please contact dochelp@microsoft.com.

Revision Summary

Date	Revision History	Revision Class	Comments
7/16/2012	0.1	New	Released new document.
10/8/2012	1.0	Major	Significantly changed the technical content.
2/11/2013	2.0	Major	Significantly changed the technical content.
7/26/2013	2.0	None	No changes to the meaning, language, or formatting of the technical content.
11/18/2013	2.0	None	No changes to the meaning, language, or formatting of the technical content.
2/10/2014	2.0	None	No changes to the meaning, language, or formatting of the technical content.
4/30/2014	2.0	None	No changes to the meaning, language, or formatting of the technical content.
7/31/2014	2.1	Minor	Clarified the meaning of the technical content.
10/30/2014	2.2	Minor	Clarified the meaning of the technical content.
5/26/2015	3.0	Major	Significantly changed the technical content.
9/14/2015	4.0	Major	Significantly changed the technical content.
6/13/2016	5.0	Major	Significantly changed the technical content.
9/14/2016	5.0	None	No changes to the meaning, language, or formatting of the technical content.
7/24/2018	6.0	Major	Significantly changed the technical content.
10/1/2018	7.0	Major	Significantly changed the technical content.
2/15/2022	7.0	None	No changes to the meaning, language, or formatting of the technical content.
5/20/2025	8.0	Major	Significantly changed the technical content.

Table of Contents

1	Introduction	5
1.1	Glossary	5
1.2	References	6
1.2.1	Normative References	6
1.2.2	Informative References	7
1.3	Overview	7
1.4	Relationship to Other Protocols	7
1.5	Prerequisites/Preconditions	8
1.6	Applicability Statement	8
1.7	Versioning and Capability Negotiation	8
1.8	Vendor-Extensible Fields	8
1.9	Standards Assignments.....	8
2	Messages.....	9
2.1	Transport	9
2.2	Common Message Syntax	9
2.2.1	Namespaces	9
2.2.2	Messages.....	9
2.2.3	Elements	9
2.2.4	Complex Types.....	10
2.2.4.1	NonEmptyArrayOfLegacyDNsType	10
2.2.5	Simple Types	10
2.2.6	Attributes	10
2.2.7	Groups	10
2.2.8	Attribute Groups.....	10
3	Protocol Details	11
3.1	ExchangeServicePortType Server Details.....	11
3.1.1	Abstract Data Model.....	11
3.1.2	Timers	11
3.1.3	Initialization.....	11
3.1.4	Message Processing Events and Sequencing Rules	11
3.1.4.1	GetNonIndexableItemDetails	11
3.1.4.1.1	Messages	12
3.1.4.1.1.1	GetNonIndexableItemDetailsSoapIn	12
3.1.4.1.1.2	GetNonIndexableItemDetailsSoapOut.....	13
3.1.4.1.2	Elements.....	14
3.1.4.1.2.1	GetNonIndexableItemDetails.....	14
3.1.4.1.2.2	GetNonIndexableItemDetailsResponse.....	14
3.1.4.1.3	Complex Types	14
3.1.4.1.3.1	GetNonIndexableItemDetailsType	15
3.1.4.1.3.2	GetNonIndexableItemDetailsResponseMessageType	15
3.1.4.1.3.3	ArrayOfNonIndexableItemDetailsType	16
3.1.4.1.3.4	NonIndexableItemDetailType	16
3.1.4.1.3.5	NonIndexableItemDetailResultType	17
3.1.4.1.4	Simple Types	17
3.1.4.1.4.1	ItemIndexErrorType	17
3.1.4.1.5	Attributes	18
3.1.4.1.6	Groups.....	18
3.1.4.1.7	Attribute Groups.....	18
3.1.4.2	GetNonIndexableItemStatistics.....	18
3.1.4.2.1	Messages	19
3.1.4.2.1.1	GetNonIndexableItemStatisticsSoapIn.....	19
3.1.4.2.1.2	GetNonIndexableItemStatisticsSoapOut.....	20
3.1.4.2.2	Elements.....	21

3.1.4.2.2.1	GetNonIndexableItemStatistics.....	21
3.1.4.2.2.2	GetNonIndexableItemStatisticsResponse	21
3.1.4.2.3	Complex Types	21
3.1.4.2.3.1	GetNonIndexableItemStatisticsType	22
3.1.4.2.3.2	GetNonIndexableItemStatisticsResponseMessageType.....	22
3.1.4.2.3.3	ArrayOfNonIndexableItemStatisticsType	23
3.1.4.2.3.4	NonIndexableItemStatisticType	23
3.1.4.2.4	Simple Types	23
3.1.4.2.5	Attributes	23
3.1.4.2.6	Groups.....	23
3.1.4.2.7	Attribute Groups.....	23
3.1.5	Timer Events.....	24
3.1.6	Other Local Events.....	24
4	Protocol Examples	25
4.1	Getting Details for Nonindexable Items	25
4.2	Getting Statistics for Nonindexable Items	26
5	Security	28
5.1	Security Considerations for Implementers	28
5.2	Index of Security Parameters	28
6	Appendix A: Full WSDL	29
7	Appendix B: Full XML Schema.....	31
7.1	http://schemas.microsoft.com/exchange/services/2006/messages Schema	31
7.2	http://schemas.microsoft.com/exchange/services/2006/types Schema.....	32
8	Appendix C: Product Behavior	34
9	Change Tracking.....	35
10	Index.....	36

1 Introduction

The Nonindexable Item Web Service Protocol enables a client to use a **web service** to retrieve **mailbox** items that cannot be indexed.

Sections 1.5, 1.8, 1.9, 2, and 3 of this specification are normative. All other sections and examples in this specification are informative.

1.1 Glossary

This document uses the following terms:

endpoint: A communication port that is exposed by an application server for a specific shared service and to which messages can be addressed.

Hypertext Transfer Protocol (HTTP): An application-level protocol for distributed, collaborative, hypermedia information systems (text, graphic images, sound, video, and other multimedia files) on the World Wide Web.

Hypertext Transfer Protocol Secure (HTTPS): An extension of HTTP that securely encrypts and decrypts web page requests. In some older protocols, "Hypertext Transfer Protocol over Secure Sockets Layer" is still used (Secure Sockets Layer has been deprecated). For more information, see [\[SSL3\]](#) and [\[RFC5246\]](#).

mailbox: A message store that contains email, calendar items, and other Message objects for a single recipient.

SOAP: A lightweight protocol for exchanging structured information in a decentralized, distributed environment. **SOAP** uses XML technologies to define an extensible messaging framework, which provides a message construct that can be exchanged over a variety of underlying protocols. The framework has been designed to be independent of any particular programming model and other implementation-specific semantics. SOAP 1.2 supersedes SOAP 1.1. See [\[SOAP1.2-1/2003\]](#).

SOAP action: The HTTP request header field used to indicate the intent of the **SOAP** request, using a URI value. See [\[SOAP1.1\]](#) section 6.1.1 for more information.

SOAP body: A container for the payload data being delivered by a SOAP message to its recipient. See [\[SOAP1.2-1/2007\]](#) section 5.3 for more information.

SOAP header: A mechanism for implementing extensions to a SOAP message in a decentralized manner without prior agreement between the communicating parties. See [\[SOAP1.2-1/2007\]](#) section 5.2 for more information.

Uniform Resource Locator (URL): A string of characters in a standardized format that identifies a document or resource on the World Wide Web. The format is as specified in [\[RFC1738\]](#).

web server: A server computer that hosts websites and responds to requests from applications.

web service: A unit of application logic that provides data and services to other applications and can be called by using standard Internet transport protocols such as **HTTP**, Simple Mail Transfer Protocol (SMTP), or File Transfer Protocol (FTP). Web services can perform functions that range from simple requests to complicated business processes.

Web Services Description Language (WSDL): An XML format for describing network services as a set of endpoints that operate on messages that contain either document-oriented or procedure-oriented information. The operations and messages are described abstractly and are bound to a concrete network protocol and message format in order to define an endpoint. Related concrete endpoints are combined into abstract endpoints, which describe a network

service. WSDL is extensible, which allows the description of endpoints and their messages regardless of the message formats or network protocols that are used.

WSDL message: An abstract, typed definition of the data that is communicated during a **WSDL operation** [WSDL]. Also, an element that describes the data being exchanged between web service providers and clients.

WSDL operation: A single action or function of a web service. The execution of a WSDL operation typically requires the exchange of messages between the service requestor and the service provider.

WSDL port type: A named set of logically-related, abstract **Web Services Description Language (WSDL)** operations and messages.

XML namespace: A collection of names that is used to identify elements, types, and attributes in XML documents identified in a URI reference [RFC3986]. A combination of XML namespace and local name allows XML documents to use elements, types, and attributes that have the same names but come from different sources. For more information, see [XMLNS-2ED].

XML namespace prefix: An abbreviated form of an **XML namespace**, as described in [XML].

XML schema: A description of a type of XML document that is typically expressed in terms of constraints on the structure and content of documents of that type, in addition to the basic syntax constraints that are imposed by XML itself. An XML schema provides a view of a document type at a relatively high level of abstraction.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[MS-OXWSCDATA] Microsoft Corporation, "[Common Web Service Data Types](#)".

[MS-OXWSCORE] Microsoft Corporation, "[Core Items Web Service Protocol](#)".

[MS-OXWSEDISC] Microsoft Corporation, "[Electronic Discovery \(eDiscovery\) Web Service Protocol](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <https://www.rfc-editor.org/info/rfc2119>

[RFC2616] Fielding, R., Gettys, J., Mogul, J., et al., "Hypertext Transfer Protocol -- HTTP/1.1", RFC 2616, June 1999, <https://www.rfc-editor.org/info/rfc2616>

[RFC2818] Rescorla, E., "HTTP Over TLS", RFC 2818, May 2000, <https://www.rfc-editor.org/info/rfc2818>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", W3C Note, May 2000, <https://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <https://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[WSIBASIC] Ballinger, K., Ehnebuske, D., Gudgin, M., et al., Eds., "Basic Profile Version 1.0", Final Material, April 2004, <http://www.ws-i.org/Profiles/BasicProfile-1.0-2004-04-16.html>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <https://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1/2] Thompson, H., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures Second Edition", W3C Recommendation, October 2004, <https://www.w3.org/TR/2004/REC-xmlschema-1-20041028/>

[XMLSCHEMA1] Thompson, H., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <https://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2/2] Biron, P., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes Second Edition", W3C Recommendation, October 2004, <https://www.w3.org/TR/2004/REC-xmlschema-2-20041028/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <https://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[MS-OXDSCLI] Microsoft Corporation, "[Autodiscover Publishing and Lookup Protocol](#)".

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

[MS-OXWSADISC] Microsoft Corporation, "[Autodiscover Publishing and Lookup SOAP-Based Web Service Protocol](#)".

1.3 Overview

The Nonindexable Item Web Service Protocol enables the client to use **web services** to retrieve details and statistics for **mailbox** items that could not be indexed.

1.4 Relationship to Other Protocols

A client that implements this protocol can use the Autodiscover Publishing and Lookup SOAP-Based Web Service Protocol, as described in [\[MS-OXWSADISC\]](#), or the Autodiscover Publishing and Lookup Protocol, as described in [\[MS-OXDSCLI\]](#), to identify the target **endpoint** to use for each operation.

This protocol uses **SOAP**, as described in [\[SOAP1.1\]](#), to specify the structure information that is exchanged between the client and the server. This protocol uses the **XML schema**, as described in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), to describe the message content that is sent to and from the server.

This protocol uses SOAP over **HTTP**, as described in [\[RFC2616\]](#), and SOAP over **HTTPS**, as described in [\[RFC2818\]](#), as shown in the following layering diagram.




Figure 1: This protocol in relation to other protocols

This protocol uses the **mailbox** search and mailbox hold information provided by the Electronic Discovery (eDiscovery) Web Service Protocol, as described in [\[MS-OXWSEDISC\]](#).

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

1.5 Prerequisites/Preconditions

The operations that this protocol defines cannot be accessed unless the correct **endpoint** is identified in the **HTTP** web requests that target this protocol. This endpoint **URL** is returned by either the Autodiscover Publishing Lookup SOAP-Based Web Service Protocol, as described in [\[MS-OXWSADISC\]](#), or the Autodiscover Publishing and Lookup Protocol, as described in [\[MS-OXDSCLI\]](#).

1.6 Applicability Statement

This protocol is applicable to environments that use **web services** to implement retrieval of **mailbox** items that could not be indexed. This protocol is applicable to all **SOAP**-based clients, as described in [\[SOAP1.1\]](#).

1.7 Versioning and Capability Negotiation

This document covers versioning issues in the following areas:

- **Supported Transports:** This protocol uses **SOAP**, as described in section [2.1](#).
- **Protocol Versions:** This protocol specifies only one **WSDL port type** version. The **RequestServerVersion** element, as described in [\[MS-OXWSCDATA\]](#) section 2.2.3.9, identifies the WSDL port type version of the request. The **ServerVersionInfo** element, as described in [\[MS-OXWSCDATA\]](#) section 2.2.3.10, identifies the version of the server responding to the request.
- **Security and Authentication Methods:** This protocol relies on the **web server** that is hosting it to perform authentication.
- **Localization:** This protocol uses date/time formats in various types, as described in section [3.1.4](#).
- **Capability Negotiation:** This protocol does not support version negotiation.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

In the following sections, the schema definition might differ from the processing rules imposed by the protocol. The **Web Services Description Language (WSDL)** in this specification provides a base description of the protocol. The schema in this specification provides a base description of the message syntax. The text that specifies the WSDL and schema might specify restrictions that reflect actual protocol behavior. For example, the schema definition might allow for an element to be empty, null, or not present but the behavior of the protocol as specified restricts the same elements to being non-empty, not null, or present.

2.1 Transport

This protocol uses SOAP 1.1, as specified in [\[SOAP1.1\]](#).

This protocol uses **SOAP** over **HTTP**, as specified in [\[RFC2616\]](#). The protocol SHOULD use secure communications by means of **HTTPS**, as defined in [\[RFC2818\]](#).

2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses **XML schema**, as defined in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and **WSDL**, as defined in [\[WSDL\]](#).

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific **XML namespace prefix** for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
soap	http://schemas.xmlsoap.org/wsdl/soap/	[SOAP1.1]
t	http://schemas.microsoft.com/exchange/services/2006/types	
tns	http://schemas.microsoft.com/exchange/services/2006/messages	
wsdl	http://schemas.xmlsoap.org/wsdl/	[WSDL]
wsi	http://ws-i.org/schemas/conformanceClaim/	[WSIBASIC]
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1/2] [XMLSCHEMA2/2]

2.2.2 Messages

This specification does not define any common **WSDL message** definitions.

2.2.3 Elements

This specification does not define any common **XML schema** element definitions.

2.2.4 Complex Types

The following table summarizes the set of common **XML schema** complex type definitions defined by this specification. XML schema complex type definitions that are specific to a particular operation are described with the operation.

Complex type	Description
NonEmptyArrayOfLegacyDNsType	The NonEmptyArrayOfLegacyDNsType complex type specifies an array of legacy distinguished names.

2.2.4.1 NonEmptyArrayOfLegacyDNsType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **NonEmptyArrayOfLegacyDNsType** complex type specifies an array of legacy distinguished names.

```
<xs:complexType name="NonEmptyArrayOfLegacyDNsType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="unbounded" name="LegacyDN" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

LegacyDN: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that represents a single legacy distinguished name.

2.2.5 Simple Types

This specification does not define any common **XML schema** simple type definitions.

2.2.6 Attributes

This specification does not define any common **XML schema** attribute definitions.

2.2.7 Groups

This specification does not define any common **XML schema** group definitions.

2.2.8 Attribute Groups

This specification does not define any common **XML schema** attribute group definitions.

3 Protocol Details

The client side of this protocol is simply a pass-through. That is, no additional timers or other state is required on the client side of this protocol. Calls made by the higher-layer protocol or application are passed directly to the transport, and the results returned by the transport are passed directly back to the higher-layer protocol or application.

In the following sections, the schema definition might be less restrictive than the processing rules imposed by the protocol. The **WSDL** in this specification matches the WSDL that shipped with the product and provides a base description of the schema. The text that introduces the WSDL specifies additional restrictions that reflect actual Microsoft product behavior. For example, the schema definition might allow for an element to be empty, null, or not present but the behavior of the protocol as specified restricts the same elements to being non-empty, not null and present.

3.1 ExchangeServicePortType Server Details

This protocol defines the ExchangeServicePortType port type with two operations, the **GetNonIndexableItemDetails** WSDL operation and the **GetNonIndexableItemStatistics** **WSDL operation**, that enable the retrieval of details and statistics for **mailbox** items that could not be indexed.

3.1.1 Abstract Data Model

None.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Message Processing Events and Sequencing Rules

The following table summarizes the list of operations as defined by this specification.

Operation	Description
GetNonIndexableItemDetails	The GetNonIndexableItemDetails WSDL operation retrieves details for items in a mailbox that could not be indexed.
GetNonIndexableItemStatistics	The GetNonIndexableItemStatistics WSDL operation retrieves statistics for items that could not be indexed.

3.1.4.1 GetNonIndexableItemDetails

The **GetNonIndexableItemDetails** WSDL operation retrieves details for items in a **mailbox** that could not be indexed.

The following is the **WSDL** port type specification of the **GetNonIndexableItemDetails** **WSDL operation**.

```

<wsdl:operation name="GetNonIndexableItemDetails"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetNonIndexableItemDetailsSoapIn"/>
  <wsdl:output message="tns:GetNonIndexableItemDetailsSoapOut"/>
</wsdl:operation>

```

The following is the WSDL binding specification of the **GetNonIndexableItemDetails** WSDL operation.

```

<wsdl:operation name="GetNonIndexableItemDetails"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetNonIndexableItemD
etails" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    <wsdl:input>
      <soap:header message="tns:GetNonIndexableItemDetailsSoapIn" part="RequestVersion"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
        <soap:header message="tns:GetNonIndexableItemDetailsSoapIn" part="ManagementRole"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
          <soap:body use="literal" parts="request"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
            </wsdl:input>
          <wsdl:output>
            <soap:body use="literal" parts="GetNonIndexableItemDetailsResult"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
              <soap:header message="tns:GetNonIndexableItemDetailsSoapOut" part="ServerVersion"
use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
                </wsdl:output>
              </wsdl:operation>

```

The client sends a **GetNonIndexableItemDetailsSoapIn** request **WSDL message**, and the server responds with a **GetNonIndexableItemDetailsSoapOut** response.

3.1.4.1.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message	Description
GetNonIndexableItemDetailsSoapIn	Specifies the request to retrieve details for items that could not be indexed.
GetNonIndexableItemDetailsSoapOut	Specifies the response to the GetNonIndexableItemDetailsSoapIn request.

3.1.4.1.1.1 GetNonIndexableItemDetailsSoapIn

The **GetNonIndexableItemDetailsSoapIn** **WSDL message** specifies the request to retrieve nonindexable item details.

The following is the **GetNonIndexableItemDetailsSoapIn** WSDL message specification.

```

<wsdl:message name="GetNonIndexableItemDetailsSoapIn"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="request" element="tns:GetNonIndexableItemDetails"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
  <wsdl:part name="ManagementRole" element="t:ManagementRole"/>

```

```
</wsdl:message>
```

The **GetNonIndexableItemDetailsSoapIn** WSDL message is the input message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/GetNonIndexableItemDetails>.

The parts of the **GetNonIndexableItemDetailsSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	GetNonIndexableItemDetails	Specifies the SOAP body of the request to retrieve details for items that could not be indexed.
RequestVersion	RequestServerVersion ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a SOAP header that identifies the schema version for the GetNonIndexableItemDetails WSDL operation request.
ManagementRole	ManagementRole ([MS-OXWSCDATA] section 2.2.3.7)	Specifies a SOAP header that identifies a user or application role.

3.1.4.1.1.2 GetNonIndexableItemDetailsSoapOut

The **GetNonIndexableItemDetailsSoapOut WSDL message** specifies the response to the **GetNonIndexableItemDetailsSoapIn** request.

The following is the **GetNonIndexableItemDetailsSoapOut** WSDL message specification.

```
<wsdl:message name="GetNonIndexableItemDetailsSoapOut"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="GetNonIndexableItemDetailsResult"
element="tns:GetNonIndexableItemDetailsResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **GetNonIndexableItemDetailsSoapOut** WSDL message is the output message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/GetNonIndexableItemDetails>.

The parts of the **GetNonIndexableItemDetailsSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
GetNonIndexableItemDetailsResult	GetNonIndexableItemDetailsResponse	Specifies the SOAP body of the response that contains the requested information.
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section 2.2.3.10)	Specifies a SOAP header that identifies the server version for the response.

A successful **GetNonIndexableItemDetails** WSDL operation request returns a **GetNonIndexableItemDetailsResponse** element with the **ResponseClass** attribute set to "Success". The **ResponseCode** element of the **GetNonIndexableItemDetailsResponse** element is set to "NoError".

If the **GetNonIndexableItemDetails** WSDL operation request is not successful, it returns a **GetNonIndexableItemDetailsResponse** element with the **ResponseClass** attribute set to "Error". The **ResponseCode** element of the **GetNonIndexableItemDetailsResponse** element is set to one of the common errors defined in [MS-OXWSCDATA] section 2.2.5.24.

3.1.4.1.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element	Description
GetNonIndexableItemDetails	The input data for the GetNonIndexableItemDetails WSDL operation .
GetNonIndexableItemDetailsResponse	The result data for the GetNonIndexableItemDetails WSDL operation .

3.1.4.1.2.1 GetNonIndexableItemDetails

The **GetNonIndexableItemDetails** element specifies the input data for the **GetNonIndexableItemDetails WSDL operation**.

```
<xs:element name="GetNonIndexableItemDetails" type="tns:GetNonIndexableItemDetailsType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.1.2.2 GetNonIndexableItemDetailsResponse

The **GetNonIndexableItemDetailsResponse** element specifies the result data for the **GetNonIndexableItemDetails WSDL operation**.

```
<xs:element name="GetNonIndexableItemDetailsResponse"
type="tns:GetNonIndexableItemDetailsResponseMessageType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.1.3 Complex Types

The following table summarizes the **XML schema** complex type definitions that are specific to this operation.

Complex type	Description
ArrayOfNonIndexableItemDetailsType	Specifies an array of NonIndexableItemDetails elements.
GetNonIndexableItemDetailsResponseMessageType	Specifies the response message for a GetNonIndexableItemDetails WSDL operation .

Complex type	Description
GetNonIndexableItemDetailsType	Specifies a request to retrieve details for items in a mailbox that could not be indexed.
NonIndexableItemDetailResultType	Specifies the results of the GetNonIndexableItemDetails WSDL operation.
NonIndexableItemDetailType	Specifies a detail for an item that could not be indexed.

3.1.4.1.3.1 GetNonIndexableItemDetailsType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetNonIndexableItemDetailsType** complex type specifies a request to retrieve details for items in a **mailbox** that could not be indexed. This type extends the **BaseRequestType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.17.

```
<xs:complexType name="GetNonIndexableItemDetailsType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" name="Mailboxes" type="t:NonEmptyArrayOfLegacyDNsType"/>
        <xs:element minOccurs="0" name="PageSize" type="xs:int"/>
        <xs:element minOccurs="0" name="PageItemReference" type="xs:string"/>
        <xs:element minOccurs="0" name="PageDirection" type="t:SearchPageDirectionType"/>
        <xs:element minOccurs="0" name="SearchArchiveOnly" type="xs:boolean"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Mailboxes: An element of type **NonEmptyArrayOfLegacyDNsType**, as defined in section [2.2.4.1](#), that represents a list of mailboxes in the format of legacy distinguished names.

PageSize: An element of type **int**, as defined in [\[XMLSCHEMA2\]](#) section 3.3.17, that represents the number of items to be returned in a single page for a search result.

PageItemReference: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that represents the item reference.

PageDirection: An element of type **SearchPageDirectionType**, as defined in [\[MS-OXWSEDISC\]](#) section 3.1.4.4.4.4, that represents the search direction, either previous or next.

SearchArchiveOnly: An element of type **boolean**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.2, that specifies whether only the archive is searched.

3.1.4.1.3.2 GetNonIndexableItemDetailsResponseMessageType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetNonIndexableItemDetailsResponseMessageType** complex type specifies the response message for a **GetNonIndexableItemDetails** **WSDL operation**.

This type extends the **ResponseMessageType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.65.

```

<xs:complexType name="GetNonIndexableItemDetailsResponseType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:ResponseType">
      <xs:sequence>
        <xs:element minOccurs="0" name="NonIndexableItemDetailsResult"
type="t:NonIndexableItemDetailResultType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

NonIndexableItemDetailsResult: An element of type **NonIndexableItemDetailResultType**, as defined in section [3.1.4.1.3.5](#), that specifies the results of the **GetNonIndexableItemDetails** WSDL operation.

3.1.4.1.3.3 ArrayOfNonIndexableItemDetailsType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ArrayOfNonIndexableItemDetailsType** complex type specifies an array of **NonIndexableItemDetailType** complex types, as specified in section [3.1.4.1.3.4](#).

```

<xs:complexType name="ArrayOfNonIndexableItemDetailsType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="NonIndexableItemDetail"
type="t:NonIndexableItemDetailType"/>
  </xs:sequence>
</xs:complexType>

```

NonIndexableItemDetail: An element of type **NonIndexableItemDetailType** that represents a single detail for an item that could not be indexed.

3.1.4.1.3.4 NonIndexableItemDetailType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **NonIndexableItemDetailType** complex type specifies a detail for an item that could not be indexed.

```

<xs:complexType name="NonIndexableItemDetailType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="ItemId" type="t:ItemIdType"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ErrorCode" type="t:ItemIndexErrorType"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ErrorDescription" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="IsPartiallyIndexed" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="IsPermanentFailure" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="SortValue" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="AttemptCount" type="xs:int"/>
    <xs:element minOccurs="0" maxOccurs="1" name="LastAttemptTime" type="xs:dateTime"/>
    <xs:element minOccurs="0" maxOccurs="1" name="AdditionalInfo" type="xs:string"/>
  </xs:sequence>
</xs:complexType>

```

ItemId: An element of type **ItemIdType**, as defined in [\[MS-OXWSCORE\]](#) section 2.2.4.25, that represents the identifier of the item that could not be indexed.

ErrorCode: An element of type **ItemIndexErrorType**, as defined in section [3.1.4.1.4.1](#). This element is for internal use only.

ErrorDescription: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that represents the description of the error returned.

IsPartiallyIndexed: An element of type **boolean**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.2, that indicates whether the item is partially indexed.

IsPermanentFailure: An element of type **boolean** that indicates whether a previous attempt to index the item was unsuccessful.

SortValue: An element of type **string** that contains a value used for sorting.

AttemptCount: An element of type **int**, as defined in [\[XMLSCHEMA2\]](#) section 3.3.17, that represents the number of attempts that have been made to index the item.

LastAttemptTime: An element of type **dateTime**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.7, that represents a time and date at which the last attempt to index the item was made.

AdditionalInfo: An element of type **string** that represents additional information.

3.1.4.1.3.5 NonIndexableItemDetailResultType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **NonIndexableItemDetailResultType** complex type specifies the results of the **GetNonIndexableItemDetails** **WSDL operation**.

```
<xs:complexType name="NonIndexableItemDetailResultType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" name="Items" type="t:ArrayOfNonIndexableItemDetailsType"/>
    <xs:element minOccurs="0" name="FailedMailboxes"
type="t:ArrayOfFailedSearchMailboxesType"/>
  </xs:sequence>
</xs:complexType>
```

Items: An element of type **ArrayOfNonIndexableItemDetailsType**, as defined in section [3.1.4.1.3.3](#), that contains an array of details for items that could not be indexed.

FailedMailboxes: An element of type **ArrayOfFailedSearchMailboxesType**, as defined in [\[MS-OXWSEDISC\]](#) section 2.2.4.1, that contains an array of **mailboxes** that failed the search.

3.1.4.1.4 Simple Types

The following table summarizes the **XML schema** simple type definitions that are specific to this operation.

Simple type	Description
ItemIndexErrorType	This type is for internal use only.

3.1.4.1.4.1 ItemIndexErrorType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/types>

The **ItemIndexErrorType** simple type is for internal use only.

```
<xs:simpleType name="ItemIndexErrorType" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="GenericError"/>
    <xs:enumeration value="Timeout"/>
    <xs:enumeration value="StaleEvent"/>
    <xs:enumeration value="MailboxOffline"/>
    <xs:enumeration value="AttachmentLimitReached"/>
    <xs:enumeration value="MarsWriterTruncation"/>
    <xs:enumeration value="DocumentParserFailure"/>
  </xs:restriction>
</xs:simpleType>
```

The following table specifies the allowable values for the **ItemIndexErrorType** simple type.

Value	Meaning
None	This value is for internal use only.
GenericError	This value is for internal use only.
Timeout	This value is for internal use only.
StaleEvent	This value is for internal use only.
MailboxOffline	This value is for internal use only.
AttachmentLimitReached	This value is for internal use only.
MarsWriterTruncation	This value is for internal use only.
DocumentParserFailure	This value is for internal use only.

3.1.4.1.5 Attributes

None.

3.1.4.1.6 Groups

None.

3.1.4.1.7 Attribute Groups

None.

3.1.4.2 GetNonIndexableItemStatistics

The **GetNonIndexableItemStatistics** WSDL operation retrieves statistics for items that could not be indexed.

The following is the **WSDL** port type specification of the **GetNonIndexableItemStatistics WSDL operation**.

```
<wsdl:operation name="GetNonIndexableItemStatistics"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:input message="tns:GetNonIndexableItemStatisticsSoapIn"/>
```

```

    <wsdl:output message="tns:GetNonIndexableItemStatisticsSoapOut"/>
  </wsdl:operation>

```

The following is the WSDL binding specification of the **GetNonIndexableItemStatistics** WSDL operation.

```

<wsdl:operation name="GetNonIndexableItemStatistics"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <soap:operation
    soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetNonIndexableItemS
    tatistics" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    <wsdl:input>
      <soap:header message="tns:GetNonIndexableItemStatisticsSoapIn" part="RequestVersion"
        use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
      <soap:header message="tns:GetNonIndexableItemStatisticsSoapIn" part="ManagementRole"
        use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
      <soap:body use="literal" parts="request"
        xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal" parts="GetNonIndexableItemStatisticsResult"
        xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
      <soap:header message="tns:GetNonIndexableItemStatisticsSoapOut" part="ServerVersion"
        use="literal" xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/">
    </wsdl:output>
  </wsdl:operation>

```

The client sends a **GetNonIndexableItemStatisticsSoapIn** request **WSDL message**, and the server responds with a **GetNonIndexableItemStatisticsSoapOut** response.

3.1.4.2.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message	Description
GetNonIndexableItemStatisticsSoapIn	Specifies the request to retrieve statistics for items that could not be indexed.
GetNonIndexableItemStatisticsSoapOut	Specifies the response to the GetNonIndexableItemStatisticsSoapIn request.

3.1.4.2.1.1 GetNonIndexableItemStatisticsSoapIn

The **GetNonIndexableItemStatisticsSoapIn** **WSDL message** specifies the request to retrieve statistics for items that could not be indexed.

The following is the **GetNonIndexableItemStatisticsSoapIn** WSDL message specification.

```

<wsdl:message name="GetNonIndexableItemStatisticsSoapIn"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="request" element="tns:GetNonIndexableItemStatistics"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
  <wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>

```

The **GetNonIndexableItemStatisticsSoapIn** WSDL message is the input message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/GetNonIndexableItemStatistics>.

The parts of the **GetNonIndexableItemStatisticsSoapIn** WSDL message are described in the following table.

Part name	Element/type	Description
request	GetNonIndexableItemStatistics	Specifies the SOAP body of the request to retrieve statistics.
RequestVersion	RequestServerVersion ([MS-OXWSCDATA] section 2.2.3.9)	Specifies a SOAP header that identifies the schema version for the GetNonIndexableItemStatistics WSDL operation request.
ManagementRole	ManagementRole ([MS-OXWSCDATA] section 2.2.3.7)	Specifies a SOAP header that identifies a user or application role.

3.1.4.2.1.2 GetNonIndexableItemStatisticsSoapOut

The **GetNonIndexableItemStatisticsSoapOut** **WSDL message** specifies the response to the **GetNonIndexableItemStatisticsSoapIn** request.

The following is the **GetNonIndexableItemStatisticsSoapOut** WSDL message specification.

```
<wsdl:message name="GetNonIndexableItemStatisticsSoapOut"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:part name="GetNonIndexableItemStatisticsResult"
element="tns:GetNonIndexableItemStatisticsResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
```

The **GetNonIndexableItemStatisticsSoapOut** WSDL message is the output message for the **SOAP action** <http://schemas.microsoft.com/exchange/services/2006/messages/GetNonIndexableItemStatistics>.

The parts of the **GetNonIndexableItemStatisticsSoapOut** WSDL message are described in the following table.

Part name	Element/type	Description
GetNonIndexableItemStatisticsResult	GetNonIndexableItemStatisticsResponse	Specifies the SOAP body of the response that contains the requested information.
ServerVersion	ServerVersionInfo ([MS-OXWSCDATA] section 2.2.3.10)	Specifies a SOAP header that identifies the server version for the response.

A successful **GetNonIndexableItemStatistics** WSDL operation request returns a **GetNonIndexableItemStatisticsResponse** element with the **ResponseClass** attribute set to "Success". The **ResponseCode** element of the **GetNonIndexableItemStatisticsResponse** element is set to "NoError".

If the **GetNonIndexableItemStatistics** WSDL operation request is not successful, it returns a **GetNonIndexableItemStatisticsResponse** element with the **ResponseClass** attribute set to "Error". The **ResponseCode** element of the **GetNonIndexableItemStatisticsResponse** element is set to one of the common errors defined in [MS-OXWSCDATA] section 2.2.5.24.

3.1.4.2.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element	Description
GetNonIndexableItemStatistics	The input data for the GetNonIndexableItemStatistics WSDL operation .
GetNonIndexableItemStatisticsResponse	The result data for the GetNonIndexableItemStatistics WSDL operation .

3.1.4.2.2.1 GetNonIndexableItemStatistics

The **GetNonIndexableItemStatistics** element specifies the input data for the **GetNonIndexableItemStatistics WSDL operation**.

```
<xs:element name="GetNonIndexableItemStatistics" type="tns:GetNonIndexableItemStatisticsType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.2.2.2 GetNonIndexableItemStatisticsResponse

The **GetNonIndexableItemStatisticsResponse** element specifies the result data for the **GetNonIndexableItemStatistics WSDL operation**.

```
<xs:element name="GetNonIndexableItemStatisticsResponse"
type="tns:GetNonIndexableItemStatisticsResponseMessageType"
xmlns:xs="http://www.w3.org/2001/XMLSchema"/>
```

3.1.4.2.3 Complex Types

The following table summarizes the **XML schema** complex type definitions that are specific to this operation.

Complex type	Description
ArrayOfNonIndexableItemStatisticsType	Specifies an array of statistics for items that could not be indexed.
GetNonIndexableItemStatisticsResponseMessageType	Specifies the response message for a GetNonIndexableItemStatistics WSDL operation .
GetNonIndexableItemStatisticsType	Specifies a request to retrieve statistics for items

Complex type	Description
	that could not be indexed.
NonIndexableItemStatisticType	Specifies a statistic for an item that could not be indexed.

3.1.4.2.3.1 GetNonIndexableItemStatisticsType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetNonIndexableItemStatisticsType** complex type specifies a request to retrieve statistics for items that could not be indexed. This type extends the **BaseRequestType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.17.

```
<xs:complexType name="GetNonIndexableItemStatisticsType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:BaseRequestType">
      <xs:sequence>
        <xs:element minOccurs="1" name="Mailboxes" type="t:NonEmptyArrayOfLegacyDNsType"/>
        <xs:element minOccurs="0" name="SearchArchiveOnly" type="xs:boolean"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

Mailboxes: An element of type **NonEmptyArrayOfLegacyDNsType**, as defined in section [2.2.4.1](#), that specifies the **mailboxes** that were not indexed although items were requested.

SearchArchiveOnly: An element of type **boolean**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.2, that specifies whether only the archive is searched.

3.1.4.2.3.2 GetNonIndexableItemStatisticsResponseMessageType

Namespace: <http://schemas.microsoft.com/exchange/services/2006/messages>

The **GetNonIndexableItemStatisticsResponseMessageType** complex type specifies the response message for a **GetNonIndexableItemStatistics WSDL operation**. This type extends the **ResponseMessageType** complex type, as specified in [\[MS-OXWSCDATA\]](#) section 2.2.4.65.

```
<xs:complexType name="GetNonIndexableItemStatisticsResponseMessageType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:ResponseMessageType">
      <xs:sequence>
        <xs:element minOccurs="0" maxOccurs="1" name="NonIndexableItemStatistics"
type="t:ArrayOfNonIndexableItemStatisticsType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

NonIndexableItemStatistics: An element of type **ArrayOfNonIndexableItemStatisticsType**, as defined in section [3.1.4.2.3.3](#), that represents an array of statistics for items that could not be indexed.

3.1.4.2.3.3 ArrayOfNonIndexableItemStatisticsType

Namespace: http://schemas.microsoft.com/exchange/services/2006/types

The **ArrayOfNonIndexableItemStatisticsType** complex type specifies an array of statistics for items that could not be indexed.

```
<xs:complexType name="ArrayOfNonIndexableItemStatisticsType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="0" maxOccurs="unbounded" name="NonIndexableItemStatistic"
type="t:NonIndexableItemStatisticType"/>
  </xs:sequence>
</xs:complexType>
```

NonIndexableItemStatistic: An element of type **NonIndexableItemStatisticType**, as defined in section [3.1.4.2.3.4](#), that represents a single statistic for an item that could not be indexed.

3.1.4.2.3.4 NonIndexableItemStatisticType

Namespace: http://schemas.microsoft.com/exchange/services/2006/types

The **NonIndexableItemStatisticType** complex type specifies a statistic for an item that could not be indexed.

```
<xs:complexType name="NonIndexableItemStatisticType"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Mailbox" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ItemCount" type="xs:long"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ErrorMessage" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

Mailbox: An element of type **string**, as defined in [\[XMLSCHEMA2\]](#) section 3.2.1, that represents the **mailbox** on which indexing failed.

ItemCount: An element of type **long**, as defined in [\[XMLSCHEMA2\]](#) section 3.3.16, that represents the number of items that could not be indexed.

ErrorMessage: An element of type **string** that contains the error message.

3.1.4.2.4 Simple Types

None.

3.1.4.2.5 Attributes

None.

3.1.4.2.6 Groups

None.

3.1.4.2.7 Attribute Groups

None.

3.1.5 Timer Events

None.

3.1.6 Other Local Events

None.

4 Protocol Examples

4.1 Getting Details for Nonindexable Items

This example of the **GetNonIndexableItemDetails** operation, as described in section [3.1.4.1](#), shows how the client retrieves from the server the details for items that could not be indexed.

```
<?xml version="1.0" encoding="UTF-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
  <soap:Header>
    <t:RequestServerVersion Version="Exchange2013" />
  </soap:Header>
  <soap:Body >
    <m:GetNonIndexableItemDetails>
      <m:Mailboxes>
        <t:LegacyDN>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=35181a742f0e47e392c8201a60d13ecf-Steve</t:LegacyDN>
      </m:Mailboxes>
      <m:SearchArchiveOnly>>false</m:SearchArchiveOnly>
    </m:GetNonIndexableItemDetails>
  </soap:Body>
</soap:Envelope>
```

The server sends the following successful response to the client. The response shows that the document had a parsing error.

```
<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Header>
    <h:ServerVersionInfo MajorVersion="15"
      MinorVersion="0"
      MajorBuildNumber="526"
      MinorBuildNumber="0"
      Version="Exchange2013"
      xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns:xsd="http://www.w3.org/2001/XMLSchema"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <GetNonIndexableItemDetailsResponse ResponseClass="Success"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
      <ResponseCode>NoError</ResponseCode>
      <NonIndexableItemDetailsResult>
        <Items xmlns="http://schemas.microsoft.com/exchange/services/2006/types">
          <NonIndexableItemDetail>
            <ItemId
              Id="AQMkAGVmnDAyODMwLTNkMzMALTRhMGQtYTRlOS1kODU3NjkwMAE2MGQARgAAA2L1bNf8ooZNtO4guk3auRYHALkzP
vMoJY1FjWrkRuQQcK0AAAMLAAAATM+8ygljUWNauRG5BBwrQAAAY2fUAAAAA==" ChangeKey="CQAAAA==" />
            <ErrorCode>DocumentParserFailure</ErrorCode>
            <ErrorDescription>The document parser encountered a processing
error.</ErrorDescription>
            <IsPartiallyIndexed>>false</IsPartiallyIndexed>
            <IsPermanentFailure>>true</IsPermanentFailure>
            <SortValue>502511175756</SortValue>
            <AttemptCount>0</AttemptCount>
            <LastAttemptTime>2012-11-15T01:56:11Z</LastAttemptTime>
          </NonIndexableItemDetail>
        </Items>
      </NonIndexableItemDetailsResult>
    </GetNonIndexableItemDetailsResponse>
  </s:Body>
</s:Envelope>
```

```

        <AdditionalInfo> 301002 Error parsing document
'exchange://localhost/Attachment/d987b1f4-9aa7-42b3-aa8c-9515a35dfala/1f3047d4-c287-41e4-
910c-feb70c1a59f0/ef402830-3d33-4a0d-a4e9-d8576900060d/85b83861-0026-418f-8464-
be2036696333/502511175756.0/binaryfile.abc'. Document has an undetectable format and will not
be parsed.</AdditionalInfo>
    </NonIndexableItemDetail>
  </Items>
</NonIndexableItemDetailsResult>
</GetNonIndexableItemDetailsResponse>
</s:Body>
</s:Envelope>

```

4.2 Getting Statistics for Nonindexable Items

This example of the **GetNonIndexableItemStatistics** operation, as described in section [3.1.4.2](#), shows how the client retrieves the statistics for an item that could not be indexed from the server.

```

<?xml version="1.0" encoding="UTF-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  xmlns:m="http://schemas.microsoft.com/exchange/services/2006/messages">
  <soap:Header>
    <t:RequestServerVersion Version="Exchange2013" />
  </soap:Header>
  <soap:Body >
    <m:GetNonIndexableItemStatistics>
      <m:Mailboxes>
        <t:LegacyDN>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=35181a742f0e47e392c8201a60d13ecf-Steve</t:LegacyDN>
      </m:Mailboxes>
      <m:SearchArchiveOnly>>false</m:SearchArchiveOnly>
    </m:GetNonIndexableItemStatistics>
  </soap:Body>
</soap:Envelope>

```

The server sends the following successful results of the request to the client. The response shows that two items in the mailbox could not be indexed.

```

<?xml version="1.0" encoding="utf-8"?>
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/">
  <s:Header>
    <h:ServerVersionInfo MajorVersion="15"
      MinorVersion="0"
      MajorBuildNumber="526"
      MinorBuildNumber="0"
      Version="Exchange2013"
      xmlns:h="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/types"
      xmlns:xsd="http://www.w3.org/2001/XMLSchema"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"/>
  </s:Header>
  <s:Body xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xmlns:xsd="http://www.w3.org/2001/XMLSchema">
    <GetNonIndexableItemStatisticsResponse ResponseClass="Success"
      xmlns="http://schemas.microsoft.com/exchange/services/2006/messages">
      <ResponseCode>NoError</ResponseCode>
      <NonIndexableItemStatistics>
        <NonIndexableItemStatistic
          xmlns="http://schemas.microsoft.com/exchange/services/2006/types">
          <Mailbox>/o=First Organization/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=35181a742f0e47e392c8201a60d13ecf-Steve</Mailbox>
          <ItemCount>2</ItemCount>
        </NonIndexableItemStatistic>
      </NonIndexableItemStatistics>
    </GetNonIndexableItemStatisticsResponse>
  </s:Body>
</s:Envelope>

```

```
</NonIndexableItemStatistics>  
</GetNonIndexableItemStatisticsResponse>  
</s:Body>  
</s:Envelope>
```

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

6 Appendix A: Full WSDL

For ease of implementation, the full WSDL is provided in this appendix.

```
<?xml version="1.0" encoding="UTF-8"?>
<wsdl:definitions xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:types>
    <xs:schema elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
version="Exchange2016" id="messages" xmlns:xs="http://www.w3.org/2001/XMLSchema">
      <xs:include schemaLocation="MS-OXWSGNI-messages.xsd"/>
    </xs:schema>
  </wsdl:types>
  <wsdl:portType name="ExchangeServicePortType">
    <wsdl:operation name="GetNonIndexableItemStatistics">
      <wsdl:input message="tns:GetNonIndexableItemStatisticsSoapIn"/>
      <wsdl:output message="tns:GetNonIndexableItemStatisticsSoapOut"/>
    </wsdl:operation>
    <wsdl:operation name="GetNonIndexableItemDetails">
      <wsdl:input message="tns:GetNonIndexableItemDetailsSoapIn"/>
      <wsdl:output message="tns:GetNonIndexableItemDetailsSoapOut"/>
    </wsdl:operation>
  </wsdl:portType>
  <wsdl:binding name="ExchangeServiceBinding" type="tns:ExchangeServicePortType">
    <wsdl:documentation>
      <wsi:Claim conformsTo="http://ws-i.org/profiles/basic/1.0" xmlns:wsi="http://ws-
i.org/schemas/conformanceClaim"/>
    </wsdl:documentation>
    <soap:binding transport="http://schemas.xmlsoap.org/soap/http"/>
    <wsdl:operation name="GetNonIndexableItemStatistics">
      <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetNonIndexableItemS
tatistics"/>
      <wsdl:input>
        <soap:header message="tns:GetNonIndexableItemStatisticsSoapIn" part="RequestVersion"
use="literal"/>
        <soap:header message="tns:GetNonIndexableItemStatisticsSoapIn" part="ManagementRole"
use="literal"/>
        <soap:body use="literal" parts="request"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal" parts="GetNonIndexableItemStatisticsResult"/>
        <soap:header message="tns:GetNonIndexableItemStatisticsSoapOut" part="ServerVersion"
use="literal"/>
      </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="GetNonIndexableItemDetails">
      <soap:operation
soapAction="http://schemas.microsoft.com/exchange/services/2006/messages/GetNonIndexableItemD
etails"/>
      <wsdl:input>
        <soap:header message="tns:GetNonIndexableItemDetailsSoapIn" part="RequestVersion"
use="literal"/>
        <soap:header message="tns:GetNonIndexableItemDetailsSoapIn" part="ManagementRole"
use="literal"/>
        <soap:body use="literal" parts="request"/>
      </wsdl:input>
      <wsdl:output>
        <soap:body use="literal" parts="GetNonIndexableItemDetailsResult"/>
        <soap:header message="tns:GetNonIndexableItemDetailsSoapOut" part="ServerVersion"
use="literal"/>
      </wsdl:output>
    </wsdl:operation>
  </wsdl:binding>

```

```
</wsdl:binding>
<wsdl:message name="GetNonIndexableItemDetailsSoapIn">
  <wsdl:part name="request" element="tns:GetNonIndexableItemDetails"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
  <wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>
<wsdl:message name="GetNonIndexableItemDetailsSoapOut">
  <wsdl:part name="GetNonIndexableItemDetailsResult"
element="tns:GetNonIndexableItemDetailsResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
<wsdl:message name="GetNonIndexableItemStatisticsSoapIn">
  <wsdl:part name="request" element="tns:GetNonIndexableItemStatistics"/>
  <wsdl:part name="RequestVersion" element="t:RequestServerVersion"/>
  <wsdl:part name="ManagementRole" element="t:ManagementRole"/>
</wsdl:message>
<wsdl:message name="GetNonIndexableItemStatisticsSoapOut">
  <wsdl:part name="GetNonIndexableItemStatisticsResult"
element="tns:GetNonIndexableItemStatisticsResponse"/>
  <wsdl:part name="ServerVersion" element="t:ServerVersionInfo"/>
</wsdl:message>
</wsdl:definitions>
```

7 Appendix B: Full XML Schema

Schema name	Prefix	Section
http://schemas.microsoft.com/exchange/services/2006/types	t	7.2
http://schemas.microsoft.com/exchange/services/2006/messages	tns	7.1

For ease of implementation, the following sections provide the full XML schema for this protocol.

7.1 [http://schemas.microsoft.com/exchange/services/2006/messages](#) Schema

This section contains the MS-OXWSGNI-messages.xsd and information about additional files that this schema file requires to operate correctly.

MS-OXWSGNI-messages.xsd includes the files listed in the following table. To operate correctly, these files have to be present in the folder that contains the **WSDL**, types schema, and messages schema files for this protocol.

File name	Defining specification/section
MS-OXWSCDATA-messages.xsd	[MS-OXWSCDATA] section 7.1
MS-OXWSGNI-types.xsd	7.2

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:tns="http://schemas.microsoft.com/exchange/services/2006/messages"
  xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
  elementFormDefault="qualified"
  targetNamespace="http://schemas.microsoft.com/exchange/services/2006/messages"
  version="Exchange2016" id="messages" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import schemaLocation="MS-OXWSGNI-types.xsd"
    namespace="http://schemas.microsoft.com/exchange/services/2006/types"/>
  <xs:include schemaLocation="MS-OXWSCDATA-messages.xsd"/>
  <xs:complexType name="GetNonIndexableItemStatisticsType">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:BaseRequestType">
        <xs:sequence>
          <xs:element minOccurs="1" name="Mailboxes" type="t:NonEmptyArrayOfLegacyDNsType"/>
          <xs:element minOccurs="0" name="SearchArchiveOnly" type="xs:boolean"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:element name="GetNonIndexableItemStatistics"
    type="tns:GetNonIndexableItemStatisticsType"/>
  <xs:complexType name="GetNonIndexableItemStatisticsResponseMessageType">
    <xs:complexContent mixed="false">
      <xs:extension base="tns:ResponseMessageType">
        <xs:sequence>
          <xs:element minOccurs="0" maxOccurs="1" name="NonIndexableItemStatistics"
            type="t:ArrayOfNonIndexableItemStatisticsType"/>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:element name="GetNonIndexableItemStatisticsResponse"
    type="tns:GetNonIndexableItemStatisticsResponseMessageType"/>
  <xs:complexType name="GetNonIndexableItemDetailsType">
```

```

<xs:complexContent mixed="false">
  <xs:extension base="tns:BaseRequestType">
    <xs:sequence>
      <xs:element minOccurs="1" name="Mailboxes" type="t:NonEmptyArrayOfLegacyDNsType"/>
      <xs:element minOccurs="0" name="PageSize" type="xs:int"/>
      <xs:element minOccurs="0" name="PageItemReference" type="xs:string"/>
      <xs:element minOccurs="0" name="PageDirection" type="t:SearchPageDirectionType"/>
      <xs:element minOccurs="0" name="SearchArchiveOnly" type="xs:boolean"/>
    </xs:sequence>
  </xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:element name="GetNonIndexableItemDetails" type="tns:GetNonIndexableItemDetailsType"/>
<xs:complexType name="GetNonIndexableItemDetailsResponseMessageType">
  <xs:complexContent mixed="false">
    <xs:extension base="tns:ResponseMessageType">
      <xs:sequence>
        <xs:element minOccurs="0" name="NonIndexableItemDetailsResult"
type="t:NonIndexableItemDetailResultType"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:element name="GetNonIndexableItemDetailsResponse"
type="tns:GetNonIndexableItemDetailsResponseMessageType"/>
</xs:schema>

```

7.2 <http://schemas.microsoft.com/exchange/services/2006/types> Schema

This section contains the MS-OXWSGNI-types.xsd and information about additional files that this schema file requires to operate correctly.

MS-OXWSGNI-types.xsd includes the files listed in the following table. To operate correctly, these files have to be present in the folder that contains the **WSDL**, types schema, and messages schema for this protocol.

File name	Defining specification/section
MS-OXWSCORE-types.xsd	[MS-OXWSCORE] section 7.2
MS-OXWSEDISC-types.xsd	[MS-OXWSEDISC] section 7.2

```

<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:t="http://schemas.microsoft.com/exchange/services/2006/types"
elementFormDefault="qualified"
targetNamespace="http://schemas.microsoft.com/exchange/services/2006/types"
version="Exchange2016" id="types" xmlns:xs="http://www.w3.org/2001/XMLSchema">
  <xs:import namespace="http://www.w3.org/XML/1998/namespace"/>
  <xs:include schemaLocation="MS-OXWSCORE-types.xsd"/>
  <xs:include schemaLocation="MS-OXWSEDISC-types.xsd"/>
  <xs:complexType name="ArrayOfNonIndexableItemDetailsType">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="NonIndexableItemDetail"
type="t:NonIndexableItemDetailType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="ArrayOfNonIndexableItemStatisticsType">
    <xs:sequence>
      <xs:element minOccurs="0" maxOccurs="unbounded" name="NonIndexableItemStatistic"
type="t:NonIndexableItemStatisticType"/>
    </xs:sequence>
  </xs:complexType>

```

```

<xs:simpleType name="ItemIndexErrorType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="GenericError"/>
    <xs:enumeration value="Timeout"/>
    <xs:enumeration value="StaleEvent"/>
    <xs:enumeration value="MailboxOffline"/>
    <xs:enumeration value="AttachmentLimitReached"/>
    <xs:enumeration value="MarsWriterTruncation"/>
    <xs:enumeration value="DocumentParserFailure"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="NonEmptyArrayOfLegacyDNsType">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="unbounded" name="LegacyDN" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="NonIndexableItemStatisticType">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="Mailbox" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ItemCount" type="xs:long"/>
    <xs:element minOccurs="0" maxOccurs="1" name="ErrorMessage" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="NonIndexableItemDetailType">
  <xs:sequence>
    <xs:element minOccurs="1" maxOccurs="1" name="ItemId" type="t:ItemIdType"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ErrorCode" type="t:ItemIndexErrorType"/>
    <xs:element minOccurs="1" maxOccurs="1" name="ErrorDescription" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="IsPartiallyIndexed" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="IsPermanentFailure" type="xs:boolean"/>
    <xs:element minOccurs="1" maxOccurs="1" name="SortValue" type="xs:string"/>
    <xs:element minOccurs="1" maxOccurs="1" name="AttemptCount" type="xs:int"/>
    <xs:element minOccurs="0" maxOccurs="1" name="LastAttemptTime" type="xs:dateTime"/>
    <xs:element minOccurs="0" maxOccurs="1" name="AdditionalInfo" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="NonIndexableItemDetailResultType">
  <xs:sequence>
    <xs:element minOccurs="0" name="Items" type="t:ArrayOfNonIndexableItemDetailsType"/>
    <xs:element minOccurs="0" name="FailedMailboxes"
type="t:ArrayOfFailedSearchMailboxesType"/>
  </xs:sequence>
</xs:complexType>
</xs:schema>

```

8 Appendix C: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include updates to those products.

- Microsoft Exchange Server 2013
- Microsoft Exchange Server 2016
- Microsoft Lync Server 2013
- Microsoft Skype for Business Server 2015
- Microsoft Skype for Business Server 2019
- Microsoft Exchange Server 2019
- Microsoft Exchange Server Subscription Edition
- Microsoft Skype for Business Server Subscription Edition

Exceptions, if any, are noted in this section. If an update version, service pack or Knowledge Base (KB) number appears with a product name, the behavior changed in that update. The new behavior also applies to subsequent updates unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

9 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as Major, Minor, or None.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements.
- A document revision that captures changes to protocol functionality.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **None** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the relevant technical content is identical to the last released version.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

Section	Description	Revision class
8 Appendix C: Product Behavior	Updated list of supported products.	Major

10 Index

A

Abstract data model
[server](#) 11
[Applicability](#) 8
[Attribute groups](#) 10
[Attributes](#) 10

C

[Capability negotiation](#) 8
[Change tracking](#) 35
Client
[overview](#) 11
[Complex types](#) 10
[NonEmptyArrayOfLegacyDNsType](#) 10

D

Data model - abstract
[server](#) 11

E

Events
[local - server](#) 24
[timer - server](#) 24
Examples
[getting details for nonindexable items](#) 25
[getting statistics for nonindexable items](#) 26
ExchangeServicePortType
[port type](#) 11

F

[Fields - vendor-extensible](#) 8
[Full WSDL](#) 29
[Full XML schema](#) 31

<http://schemas.microsoft.com/exchange/service/2006/messages.Schema> 31

<http://schemas.microsoft.com/exchange/service/2006/types.Schema> 32

G

[Getting details for nonindexable items example](#) 25
[Getting statistics for nonindexable items example](#) 26
[Glossary](#) 5
[Groups](#) 10

I

[Implementer - security considerations](#) 28
[Index of security parameters](#) 28
[Informative references](#) 7
Initialization
[server](#) 11
[Introduction](#) 5

L

Local events
[server](#) 24

M

Message processing
[server](#) 11
Messages
[attribute groups](#) 10
[attributes](#) 10
[complex types](#) 10
[elements](#) 9
[enumerated](#) 9
[groups](#) 10
[namespaces](#) 9
[NonEmptyArrayOfLegacyDNsType complex type](#) 10
[overview](#) 9
[simple types](#) 10
[syntax](#) 9
[transport](#) 9

N

[Namespaces](#) 9
[NonEmptyArrayOfLegacyDNsType complex type](#) 10
[Normative references](#) 6

O

Operations
[GetNonIndexableItemDetails](#) 11
[GetNonIndexableItemStatistics](#) 18
[Overview \(synopsis\)](#) 7

P

[Parameters - security index](#) 28
Port types
[ExchangeServicePortType](#) 11
[Preconditions](#) 8
[Prerequisites](#) 8
[Product behavior](#) 34
Protocol Details
[overview](#) 11

R

[References](#) 6
[informative](#) 7
[normative](#) 6
[Relationship to other protocols](#) 7

S

Security
[implementer considerations](#) 28
[parameter index](#) 28
Sequencing rules
[server](#) 11

Server

- [abstract data model](#) 11
 - [ExchangeServicePortType port type](#) 11
 - [GetNonIndexableItemDetails operation](#) 11
 - [GetNonIndexableItemStatistics operation](#) 18
 - [initialization](#) 11
 - [local events](#) 24
 - [message processing](#) 11
 - [overview](#) 11
 - [sequencing rules](#) 11
 - [timer events](#) 24
 - [timers](#) 11
 - [Simple types](#) 10
 - [Standards assignments](#) 8
- Syntax
- [messages - overview](#) 9

T

Timer events

- [server](#) 24
- Timers
- [server](#) 11
 - [Tracking changes](#) 35
 - [Transport](#) 9
- Types
- [complex](#) 10
 - [simple](#) 10

V

- [Vendor-extensible fields](#) 8
- [Versioning](#) 8

W

- [WSDL](#) 29

X

- [XML schema](#) 31
 - <http://schemas.microsoft.com/exchange/service/2006/messages.Schema> 31
 - <http://schemas.microsoft.com/exchange/service/2006/types.Schema> 32