

# [MS-OXWSLVID]:

## Federated Internet Authentication Web Service Protocol

---

### Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **License Programs.** To see all of the protocols in scope under a specific license program and the associated patents, visit the [Patent Map](#).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

**Support.** For questions and support, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

## Revision Summary

Date	Revision History	Revision Class	Comments
11/4/2009	1.0.0	Major	Initial availability
2/10/2010	1.1.0	Minor	Updated the technical content.
5/5/2010	1.2.0	Minor	Updated the technical content.
8/4/2010	2.0	Major	Significantly changed the technical content.
11/3/2010	2.1	Minor	Clarified the meaning of the technical content.
3/18/2011	3.0	Major	Significantly changed the technical content.
8/5/2011	3.1	Minor	Clarified the meaning of the technical content.
10/7/2011	3.1	None	No changes to the meaning, language, or formatting of the technical content.
1/20/2012	4.0	Major	Significantly changed the technical content.
4/27/2012	4.0	None	No changes to the meaning, language, or formatting of the technical content.
7/16/2012	4.1	Minor	Clarified the meaning of the technical content.
10/8/2012	5.0	Major	Significantly changed the technical content.
2/11/2013	5.0	None	No changes to the meaning, language, or formatting of the technical content.
7/26/2013	6.0	Major	Significantly changed the technical content.
11/18/2013	6.0	None	No changes to the meaning, language, or formatting of the technical content.
2/10/2014	6.0	None	No changes to the meaning, language, or formatting of the technical content.
4/30/2014	6.1	Minor	Clarified the meaning of the technical content.
7/31/2014	6.2	Minor	Clarified the meaning of the technical content.
10/30/2014	6.2	None	No changes to the meaning, language, or formatting of the technical content.
5/26/2015	7.0	Major	Significantly changed the technical content.
9/14/2015	7.0	None	No changes to the meaning, language, or formatting of the technical content.
6/13/2016	7.0	None	No changes to the meaning, language, or formatting of the technical content.
9/14/2016	7.0	None	No changes to the meaning, language, or formatting of the technical content.
6/20/2017	7.0	None	No changes to the meaning, language, or formatting of the technical content.
9/19/2017	7.1	Minor	Clarified the meaning of the technical content.

<b>Date</b>	<b>Revision History</b>	<b>Revision Class</b>	<b>Comments</b>
12/12/2017	7.1	None	No changes to the meaning, language, or formatting of the technical content.
7/24/2018	8.0	Major	Significantly changed the technical content.
10/1/2018	9.0	Major	Significantly changed the technical content.
5/20/2025	10.0	Major	Significantly changed the technical content.

# Table of Contents

<b>1</b>	<b>Introduction</b>	<b>8</b>
1.1	Glossary	8
1.2	References	10
1.2.1	Normative References	10
1.2.2	Informative References	11
1.3	Overview	11
1.4	Relationship to Other Protocols	11
1.5	Prerequisites/Preconditions	12
1.6	Applicability Statement	12
1.7	Versioning and Capability Negotiation	12
1.8	Vendor-Extensible Fields	12
1.9	Standards Assignments	12
<b>2</b>	<b>Messages</b>	<b>13</b>
2.1	Transport	13
2.2	Common Message Syntax	13
2.2.1	Namespaces	13
2.2.2	Messages	13
2.2.3	Elements	14
2.2.3.1	tns:DomainOwnershipProofHeader Element	14
2.2.3.2	s:Security Element	14
2.2.4	Complex Types	14
2.2.4.1	tns:ArrayOfProperty Complex Type	15
2.2.4.2	tns:DomainInfo Complex Type	15
2.2.4.3	tns:DomainOwnershipProofHeader Complex Type	16
2.2.4.4	tns:Property Complex Type	17
2.2.4.5	s1:WSSecurityHeader Complex Type	17
2.2.5	Simple Types	18
2.2.5.1	tns:DomainState Simple Type	18
2.2.6	Attributes	19
2.2.7	Groups	19
2.2.8	Attribute Groups	19
<b>3</b>	<b>Protocol Details</b>	<b>20</b>
3.1	ManageDelegationSoap Client Details	20
3.1.1	Abstract Data Model	20
3.1.2	Timers	20
3.1.3	Initialization	21
3.1.4	Message Processing Events and Sequencing Rules	21
3.1.4.1	AddUri Operation	21
3.1.4.1.1	Messages	22
3.1.4.1.1.1	tns:AddUriSoapIn Message	22
3.1.4.1.1.2	tns:AddUriSoapOut Message	22
3.1.4.1.2	Elements	23
3.1.4.1.2.1	tns:AddUri Element	23
3.1.4.1.2.2	tns:AddUriResponse Element	23
3.1.4.2	CreateAppId Operation	24
3.1.4.2.1	Messages	24
3.1.4.2.1.1	tns:CreateAppIdSoapIn Message	24
3.1.4.2.1.2	tns:CreateAppIdSoapOut Message	25
3.1.4.2.2	Elements	25
3.1.4.2.2.1	tns:CreateAppId Element	25
3.1.4.2.2.2	tns:CreateAppIdResponse Element	26
3.1.4.2.3	Complex Types	26
3.1.4.2.3.1	tns:AppIdInfo Complex Type	26

3.1.4.3	GetDomainInfo Operation .....	27
3.1.4.3.1	Messages.....	27
3.1.4.3.1.1	tns:GetDomainInfoSoapIn Message .....	28
3.1.4.3.1.2	tns:GetDomainInfoSoapOut Message .....	28
3.1.4.3.2	Elements .....	28
3.1.4.3.2.1	tns:GetDomainInfo Element.....	29
3.1.4.3.2.2	tns:GetDomainInfoResponse Element.....	29
3.1.4.4	ReleaseDomain Operation .....	30
3.1.4.4.1	Messages.....	30
3.1.4.4.1.1	tns:ReleaseDomainSoapIn Message .....	30
3.1.4.4.1.2	tns:ReleaseDomainSoapOut Message .....	31
3.1.4.4.2	Elements .....	31
3.1.4.4.2.1	tns:ReleaseDomain Element .....	31
3.1.4.4.2.2	tns:ReleaseDomainResponse Element .....	32
3.1.4.5	RemoveUri Operation .....	32
3.1.4.5.1	Messages.....	32
3.1.4.5.1.1	tns:RemoveUriSoapIn Message .....	33
3.1.4.5.1.2	tns:RemoveUriSoapOut Message .....	33
3.1.4.5.2	Elements .....	33
3.1.4.5.2.1	tns:RemoveUri Element .....	34
3.1.4.5.2.2	tns:RemoveUriResponse Element .....	34
3.1.4.6	ReserveDomain Operation.....	34
3.1.4.6.1	Messages.....	35
3.1.4.6.1.1	tns:ReserveDomainSoapIn Message .....	35
3.1.4.6.1.2	tns:ReserveDomainSoapOut Message .....	35
3.1.4.6.2	Elements .....	36
3.1.4.6.2.1	tns:ReserveDomain Element.....	36
3.1.4.6.2.2	tns:ReserveDomainResponse Element .....	37
3.1.4.7	UpdateAppIdCertificate Operation.....	37
3.1.4.7.1	Messages.....	37
3.1.4.7.1.1	tns:UpdateAppIdCertificateSoapIn Message.....	38
3.1.4.7.1.2	tns:UpdateAppIdCertificateSoapOut Message.....	38
3.1.4.7.2	Elements .....	38
3.1.4.7.2.1	tns:UpdateAppIdCertificate Element.....	39
3.1.4.7.2.2	tns:UpdateAppIdCertificateResponse Element.....	39
3.1.4.8	UpdateAppIdProperties Operation.....	40
3.1.4.8.1	Messages.....	40
3.1.4.8.1.1	tns:UpdateAppIdPropertiesSoapIn Message.....	40
3.1.4.8.1.2	tns:UpdateAppIdPropertiesSoapOut Message.....	41
3.1.4.8.2	Elements .....	41
3.1.4.8.2.1	tns:UpdateAppIdProperties Element .....	41
3.1.4.8.2.2	tns:UpdateAppIdPropertiesResponse Element .....	42
3.1.5	Timer Events.....	42
3.1.6	Other Local Events .....	42
3.2	ManageDelegation2Soap Client Details.....	42
3.2.1	Abstract Data Model .....	42
3.2.2	Timers .....	43
3.2.3	Initialization .....	43
3.2.4	Message Processing Events and Sequencing Rules .....	43
3.2.4.1	AddUri Operation.....	44
3.2.4.1.1	Messages.....	44
3.2.4.1.1.1	tns:AddUriDomainOwnershipProofHeader Message .....	45
3.2.4.1.1.2	tns:AddUriSecurity Message .....	45
3.2.4.1.1.3	tns:AddUriSoapIn Message.....	45
3.2.4.1.1.4	tns:AddUriSoapOut Message.....	46
3.2.4.1.2	Elements .....	46
3.2.4.1.2.1	tns:AddUri Element.....	46
3.2.4.1.2.2	tns:AddUriResponse Element .....	47

3.2.4.2	CreateAppId Operation .....	47
3.2.4.2.1	Messages.....	48
3.2.4.2.1.1	tns:CreateAppIdDomainOwnershipProofHeader Message .....	48
3.2.4.2.1.2	tns:CreateAppIdSecurity Message.....	48
3.2.4.2.1.3	tns:CreateAppIdSoapIn Message .....	49
3.2.4.2.1.4	tns:CreateAppIdSoapOut Message .....	49
3.2.4.2.2	Elements .....	50
3.2.4.2.2.1	tns:CreateAppId Element .....	50
3.2.4.2.2.2	tns:CreateAppIdResponse Element .....	50
3.2.4.2.3	Complex Types .....	51
3.2.4.2.3.1	t:AppIdInfo Complex Type.....	51
3.2.4.3	GetDomainInfo Operation .....	51
3.2.4.3.1	Messages.....	52
3.2.4.3.1.1	tns:GetDomainInfoSecurity Message .....	52
3.2.4.3.1.2	tns:GetDomainInfoSoapIn Message .....	53
3.2.4.3.1.3	tns:GetDomainInfoSoapOut Message .....	53
3.2.4.3.2	Elements .....	53
3.2.4.3.2.1	tns:GetDomainInfo Element.....	54
3.2.4.3.2.2	tns:GetDomainInfoResponse Element.....	54
3.2.4.4	ReleaseDomain Operation .....	55
3.2.4.4.1	Messages.....	55
3.2.4.4.1.1	tns:ReleaseDomainSecurity Message.....	55
3.2.4.4.1.2	tns:ReleaseDomainSoapIn Message .....	56
3.2.4.4.1.3	tns:ReleaseDomainSoapOut Message .....	56
3.2.4.4.2	Elements .....	56
3.2.4.4.2.1	tns:ReleaseDomain Element .....	57
3.2.4.4.2.2	tns:ReleaseDomainResponse Element .....	57
3.2.4.5	RemoveUri Operation .....	57
3.2.4.5.1	Messages.....	58
3.2.4.5.1.1	tns:RemoveUriSecurity Message.....	58
3.2.4.5.1.2	tns:RemoveUriSoapIn Message .....	59
3.2.4.5.1.3	tns:RemoveUriSoapOut Message .....	59
3.2.4.5.2	Elements .....	59
3.2.4.5.2.1	tns:RemoveUri Element .....	60
3.2.4.5.2.2	tns:RemoveUriResponse Element .....	60
3.2.4.6	ReserveDomain Operation.....	60
3.2.4.6.1	Messages.....	61
3.2.4.6.1.1	tns:ReserveDomainDomainOwnershipProofHeader Message .....	61
3.2.4.6.1.2	tns:ReserveDomainSecurity Message .....	62
3.2.4.6.1.3	tns:ReserveDomainSoapIn Message.....	62
3.2.4.6.1.4	tns:ReserveDomainSoapOut Message.....	62
3.2.4.6.2	Elements .....	63
3.2.4.6.2.1	tns:ReserveDomain Element.....	63
3.2.4.6.2.2	tns:ReserveDomainResponse Element .....	64
3.2.4.7	UpdateAppIdCertificate Operation.....	64
3.2.4.7.1	Messages.....	64
3.2.4.7.1.1	tns:UpdateAppIdCertificateSecurity Message .....	65
3.2.4.7.1.2	tns:UpdateAppIdCertificateSoapIn Message.....	65
3.2.4.7.1.3	tns:UpdateAppIdCertificateSoapOut Message.....	65
3.2.4.7.2	Elements .....	66
3.2.4.7.2.1	tns:UpdateAppIdCertificate Element.....	66
3.2.4.7.2.2	tns:UpdateAppIdCertificateResponse Element.....	67
3.2.4.8	UpdateAppIdProperties Operation.....	67
3.2.4.8.1	Messages.....	67
3.2.4.8.1.1	tns:UpdateAppIdPropertiesSecurity Message .....	68
3.2.4.8.1.2	tns:UpdateAppIdPropertiesSoapIn Message.....	68
3.2.4.8.1.3	tns:UpdateAppIdPropertiesSoapOut Message.....	68
3.2.4.8.2	Elements .....	69

3.2.4.8.2.1	tns:UpdateAppIdProperties Element .....	69
3.2.4.8.2.2	tns:UpdateAppIdPropertiesResponse Element .....	70
3.2.5	Timer Events .....	70
3.2.6	Other Local Events .....	70
3.3	Federation Metadata Client Details .....	70
3.3.1	Abstract Data Model .....	71
3.3.2	Timers .....	71
3.3.3	Initialization .....	71
3.3.4	Message Processing Events and Sequencing Rules .....	71
3.3.4.1	Requesting the Service Issue a Token .....	71
3.3.4.1.1	Token Request .....	71
3.3.4.1.2	Token Response .....	76
3.3.4.1.3	Encrypted and Unencrypted Tokens .....	78
3.3.5	Timer Events .....	81
3.3.6	Other Local Events .....	81
<b>4</b>	<b>Protocol Examples .....</b>	<b>82</b>
4.1	Registering with a Security Token Service .....	82
4.1.1	Creating an Application Identifier .....	82
4.1.2	Reserving a Federated Organization Domain .....	83
4.1.3	Retrieving Domain Information .....	84
4.1.4	Registering a Domain Name .....	85
4.1.5	Removing a Registered Domain Name .....	85
4.1.6	Updating a Certificate .....	86
<b>5</b>	<b>Security .....</b>	<b>88</b>
5.1	Security Considerations for Implementers .....	88
5.2	Index of Security Parameters .....	88
<b>6</b>	<b>Appendix A: Full WSDL .....</b>	<b>89</b>
6.1	ManageDelegationSoap WSDL .....	89
6.2	ManageDelegation2Soap WSDL .....	95
<b>7</b>	<b>Appendix B: Product Behavior .....</b>	<b>105</b>
<b>8</b>	<b>Change Tracking .....</b>	<b>107</b>
<b>9</b>	<b>Index .....</b>	<b>108</b>

# 1 Introduction

The Federated Internet Authentication Web Service Protocol defines the interaction between the server and standard Internet authentication protocols. The server uses this protocol to call external Web services to obtain security tokens that are then used by other Web service protocols to authenticate a transaction.

Sections 1.5, 1.8, 1.9, 2, and 3 of this specification are normative. All other sections and examples in this specification are informative.

## 1.1 Glossary

This document uses the following terms:

**Active Directory:** The Windows implementation of a general-purpose directory service, which uses LDAP as its primary access protocol. Active Directory stores information about a variety of objects in the network such as user accounts, computer accounts, groups, and all related credential information used by Kerberos [\[MS-KILE\]](#). Active Directory is either deployed as Active Directory Domain Services (AD DS) or Active Directory Lightweight Directory Services (AD LDS), which are both described in [\[MS-ADOD\]](#): Active Directory Protocols Overview.

**Active Directory object:** A set of directory objects that are used within **Active Directory** as defined in [\[MS-ADTS\]](#) section 3.1.1. An **Active Directory object** can be identified by a dsname. See also directory object.

**base64 encoding:** A binary-to-text encoding scheme whereby an arbitrary sequence of bytes is converted to a sequence of printable ASCII characters, as described in [\[RFC4648\]](#).

**certificate:** When referring to X.509v3 certificates, that information consists of a public key, a distinguished name (DN) of some entity assumed to have control over the private key corresponding to the **public key** in the certificate, and some number of other attributes and extensions assumed to relate to the entity thus referenced. Other forms of certificates can bind other pieces of information.

**Coordinated Universal Time (UTC):** A high-precision atomic time standard that approximately tracks Universal Time (UT). It is the basis for legal, civil time all over the Earth. Time zones around the world are expressed as positive and negative offsets from UTC. In this role, it is also referred to as Zulu time (Z) and Greenwich Mean Time (GMT). In these specifications, all references to UTC refer to the time at UTC-0 (or GMT).

**domain:** A set of users and computers sharing a common namespace and management infrastructure. At least one computer member of the set has to act as a domain controller (DC) and host a member list that identifies all members of the domain, as well as optionally hosting the **Active Directory** service. The domain controller provides authentication of members, creating a unit of trust for its members. Each domain has an identifier that is shared among its members. For more information, see [\[MS-AUTHSOD\]](#) section 1.1.1.5 and [\[MS-ADTS\]](#).

**domain name:** The name given by an administrator to a collection of networked computers that share a common directory. Part of the domain naming service naming structure, domain names consist of a sequence of name labels separated by periods.

**Domain Name System (DNS):** A hierarchical, distributed database that contains mappings of **domain names** to various types of data, such as IP addresses. DNS enables the location of computers and services by user-friendly names, and it also enables the discovery of other information stored in the database.

**Hypertext Transfer Protocol Secure (HTTPS):** An extension of HTTP that securely encrypts and decrypts web page requests. In some older protocols, "Hypertext Transfer Protocol over Secure

Sockets Layer" is still used (Secure Sockets Layer has been deprecated). For more information, see [\[SSL3\]](#) and [\[RFC5246\]](#).

**private key:** One of a pair of keys used in public-key cryptography. The private key is kept secret and is used to decrypt data that has been encrypted with the corresponding public key. For an introduction to this concept, see [\[CRYPTO\]](#) section 1.8 and [\[IEEE1363\]](#) section 3.1.

**public key:** One of a pair of keys used in public-key cryptography. The public key is distributed freely and published as part of a digital certificate. For an introduction to this concept, see [\[CRYPTO\]](#) section 1.8 and [\[IEEE1363\]](#) section 3.1.

**security token service (STS):** A web service that issues claims and packages them in encrypted security tokens.

**SOAP action:** The HTTP request header field used to indicate the intent of the SOAP request, using a **URI** value. See [\[SOAP1.1\]](#) section 6.1.1 for more information.

**SOAP body:** A container for the payload data being delivered by a **SOAP message** to its recipient. See [\[SOAP1.2-1/2007\]](#) section 5.3 for more information.

**SOAP header:** A mechanism for implementing extensions to a **SOAP message** in a decentralized manner without prior agreement between the communicating parties. See [\[SOAP1.2-1/2007\]](#) section 5.2 for more information.

**SOAP message:** An **XML** document consisting of a mandatory SOAP envelope, an optional **SOAP header**, and a mandatory **SOAP body**. See [\[SOAP1.2-1/2007\]](#) section 5 for more information.

**Uniform Resource Identifier (URI):** A string that identifies a resource. The URI is an addressing mechanism defined in Internet Engineering Task Force (IETF) Uniform Resource Identifier (URI): Generic Syntax [\[RFC3986\]](#).

**Uniform Resource Locator (URL):** A string of characters in a standardized format that identifies a document or resource on the World Wide Web. The format is as specified in [\[RFC1738\]](#).

**user principal name (UPN):** A user account name (sometimes referred to as the user logon name) and a domain name that identifies the domain in which the user account is located. This is the standard usage for logging on to a Windows domain. The format is: someone@example.com (in the form of an email address). In **Active Directory**, the userPrincipalName attribute of the account object, as described in [\[MS-ADTS\]](#).

**Web Services Description Language (WSDL):** An XML format for describing network services as a set of endpoints that operate on messages that contain either document-oriented or procedure-oriented information. The operations and messages are described abstractly and are bound to a concrete network protocol and message format in order to define an endpoint. Related concrete endpoints are combined into abstract endpoints, which describe a network service. WSDL is extensible, which allows the description of endpoints and their messages regardless of the message formats or network protocols that are used.

**WSDL message:** An abstract, typed definition of the data that is communicated during a WSDL operation [\[WSDL\]](#). Also, an element that describes the data being exchanged between web service providers and clients.

**WSDL port type:** A named set of logically-related, abstract **Web Services Description Language (WSDL)** operations and messages.

**X.509:** An ITU-T standard for public key infrastructure subsequently adapted by the IETF, as specified in [\[RFC3280\]](#).

**XML:** The Extensible Markup Language, as described in [\[XML1.0\]](#).

**XML namespace:** A collection of names that is used to identify elements, types, and attributes in XML documents identified in a URI reference [RFC3986]. A combination of XML namespace and local name allows XML documents to use elements, types, and attributes that have the same names but come from different sources. For more information, see [\[XMLNS-2ED\]](#).

**XML schema:** A description of a type of XML document that is typically expressed in terms of constraints on the structure and content of documents of that type, in addition to the basic syntax constraints that are imposed by **XML** itself. An XML schema provides a view of a document type at a relatively high level of abstraction.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <https://www.rfc-editor.org/info/rfc2119>

[SAML] OASIS, "Web Services Security: SAML Token Profile", Oasis Standard, December 2004, <http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-1.0.pdf>

[SOAP1.1] Box, D., Ehnebuske, D., Kakivaya, G., et al., "Simple Object Access Protocol (SOAP) 1.1", W3C Note, May 2000, <https://www.w3.org/TR/2000/NOTE-SOAP-20000508/>

[SOAP1.2/1] Gudgin, M., Hadley, M., Mendelsohn, N., Moreau, J., and Nielsen, H.F., "SOAP Version 1.2 Part 1: Messaging Framework", W3C Recommendation, June 2003, <http://www.w3.org/TR/2003/REC-soap12-part1-20030624>

[WSADDRBIND] Gudgin, M., Hadley, M., and Rogers, T., Eds., "Web Services Addressing 1.0 - SOAP Binding", W3C Recommendation, May 2006, <http://www.w3.org/TR/2006/REC-ws-addr-soap-20060509/>

[WSDLSOAP] Angelov, D., Ballinger, K., Butek, R., et al., "WSDL 1.1 Binding Extension for SOAP 1.2", W3C Member Submission, April 2006, <http://www.w3.org/Submission/2006/SUBM-wsdl11soap12-20060405/>

[WSDL] Christensen, E., Curbera, F., Meredith, G., and Weerawarana, S., "Web Services Description Language (WSDL) 1.1", W3C Note, March 2001, <https://www.w3.org/TR/2001/NOTE-wsdl-20010315>

[WSFederation] Kaler, C., Nadalin, A., Bajaj, S., et al., "Web Services Federation Language (WS-Federation)", Version 1.1, December 2006, <http://specs.xmlsoap.org/ws/2006/12/federation/ws-federation.pdf>

[WSS] OASIS, "Web Services Security: SOAP Message Security 1.1 (WS-Security 2004)", February 2006, <https://www.oasis-open.org/committees/download.php/16790/wss-v1.1-spec-os-SOAPMessageSecurity.pdf>

[WSTrust1.4] OASIS Standard, "WS-Trust 1.4", February 2009, <http://docs.oasis-open.org/ws-sx/ws-trust/v1.4/os/ws-trust-1.4-spec-os.doc>

[XMLDSig2] Bartel, M., Boyer, J., Fox, B., et al., "XML Signature Syntax and Processing (Second Edition)", W3C Recommendation, June 2008, <http://www.w3.org/TR/2008/REC-xmlsig-core-20080610/>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <https://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <https://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <https://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

[XPath] Clark, J. and DeRose, S., "XML Path Language (XPath), Version 1.0", W3C Recommendation, November 1999, <http://www.w3.org/TR/1999/REC-xpath-19991116/>

### 1.2.2 Informative References

[FIPS180-2] National Institute of Standards and Technology, "Secure Hash Standard", FIPS PUB 180-2, August 2002, <http://csrc.nist.gov/publications/fips/fips180-2/fips180-2.pdf>

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

[MS-OXWSMSHR] Microsoft Corporation, "[Folder Sharing Web Service Protocol](#)".

### 1.3 Overview

The Federated Internet Authentication Web Service Protocol defines the interactions between the server and standard Internet authentication protocols to provide authentication information to other services on the server. This protocol uses the following:

- The Managed Delegation Web service, to establish a relationship with a **security token service (STS)**. The operations that are exposed by the Managed Delegation Web service are described in section [3.1](#) and section [3.2](#).
- The **Federation** element, as described in [\[WSFederation\]](#), to provide the security tokens and endpoints that are used to create authentication tokens that can be used to authenticate users and services with other organizations.
- The authentication token that is returned by an STS, as described in [\[WSTrust1.4\]](#).

### 1.4 Relationship to Other Protocols

The Federated Internet Authentication Web Service Protocol uses the standard Web Service Federation Language Protocol, as described in [\[WSFederation\]](#), and the WS-Trust 1.4 Protocol, as described in [\[WSTrust1.4\]](#), to provide authentication services for a server. The Folder Sharing Web Service Protocol, as described in [\[MS-OXWSMSHR\]](#), uses this protocol for authentication services.

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

## 1.5 Prerequisites/Preconditions

The Federated Internet Authentication Web Service Protocol uses services that are provided by external Web services to establish federated relationships between organizations. In order to operate, the protocol requires that the service provide the following:

- The **URL** of a service that provides a Federation Metadata Document, as described in [\[WSFederation\]](#) section 3.1, with the fields and values as described in section [3.3.1](#).
- The URL of a delegation management service that provides services, as described in section [3.1](#) or section [3.2](#).

## 1.6 Applicability Statement

This protocol is applicable to applications that request federated authentication information on behalf of a client, and applications that expose Web services that provide federated authentication information to servers.

## 1.7 Versioning and Capability Negotiation

None.

## 1.8 Vendor-Extensible Fields

None.

## 1.9 Standards Assignments

None.

## 2 Messages

In the following sections, the schema definition might differ from the processing rules imposed by the protocol. The **WSDL** in this specification provides a base description of the protocol. The schema in this specification provides a base description of the message syntax. The text that specifies the WSDL and schema might specify restrictions that reflect actual protocol behavior. For example, the schema definition might allow for an element to be **empty**, **null**, or **not present** but the behavior of the protocol as specified restricts the same elements to being **non-empty**, **not null**, or **present**.

### 2.1 Transport

Protocol servers support SOAP over **HTTPS**. Protocol messages are formatted as specified in [\[SOAP1.1\]](#) or in [\[SOAP1.2/1\]](#). Security tokens are used as specified in [\[WSS\]](#). Security tokens are exchanged as specified in [\[WSTrust1.4\]](#). Web service addresses are bound as specified in [\[WSADDRBIND\]](#).

### 2.2 Common Message Syntax

This section contains common definitions that are used by this protocol. The syntax of the definitions uses **XML schema**, as defined in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#), and **Web Services Description Language (WSDL)**, as defined in [\[WSDL\]](#).

#### 2.2.1 Namespaces

This specification defines and references various **XML namespaces** by using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
s	<a href="http://www.w3.org/2001/XMLSchema">http://www.w3.org/2001/XMLSchema</a>	<a href="#">[XMLNS]</a>
soap	<a href="http://schemas.xmlsoap.org/wsdl/soap/">http://schemas.xmlsoap.org/wsdl/soap/</a>	<a href="#">[SOAP1.1]</a>
soap12	<a href="http://schemas.xmlsoap.org/wsdl/soap12/">http://schemas.xmlsoap.org/wsdl/soap12/</a>	<a href="#">[WSDLSOAP]</a>
s1	<a href="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd">http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd</a>	<a href="#">[WSS]</a>
s2	<a href="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd">http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd</a>	<a href="#">[WSS]</a>
s3	<a href="http://www.w3.org/2000/09/xmldsig#">http://www.w3.org/2000/09/xmldsig#</a>	<a href="#">[XMLDSig2]</a>
tns	<a href="http://domains.live.com/Service/ManageDelegation2/V1.0">http://domains.live.com/Service/ManageDelegation2/V1.0</a>	
wsdl	<a href="http://schemas.xmlsoap.org/WSDL/">http://schemas.xmlsoap.org/WSDL/</a>	<a href="#">[WSDL]</a>

#### 2.2.2 Messages

This specification does not define any common **WSDL message** definitions.

## 2.2.3 Elements

The following table summarizes the set of common **XML schema** element definitions that are defined by this specification. XML schema element definitions that are specific to a particular operation are described with the operation.

Element name	Description
<b>DomainOwnershipProofHeader</b>	Specifies the security credentials that identify the owner of a <b>domain</b> that is participating in the federation management service, as described in <a href="#">[WSFederation]</a> .
<b>Security</b>	Specifies the elements of the <b>WSSecurityHeader</b> element that are used by the Federated Internet Authentication Web Service Protocol.

### 2.2.3.1 tns:DomainOwnershipProofHeader Element

The **DomainOwnershipProofHeader** element defines the credentials that are required to prove ownership of a domain that is participating in a federation management service.

```
<xs:element name="tns:DomainOwnershipProofHeader"
  type="tns:DomainOwnershipProofHeader"
/>
```

### 2.2.3.2 s:Security Element

The **Security** element specifies the elements of the **WSSecurityHeader** element that are used by the Federated Internet Authentication Web Service Protocol. These elements are **Timestamp**, as specified in [\[WSS\]](#) Appendix C, and **Signature**, as specified in [\[XMLDSig2\]](#).

```
<xs:element name="s:Security"
  type="s1:WSSecurityHeader"
/>
```

## 2.2.4 Complex Types

The following table summarizes the set of common **XML schema** complex types that are defined by this specification. XML schema complex type definitions that are specific to a particular operation are defined with the operation.

Complex type name	Description
<b>ArrayOfProperty</b>	Specifies an array of property name/value pairs for a managed delegate relationship.
<b>DomainInfo</b>	Specifies the domain information that is returned by the <b>GetDomainInfo</b> operation.
<b>DomainOwnershipProofHeader</b>	Specifies the credentials that are required to prove ownership of a domain.
<b>Property</b>	Specifies a name/value pair for a managed delegate relationship.
<b>WSSecurityHeader</b>	Specifies the elements of the standard <b>WSSecurityHeader</b> element that

Complex type name	Description
	are used by the Federated Internet Authentication Web Service Protocol.

### 2.2.4.1 tns:ArrayOfProperty Complex Type

The **ArrayOfProperty** complex type specifies one or more **Property** complex type name/value pairs, as specified in section [2.2.4.4](#).

```
<xs:complexType name="ArrayOfProperty">
  <xs:sequence>
    <xs:element name="Property"
      type="tns:Property"
      minOccurs="0"
      maxOccurs="unbounded"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **ArrayOfProperty** complex type.

Element name	Type	Description
<b>Property</b>	<b>tns:Property</b> (section <a href="#">2.2.4.4</a> )	A name/value pair that describes a managed delegation relationship property.

### 2.2.4.2 tns:DomainInfo Complex Type

The **DomainInfo** complex type defines the domain information that is returned by the **GetDomainInfo** operation, as specified in section [3.1.4.3](#).

```
<xs:complexType name="DomainInfo">
  <xs:sequence>
    <xs:element name="DomainName"
      type="s:string"
      maxOccurs="1"
      minOccurs="0"
    />
    <xs:element name="AppId"
      type="s:string"
      maxOccurs="1"
      minOccurs="0"
    />
    <xs:element name="DomainState"
      type="tns:DomainState"
      maxOccurs="1"
      minOccurs="1"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **DomainInfo** complex type.

Element name	Type	Description
<b>DomainName</b>	<b>s:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the registered name of the domain.
<b>AppId</b>	<b>s:string</b>	Specifies the application identifier that is associated with the domain.
<b>DomainState</b>	<b>tns:DomainState</b> (section <a href="#">2.2.5.1</a> )	Specifies the current state of the domain. MUST be present.

### 2.2.4.3 tns:DomainOwnershipProofHeader Complex Type

The **DomainOwnershipProofHeader** complex type specifies the credentials that are required to prove ownership of a domain that is participating in a federation management service.

```
<xs:complexType name="DomainOwnershipProofHeader">
  <xs:sequence>
    <xs:element name="Domain"
      type="s:string"
      maxOccurs="1"
      minOccurs="0"
    />
    <xs:element name="HashAlgorithm"
      type="s:string"
    />
    <xs:element name="Signature"
      type="s:string"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **DomainOwnershipProofHeader** complex type.

Element name	Type	Description
<b>Domain</b>	<b>s:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the name of the domain that is participating in the federation management service.
<b>HashAlgorithm</b>	<b>s:string</b>	Specifies the hash algorithm that is used to create the signature.
<b>Signature</b>	<b>s:string</b>	Specifies the signature of the domain owner.

Create the **Signature** element by performing the following algorithm:

- Sign the **Domain** element with the private key from the certificate used to authenticate the domain with the **STS**.
- Hash the certificate signature with the SHA-512 hash algorithm, as described in [\[FIPS180-2\]](#).
- Encode the hashed value of the signature with **base64 encoding**.

The server compares the value of the **Signature** element with the contents of a TXT record on the **Domain Name System (DNS)** server for the domain specified in the **Domain** element to determine whether the application is authorized to make Web service calls for the domain.

## 2.2.4.4 tns:Property Complex Type

The **Property** complex type specifies a managed delegation property as a name/value pair.

```
<xs:complexType name="Property">
  <xs:sequence>
    <xs:element name="Name"
      type="s:string"
      maxOccurs="1"
      minOccurs="0"
    />
    <xs:element name="Value"
      type="s:string"
      maxOccurs="1"
      minOccurs="0"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **Property** complex type.

Element name	Type	Description
<b>Name</b>	<b>s:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the name of the property.
<b>Value</b>	<b>s:string</b>	Specifies the value of the property expressed as a string.

## 2.2.4.5 s1:WSSecurityHeader Complex Type

The **WSSecurityHeader** complex type specifies the elements of the **WSSecurityHeader** element that are used by the Federated Internet Authentication Web Service Protocol.

```
<xs:complexType name="WSSecurityHeader">
  <xs:sequence>
    <xs:element
      minOccurs="0"
      maxOccurs="1"
      ref="s2:Timestamp"
    />
    <xs:element
      minOccurs="0"
      maxOccurs="1"
      ref="s3:Signature"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **WSSecurityHeader** complex type.

Element name	Type	Description
<b>Timestamp</b>	<b>s2:Timestamp</b> <a href="#">[WSS]</a> Appendix C	Specifies the date and time that the request was created. The <b>Timestamp</b> element MUST contain a <b>Created</b> and an <b>Expired</b> element.
<b>Signature</b>	<b>s3:Signature</b>	Specifies the signature for the request. The signature is created by signing the <b>Timestamp</b> element with the <b>X.509 certificate private key</b> that is

Element name	Type	Description
	<a href="#">[XMLDSig2]</a>	associated with the <b>domain</b> owner. The <b>Signature</b> element MUST contain the signature method and the X.509 certificate <b>public key</b> .

## 2.2.5 Simple Types

The following table summarizes the set of common **XML schema** simple types that are defined by this specification. XML schema simple type definitions that are specific to a particular operation are defined with the operation.

Simple type name	Description
<b>DomainState</b>	Specifies the possible states that can be returned by the <b>GetDomainInfo</b> operation.

### 2.2.5.1 tns:DomainState Simple Type

The **DomainState** simple type specifies the possible states that can be returned by the **GetDomainInfo** operation, as specified in sections [3.1.4.3](#) and [3.2.4.3](#).

```
<xs:simpleType name="DomainState">
  <xs:restriction
    base="s:string"
  >
    <xs:enumeration
      value="PendingActivation"
    />
    <xs:enumeration
      value="Active"
    />
    <xs:enumeration
      value="PendingRelease"
    />
  </xs:restriction>
</xs:simpleType>
```

The following table lists the values that are defined by the **DomainState** simple type.

Value	Meaning
PendingActivation	The request to create a <b>domain</b> has been received but it is not yet active.
Active	The domain is active.
PendingRelease	The request to release a domain has been received, but the domain has not yet been released.

## 2.2.6 Attributes

This specification does not define any common **XML schema** attribute definitions.

## 2.2.7 Groups

This specification does not define any common **XML schema** group definitions.

## 2.2.8 Attribute Groups

This specification does not define any common **XML schema** attribute group definitions.

## 3 Protocol Details

The Federated Internet Authentication Web Service Protocol does not act as a server, and does not expose any services to outside callers. This specification describes the server's interactions as a client to external services.

### 3.1 ManageDelegationSoap Client Details

This client protocol is used by client applications to identify server applications and authenticate those server applications.

#### 3.1.1 Abstract Data Model

This section contains a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that specified in this document.

This protocol is used by client applications to identify server applications and authenticate those server applications. It uses the standard Internet authentication techniques specified in [\[SAML\]](#), [\[WSFederation\]](#), [\[WSS\]](#), [\[WSTrust1.4\]](#), and [\[XMLDSig2\]](#) for that identification and authentication.

Clients that implement this protocol take the following steps to establish a relationship with the federation management service:

1. Create an application identifier by using the **CreateAppId** operation, as specified in section [3.1.4.2](#).
2. Place the application identifier on the **domain's DNS** server as a TXT record.
3. Reserve a **domain name** with the federation management service by using the **ReserveDomain** operation, as specified in section [3.1.4.6](#).
4. Register the **URI** that is associated with the domain with the federation management service by using the **AddUri** operation, as specified in section [3.1.4.1](#).

Clients can request and modify information stored with the federation management service by doing the following:

- Using the **GetDomainInfo** operation, as specified in section [3.1.4.3](#), to retrieve domain information from the federation management service.
- Modifying the information stored with the federation management service by using the **UpdateAppIdCertificate** operation, as specified in section [3.1.4.7](#), and the **UpdateAppIdProperties** operation, as specified in section [3.1.4.8](#).

Clients can end participation with the federation management service by doing the following:

- Using the **RemoveUri** operation, as specified in section [3.1.4.5](#), to remove a URI registered to the domain.
- Using the **ReleaseDomain** operation, as specified in section [3.1.4.4](#), to remove a registered domain from the federation management service.

#### 3.1.2 Timers

None.

### 3.1.3 Initialization

Before calling this protocol, the client application requires the following:

- The URL of a service that provides a Federation Metadata Document, as specified in [\[WSFederation\]](#) section 3.1, with the fields and values as specified in section [3.3.<1>](#)
- The URL of a delegation management service that provides services as described in section [3.1.<2>](#)
- A **DNS** TXT record containing the client's application ID on the DNS server for the **domain**.

### 3.1.4 Message Processing Events and Sequencing Rules

This protocol uses the operations that are listed in the following table.

Operation name	Description
<b>AddUri</b>	Registers a <b>URI</b> with the federation management service.
<b>CreateAppId</b>	Creates an application identifier for an organization with the federation management service.
<b>GetDomainInfo</b>	Gets <b>domain</b> status information from the federation management service.
<b>ReleaseDomain</b>	Removes a domain from the federation management service.
<b>RemoveUri</b>	Removes a registered URI from the federation management service.
<b>ReserveDomain</b>	Verifies that a domain has to be managed by the specified application identifier.
<b>UpdateAppIdCertificate</b>	Updates the security certificate that is associated with an application identifier.
<b>UpdateAppIdProperties</b>	Updates the organizational information that is associated with an application identifier.

#### 3.1.4.1 AddUri Operation

The **AddUri** operation registers the **URL** of an organization that is participating in the federation management service.

The following is the **WSDL port type** specification for this operation.

```
<wsdl:operation name="AddUri">
  <wsdl:input message="tns:AddUriSoapIn" />
  <wsdl:output message="tns:AddUriSoapOut" />
</wsdl:operation>
```

The following is the **WSDL binding** specification for this operation.

```
<wsdl:operation name="AddUri">
  <soap:operation soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/AddUri"
  style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

```

</wsdl:output>
</wsdl:operation>

```

### 3.1.4.1.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>AddUriSoapIn</b>	Specifies the <b>SOAP message</b> that requests the application identifier.
<b>AddUriSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

#### 3.1.4.1.1.1 tns:AddUriSoapIn Message

The **AddUriSoapIn WSDL message** specifies a request to register a **URI** with the federation management service.

```

<wsdl:message name="AddUriSoapIn">
  <wsdl:part name="parameters" element="tns:AddUri" />
</wsdl:message>

```

The **AddUriSoapIn** WSDL message is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/AddUri>.

The part of the **AddUriSoapIn** WSDL message is described in the following table.

Part Name	Element/type	Description
<b>parameters</b>	<b>tns:AddUri</b> (section <a href="#">3.2.4.1.2.1</a> )	Specifies the <b>SOAP body</b> of the request to register a URI with the federation management service.

#### 3.1.4.1.1.2 tns:AddUriSoapOut Message

The **AddUriSoapOut WSDL message** specifies the response to a request to register a **URI** with the federation management server.

```

<wsdl:message name="AddUriSoapOut">
  <wsdl:part name="parameters" element="tns:AddUriResponse" />
</wsdl:message>

```

The **AddUriSoapOut** WSDL message is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/AddUri>.

The part of the **AddUriSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:AddUriResponse</b> (section <a href="#">3.2.4.1.2.2</a> )	Specifies the <b>SOAP body</b> of the response.

### 3.1.4.1.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>AddUri</b>	Specifies the <b>URI</b> that is to be added to the federation management service.
<b>AddUriResponse</b>	Specifies the response from the <b>AddUri</b> operation.

#### 3.1.4.1.2.1 tns:AddUri Element

The **AddUri** element specifies the **URI** that is to be added to the federation management service by the **AddUri** operation.

```
<xs:element name="AddUri">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ownerAppId"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
      <xs:element name="uri"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **AddUri** element.

Element name	Type	Description
<b>ownerAppId</b>	<b>s:string</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the application identifier that is assigned to the entity that is requesting that the URI be registered with a federation management service.
<b>uri</b>	<b>s:string</b>	Specifies the URI to register with the federation management service.

#### 3.1.4.1.2.2 tns:AddUriResponse Element

The **AddUriResponse** element specifies the response from the **AddUri** operation (section [3.1.4.1](#)).

```
<xs:element name="AddUriResponse">
  <xs:complexType />
</xs:element>
```

### 3.1.4.2 CreateAppId Operation

The **CreateAppId** operation creates an identifier for an organization that participates in a federation management service. The identifier that is returned by the **CreateAppId** operation is used when calling operations on the federation management server to identify the organization that is making the request.

The following is the **WSDL port type** specification for this operation.

```
<wsdl:operation name="CreateAppId">
  <wsdl:input message="tns:CreateAppIdSoapIn" />
  <wsdl:output message="tns:CreateAppIdSoapOut" />
</wsdl:operation>
```

The following is the **WSDL binding** specification for this operation.

```
<wsdl:operation name="CreateAppId">
  <soap:operation
  soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/CreateAppId"
  style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

The **CreateAppId** operation requires that the certificate specified in the input message be attached as a **SOAP header** to the request.

#### 3.1.4.2.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>CreateAppIdSoapIn</b>	Specifies the <b>SOAP message</b> that requests the application identifier.
<b>CreateAppIdSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

##### 3.1.4.2.1.1 tns:CreateAppIdSoapIn Message

The **CreateAppIdSoapIn WSDL message** specifies the request to create an application identifier.

```
<wsdl:message name="CreateAppIdSoapIn">
  <wsdl:part name="parameters" element="tns:CreateAppId" />
</wsdl:message>
```

The **CreateAppIdSoapIn WSDL message** is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/CreateAppId>.

The parts of the **CreateAppIdSoapIn WSDL message** is described in the following table.

Part name	Element/type	Description
parameters	<b>tns:CreateAppId</b> (section <a href="#">3.2.4.2.2.1</a> )	Contains the <b>SOAP body</b> of the request to create an application identifier.

### 3.1.4.2.1.2 tns:CreateAppIdSoapOut Message

The **CreateAppIdSoapOut WSDL message** specifies the response to a request to create an application identifier.

```
<wsdl:message name="CreateAppIdSoapOut">
  <wsdl:part name="parameters" element="tns:CreateAppIdResponse" />
</wsdl:message>
```

The **CreateAppIdSoapOut WSDL message** is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/CreateAppId>.

The part of the **CreateAppIdSoapOut WSDL message** is described in the following table.

Part name	Element/type	Description
parameters	<b>tns:CreateAppIdResponse</b> (section <a href="#">3.2.4.2.2.2</a> )	Specifies the <b>SOAP body</b> of the response that contains the application identifier and administrative key.

### 3.1.4.2.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>CreateAppId</b>	Specifies the information that is required to establish a relationship with a federation management service.
<b>CreateAppIdResponse</b>	Specifies the response from the <b>CreateAppId</b> operation that contains an application identifier.

#### 3.1.4.2.2.1 tns:CreateAppId Element

The **CreateAppId** element specifies the information that is required to establish a relationship with a federation management service.

```
<xs:element name="CreateAppId">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="cerfiticcate"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="properties"
        type="tns:ArrayOfProperty"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```

    />
  </xs:sequence>
</xs:complexType>
</xs:element>

```

The following table lists the child elements of the **CreateAppId** element.

Element name	Type	Description
<b>certificate</b>	<b>s:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the certificate that will be used for application identifier management and for encryption of the delegation ticket for this <b>domain</b> . MUST be a string encoded with <b>base64 encoding</b> .
<b>properties</b>	<b>tns:ArrayOfProperty</b> (section <a href="#">2.2.4.1</a> )	Specifies additional information about the organization. Can be present.

### 3.1.4.2.2 tns:CreateAppIdResponse Element

The **CreateAppIdResponse** element specifies the response from the **CreateAppId** operation, as specified in section [3.1.4.2](#), that contains an application identifier and administrative key.

```

<xs:element name="CreateAppIdResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="CreateAppIdResult"
        type="tns:AppIdInfo"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

The following table lists the child elements of the **CreateAppIdResponse** element.

Element name	Type	Description
<b>CreateAppIdResult</b>	<b>tns:AppIdInfo</b> (section <a href="#">3.1.4.2.3.1</a> )	Specifies an application identifier and the associated administrative key.

### 3.1.4.2.3 Complex Types

The following table summarizes the **XML schema** complex type definitions that are specific to this operation.

Complex type	Description
<b>AppIdInfo</b>	Specifies an application identifier and administrative key.

#### 3.1.4.2.3.1 tns:AppIdInfo Complex Type

The **AppIdInfo** complex type specifies an application identifier and the associated administrative key.

```
<xs:complexType name="AppIdInfo">
  <xs:sequence>
    <xs:element name="AppId"
      type="s:string"
    />
    <xs:element name="AdminKey"
      type="s:string"
    />
  </xs:sequence>
</xs:complexType>
```

The following table lists the child elements of the **AppIdInfo** complex type.

Element name	Type	Description
<b>AppId</b>	<b>s:string</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies an application identifier.
<b>AdminKey</b>	<b>s:string</b>	Specifies the administrative key that is associated with the application identifier.

### 3.1.4.3 GetDomainInfo Operation

The **GetDomainInfo** operation retrieves federation status information for a domain.

The following is the **WSDL port type** specification for this operation.

```
<wsdl:operation name="GetDomainInfo">
  <wsdl:input message="tns:GetDomainInfoSoapIn" />
  <wsdl:output message="tns:GetDomainInfoSoapOut" />
</wsdl:operation>
```

The following is the **WSDL binding** specification for this operation.

```
<wsdl:operation name="GetDomainInfo">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/GetDomainInfo"
    style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

#### 3.1.4.3.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>GetDomainInfoSoapIn</b>	Specifies the <b>SOAP message</b> that requests the <b>domain</b> information.
<b>GetDomainInfoSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

### 3.1.4.3.1.1 tns:GetDomainInfoSoapIn Message

The **GetDomainInfoSoapIn WSDL message** specifies a request to return **domain** information.

```
<wsdl:message name="GetDomainInfoSoapIn">
  <wsdl:part name="parameters" element="tns:GetDomainInfo" />
</wsdl:message>
```

The **GetDomainInfoSoapIn WSDL message** is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/GetDomainInfo>.

The part of the **GetDomainInfoSoapIn WSDL message** is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:GetDomainInfo</b> (section <a href="#">3.1.4.3.2.1</a> )	Specifies the SOAP body of the request to return domain information.

### 3.1.4.3.1.2 tns:GetDomainInfoSoapOut Message

The **GetDomainInfoSoapOut WSDL message** specifies the response to a request for **domain** information.

```
<wsdl:message name="GetDomainInfoSoapOut">
  <wsdl:part name="parameters" element="tns:GetDomainInfoResponse" />
</wsdl:message>
```

The **GetDomainInfoSoapOut WSDL message** is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/GetDomainInfo>.

The part of the **GetDomainInfoSoapOut WSDL message** is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:GetDomainInfoResponse</b> (section <a href="#">3.1.4.3.2.2</a> )	Specifies the SOAP body of the response containing information about the requested domain.

### 3.1.4.3.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>GetDomainInfo</b>	Specifies the information that is required to request <b>domain</b> information from a federation management service.
<b>GetDomainInfoResponse</b>	Specifies the response from the <b>GetDomainInfo</b> operation.

### 3.1.4.3.2.1 tns:GetDomainInfo Element

The **GetDomainInfo** element specifies the information that is needed to request the current status of a **domain**.

```
<xs:element name="GetDomainInfo">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ownerAppId"
        type="s:string"
      />
      <xs:element name="domainName"
        type="s:string"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **GetDomainInfo** element.

Element name	Type	Description
<b>ownerAppId</b>	<b>s:string</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the application identifier of the domain owner.
<b>domainName</b>	<b>s:string</b>	Specifies the domain for which information is to be returned.

### 3.1.4.3.2.2 tns:GetDomainInfoResponse Element

The **GetDomainInfoResponse** element specifies the response from a **GetDomainInfo** operation request.

```
<xs:element name="GetDomainInfoResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="GetDomainInfoResult"
        type="tns:DomainState"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **GetDomainInfoResponse** element.

Element name	Type	Description
<b>GetDomainInfoResult</b>	<b>tns:DomainState</b> (section <a href="#">2.2.5.1</a> )	Specifies the <b>domain</b> status information.

### 3.1.4.4 ReleaseDomain Operation

The **ReleaseDomain** operation releases the specified **domain** from federation management services.

The following is the **WSDL port type** specification for this operation.

```
<wsdl:operation name="ReleaseDomain">
  <wsdl:input message="tns:ReleaseDomainSoapIn" />
  <wsdl:output message="tns:ReleaseDomainSoapOut" />
</wsdl:operation>
```

The following is the **WSDL binding** specification for this operation.

```
<wsdl:operation name="ReleaseDomain">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/ReleaseDomain"
    style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

#### 3.1.4.4.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>ReleaseDomainSoapIn</b>	Specifies the <b>SOAP message</b> that requests that the <b>domain</b> be released from the federation management service.
<b>ReleaseDomainSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

##### 3.1.4.4.1.1 tns:ReleaseDomainSoapIn Message

The **ReleaseDomainSoapIn** **WSDL message** specifies the **domain** to release from the federation management service.

```
<wsdl:message name="ReleaseDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReleaseDomain" />
</wsdl:message>
```

The **ReleaseDomainSoapIn** WSDL message is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/ReleaseDomain>.

The part of the **ReleaseDomainSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:ReleaseDomain</b> (section <a href="#">3.1.4.4.2.1</a> )	Specifies the <b>SOAP body</b> of the request to release a domain.

### 3.1.4.4.1.2 tns:ReleaseDomainSoapOut Message

The **ReleaseDomainSoapOut WSDL message** specifies the response from a request to release a domain from the federation management service.

```
<wsdl:message name="ReleaseDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReleaseDomainResponse" />
</wsdl:message>
```

The **ReleaseDomainSoapOut** WSDL message is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/ReleaseDomain>.

The part of the **ReleaseDomainSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:ReleaseDomainResponse</b> (section <a href="#">3.1.4.4.2.2</a> )	Defines the <b>SOAP body</b> of the response from the request to release a <b>domain</b> from the federation management service.

### 3.1.4.4.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>ReleaseDomain</b>	Specifies the information that is required to release a <b>domain</b> from the federation management service.
<b>ReleaseDomainResponse</b>	Specifies the response from the <b>ReleaseDomain</b> operation.

#### 3.1.4.4.2.1 tns:ReleaseDomain Element

The **ReleaseDomain** element specifies the information that is required for the **ReleaseDomain** operation.

```
<xs:element name="ReleaseDomain">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ownerAppId"
        type="s:string"
      />
      <xs:element name="domainName"
        type="s:string"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

```

    />
  </xs:sequence>
</xs:complexType>
</xs:element>

```

The following table lists the child elements of the **ReleaseDomain** element.

Element name	Type	Description
<b>ownerAppId</b>	<b>s:string</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the application identifier assigned to the domain manager when the <b>domain</b> was registered with the federation management service.
<b>domainName</b>	<b>s:string</b>	Specifies the domain to release.

### 3.1.4.4.2 tns:ReleaseDomainResponse Element

The **ReleaseDomainResponse** element specifies the response from the **ReleaseDomain** operation.

```

<xs:element name="ReleaseDomainResponse">
  <xs:complexType />
</xs:element>

```

### 3.1.4.5 RemoveUri Operation

The **RemoveUri** operation removes a previously registered **URI** from the federation management service.

The following is the **WSDL port type** specification for the operation.

```

<wsdl:operation name="RemoveUri">
  <wsdl:input message="tns:RemoveUriSoapIn" />
  <wsdl:output message="tns:RemoveUriSoapOut" />
</wsdl:operation>

```

The following is the **WSDL binding** specification for the operation.

```

<wsdl:operation name="RemoveUri">
  <soap:operation
soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/RemoveUri" style="document"
/>
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>

```

### 3.1.4.5.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>RemoveUriSoapIn</b>	Specifies the <b>SOAP message</b> that requests the <b>URI</b> be removed.
<b>RemoveUriSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

### 3.1.4.5.1.1 tns:RemoveUriSoapIn Message

The **RemoveUriSoapIn WSDL message** defines one part that specifies a request to remove a **URI** from the federation management server.

```
<wsdl:message name="RemoveUriSoapIn">
  <wsdl:part name="parameters" element="tns:RemoveUri" />
</wsdl:message>
```

The **RemoveUriSoapIn** WSDL message is the input message for the SOAP action <http://domains.live.com/Service/ManageDelegation/V1.0/RemoveUri>.

The part of the **RemoveUriSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:RemoveUri</b> (section <a href="#">3.1.4.5.2.1</a> )	Specifies the <b>SOAP body</b> of the request that provides the application identifier of the URI owner and the URI to remove from the federation management server.

### 3.1.4.5.1.2 tns:RemoveUriSoapOut Message

The **RemoveUriSoapOut WSDL message** specifies the response to a request to remove a **URI** from the federation management server.

```
<wsdl:message name="RemoveUriSoapOut">
  <wsdl:part name="parameters" element="tns:RemoveUriResponse" />
</wsdl:message>
```

The **RemoveUriSoapOut** WSDL message is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/RemoveUri>.

The part of the **RemoveUriSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:RemoveUriResponse</b> (section <a href="#">3.1.4.5.2.2</a> )	Specifies the <b>SOAP body</b> of the response from the operation.

## 3.1.4.5.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>RemoveUri</b>	Specifies the information that is required to remove a <b>URI</b> from the federation management service.
<b>RemoveUriResponse</b>	Specifies the response from the <b>RemoveUri</b> operation.

### 3.1.4.5.2.1 tns:RemoveUri Element

The **RemoveUri** element specifies the application identifier and **URI** to remove.

```
<xs:element name="RemoveUri">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ownerAppId"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
      <xs:element name="uri"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **RemoveUri** element.

Element name	Type	Description
<b>ownerAppId</b>	<b>s:string</b> ( <a href="#">XMLSCHEMA21</a> )	Specifies the application identifier of the organization that is removing the URI.
<b>uri</b>	<b>s:string</b>	Specifies the URI to remove.

### 3.1.4.5.2.2 tns:RemoveUriResponse Element

The **RemoveUriResponse** element specifies the response from the **RemoveUri** operation.

```
<xs:element name="RemoveUriResponse">
  <xs:complexType />
</xs:element>
```

### 3.1.4.6 ReserveDomain Operation

The **ReserveDomain** operation verifies that a specified **domain** is to be associated with an application identifier.

The following is the **WSDL port type** specification for the operation.

```
<wsdl:operation name="ReserveDomain">
  <wsdl:input message="tns:ReserveDomainSoapIn" />
  <wsdl:output message="tns:ReserveDomainSoapOut" />
</wsdl:operation>
```

The following is the **WSDL binding** specification for the operation.

```
<wsdl:operation name="ReserveDomain">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/ReserveDomain"
    style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

### 3.1.4.6.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>ReserveDomainSoapIn</b>	Specifies the <b>SOAP message</b> that requests that the <b>domain</b> be reserved.
<b>ReserveDomainSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

#### 3.1.4.6.1.1 tns:ReserveDomainSoapIn Message

The **ReserveDomainSoapIn WSDL message** specifies a request to reserve a **domain** with the federation management service.

```
<wsdl:message name="ReserveDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReserveDomain" />
</wsdl:message>
```

The **ReserveDomainSoapIn WSDL message** is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/ReserveDomain>.

The part of the **ReserveDomainSoapIn WSDL message** is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:ReserveDomain</b> (section <a href="#">3.1.4.6.2.1</a> )	Specifies the <b>SOAP body</b> of the request to reserve a domain.

#### 3.1.4.6.1.2 tns:ReserveDomainSoapOut Message

The **ReserveDomainSoapOut WSDL message** specifies the response from a request to reserve a **domain** with the federation management server.

```
<wsdl:message name="ReserveDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReserveDomainResponse" />
</wsdl:message>
```

The **ReserveDomainSoapOut** WSDL message is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/ReserveDomain>.

The part of the **ReserveDomainSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:ReserveDomainResponse</b> (section <a href="#">3.1.4.6.2.2</a> )	Specifies the <b>SOAP body</b> of the response from the operation.

### 3.1.4.6.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>ReserveDomain</b>	Specifies the information that is required to register a <b>domain</b> with a federation management service.
<b>ReserveDomainResponse</b>	Specifies the response from the <b>ReserveDomain</b> operation.

#### 3.1.4.6.2.1 tns:ReserveDomain Element

The **ReserveDomain** element specifies the information that is required to reserve a **domain** for federation management by using the **ReserveDomain** operation.

```
<xs:element name="ReserveDomain">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ownerAppId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="domainName"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
      <xs:element name="programId"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **ReserveDomain** element.

Element name	Type	Description
<b>ownerAppId</b>	<b>s:string</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the application identifier of the organization that wants to reserve the domain.
<b>domainName</b>	<b>s:string</b>	Specifies the domain name of the domain to reserve for federation management.
<b>programId</b>	<b>s:string</b>	Reserved for future use. <a href="#">&lt;3&gt;</a>

### 3.1.4.6.2.2 tns:ReserveDomainResponse Element

The **ReserveDomainResponse** element specifies the response from the **ReserveDomain** operation.

```
<xs:element name="ReserveDomainResponse">
  <xs:complexType />
</xs:element>
```

### 3.1.4.7 UpdateAppIdCertificate Operation

The **UpdateAppIdCertificate** operation updates the security certificate that is associated with an application identifier. After the certificate is updated, all subsequent calls to federation management operations use the new certificate for identification and encryption.

The following is the **WSDL port type** specification for the operation.

```
<wsdl:operation name="UpdateAppIdCertificate">
  <wsdl:input message="tns:UpdateAppIdCertificateSoapIn" />
  <wsdl:output message="tns:UpdateAppIdCertificateSoapOut" />
</wsdl:operation>
```

The following is the **WSDL** binding specification for the operation.

```
<wsdl:operation name="UpdateAppIdCertificate">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdCertificate"
    style="document" />
  <wsdl:input>
    <soap12:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

#### 3.1.4.7.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>UpdateAppIdCertificateSoapIn</b>	Specifies the <b>SOAP message</b> that requests that the security certificate be updated.
<b>UpdateAppIdCertificateSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

### 3.1.4.7.1.1 tns:UpdateAppIdCertificateSoapIn Message

The **UpdateAppIdCertificateSoapIn WSDL message** specifies a request to update the security certificate that is associated with an application identifier.

```
<wsdl:message name="UpdateAppIdCertificateSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificate" />
</wsdl:message>
```

The **UpdateAppIdCertificateSoapIn WSDL message** is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdCertificate>.

The part of the **UpdateAppIdCertificateSoapIn WSDL message** is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:UpdateAppIdCertificate</b> (section <a href="#">3.1.4.7.2.1</a> )	Specifies the <b>SOAP body</b> of a request to update the security certificate that is associated with an application identifier.

### 3.1.4.7.1.2 tns:UpdateAppIdCertificateSoapOut Message

The **UpdateAppIdCertificateSoapOut WSDL message** specifies the response from a request to update the security certificate associated with an application identifier.

```
<wsdl:message name="UpdateAppIdCertificateSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificateResponse" />
</wsdl:message>
```

The **UpdateAppIdCertificateSoapOut WSDL message** is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdCertificate>.

The part of the **UpdateAppIdCertificateSoapOut WSDL message** is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:UpdateAppIdCertificateResponse</b> (section <a href="#">3.1.4.7.2.2</a> )	Specifies the <b>SOAP body</b> of the response from the server.

### 3.1.4.7.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>UpdateAppIdCertificate</b>	Specifies the information that is required to update the security certificate with a federation management service.
<b>UpdateAppIdCertificateResponse</b>	Specifies the response from the <b>UpdateAppIdCertificate</b> operation.

### 3.1.4.7.2.1 tns:UpdateAppIdCertificate Element

The **UpdateAppIdCertificate** element specifies the authentication information and new certificate to replace the existing certificate for the **UpdateAppIdCertificate** operation.

```
<xs:element name="UpdateAppIdCertificate"
  maxOccurs="1"
  minOccurs="0"
  >
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
        />
      <xs:element name="appIdAdminKey"
        type="s:string"
        />
      <xs:element name="newCertificate"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
        />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **UpdateAppIdCertificate** element.

Element name	Type	Description
<b>appId</b>	<b>s:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the application identifier for the organization that is changing the security certificate that is associated with the application identifier.
<b>appIdAdminKey</b>	<b>s:string</b>	Specifies the administrative key that was associated with the application identifier when the application identifier was created.
<b>1. newCertificate</b>	<b>s:string</b>	Specifies the new security certificate as a string encoded with <b>base64 encoding</b> .

### 3.1.4.7.2.2 tns:UpdateAppIdCertificateResponse Element

The **UpdateAppIdCertificateResponse** element specifies the response from the **UpdateAppIdCertificate** operation.

```
<xs:element name="UpdateAppIdCertificateResponse">
```

```
<xs:complexType />
</xs:element>
```

### 3.1.4.8 UpdateAppIdProperties Operation

The **UpdateAppIdProperties** operation updates the additional information about an organization that is stored with the federation management service.

The following is the **WSDL port type** specification for the operation.

```
<wsdl:operation name="UpdateAppIdProperties">
  <wsdl:input message="tns:UpdateAppIdPropertiesSoapIn" />
  <wsdl:output message="tns:UpdateAppIdPropertiesSoapOut" />
</wsdl:operation>
```

The following is the **WSDL binding** specification for the operation.

```
<wsdl:operation name="UpdateAppIdProperties">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdProperties"
    style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

#### 3.1.4.8.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>UpdateAppIdPropertiesSoapIn</b>	Specifies the <b>SOAP message</b> that requests that the properties be updated.
<b>UpdateAppIdPropertiesSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

##### 3.1.4.8.1.1 tns:UpdateAppIdPropertiesSoapIn Message

The **UpdateAppIdPropertiesSoapIn** **WSDL message** identifies the application properties to update.

```
<wsdl:message name="UpdateAppIdPropertiesSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdProperties" />
</wsdl:message>
```

The **UpdateAppIdPropertiesSoapIn** WSDL message is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdProperties>.

The part of the **UpdateAppIdPropertiesSoapIn** WSDL message is described the following table.

Part name	Element/type	Description
parameters	<b>tns:UpdateAppIdProperties</b> (section <a href="#">3.1.4.8.2.1</a> )	Specifies the <b>SOAP body</b> that identifies the properties to modify.

### 3.1.4.8.1.2 tns:UpdateAppIdPropertiesSoapOut Message

The **UpdateAppIdPropertiesSoapOut** **WSDL message** specifies the response from a request to update application properties.

```
<wsdl:message name="UpdateAppIdPropertiesSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAppIdPropertiesResponse" />
</wsdl:message>
```

The **UpdateAppIdPropertiesSoapOut** WSDL message is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdProperties>.

The part of the **UpdateAppIdPropertiesSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	<b>tns:UpdateAppIdPropertiesResponse</b> (section <a href="#">3.1.4.8.2.2</a> )	Defines the <b>SOAP body</b> of the response.

### 3.1.4.8.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>UpdateAppIdProperties</b>	Specifies the information that is required to update the properties that are stored with a federation management service.
<b>UpdateAppIdPropertiesResponse</b>	Specifies the response from the <b>UpdateAppIdProperties</b> operation.

#### 3.1.4.8.2.1 tns:UpdateAppIdProperties Element

The **UpdateAppIdProperties** element specifies the organization properties to modify with the **UpdateAppIdProperties** operation.

```
<xs:element name="UpdateAppIdProperties">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="ownerAppId"
        type="s:string"
        maxOccurs="1"
        minOccurs="0"
      />
      <xs:element name="properties"
```

```

        type="tns:ArrayOfProperty"
        maxOccurs="1"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

The following table lists the child elements of the UpdateAppIdProperties element.

Element name	Type	Description
<b>ownerAppId</b>	<b>s:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the application identifier of the organization that is changing properties.
<b>properties</b>	<b>tns:ArrayOfProperty</b> (section <a href="#">2.2.4.1</a> )	Specifies one or more properties to modify.

### 3.1.4.8.2.2 tns:UpdateAppIdPropertiesResponse Element

The **UpdateAppIdPropertiesResponse** element specifies the response from the **UpdateAppIdProperties** operation.

```

<xs:element name="UpdateAppIdPropertiesResponse">
  <xs:complexType />
</xs:element>

```

### 3.1.5 Timer Events

None.

### 3.1.6 Other Local Events

None.

## 3.2 ManageDelegation2Soap Client Details

This client protocol is used by client applications to identify server applications and authenticate those server applications.

### 3.2.1 Abstract Data Model

This section contains a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that specified in this document.

This protocol is used by client applications to identify server applications and authenticate those server applications. It uses the standard Internet authentication techniques specified in [\[SAML\]](#), [\[WSFederation\]](#), [\[WSS\]](#), [\[WSTrust1.4\]](#), and [\[XMLDSig2\]](#) for that identification and authentication.

Clients that implement this protocol take the following steps to establish a relationship with the federation management service:

1. Create an application identifier by using the **CreateAppId** operation, as specified in section [3.2.4.2](#).
2. Create a **domain** identifier by hashing the **URI** of the domain and place the domain identifier on the domain's **DNS** server as a TXT record.
3. Reserve a **domain name** with the federation management service by using the **ReserveDomain** operation, as specified in section [3.2.4.6](#).
4. Register the URI that is associated with the domain with the federation management service by using the **AddUri** operation, as specified in section [3.2.4.1](#).

Clients can request and modify information stored with the federation management service by doing the following:

- Using the **GetDomainInfo** operation, as specified in section [3.2.4.3](#), to retrieve domain information from the federation management service.
- Modifying the information stored with the federation management service by using the **UpdateAppIdCertificate** operation, as specified in section [3.2.4.7](#), and the **UpdateAppIdProperties** operation, as specified in section [3.2.4.8](#).

Clients can end participation with the federation management service by doing the following:

- Using the **RemoveUri** operation, as specified in section [3.2.4.5](#), to remove a URI registered to the domain.
- Using the **ReleaseDomain** operation, as specified in section [3.2.4.4](#), to remove a registered domain from the federation management service.

### 3.2.2 Timers

None.

### 3.2.3 Initialization

Before calling this protocol, the client application requires the following:

- The URL of a service that provides a Federation Metadata Document, as specified in [\[WSFederation\]](#) section 3.1, with the fields and values as specified in section [3.3.<4>](#)
- The URL of a delegation management service that provides services as specified in section [3.2.4.<5>](#)
- A **DNS** TXT record containing a **domain** proof string, as specified in section [2.2.4.3](#), on the DNS server for the domain.

### 3.2.4 Message Processing Events and Sequencing Rules

This protocol uses the operations that are listed in the following table.

Operation name	Description
<b>AddUri</b>	Registers a <b>URI</b> with the federation management service.
<b>CreateAppId</b>	Creates an application identifier for an organization with the federation management

Operation name	Description
	service.
<b>GetDomainInfo</b>	Gets <b>domain</b> status information from the federation management service.
<b>ReleaseDomain</b>	Removes a domain from the federation management service.
<b>RemoveUri</b>	Removes a registered URI from the federation management service.
<b>ReserveDomain</b>	Verifies that a domain is managed by the specified application identifier.
<b>UpdateAppIdCertificate</b>	Updates the security certificate associated with an application identifier.
<b>UpdateAppIdProperties</b>	Updates the organizational information associated with an application identifier.

### 3.2.4.1 AddUri Operation

The **AddUri** operation registers the **URI** of an organization that participates in the federation management service.

The following is the **WSDL port type** specification of the operation.

```
<wsdl:operation name="AddUri">
  <wsdl:input message="tns:AddUriSoapIn" />
  <wsdl:output message="tns:AddUriSoapOut" />
</wsdl:operation>
```

The following is the **WSDL binding** specification of the operation.

```
<wsdl:operation name="AddUri">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/AddUri" style="document"
  />
  <wsdl:input>
    <soap12:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

The **AddUriDomainOwnershipProofHeader** message, as specified in section [3.2.4.1.1.1](#), and **AddUriSecurity** message, as specified in section [3.2.4.1.1.2](#), MUST be attached as **SOAP headers** to **AddUri** operation requests.

#### 3.2.4.1.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>AddUriDomainOwnershipProofHeader</b>	Specifies a <b>SOAP header</b> that authenticates <b>domain</b> ownership.
<b>AddUriSecurity</b>	Specifies a SOAP header that authenticates the request.

Message name	Description
<b>AddUriSoapIn</b>	Specifies the <b>SOAP message</b> that requests the application identifier.
<b>AddUriSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

### 3.2.4.1.1.1 tns:AddUriDomainOwnershipProofHeader Message

The **AddUriDomainOwnershipProofHeader WSDL message** specifies the **SOAP header** that identifies the requester as the owner of a **domain**.

```
<wsdl:message name="AddUriDomainOwnershipProofHeader">
  <wsdl:part name="DomainOwnershipProofHeader" element="tns:DomainOwnershipProofHeader" />
</wsdl:message>
```

The part of the **AddUriDomainOwnershipProofHeader WSDL message** is described in the following table.

Part name	Element/type	Description
<b>DomainOwnershipProofHeader</b>	<b>tns:DomainOwnershipProofHeader</b> (section <a href="#">2.2.3.1</a> )	Specifies the credentials that are required to prove ownership of a domain that is participating in a federation management service.

### 3.2.4.1.1.2 tns:AddUriSecurity Message

The **AddUriSecurity WSDL message** specifies the **SOAP header** that authenticates a request to register a **URI** with the federation management service.

```
<wsdl:message name="AddUriSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **AddUriSecurity WSDL message** is described in the following table.

Part name	Element/type	Description
<b>Security</b>	<b>s:Security</b> (section <a href="#">2.2.3.2</a> )	Specifies the SOAP header that contains the security elements needed to authenticate the request.

### 3.2.4.1.1.3 tns:AddUriSoapIn Message

The **AddUriSoapIn WSDL message** specifies the **SOAP message** that represents a request to register a **URI** with the federation management service.

```
<wsdl:message name="AddUriSoapIn">
```

```
<wsdl:part name="parameters" element="tns:AddUri" />
</wsdl:message>
```

The **AddUriSoapIn** WSDL message is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/AddUri>.

The part of the **AddUriSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:AddUri</b> (section <a href="#">3.2.4.1.2.1</a> )	Specifies the <b>SOAP body</b> of the request to register a URI with the federation management service.

### 3.2.4.1.1.4 tns:AddUriSoapOut Message

The **AddUriSoapOut** **WSDL message** specifies the **SOAP message** that represents a response from a request to register a **URI** with the federation management service.

```
<wsdl:message name="AddUriSoapOut">
  <wsdl:part name="parameters" element="tns:AddUriResponse" />
</wsdl:message>
```

The **AddUriSoapOut** WSDL message is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/AddUri>.

The part of the **AddUriSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:AddUriResponse</b> (section <a href="#">3.2.4.1.2.2</a> )	Specifies the <b>SOAP body</b> of the response.

### 3.2.4.1.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>AddUri</b>	Specifies the <b>URI</b> that is to be added to the federation management service.
<b>AddUriResponse</b>	Specifies the response from <b>AddUri</b> operation.

#### 3.2.4.1.2.1 tns:AddUri Element

The **AddUri** element specifies the **URI** that is to be added to the federation management service by the **AddUri** operation.

```
<xs:element name="AddUri">
  <xs:complexType>
    <xs:sequence>
```

```

    <xs:element name="appId"
      type="s:string"
      minOccurs="0"
      maxOccurs="1"
    />
    <xs:element name="uri"
      type="s:string"
      maxOccurs="1"
      minOccurs="0"
    />
  </xs:sequence>
</xs:complexType>
</xs:element>

```

The following table lists the child elements of the **AddUri** element.

Element name	Type	Description
<b>appId</b>	<b>s:string</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the application identifier that is assigned to the entity requesting that the URI be registered with a federation management service.
<b>uri</b>	<b>s:string</b>	Specifies the URI to register with the federation management service.

### 3.2.4.1.2.2 tns:AddUriResponse Element

The **AddUriResponse** element specifies the response from the **AddUri** operation.

```

<xs:element name="AddUriResponse">
  <xs:complexType />
</xs:element>

```

### 3.2.4.2 CreateAppId Operation

The **CreateAppId** operation creates an identifier for an organization that participates in a federation management service. The identifier that is returned by the **CreateAppId** operation is used when calling operations on the federation management server to identify the organization that is making the request.

The following is the **WSDL port type** specification for the operation.

```

<wsdl:operation name="CreateAppId">
  <wsdl:input message="tns:CreateAppIdSoapIn" />
  <wsdl:output message="tns:CreateAppIdSoapOut" />
</wsdl:operation>

```

The following is the **WSDL binding** specification for the operation.

```

<wsdl:operation name="CreateAppId">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/CreateAppId"
    style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
</wsdl:operation>

```

```

</wsdl:input>
<wsdl:output>
  <soap:body use="literal" />
</wsdl:output>
</wsdl:operation>

```

The **CreateAppIdDomainOwnershipProofHeader** message, as specified in section [3.2.4.2.1.1](#), and **CreateAppIdSecurity** message, as specified in section [3.2.4.2.1.2](#)), MUST be attached as SOAP headers to **CreateAppId** operation requests.

### 3.2.4.2.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message	Description
<b>CreateAppIdDomainOwnershipProofHeader</b>	Specifies a <b>SOAP header</b> that authenticates <b>domain</b> ownership.
<b>CreateAppIdSecurity</b>	Specifies a SOAP header that authenticates the request.
<b>CreateAppIdSoapIn</b>	Specifies the <b>SOAP message</b> that requests the application identifier.
<b>CreateAppIdSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

#### 3.2.4.2.1.1 tns:CreateAppIdDomainOwnershipProofHeader Message

The **CreateAppIdDomainOwnershipProofHeader** **WSDL message** specifies the **SOAP header** that identifies the requester as the owner of a **domain**.

```

<wsdl:message name="CreateAppIdDomainOwnershipProofHeader">
  <wsdl:part name="DomainOwnershipProofHeader" element="DomainOwnershipProofHeader" />
</wsdl:message>

```

The part of the **CreateAppIdDomainOwnershipProofHeader** WSDL message is described in the following table.

Part name	Element/type	Description
<b>DomainOwnershipProofHeader</b>	<b>tns:DomainOwnershipProofHeader</b> (section <a href="#">2.2.4.3</a> )	Specifies the SOAP header that contains the credentials that are required to prove ownership of a domain that is participating in a federation management service.

#### 3.2.4.2.1.2 tns:CreateAppIdSecurity Message

The **CreateAppIdSecurity** **WSDL message** specifies the **SOAP header** that authenticates a request to create an application identifier with the federation management service.

```
<wsdl:message name="CreateAppIdSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **CreateAppIdSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
<b>Security</b>	<b>s:Security</b> (section <a href="#">2.2.3.2</a> )	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

### 3.2.4.2.1.3 tns:CreateAppIdSoapIn Message

The **CreateAppIdSoapIn** WSDL message specifies the **SOAP message** that represents a request to create an application identifier with the federation management service.

```
<wsdl:message name="CreateAppIdSoapIn">
  <wsdl:part name="parameters" element="tns:CreateAppId" />
</wsdl:message>
```

The **CreateAppIdSoapIn** WSDL message is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/CreateAppId>.

The part of the **CreateAppIdSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:CreateAppId</b> (section <a href="#">3.2.4.2.2.1</a> )	Specifies the <b>SOAP body</b> of the request to create an application identifier.

### 3.2.4.2.1.4 tns:CreateAppIdSoapOut Message

The **CreateAppIdSoapOut** WSDL message specifies the **SOAP message** that represents a response to a request to create an identifier for an organization that participates in a federation management service.

```
<wsdl:message name="CreateAppIdSoapOut">
  <wsdl:part name="parameters" element="tns:CreateAppIdResponse" />
</wsdl:message>
```

The **CreateAppIdSoapOut** WSDL message is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/CreateAppId>.

The part of the **CreateAppIdSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:CreateAppIdResponse</b> (section <a href="#">3.2.4.2.2.2</a> )	Specifies the <b>SOAP body</b> of the response.

### 3.2.4.2.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>CreateAppId</b>	Specifies the information that is required to establish a relationship with a federation management service.
<b>CreateAppIdResponse</b>	Specifies the response from the <b>CreateAppId</b> operation that contains an application identifier.

#### 3.2.4.2.2.1 tns:CreateAppId Element

The **CreateAppId** element specifies the information that is required to establish a relationship with a federation management service.

```
<xs:element name="CreateAppId">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="uri"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="properties"
        type="tns:ArrayOfProperty"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **CreateAppId** element.

Element name	Type	Description
<b>uri</b>	<b>s:string</b> ( <a href="#">IXMLSCHEMA21</a> )	Specifies the <b>URI</b> that identifies the entity requesting an application identifier.
<b>properties</b>	<b>tns:ArrayOfProperty</b> (section <a href="#">2.2.4.1</a> )	Specifies additional information about the organization. Can be present.

#### 3.2.4.2.2.2 tns:CreateAppIdResponse Element

The **CreateAppIdResponse** element specifies the response from the **CreateAppId** operation that contains the application identifier.

```
<xs:element name="CreateAppIdResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="CreateAppIdResult"
```

```

        type="tns:AppIdInfo"
        maxOccurs="1"
        minOccurs="0"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>

```

The following table lists the child elements of the **CreateAppIdResponse** element.

Element name	Type	Description
<b>CreateAppIdResult</b>	<b>tns:AppIdInfo</b> (section <a href="#">3.2.4.2.3.1</a> )	Specifies the application identifier. Can be present.

### 3.2.4.2.3 Complex Types

The following table summarizes the **XML schema** complex type definitions that are specific to this operation.

Complex Type name	Description
<b>AppIdInfo</b>	Specifies an application identifier.

#### 3.2.4.2.3.1 t:AppIdInfo Complex Type

The **AppIdInfo** complex type specifies an application identifier.

```

<xs:complexType name="AppIdInfo">
  <xs:sequence>
    <xs:element name="AppId"
      type="s:string"
      minOccurs="0"
      maxOccurs="1"
    />
  </xs:sequence>
</xs:complexType>

```

The following table lists the child elements of the **AppIdInfo** complex type.

Element name	Type	Description
<b>AppId</b>	<b>s:string</b> [ <a href="#">XMLSCHEMA2</a> ]	Specifies an application identifier. Can be present.

### 3.2.4.3 GetDomainInfo Operation

The **GetDomainInfo** operation retrieves federation status information for a **domain**.

The following is the **WSDL port type** specification for the operation.

```
<wsdl:operation name="GetDomainInfo">
  <wsdl:input message="tns:GetDomainInfoSoapIn" />
  <wsdl:output message="tns:GetDomainInfoSoapOut" />
</wsdl:operation>
```

The following is the **WSDL binding** specification for the operation.

```
<wsdl:operation name="GetDomainInfo">
  <soap:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/GetDomainInfo"
    style="document" />
  <wsdl:input>
    <soap:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

The **GetDomainInfoSecurity** message, as specified in section [3.2.4.3.1.1](#), MUST be attached as a SOAP header to **GetDomainInfo** operation requests.

### 3.2.4.3.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>GetDomainInfoSecurity</b>	Specifies a <b>SOAP header</b> that authenticates the request.
<b>GetDomainInfoSoapIn</b>	Specifies the <b>SOAP message</b> that requests the <b>domain</b> information.
<b>GetDomainInfoSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

#### 3.2.4.3.1.1 tns:GetDomainInfoSecurity Message

The **GetDomainSecurity** **WSDL message** specifies the **SOAP header** that authenticates a request for **domain** information from the federation management service.

```
<wsdl:message name="GetDomainInfoSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **GetDomainSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
<b>Security</b>	<b>s:Security</b> (section <a href="#">2.2.3.2</a> )	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

### 3.2.4.3.1.2 tns:GetDomainInfoSoapIn Message

The **GetDomainInfoSoapIn WSDL message** specifies the **SOAP message** that represents a request for **domain** information from the federation management service.

```
<wsdl:message name="GetDomainInfoSoapIn">
  <wsdl:part name="parameters" element="tns:GetDomainInfo" />
</wsdl:message>
```

The **GetDomainInfoSoapIn** WSDL message is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/GetDomainInfo>.

The part of the **GetDomainInfoSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	<b>tns:GetDomainInfo</b> (section <a href="#">3.2.4.3.2.1</a> )	Specifies the SOAP body of the request for domain information.

### 3.2.4.3.1.3 tns:GetDomainInfoSoapOut Message

The **GetDomainInfoSoapOut WSDL message** specifies the **SOAP message** that represents a response to a request for **domain** information from a federation management service.

```
<wsdl:message name="GetDomainInfoSoapOut">
  <wsdl:part name="parameters" element="tns:GetDomainInfoResponse" />
</wsdl:message>
```

The **GetDomainInfoSoapOut** WSDL message is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/GetDomainInfo>.

The part of the **GetDomainInfoSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	<b>tns:GetDomainInfoResponse</b> (section <a href="#">3.2.4.3.2.2</a> )	Specifies the <b>SOAP body</b> of the response from the server.

### 3.2.4.3.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>GetDomainInfo</b>	Specifies the information that is required to request <b>domain</b> information from federation management service.
<b>GetDomainInfoResponse</b>	Specifies the response from the <b>GetDomainInfo</b> operation.

### 3.2.4.3.2.1 tns:GetDomainInfo Element

The **GetDomainInfo** element specifies the information that is required to request **domain** information from a federation management service.

```
<xs:element name="GetDomainInfo">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="domainName"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **GetDomainInfo** element.

Element name	Type	Description
<b>appId</b>	<b>s:string</b> ( <a href="#">IXMLSCHEMA21</a> )	Specifies the application identifier assigned to the organization by the federation management service. Can be present.
<b>domainName</b>	<b>s:string</b>	Specifies the domain for which information is requested. Can be present.

### 3.2.4.3.2.2 tns:GetDomainInfoResponse Element

The **GetDomainInfoResponse** element specifies the response from the **GetDomainInfo** operation that contains the application identifier.

```
<xs:element name="GetDomainInfoResponse">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="GetDomainInfoResult"
        type="tns:DomainInfo"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **GetDomainInfoResponse** element.

Element name	Type	Description
<b>GetDomainInfoResult</b>	<b>tns:DomainInfo</b> (section <a href="#">2.2.4.2</a> )	Specifies the <b>domain</b> status information.

Element name	Type	Description
		Can be present.

### 3.2.4.4 ReleaseDomain Operation

The **ReleaseDomain** operation releases the specified **domain** from federation management services.

The following is **WSDL port type** specification for the operation.

```
<wsdl:operation name="ReleaseDomain">
  <wsdl:input message="tns:ReleaseDomainSoapIn" />
  <wsdl:output message="tns:ReleaseDomainSoapOut" />
</wsdl:operation>
```

The following is the **WSDL** binding specification for the operation.

```
<wsdl:operation name="ReleaseDomain">
  <soap12:operation
  soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/ReleaseDomain"
  style="document" />
  <wsdl:input>
    <soap12:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

The **ReleaseDomainSecurity** message, as specified in section [3.2.4.4.1.1](#), MUST be attached as a **SOAP header** to **ReleaseDomain** operation requests.

#### 3.2.4.4.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>ReleaseDomainSecurity</b>	Specifies a <b>SOAP header</b> that authenticates the request.
<b>ReleaseDomainSoapIn</b>	Specifies the <b>SOAP message</b> that requests the <b>domain</b> information.
<b>ReleaseDomainSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

##### 3.2.4.4.1.1 tns:ReleaseDomainSecurity Message

The **ReleaseDomainSecurity** **WSDL message** specifies the **SOAP header** that authenticates a request to release a domain from the federation management service.

```
<wsdl:message name="ReleaseDomainSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **ReleaseDomainSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
<b>Security</b>	<b>s:Security</b> (section <a href="#">2.2.3.2</a> )	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

### 3.2.4.4.1.2 tns:ReleaseDomainSoapIn Message

The **ReleaseDomainSoapIn** WSDL message specifies the **SOAP message** that represents a request to release a **domain** from the federation management service.

```
<wsdl:message name="ReleaseDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReleaseDomain" />
</wsdl:message>
```

The **ReleaseDomainSoapIn** WSDL message is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/ReleaseDomain>.

The part of the **ReleaseDomainSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:ReleaseDomain</b> (section <a href="#">3.2.4.4.2.1</a> )	Specifies the <b>SOAP body</b> the request to release a domain from the federation management service.

### 3.2.4.4.1.3 tns:ReleaseDomainSoapOut Message

The **ReleaseDomainSoapOut** WSDL message specifies the **SOAP message** that represents a response to a request to release a **domain** from federation management service.

```
<wsdl:message name="ReleaseDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReleaseDomainResponse" />
</wsdl:message>
```

The **ReleaseDomainSoapOut** WSDL message is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/ReleaseDomain>.

The part of the **ReleaseDomainSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:ReleaseDomainResponse</b> (section <a href="#">3.2.4.4.2.2</a> )	Specifies the <b>SOAP body</b> of the response from the server.

### 3.2.4.4.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>ReleaseDomain</b>	Specifies the information that is required to release a <b>domain</b> from federation management service.
<b>ReleaseDomainResponse</b>	Specifies the response from the <b>ReleaseDomain</b> operation.

### 3.2.4.4.2.1 tns:ReleaseDomain Element

The **ReleaseDomain** element specifies the information that is required to release a **domain** from federation management service.

```
<xs:element name="ReleaseDomain">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="domainName"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **ReleaseDomain** element.

Element name	Type	Description
<b>appId</b>	<b>s:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the application identifier assigned to the organization by the federation management service. Can be present.
<b>domainName</b>	<b>s:string</b>	Specifies the domain to be released. Can be present.

### 3.2.4.4.2.2 tns:ReleaseDomainResponse Element

The **ReleaseDomainResponse** element specifies the response from the **ReleaseDomain** operation.

```
<xs:element name="ReleaseDomainResponse">
  <xs:complexType />
</xs:element>
```

### 3.2.4.5 RemoveUri Operation

The **RemoveUri** operation removes a previously registered **URI** from the federation management service.

The following is the **WSDL port type** specification for the operation.

```
<wsdl:operation name="RemoveUri">
  <wsdl:input message="tns:RemoveUriSoapIn" />
  <wsdl:output message="tns:RemoveUriSoapOut" />
</wsdl:operation>
```

The following is the **WSDL binding** specification for the operation.

```
<wsdl:operation name="RemoveUri">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/RemoveUri"
    style="document" />
  <wsdl:input>
    <soap12:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

The **RemoveUriSecurity** message, as specified in section [3.2.4.5.1.1](#), MUST be attached as a **SOAP header** to **RemoveUri** operation requests.

### 3.2.4.5.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>RemoveUriSecurity</b>	Specifies a <b>SOAP header</b> that authenticates the request.
<b>RemoveUriSoapIn</b>	Specifies the <b>SOAP message</b> that requests the <b>URI</b> be removed.
<b>RemoveUriSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

#### 3.2.4.5.1.1 tns:RemoveUriSecurity Message

The **RemoveUriSecurity** **WSDL message** specifies the **SOAP header** that authenticates a request to remove a **URI** from the federation management service.

```
<wsdl:message name="RemoveUriSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **RemoveUriSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
<b>Security</b>	<b>s:Security</b> (section <a href="#">2.2.3.2</a> )	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

### 3.2.4.5.1.2 tns:RemoveUriSoapIn Message

The **RemoveUriSoapIn WSDL message** specifies the **SOAP message** that represents a request to remove a **URI** from the federation management service.

```
<wsdl:message name="RemoveUriSoapIn">
  <wsdl:part name="parameters" element="tns:RemoveUri" />
</wsdl:message>
```

The **RemoveUriSoapIn WSDL message** is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/RemoveUri>.

The part of the **RemoveUriSoapIn WSDL message** is described in the following table.

Part name	Element/type	Description
parameters	<b>tns:RemoveUri</b> (section <a href="#">3.2.4.5.2.1</a> )	Specifies the <b>SOAP body</b> of the request to remove the URI from the federation management service.

### 3.2.4.5.1.3 tns:RemoveUriSoapOut Message

The **RemoveUriSoapOut WSDL message** specifies the **SOAP message** that represents a response to a request to remove a **URI** from federation management service.

```
<wsdl:message name="RemoveUriSoapOut">
  <wsdl:part name="parameters" element="tns:RemoveUriResponse" />
</wsdl:message>
```

The **RemoveUriSoapOut WSDL message** is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/RemoveUri>.

The part of the **RemoveUriSoapOut WSDL message** is described in the following table.

Part name	Element/type	Description
parameters	<b>tns:RemoveUriResponse</b> (section <a href="#">3.2.4.5.2.2</a> )	Specifies the <b>SOAP body</b> of the response from the server.

### 3.2.4.5.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>RemoveUri</b>	Specifies the information that is required to remove a <b>URI</b> from federation management service.
<b>RemoveUriResponse</b>	Specifies the response from the <b>RemoveUri</b> operation.

### 3.2.4.5.2.1 tns:RemoveUri Element

The **RemoveUri** element specifies the information that is required to remove a **URI** from federation management service.

```
<xs:element name="RemoveUri">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="uri"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **RemoveUri** element.

Element name	Type	Description
<b>appId</b>	<b>s:string</b> ( <a href="#">XMLSCHEMA21</a> )	Specifies the application identifier assigned to the organization by the federation management service. Can be present.
<b>uri</b>	<b>s:string</b>	Specifies the URI to be removed. Can be present.

### 3.2.4.5.2.2 tns:RemoveUriResponse Element

The **RemoveUriResponse** element specifies the response from the **RemoveUri** operation.

```
<xs:element name="RemoveUriResponse">
  <xs:complexType />
</xs:element>
```

### 3.2.4.6 ReserveDomain Operation

The **ReserveDomain** operation verifies that a specified **domain** is to be associated with an application identifier.

The following is the **WSDL port type** specification for the operation.

```
<wsdl:operation name="ReserveDomain">
  <wsdl:input message="tns:ReserveDomainSoapIn" />
  <wsdl:output message="tns:ReserveDomainSoapOut" />
</wsdl:operation>
```

The following is the **WSDL** binding specification for the operation.

```
<wsdl:operation name="ReserveDomain">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/ReserveDomain"
    style="document" />
  <wsdl:input>
    <soap12:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

The **ReserveDomainDomainOwnershipProofHeader** message, as specified in section [3.2.4.6.1.1](#), and the **ReserveDomainSecurity** message, as specified in section [3.2.4.6.1.2](#), MUST be attached as **SOAP headers** to **ReserveDomain** operation requests.

### 3.2.4.6.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>ReserveDomainDomainOwnershipProofHeader</b>	Specifies a <b>SOAP header</b> that authenticates <b>domain</b> ownership.
<b>ReserveDomainSecurity</b>	Specifies a SOAP header that authenticates the request.
<b>ReserveDomainSoapIn</b>	Specifies the <b>SOAP message</b> that requests the domain be reserved.
<b>ReserveDomainSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

#### 3.2.4.6.1.1 tns:ReserveDomainDomainOwnershipProofHeader Message

The **ReserveDomainDomainOwnershipProofHeader** **WSDL message** specifies the **SOAP header** that identifies the requester as the owner of a **domain**.

```
<wsdl:message name="ReserveDomainDomainOwnershipProofHeader">
  <wsdl:part name="DomainOwnershipProofHeader" element="tns:DomainOwnershipProofHeader" />
</wsdl:message>
```

The part of the **ReserveDomainDomainOwnershipProofHeader** WSDL message is described in the following table.

Part name	Element/type	Description
<b>DomainOwnershipProofHeader</b>	<b>tns:DomainOwnershipProofHeader</b> (section <a href="#">2.2.3.1</a> )	Specifies the SOAP header that contains the credentials that are required to prove ownership of a domain that is participating in a federation management service.

### 3.2.4.6.1.2 tns:ReserveDomainSecurity Message

The **ReserveDomainSecurity WSDL message** specifies the **SOAP header** that authenticates a request to reserve a **domain** with the federation management service.

```
<wsdl:message name="ReserveSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **ReserveSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
<b>Security</b>	<b>s:Security</b> (section <a href="#">2.2.3.2</a> )	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

### 3.2.4.6.1.3 tns:ReserveDomainSoapIn Message

The **ReserveDomainSoapIn WSDL message** specifies the **SOAP message** that represents a request to register a **domain** with the federation management service.

```
<wsdl:message name="ReserveDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReserveDomain" />
</wsdl:message>
```

The **ReserveDomainSoapIn** WSDL message is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/ReserveDomain>.

The part of the **ReserveDomainSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:ReserveDomain</b> (section <a href="#">3.2.4.6.2.1</a> )	Specifies the <b>SOAP body</b> of the request to register a domain with the federation management service.

### 3.2.4.6.1.4 tns:ReserveDomainSoapOut Message

The **ReserveDomainSoapOut WSDL message** specifies the **SOAP message** that represents a response to a request to register a **domain** with the federation management service.

```
<wsdl:message name="ReserveDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReserveDomainResponse" />
</wsdl:message>
```

The **ReserveDomainSoapOut** WSDL message is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/ReserveDomain>.

The part of the **ReserveDomainSoapOut** WSDL message is described in the following table.

Part name	Element/type	Description
parameters	<b>tns:ReserveDomainResponse</b> (section <a href="#">3.2.4.6.2.2</a> )	Specifies the <b>SOAP body</b> of the response from the server.

### 3.2.4.6.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>ReserveDomain</b>	Specifies the information that is required to register a <b>domain</b> with a federation management service.
<b>ReserveDomainResponse</b>	Specifies the response from the <b>ReserveDomain</b> operation.

#### 3.2.4.6.2.1 tns:ReserveDomain Element

The **ReserveDomain** element specifies the information that is required to reserve a **domain** with a federation management service.

```
<xs:element name="ReserveDomain">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="domainName"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="programId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **ReserveDomain** element.

Element name	Type	Description
<b>appId</b>	<b>s:string</b> ( <a href="#">XMLSCHEMA2</a> )	Specifies the application identifier assigned to the organization by the federation management service. Can be present.
<b>domainName</b>	<b>s:string</b>	Specifies the domain that is to be registered. Can be present.

Element name	Type	Description
<b>programId</b>	<b>s:string</b>	Reserved for future use. <a href="#">&lt;6&gt;</a> Can be present.

### 3.2.4.6.2.2 tns:ReserveDomainResponse Element

The **ReserveDomainResponse** element specifies the response from the **ReserveDomain** operation.

```
<xs:element name="ReserveDomainResponse">
  <xs:complexType />
</xs:element>
```

### 3.2.4.7 UpdateAppIdCertificate Operation

The **UpdateAppIdCertificate** operation updates the security certificate that is associated with an application identifier. After the certificate is updated, all subsequent calls to federation management operations use the new certificate for identification and encryption.

The following is the **WSDL port type** specification for the operation.

```
<wsdl:operation name="UpdateAppIdCertificate">
  <wsdl:input message="tns:UpdateAppIdCertificate SoapIn" />
  <wsdl:output message="tns:UpdateAppIdCertificate SoapOut" />
</wsdl:operation>
```

The following is the **WSDL binding** specification for the operation.

```
<wsdl:operation name="UpdateAppIdCertificate">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/UpdateAppIdCertificate"
    style="document" />
  <wsdl:input>
    <soap12:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

The **UpdateAppIdCertificateSecurity** message, as specified in section [3.2.4.7.1.1](#), MUST be attached as a **SOAP header** to **UpdateAppIdCertificate** operation requests.

#### 3.2.4.7.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>UpdateAppIdCertificateSecurity</b>	Specifies a <b>SOAP header</b> that authenticates the request.

Message name	Description
<b>UpdateAppIdCertificateSoapIn</b>	Specifies the <b>SOAP message</b> that requests the security certificate be updated.
<b>UpdateAppIdCertificateSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

### 3.2.4.7.1.1 tns:UpdateAppIdCertificateSecurity Message

The **UpdateAppIdCertificateSecurity WSDL message** specifies the **SOAP header** that authenticates a request to update the security certificate of the federation management service.

```
<wsdl:message name="UpdateAppIdCertificateSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **UpdateAppIdCertificateSecurity WSDL message** is described in the following table.

Part name	Element/type	Description
<b>Security</b>	<b>s:Security</b> (section <a href="#">2.2.3.2</a> )	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

### 3.2.4.7.1.2 tns:UpdateAppIdCertificateSoapIn Message

The **UpdateAppIdCertificateSoapIn WSDL message** specifies the **SOAP message** that represents a request to update the security certificate with the federation management service.

```
<wsdl:message name="UpdateAppIdCertificateSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificate" />
</wsdl:message>
```

The **UpdateAppIdCertificateSoapIn WSDL message** is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/UpdateAppIdCertificate>.

The part of the **UpdateAppIdCertificateSoapIn WSDL message** is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:UpdateAppIdCertificate</b> (section <a href="#">3.2.4.7.2.1</a> ).	Specifies the <b>SOAP body</b> of the request to update the security certificate with the federation management service.

### 3.2.4.7.1.3 tns:UpdateAppIdCertificateSoapOut Message

The **UpdateAppIdCertificateSoapOut WSDL message** specifies the **SOAP message** that represents a response to a request to remove a **URI** from federation management service.

```
<wsdl:message name="UpdateAppIdCertificateSoapOut">
```

```
<wsdl:part name="parameters" element="tns:UpdateAppIdCertificateResponse" />
</wsdl:message>
```

The **UpdateAppIdCertificateSoapOut** WSDL message is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/UpdateAppIdCertificate>.

The **UpdateAppIdCertificateSoapOut** WSDL message specifies one part, as described in the following table.

Part name	Element/type	Description
parameters	<b>tns:UpdateAppIdCertificateResponse</b> (section <a href="#">3.2.4.7.2.2</a> ).	Specifies <b>SOAP body</b> of the response from the server.

### 3.2.4.7.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>UpdateAppIdCertificate</b>	Specifies the information that is required to update the security certificate with a federation management service.
<b>UpdateAppIdCertificateResponse</b>	Specifies the response from the <b>UpdateAppIdCertificate</b> operation (section <a href="#">3.2.4.7</a> ).

#### 3.2.4.7.2.1 tns:UpdateAppIdCertificate Element

The **UpdateAppIdCertificate** element specifies the information that is required update a security certificate with a federation management service.

```
<xs:element name="UpdateAppIdCertificate">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="newCertificate"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **UpdateAppIdCertificate** element.

Element name	Type	Description
<b>appId</b>	<b>s:string</b> ( <a href="#">XMLSCHEMA21</a> )	Specifies the application identifier assigned to the organization by the federation management service. Can be present.
<b>newCertificate</b>	<b>s:string</b>	Specifies the new security certificate as a string encoded with <b>base64 encoding</b> . Can be present.

### 3.2.4.7.2 tns:UpdateAppIdCertificateResponse Element

The **UpdateAppIdCertificateResponse** element specifies the response from the **UpdateAppIdCertificate** operation.

```
<xs:element name="UpdateAppIdCertificateResponse">
  <xs:complexType />
</xs:element>
```

### 3.2.4.8 UpdateAppIdProperties Operation

The **UpdateAppIdProperties** operation updates the additional information about an organization that is stored with the federation management service.

The following is the **WSDL port type** specification for the operation.

```
<wsdl:operation name="UpdateAppIdProperties">
  <wsdl:input message="tns:UpdateAppIdPropertiesSoapIn" />
  <wsdl:output message="tns:UpdateAppIdPropertiesSoapOut" />
</wsdl:operation>
```

The following is the **WSDL binding** specification for the operation.

```
<wsdl:operation name="UpdateAppIdProperties">
  <soap12:operation
    soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/UpdateAppIdProperties"
    style="document" />
  <wsdl:input>
    <soap12:body use="literal" />
  </wsdl:input>
  <wsdl:output>
    <soap12:body use="literal" />
  </wsdl:output>
</wsdl:operation>
```

The **UpdateAppIdPropertiesSecurity** message, as specified in section [3.2.4.8.1.1](#), MUST be attached as a **SOAP header** to **UpdateAppIdProperties** operation requests.

#### 3.2.4.8.1 Messages

The following table summarizes the set of **WSDL message** definitions that are specific to this operation.

Message name	Description
<b>UpdateAppIdPropertiesSecurity</b>	Specifies a <b>SOAP header</b> that authenticates the request.
<b>UpdateAppIdPropertiesSoapIn</b>	Specifies the <b>SOAP message</b> that requests the properties be updated.
<b>UpdateAppIdPropertiesSoapOut</b>	Specifies the SOAP message that is returned by the server in response.

### 3.2.4.8.1.1 tns:UpdateAppIdPropertiesSecurity Message

The **UpdateAppIdPropertiesSecurity WSDL message** specifies the **SOAP header** that authenticates a request to update the security certificate of the federation management service.

```
<wsdl:message name="UpdateAppIdPropertiesSecurity">
  <wsdl:part name="Security" element="s:Security" />
</wsdl:message>
```

The part of the **UpdateAppIdPropertiesSecurity** WSDL message is described in the following table.

Part name	Element/type	Description
<b>Security</b>	<b>s:Security</b> (section <a href="#">2.2.3.2</a> )	Specifies the SOAP header that contains the security elements that are needed to authenticate the request.

### 3.2.4.8.1.2 tns:UpdateAppIdPropertiesSoapIn Message

The **UpdateAppIdPropertiesSoapIn WSDL message** specifies the **SOAP message** that represents a request to register a domain with the federation management service.

```
<wsdl:message name="UpdateAppIdPropertiesSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdProperties" />
</wsdl:message>
```

The **UpdateAppIdPropertiesSoapIn** WSDL message is the input message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/UpdateAppIdProperties>.

The part of the **UpdateAppIdPropertiesSoapIn** WSDL message is described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:UpdateAppIdProperties</b> (section <a href="#">3.2.4.8.2.1</a> )	Specifies the <b>SOAP body</b> of the request containing the properties to modify.

### 3.2.4.8.1.3 tns:UpdateAppIdPropertiesSoapOut Message

The **UpdateAppIdPropertiesSoapOut WSDL message** specifies the **SOAP message** that represents a response to a request to remove a URI from federation management service.

```
<wsdl:message name="UpdateAppIdPropertiesSoapOut">
```

```
<wsdl:part name="parameters" element="tns:UpdateAppIdPropertiesResponse" />
</wsdl:message>
```

The **UpdateAppIdPropertiesSoapOut** WSDL message is the output message for the **SOAP action** <http://domains.live.com/Service/ManageDelegation2/V1.0/UpdateAppIdProperties>.

The **UpdateAppIdPropertiesSoapOut** WSDL message specifies one part, as described in the following table.

Part name	Element/type	Description
<b>parameters</b>	<b>tns:UpdateAppIdPropertiesResponse</b> (section <a href="#">3.2.4.8.2.2</a> )	Specifies the <b>SOAP body</b> of the response from the server.

### 3.2.4.8.2 Elements

The following table summarizes the **XML schema** element definitions that are specific to this operation.

Element name	Description
<b>UpdateAppIdProperties</b>	Specifies the information that is required to update the properties stored with a federation management service.
<b>UpdateAppIdPropertiesResponse</b>	Specifies the response from the <b>UpdateAppIdProperties</b> operation.

#### 3.2.4.8.2.1 tns:UpdateAppIdProperties Element

The **UpdateAppIdProperties** element specifies organization properties to modify with a federation management service.

```
<xs:element name="UpdateAppIdProperties">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="appId"
        type="s:string"
        minOccurs="0"
        maxOccurs="1"
      />
      <xs:element name="properties"
        type="tns:ArrayOfProperty"
        minOccurs="0"
        maxOccurs="1"
      />
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The following table lists the child elements of the **UpdateAppIdProperties** element.

Element name	Type	Description
<b>appId</b>	<b>s:string</b> ( <a href="#">[XMLSCHEMA2]</a> )	Specifies the application identifier assigned to the organization by the federation management service. Can be present.
<b>properties</b>	<b>tns:ArrayOfProperty</b> (section <a href="#">2.2.4.1</a> )	Specifies one or more properties to modify. Can be present.

### 3.2.4.8.2 tns:UpdateAppIdPropertiesResponse Element

The **UpdateAppIdPropertiesResponse** element specifies the response from the **UpdateAppIdProperties** operation.

```
<xs:element name="UpdateAppIdPropertiesResponse">
  <xs:complexType />
</xs:element>
```

### 3.2.5 Timer Events

None.

### 3.2.6 Other Local Events

None.

## 3.3 Federation Metadata Client Details

The Federated Internet Authentication Web Service Protocol uses elements from the Federation Metadata XML Document, as specified in [\[WSFederation\]](#).

The following table lists the **XML** elements and element values that the protocol uses from the Federation Metadata Document.

Element name	Description
<b>FederationMetadata</b>	MUST be present. MUST contain at least one <b>Federation</b> element.
<b>Federation</b>	MUST be present. MUST contain at least one of each of the following elements: <ul style="list-style-type: none"> <li>▪ <b>TokenSigningKeyInfo</b></li> <li>▪ <b>IssuerNamesOffered</b></li> <li>▪ <b>TargetServiceEndpoints</b></li> <li>▪ <b>WebRequestorRedirectEndpoints</b></li> </ul>
<b>TokenSigningKeyInfo</b>	At least one instance MUST be present. MUST contain at least one <b>X509Certificate</b> element. The first instance MUST contain the <b>Id</b> attribute with the value "stscer". The second instance, if any, MUST contain the <b>Id</b> attribute with the value "stsbcer".

Element name	Description
<b>X509Certificate</b>	MUST be present.
<b>IssuerNamesOffered</b>	MUST be present. MUST contain the <b>uri</b> attribute with the value "uri:WindowsLiveId".
<b>TargetServiceEndpoints</b>	MUST be present. MUST contain at least one <b>Address</b> element which MUST contain a valid absolute path <b>URI</b> .
<b>WebRequestorRedirectEndpoints</b>	MUST be present. MUST contain at least one <b>Address</b> element which MUST contain a valid absolute path URI.

### 3.3.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

The Federation Metadata Document, as specified in [\[WSFederation\]](#), is stateless; however, the server can cache certain values that are contained in the Federation Metadata Document to improve performance.

### 3.3.2 Timers

None.

### 3.3.3 Initialization

None.

### 3.3.4 Message Processing Events and Sequencing Rules

None.

#### 3.3.4.1 Requesting the Service Issue a Token

This section specifies the required elements and values that the request and response from the **STS** contain, and the required elements and values of the encrypted and unencrypted tokens.

##### 3.3.4.1.1 Token Request

The following is a token request that is sent to an **STS**. The required elements and values are specified after the token request.

```
<s:Envelope xmlns:s="http://www.w3.org/2003/05/soap-envelope"
  xmlns:a="http://www.w3.org/2005/08/addressing" xmlns:u="http://docs.oasis-
  open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" xmlns:o="http://docs.oasis-
  open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
  xmlns:t="http://schemas.xmlsoap.org/ws/2005/02/trust"
  xmlns:auth="http://schemas.xmlsoap.org/ws/2006/12/authorization"
  xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy">
  <s:Header>
```

```

    <a:To s:mustUnderstand="1" u:Id="_1">https://login.live-
int.com:44329/liveidSTS.srf</a:To>
    <a:Action
s:mustUnderstand="1">http://schemas.xmlsoap.org/ws/2005/02/trust/RST/Issue</a:Action>
    <a:MessageID>urn:uuid:64f95d31-e078-4f2e-8bb2-d8e6e183alf0</a:MessageID>
    <a:ReplyTo>
      <a:Address>http://www.w3.org/2005/08/addressing/anonymous</a:Address>
    </a:ReplyTo>
    <o:Security s:mustUnderstand="1">
      <u:Timestamp u:Id="_0">
        <u:Created>2009-09-24T17:34:08Z</u:Created>
        <u:Expires>2009-09-24T17:39:08Z</u:Expires>
      </u:Timestamp>
      <Signature xmlns="http://www.w3.org/2000/09/xmldsig#">
        <SignedInfo>
          <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
          <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
          <Reference URI="#_1">
            <Transforms>
              <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
            </Transforms>
            <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
            <DigestValue>Y6HYkPrH5NqSrdcLg8AYXDphZ74=</DigestValue>
          </Reference>
          <Reference URI="#_0">
            <Transforms>
              <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
            </Transforms>
            <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
            <DigestValue>1Taikh1jTPazJ2KnVddUmByNd/s=</DigestValue>
          </Reference>
        </SignedInfo>
        <SignatureValue>dbpePnJ3w7i6Ro09jhxzd60HKt3ssZPuSWVk ... ==</SignatureValue>
        <KeyInfo>
          <o:SecurityTokenReference>
            <o:KeyIdentifier ValueType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-
wss-x509-token-profile-
1.0#X509SubjectKeyIdentifier">sUwVAnqj8qmOw5IJ7L0Z7s8fEh4=</o:KeyIdentifier>
            </o:SecurityTokenReference>
          </KeyInfo>
        </Signature>
      </o:Security>
    </s:Header>
    <s:Body>
      <t:RequestSecurityToken Id="uuid-e067aa03-623a-4120-b8d9-64b60e8f1104">
        <t:RequestType>http://schemas.xmlsoap.org/ws/2005/02/trust/Issue</t:RequestType>
        <t:TokenType>http://docs.oasis-open.org/wss/oasis-wss-saml-token-profile-
1.1#SAMLV1.1</t:TokenType>
        <t:KeyType>http://schemas.xmlsoap.org/ws/2005/02/trust/SymmetricKey</t:KeyType>
        <t:KeySize>256</t:KeySize>
        <t:CanonicalizationAlgorithm>http://www.w3.org/2001/10/xml-exc-
c14n#</t:CanonicalizationAlgorithm>
        <t:EncryptionAlgorithm>http://www.w3.org/2001/04/xmlenc#aes256-
cbc</t:EncryptionAlgorithm>
        <t:EncryptWith>http://www.w3.org/2001/04/xmlenc#aes256-cbc</t:EncryptWith>
        <t:SignWith>http://www.w3.org/2000/09/xmldsig#hmac-sha1</t:SignWith>

<t:ComputedKeyAlgorithm>http://schemas.xmlsoap.org/ws/2005/02/trust/CK/PSHA1</t:ComputedKeyAl
gorithm>
      <wsp:AppliesTo>
        <a:EndpointReference>
          <a:Address>http://fabrikam.com</a:Address>
        </a:EndpointReference>
      </wsp:AppliesTo>
      <t:OnBehalfOf>
        <saml:Assertion MajorVersion="1" MinorVersion="1" AssertionID="saml-6c5a4142-8257-
4efa-8b45-491feee53159" Issuer="contoso.com" IssueInstant="2009-09-24T17:34:09.095Z"
xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion">

```

```

    <saml:Conditions NotBefore="2009-09-24T17:34:09.079Z" NotOnOrAfter="2009-09-
24T17:39:09.079Z">
      <saml:AudienceRestrictionCondition>
        <saml:Audience>uri:WindowsLiveID</saml:Audience>
      </saml:AudienceRestrictionCondition>
    </saml:Conditions>
    <saml:AttributeStatement>
      <saml:Subject>
        <saml:NameIdentifier
Format="http://schemas.microsoft.com/LiveID/Federation/2008/05/ImmutableID">A0/HqOjr7EOU8HUUV
2Tgfg==@contoso.com</saml:NameIdentifier>
        <saml:SubjectConfirmation>
          <saml:ConfirmationMethod>urn:oasis:names:tc:SAML:1.0:cm:sender-
vouches</saml:ConfirmationMethod>
        </saml:SubjectConfirmation>
      </saml:Subject>
      <saml:Attribute AttributeName="EmailAddress"
AttributeNamespace="http://schemas.xmlsoap.org/ws/2005/05/identity/claims">
        <saml:AttributeValue>joe@contoso.com</saml:AttributeValue>
      </saml:Attribute>
    </saml:AttributeStatement>
    <saml:AuthenticationStatement
AuthenticationMethod="urn:oasis:names:tc:SAML:1.0:am:password" AuthenticationInstant="2009-
09-24T17:34:09.095Z">
      <saml:Subject>
        <saml:NameIdentifier
Format="http://schemas.microsoft.com/LiveID/Federation/2008/05/ImmutableID">A0/HqOjr7EOU8HUUV
2Tgfg==@contoso.com</saml:NameIdentifier>
        <saml:SubjectConfirmation>
          <saml:ConfirmationMethod>urn:oasis:names:tc:SAML:1.0:cm:sender-
vouches</saml:ConfirmationMethod>
        </saml:SubjectConfirmation>
      </saml:Subject>
    </saml:AuthenticationStatement>
    <Signature xmlns="http://www.w3.org/2000/09/xmldsig#">
      <SignedInfo>
        <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
        <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
        <Reference URI="#saml-6c5a4142-8257-4efa-8b45-491feee53159">
          <Transforms>
            <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-
signature" />
            <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
          </Transforms>
          <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
          <DigestValue>2fQF5XM8cqkXR/D0d/TigD3c6YM=</DigestValue>
        </Reference>
      </SignedInfo>
      <SignatureValue>b+MQeAJwlIKGjowGkE1+ookJ626nZ5 ... ==</SignatureValue>
      <KeyInfo>
        <o:SecurityTokenReference xmlns:o="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd">
          <o:KeyIdentifier Value="http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-x509-token-profile-
1.0#X509SubjectKeyIdentifier">sUwVAnqj8qmOw5IJ7L0Z7s8fEh4=</o:KeyIdentifier>
        </o:SecurityTokenReference>
      </KeyInfo>
    </Signature>
  </saml:Assertion>
</t:OnBehalfOf>
<auth:AdditionalContext>
  <auth:ContextItem
Scope="http://schemas.xmlsoap.org/ws/2006/12/authorization/ctx/requestor"
Name="http://schemas.microsoft.com/wlid/requestor">
    <auth:Value>contoso.com</auth:Value>
  </auth:ContextItem>
</auth:AdditionalContext>
<t:Claims Dialect="http://schemas.xmlsoap.org/ws/2006/12/authorization/authclaims">

```

```

    <auth:ClaimType
Uri="http://schemas.xmlsoap.org/ws/2006/12/authorization/claims/action">
    <auth:Value>MSExchange.SharingCalendarFreeBusy</auth:Value>
    </auth:ClaimType>
  </t:Claims>
  <wsp:PolicyReference URI="EX_MBI_FED_SSL"></wsp:PolicyReference>
</t:RequestSecurityToken>
</s:Body>
</s:Envelope>

```

The following attributes and elements are required.

- **/s:Envelope/s:Header/a:To** The **URI** in this element is taken from the **/Federation Metadata/Federation/TargetServiceEndpoint** element of the federation metadata document provided by the STS.
- **/s:Envelope/s:Header/o:Security/u:Timestamp/u:Created** The **Coordinated Universal Time (UTC)** time at which the request is made.
- **/s:Envelope/s:Header/o:Security/u:Timestamp/u:Expires** The UTC time at which the offer for the authentication token expires. This is the create time plus a duration. [<7>](#)
- **/s:Envelope/s:Header/o:Security/Signature** The standard signature of the **To** and **Timestamp** headers, as specified in [\[XMLDSig2\]](#).
- **/s:Envelope/s:Header/o:Security/Signature/Reference/DigestValue** The digest value that is returned by the specified digest method of the previous **To** and **Timestamp** headers, as specified in [\[XMLDSig2\]](#).
- **/s:Envelope/s:Header/o:Security/Signature/SignatureValue** The signature of the **To** and **Timestamp** headers, as specified in [\[XMLDSig2\]](#).
- **/s:Envelope/s:Header/o:Security/Signature/KeyInfo/o:SecurityTokenReference/o:KeyIdentifier** The **SubjectKeyIdentifier** value of the X509 certificate that is associated with the organization and sent to the STS by using the **CreateAppId** operation, as specified in section [3.2.4.2](#), or **UpdateAppIdCertificate** operation, as specified in section [3.2.4.7](#).
- **/s:Envelope/s:Body/s:RequestSecurityToken/wsp:AppliesTo/a:EndpointReference/a:Address** The URI of the organization to which the token will be sent.
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:Assertion** Attributes of the **saml:Assertion** element, as shown in the following table.

Attribute	Value
<b>AssertionId</b>	A unique identifier that identifies this specific token request.
<b>Issuer</b>	The URI of the organization that is requesting the token. This URI is the same as the value that is sent to the STS with the <b>AddUri</b> operation, <a href="#">&lt;8&gt;</a> as specified in section <a href="#">3.2.4.1</a> .
<b>IssueInstant</b>	The UTC date and time that the request is made.

- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:Conditions** Attributes of the **saml:Conditions** element, as shown in the following table.

Attribute	Value
-----------	-------

Attribute	Value
<b>NotBefore</b>	The <b>UTC</b> date and time that the request is made.
<b>NoOnOrAfter</b>	The <b>UTC</b> date and time that the offer expires.

- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:Conditions/saml:AudienceRestrictionCondition/saml:Audience** MUST be set to the URI of the STS. <9>
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AttributeStatement/saml:Subject/saml:NameIdentifier** The **Format** attribute of the **saml:NameIdentifier** element MUST be set to an identifier of the user for whom the token is requested. <10>
- **s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AttributeStatement/saml:Attribute** An attribute MUST be set to the e-mail address of the user for whom the token is requested. The **AttributeName** MUST be "EmailAddress".
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AttributeStatement/saml:Attribute/saml:AttributeValue** The e-mail address of the user for whom the token is requested. The **domain** part of the e-mail address MUST be one of the URI values previously registered with the **AddUri** operation, as specified in section 3.2.4.1.
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AuthenticationStatement/saml:Subject/saml:NameIdentifier** The **Format** attribute of the **saml:NameIdentifier** element MUST be set to an identifier of the user for whom the token is requested. The identifier MUST be the same as the **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AttributeStatement/saml:subject/saml:NameIdentifier** element value. <11>
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AuthenticationStatement/saml:Signature** The **Signature** element is set to the standard **XML** signature of the **OnBehalfOf** element, as specified in [XMLDSig2]. Expected values for elements of the **Signature** element are as follows:
  - **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AuthenticationStatement/saml:Signature/KeyInfo/o:KeyIdentifier** MUST be the **SubjectKeyIdentifier** element of the X509 certificate that is used when calling the **CreateAppId** operation, as specified as in section 3.2.4.2.
- **/s:Envelope/s:Body/t:RequestSecurityToken/auth:AdditionalContext/auth:ContextItem** A **ContextItem** element with the **Scope** attribute set to "**http://schemas.xmlsoap.org/ws/2006/12/authorization/ctx/requestor**" and the **name** element set to "**http://schemas.microsoft.com/wild/requestor**" MUST be present.
- **/s:Envelope/s:Body/t:RequestSecurityToken/auth:AdditionalContext/auth:ContextItem/auth:Value** MUST be set to the same URI as the value used for the **Issuer** attribute of the **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:Assertion** element.
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:Claims** The request MUST contain a **t:Claims** element with the **Dialect** attribute value set to "**http://schemas.xmlsoap.org/ws/2006/12/authorization/authclaims**" and containing at least one **auth:ClaimType** element.
- **/s:Envelope/s:Body/t:RequestSecurityToken/t:Claims/auth:ClaimType** The request MUST contain an **auth:ClaimType** element with the **Uri** attribute value set to

"http://schemas.xmlsoap.org/ws/2006/12/authorization/claims/action" and containing at least one **auth:Value** element.

- **/s:Envelope/s:Body/t:RequestSecurityToken/t:Claims/auth:ClaimType/auth:Value** MUST be set to the name of the token requested. Can be any one of the following names.
  - **MSExchange.SharingInviteMessage**
  - **MSExchange.SharingCalendarFreeBusy**
  - **MSExchange.SharingRead**
  - **MSExchange.DeliveryExternalSubmit**
  - **MSExchange.DeliveryInternalSubmit**
  - **MSExchange.MailboxMove**
  - **MSExchange.Autodiscover**
  - **MSExchange.CertificationWS**
  - **MSExchange.LicensingWS**
- **/s:Envelope/s:Body/t:RequestSecurityToken/wsp:PolicyReference** The request MUST contain one **wsp:Policy** element with the URI attribute value set to the token policy to use. [<12>](#)

### 3.3.4.1.2 Token Response

The following is a token response that is sent from an **STS**. The required elements and values are specified after the token response.

```
<S:Envelope xmlns:S="http://www.w3.org/2003/05/soap-envelope" xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" xmlns:wsa="http://www.w3.org/2005/08/addressing">
  <S:Header>
    <wsa:Action xmlns:S="http://www.w3.org/2003/05/soap-envelope"
xmlns:wsa="http://www.w3.org/2005/08/addressing" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" wsu:Id="Action"
S:mustUnderstand="1">http://schemas.xmlsoap.org/ws/2005/02/trust/RSTR/Issue</wsa:Action>
    <wsa:To xmlns:S="http://www.w3.org/2003/05/soap-envelope"
xmlns:wsa="http://www.w3.org/2005/08/addressing" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" wsu:Id="To"
S:mustUnderstand="1">http://schemas.xmlsoap.org/ws/2004/08/addressing/role/anonymous</wsa:To>
    <wsse:Security S:mustUnderstand="1">
      <wsu:Timestamp xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" wsu:Id="TS">
        <wsu:Created>2009-09-24T17:34:01Z</wsu:Created>
        <wsu:Expires>2009-09-24T17:39:01Z</wsu:Expires>
      </wsu:Timestamp>
    </wsse:Security>
  </S:Header>
  <S:Body>
    <wst:RequestSecurityTokenResponse xmlns:S="http://www.w3.org/2003/05/soap-envelope"
xmlns:wst="http://schemas.xmlsoap.org/ws/2005/02/trust" xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd"
xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion"
xmlns:wsp="http://schemas.xmlsoap.org/ws/2004/09/policy"
xmlns:psf="http://schemas.microsoft.com/Passport/SoapServices/SOAPFault">
      <wst:TokenType>urn:oasis:names:tc:SAML:1.0</wst:TokenType>
      <wsp:AppliesTo xmlns:wsa="http://www.w3.org/2005/08/addressing">
        <wsa:EndpointReference>
          <wsa:Address>http://fabrikam.com</wsa:Address>
        </wsa:EndpointReference>
      </wsp:AppliesTo>
    </S:Body>
</S:Envelope>
```

```

    </wsa:EndpointReference>
  </wsp:AppliesTo>
  <wst:Lifetime>
    <wsu:Created>2009-09-24T17:34:01Z</wsu:Created>
    <wsu:Expires>2009-10-09T17:34:01Z</wsu:Expires>
  </wst:Lifetime>
  <wst:RequestedSecurityToken>
    <EncryptedData xmlns="http://www.w3.org/2001/04/xmlenc#" Id="Assertion0"
Type="http://www.w3.org/2001/04/xmlenc#Element">
      <EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmlenc#tripleDES-
cbc"></EncryptionMethod>
      <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
        <EncryptedKey>
          <EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmlenc#rsa-oaep-
mgflp"></EncryptionMethod>
          <ds:KeyInfo Id="keyinfo">
            <wsse:SecurityTokenReference>
              <wsse:KeyIdentifier EncodingType="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-soap-message-security-1.0#Base64Binary"
ValueType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
1.0#X509SubjectKeyIdentifier">sUwVAnqj8qmOw5IJ7L0Z7s8fEh4=</wsse:KeyIdentifier>
            </wsse:SecurityTokenReference>
          </ds:KeyInfo>
        <CipherData>
          <CipherValue>mfYn2OYAGs6YaXw5P8L79mmHvHbd3+Of1QWprAmRww/Finek03IEa/r7LlxxGfb7FAA+ScthkQA...
          ==</CipherValue>
        </CipherData>
      </EncryptedKey>
    </ds:KeyInfo>
  </CipherData>
<CipherValue>B5B4B/PrdcBj9s8CQxBs6pNNLFlA9VeA4Y5ZIM6VBkDYwX6zmnCmBkOghx9pPrSGxmp2KChWU5QAKHsJ
...==</CipherValue>
  </CipherData>
</EncryptedData>
</wst:RequestedSecurityToken>
<wst:RequestedAttachedReference>
  <wsse:SecurityTokenReference>
    <wsse:KeyIdentifier ValueType="http://docs.oasis-open.org/wss/oasis-wss-saml-token-
profile-1.0#SAMLAssertionID">uuid-c3a658d0-d832-43dc-bf57-2bfba93c13e5</wsse:KeyIdentifier>
  </wsse:SecurityTokenReference>
</wst:RequestedAttachedReference>
<wst:RequestedUnattachedReference>
  <wsse:SecurityTokenReference>
    <wsse:KeyIdentifier ValueType="http://docs.oasis-open.org/wss/oasis-wss-saml-token-
profile-1.0#SAMLAssertionID">uuid-c3a658d0-d832-43dc-bf57-2bfba93c13e5</wsse:KeyIdentifier>
  </wsse:SecurityTokenReference>
</wst:RequestedUnattachedReference>
<wst:RequestedProofToken>
  <wst:BinarySecret>TfKqVImHiU1ePfaBrAE6P6Jevxw1/XF8</wst:BinarySecret>
</wst:RequestedProofToken>
</wst:RequestSecurityTokenResponse>
</S:Body>
</S:Envelope>

```

The following attributes and elements are required.

- **/s:body/wst:RequestSecurityTokenResponse** The response from the server MUST contain at least one **wst:RequestSecurityTokenResponse** element, as specified in [\[WSTrust1.4\]](#), with child elements as follows.
- **/s:body/wst:RequestSecurityTokenResponse/wsp:AppliesTo** The response MUST contain the **wsp:AppliesTo** element with at least one child **wsa:EndpointReference** element.

- **/s:body/wst:RequestSecurityTokenResponse/wsp:AppliesTo/wsa:EndpointReference/wsa:Address** The **wsa:Address** element MUST contain the same value as the **/s:Envelope/s:Body/t:RequestSecurityToken/wsp:AppliesTo/a:EndpointReference/a:Address** element specified in the token request.
- **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedSecurityToken** The response MUST contain at most one **wst:RequestedSecurityToken** element that MUST contain one and only one **EncryptedData** child element that contains the encrypted token that will be sent to another service for authentication. The required elements of the token are specified in section [3.3.4.1.3](#).
- **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedAttachedReference** The response MUST contain at least one **wst:RequestedAttachedReference** element that contains a least one child **wsse:SecurityTokenReference** element.
- **/sbody/wst:RequestSecurityTokenResponse/wst:RequestedAttachedReference/wsse:SecurityTokenReference** The response MUST contain at least one **wsse:SecurityTokenReference** element that contains at least one child **wsse:KeyIdentifier** element.
- **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedAttachedReference/wsse:SecurityTokenReference/wsse:KeyIdentifier** The response MUST contain at least one **wsse:KeyIdentifier** element that contains the identifier of the SAML assertion encrypted within the **RequestedSecurityToken** element.
- **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedProofToken** The response MUST contain at least one **wst:RequestedProofToken** element that contains at least one child **wst:BinarySecret** element.
- **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedAttachedReference/wst:RequestedProofToken/wst:BinarySecret** The response MUST contain a **BinarySecret** element with the value set to the symmetric key that is encrypted in the **RequestedSecurityToken** element.

### 3.3.4.1.3 Encrypted and Unencrypted Tokens

This section shows the required attributes and elements of the encrypted and unencrypted tokens that are received from the **STS**.

The following is an encrypted token from an **STS**. The required elements and values are specified after the encrypted and unencrypted tokens.

```
<EncryptedData xmlns="http://www.w3.org/2001/04/xmlenc#" Id="Assertion0"
Type="http://www.w3.org/2001/04/xmlenc#Element">
  <EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmlenc#tripleDES-
cbc"></EncryptionMethod>
  <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
    <EncryptedKey>
      <EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmlenc#rsa-oeap-
mgflp"></EncryptionMethod>
      <ds:KeyInfo Id="keyinfo">
        <wsse:SecurityTokenReference>
          <wsse:KeyIdentifier EncodingType="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-
soap-message-security-1.0#Base64Binary" ValueType="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
1.0#X509SubjectKeyIdentifier">sUwVAnqj8qmOw5IJ7L0Z7s8fEh4=</wsse:KeyIdentifier>
        </wsse:SecurityTokenReference>
      </ds:KeyInfo>
    <CipherData>
      <CipherValue>mfYn2OYAGs6YaXw5P8L79mmHvHbd3+Of1QWprAmRww/Finek03IEa/r7LlxxGfb7FAA+ScthkQA...
    </CipherValue>
  </ds:KeyInfo>
</EncryptedData>
```

```

    </CipherData>
  </EncryptedKey>
</ds:KeyInfo>
<CipherData>
<CipherValue>B5B4B/PrdcBj9s8CQxBs6pNNLFlA9VeA4Y5ZIM6VBkDYwX6zmnCmBkOghx9pPrSGxmp2KChWU5QAKHsJ
...=</CipherValue>
</CipherData>
</EncryptedData>

```

The following is an encrypted token from an STS. The required elements and values are specified after the token.

```

<saml:Assertion xmlns:saml="urn:oasis:names:tc:SAML:1.0:assertion" AssertionID="uuid-
c3a658d0-d832-43dc-bf57-2bfba93c13e5" IssueInstant="2009-09-24T17:34:01Z"
Issuer="uri:WindowsLiveID" MajorVersion="1" MinorVersion="1">
  <saml:Conditions NotBefore="2009-09-24T17:34:01Z" NotOnOrAfter="2009-10-09T17:34:01Z">
    <saml:AudienceRestrictionCondition>
      <saml:Audience>http://fabrikam.com</samlAudience >
    </saml:AudienceRestrictionCondition>
  </saml:Conditions>
  <saml:AuthenticationStatement AuthenticationInstant="2009-09-24T17:34:01Z"
AuthenticationMethod="urn:oasis:names:tc:SAML:1.0:am:password">
    <saml:Subject>
      <saml:NameIdentifier
Format="http://schemas.xmlsoap.org/claims/UPN">a744b0351351444d3087ca806986b9a0@Live.com</sam
l:NameIdentifier>
      <saml:SubjectConfirmation>
        <saml:ConfirmationMethod>urn:oasis:names:tc:saml:1.0:cm:holder-of-
key</saml:ConfirmationMethod>
        <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#">
          <e:EncryptedKey xmlns:e="http://www.w3.org/2001/04/xmlenc#">
            <e:EncryptionMethod Algorithm="http://www.w3.org/2001/04/xmlenc#rsa-oaep-
mgflp"></e:EncryptionMethod>
            <ds:KeyInfo Id="keyinfo">
              <wsse:SecurityTokenReference xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-wssecurity-secext-1.0.xsd">
                <wsse:KeyIdentifier EncodingType="http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-soap-message-security-1.0#Base64Binary" ValueType="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
1.0#X509SubjectKeyIdentifier">sUwVAnqj8qmOw5IJ7L0Z7s8fEh4=</wsse:KeyIdentifier>
              </wsse:SecurityTokenReference>
            </ds:KeyInfo>
          <e:CipherData>
            <e:CipherValue>1RRb1PaUiQrsdA0me/Q4Gt6RVHkDm5ehPNZaDoiQ ... ==</e:CipherValue>
          </e:CipherData>
        </e:EncryptedKey>
      </ds:KeyInfo>
    </saml:SubjectConfirmation>
  </saml:Subject>
</saml:AuthenticationStatement>
<saml:AttributeStatement>
  <saml:Subject>
    <saml:NameIdentifier
Format="http://schemas.xmlsoap.org/claims/UPN">a744b0351351444d3087ca806986b9a0@Live.com</sam
l:NameIdentifier>
    </saml:Subject>
    <saml:Attribute AttributeName="RequestorDomain"
AttributeNameNamespace="http://schemas.microsoft.com/ws/2006/04/identity/claims">
      <saml:AttributeValue>contoso.com</saml:AttributeValue>
    </saml:Attribute>
    <saml:Attribute AttributeName="EmailAddress"
AttributeNameNamespace="http://schemas.xmlsoap.org/claims">
      <saml:AttributeValue>joe@contoso.com</saml:AttributeValue>
    </saml:Attribute>
    <saml:Attribute AttributeName="action"
AttributeNameNamespace="http://schemas.xmlsoap.org/ws/2006/12/authorization/claims">

```

```

    <saml:AttributeValue>MSExchange.SharingCalendarFreeBusy</saml:AttributeValue>
  </saml:Attribute>
  <saml:Attribute AttributeName="ThirdPartyRequested"
AttributeNamespace="http://schemas.microsoft.com/ws/2006/04/identity/claims">
    <saml:AttributeValue></saml:AttributeValue>
  </saml:Attribute>
  <saml:Attribute AttributeName="AuthenticatingAuthority"
AttributeNamespace="http://schemas.microsoft.com/ws/2008/06/identity">
    <saml:AttributeValue>http://contoso.com</saml:AttributeValue>
  </saml:Attribute>
</saml:AttributeStatement>
<Signature xmlns="http://www.w3.org/2000/09/xmldsig#">
  <SignedInfo>
    <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-
c14n#"></CanonicalizationMethod>
    <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-
shal"></SignatureMethod>
    <Reference URI="#uuid-c3a658d0-d832-43dc-bf57-2bfa93c13e5">
      <Transforms>
        <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature"></Transform>
        <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#"></Transform>
      </Transforms>
      <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1"></DigestMethod>
      <DigestValue>DP2Bg6+h59Uw4zc8DjRNJ4UQAlw=</DigestValue>
    </Reference>
  </SignedInfo>
  <SignatureValue>
    baY0k5dLPuPHKCwTgMATaXKEJL4vX8GeWvaQgCeZchNUbXij1BmPH/Lqu/lHtFavGpLDJ+ukbGeV
    vKWveIGCnre8SCYBUBHlwi0FSw+p+pmFGLRytRG4mkAzEI9dskGnW0RlhFfSVDzvnSBGwrNzSH5o
    Y9hKDVT5emRGeYpDQYc=
  </SignatureValue>
  <ds:KeyInfo xmlns:ds="http://www.w3.org/2000/09/xmldsig#" Id="keyinfo">
    <wsse:SecurityTokenReference xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-wssecurity-secext-1.0.xsd">
      <wsse:KeyIdentifier EncodingType="http://docs.oasis-open.org/wss/2004/01/oasis-
200401-wss-soap-message-security-1.0#Base64Binary" ValueType="http://docs.oasis-
open.org/wss/2004/01/oasis-200401-wss-x509-token-profile-
1.0#X509SubjectKeyIdentifier">VbJyIcGL0AjB4/Wm4DqUZux6uUk=</wsse:KeyIdentifier>
    </wsse:SecurityTokenReference>
  </ds:KeyInfo>
</Signature>
</saml:Assertion>

```

The following elements and attributes are required.

- **/saml:Assertion** The **AssertionID** attribute MUST match the **/s:body/wst:RequestSecurityTokenResponse/wst:RequestedAttachedReference/wsse:SecurityTokenReference/wsse:KeyIdentifier** element in the response from the STS.
- **/saml:Assertion/saml:Conditions/saml:AudienceRestrictionCondition/saml:Audience** The **saml:Audience** element MUST contain the same value as the **/s:Envelope/s:Body/t:RequestSecurityToken/wsp:AppliesTo/a:EndpointReference/a:Address** element in the request.
- **/saml:Assertion/saml:AuthenticationStatement/saml:Subject/saml:NameIdentifier** The **saml:NameIdentifier** element MUST be present and MUST be in **UPN** syntax, but can be any value that the STS wants; however it is the same for each **/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:AuthenticationStatement/saml:Subject/saml:NameIdentifier** element in the request.
- **/saml:Assertion/saml:AuthenticationStatement/saml:Subject/saml:SubjectConfirmation** The **saml:SubjectConfirmation** element MUST be present and MUST be in the format specified in [\[SAML\]](#).

- **/saml:Assertion/saml:AttributeStatement/saml:Subject/saml:NameIdentifier** The value of the **saml:NameIdentifier** element MUST be the same as the **/saml:Assertion/saml:AuthenticationStatement/saml:Subject/saml:NameIdentifier** element.
- **/saml:Assertion/saml:AttributeStatement/saml:Attribute** The **saml:Attribute** element MUST contain the attributes of the **AttributeValue** child element of the **Attribute** element that are listed in the following table.

Attribute name	AttributeValue element
<b>RequestorDomain</b>	MUST be the same as the <b>/s:Envelope/s:Body/s:RequestSecurityToken/auth:AdditionalContext/auth:ContextItem/auth:Value</b> element in the token request.
<b>EmailAddress</b>	MUST be the same as the <b>/s:Envelope/s:Body/t:RequestSecurityToken/t:OnBehalfOf/saml:Assertion/saml:AttributeStatement/saml:Attribute@[EmailAddress]\AttributeValue</b> element in the token request.
<b>action</b>	MUST be the same as the <b>/s:Envelope/s:Body/t:RequestSecurityToken/t:Claims\auth:ClaimType@[.../Action]\auth:Value</b> element in the token request.
<b>ThirdPartyRequested</b>	MUST NOT contain a value.
<b>AuthenticatingAuthority</b>	MUST contain a <b>domain name</b> previously registered with the <b>AddUri</b> operation, as specified in section <a href="#">3.2.4.1</a> .

- **/saml:Assertion/Signature** The **Signature** element MUST be a standard signature, as specified in [\[XMLDSig2\]](#), and MUST sign the entire **Assertion** element.

### 3.3.5 Timer Events

None.

### 3.3.6 Other Local Events

None.

## 4 Protocol Examples

The following examples show the **XML** messages that are used by the Federated Internet Authentication Web Service Protocol. Where the Federated Internet Authentication Web Service Protocol requires specific values in an element of the XML document, the element node is described by using the syntax described in [\[XPATH\]](#).

### 4.1 Registering with a Security Token Service

The following examples show the **XML** messages that are used by the Federated Internet Authentication Web Service Protocol to communicate with the Managed Delegation Web service that is exposed by an **STS**. Where the Federated Internet Authentication Web Service Protocol requires specific values in an element of the XML document, the element node is described by using the syntax described in [\[XPATH\]](#).

#### 4.1.1 Creating an Application Identifier

This example shows the request and response messages that are sent to and received from the **CreateAppId** operation.

The following is an example of the request that was sent to the **CreateAppId** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CreateAppId xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <certificate>MIIIFCjCCBLSgAwIBAgIKFZsHigAGA...</certificate>
    </CreateAppId>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements are used in the example:

- **/soap:Envelope/soap:Body/CreateAppId/certificate:** The certificate in **base64 encoding** that will be used to identify requests from the organization and to encrypt information sent to the organization.

The following is an example of the response that is returned by the **CreateAppId** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <CreateAppIdResponse xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <CreateAppIdResult>
        <AppId>0000000060000EB9</AppId>
        <AdminKey>6MoWllqVuL/sYZFCNPcGRhn+dyVX4TR4J9xFZsB7jKU=</AdminKey>
      </CreateAppIdResult>
    </CreateAppIdResponse>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements are used in the example:

- **/soap:Envelope/soap:Body/CreateAppIdResponse/CreateAppIdResult/AppId:** The application identifier that is assigned to the organization by the **STS**. The application identifier can be any combination of letters and numbers.
- **/soap:Envelope/soap:Body/CreateAppIdResponse/CreateAppIdResult/AdminKey:** The administrative key that is assigned to the organization by the STS. This key is used to identify the organization when changing administrative information that is maintained by the STS. The administrative key can be any combination of letters and numbers.

#### 4.1.2 Reserving a Federated Organization Domain

This example shows the request and response messages that are sent to and received from the **ReserveDomain** operation.

The following is an example of the request that is sent to the **ReserveDomain** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <ReserveDomain xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <ownerAppId>0000000060000EB9</ownerAppId>
      <domainName>contoso.com</domainName>
      <programId></programId>
    </ReserveDomain>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements used in the example:

- **/soap:Envelope/soap:Body/ReserveDomain/ownerAppId:** The application identifier that is assigned to the organization by the **STS**. This value is returned in response to the **CreateAppId** operation.
- **/soap:Envelope/soap:Body/ReserveDomain/domainName:** The **domain name** of the organization.
- **/soap:Envelope/soap:Body/ReserveDomain/programId:** This element is reserved for future use.

The following is an example of the response that is returned by the **ReserveDomain** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <ReserveDomainResponse xmlns="http://domains.live.com/Service/ManageDelegation/V1.0" />
  </soap:Body>
</soap:Envelope>
```

### 4.1.3 Retrieving Domain Information

This example shows the request and response messages that are sent to and received from the **GetDomainInfo** operation.

The following is an example of the request that is sent to the **GetDomainInfo** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetDomainInfo xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <ownerAppId>0000000060000EB9</ownerAppId>
      <domainName>contoso.com</domainName>
    </GetDomainInfo>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements are used in the example:

- **/soap:Envelope/soap:Body/GetDomainInfo/ownerAppId:** The application identifier that is assigned to the organization by the **STS**. The application identifier can be any combination of letters and numbers.
- **/soap:Envelope/soap:Body/GetDomainInfo/domainName:** The **domain name** of the organization.

The following is an example of the response that is returned by the **GetDomainInfo** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <GetDomainInfoResponse xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <GetDomainInfoResult>
        <DomainName>vyotqn-dom.extest.microsoft.com</DomainName>
        <AppId>0000000060000EB9</AppId>
        <DomainState>Active</DomainState>
      </GetDomainInfoResult>
    </GetDomainInfoResponse>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements are used the example:

- **/soap:Envelope/soap:Body/GetDomainInfoResponse/GetDomainInfoResult/DomainName:** The **domain** registered by the organization with the STS.
- **/soap:Envelope/soap:Body/GetDomainInfoResponse/GetDomainInfoResult/AppId:** The application identifier that is assigned to the organization by the STS. The application identifier can be any combination of letters and numbers.
- **/soap:Envelope/soap:Body/GetDomainInfoResponse/GetDomainInfoResult/DomainState:** The current state of the domain. The possible states are described by the **DomainState** simple type, as described in section [2.2.5.1](#).

#### 4.1.4 Registering a Domain Name

This example shows the request and response messages that are sent to and received from the **AddUri** operation.

The following is an example of the request that is sent to the **AddUri** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <AddUri xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <ownerAppId>0000000060000EB9</ownerAppId>
      <uri>VYOTQN-DOM.EXTEST.MICROSOFT.COM</uri>
    </AddUri>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements are used in the example:

- **/soap:Envelope/soap:Body/AddUri/ownerAppId**: The application identifier that is assigned to the organization by the **STS**. The application identifier can be any combination of letters and numbers.
- **/soap:Envelope/soap:Body/AddUri/uri**: The **domain** name of the organization.

The following is an example of the response that is returned by the **AddUri** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <AddUriResponse xmlns="http://domains.live.com/Service/ManageDelegation/V1.0" />
  </soap:Body>
</soap:Envelope>
```

#### 4.1.5 Removing a Registered Domain Name

This example shows the request and response messages that are sent to and received from the **RemoveUri** operation.

The following is an example of the request that is sent to the **RemoveUri** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <RemoveUri xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <ownerAppId>0000000060000EB9</ownerAppId>
      <uri>contoso.com</uri>
    </RemoveUri>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements are used in the example:

- **/soap:Envelope/soap:Body/RemoveUri/ownerAppId:** The application identifier that is assigned to the organization by the **STS**. The application identifier can be any combination of letters and numbers.
- **/soap:Envelope/soap:Body/RemoveUri/uri:** The organization **domain name** to remove.

The following is an example of the response that is returned by the **RemoveUri** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <RemoveUriResponse xmlns="http://domains.live.com/Service/ManageDelegation/V1.0" />
  </soap:Body>
</soap:Envelope>
```

#### 4.1.6 Updating a Certificate

This example shows the request and response messages that are sent to and received from the **UpdateAppIdCertificate** operation.

The following is an example of the request that is sent to the **UpdateAppIdCertificate** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <UpdateAppIdCertificate xmlns="http://domains.live.com/Service/ManageDelegation/V1.0">
      <appId>0000000060000EB9</appId>
      <appIdAdminKey>6MoW1lqVuL/sYZFCNPcGRhn+dyVX4TR4J9xFZsB7jKU=</appIdAdminKey>
      <newCertificate>MIIFTTCBPegAwIBAgIKIl... </newCertificate>
    </UpdateAppIdCertificate>
  </soap:Body>
</soap:Envelope>
```

The following required attributes and elements are used in the example:

- **/soap:Envelope/soap:Body/UpdateAppIdCertificate/appId:** The application identifier that is assigned to the organization by the **STS**. The application identifier can be any combination of letters and numbers.
- **/soap:Envelope/soap:Body/UpdateAppIdCertificate/apIdAdminKey:** The administrative key that is assigned to the organization by the STS.
- **/soap:Envelope/soap:Body/UpdateAppIdCertificate/newCertificate:** The new certificate in **base64 encoding** that will be used to identify requests from the organization and to encrypt information that is sent to the organization.

The following is an example of the response that is returned by the **UpdateAppIdCertificate** operation.

```
<?xml version="1.0" encoding="utf-8"?>
<soap:Envelope xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <soap:Body>
    <UpdateAppIdCertificateResponse
xmlns="http://domains.live.com/Service/ManageDelegation/V1.0" />
  </soap:Body>
</soap:Envelope>
```

## **5 Security**

### **5.1 Security Considerations for Implementers**

None.

### **5.2 Index of Security Parameters**

None.

## 6 Appendix A: Full WSDL

The **XML** files that are listed in the following table are required in order to implement the functionality specified in this document.

File name	Description	Section
ManageLiveFederation.wsdl	Defines the <b>ManageDelegationSoap</b> client protocol.	<a href="#">6.1</a>
ManageDelegation2.wsdl	Defines the <b>ManageDelegation2Soap</b> client protocol.	<a href="#">6.2</a>

For ease of implementation, the full **WSDL** files are provided in the following sections.

### 6.1 ManageDelegationSoap WSDL

This section contains the **WSDL** that defines the operations, messages, types, and elements used by the **ManageDelegationSoap** client protocol described in section [3.1](#).

```
<?xml version="1.0" encoding="us-ascii"?>
<wsdl:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:tns="http://domains.live.com/Service/ManageDelegation/V1.0"
  xmlns:s="http://www.w3.org/2001/XMLSchema"
  xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
  xmlns:http="http://schemas.xmlsoap.org/wsdl/http/"
  targetNamespace="http://domains.live.com/Service/ManageDelegation/V1.0"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/">
  <wsdl:types>
    <s:schema elementFormDefault="qualified"
      targetNamespace="http://domains.live.com/Service/ManageDelegation/V1.0">
      <s:element name="CreateAppId">
        <s:complexType>
          <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="certificate"
              type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="properties"
              type="tns:ArrayOfProperty" />
          </s:sequence>
        </s:complexType>
      </s:element>
      <s:complexType name="ArrayOfProperty">
        <s:sequence>
          <s:element minOccurs="0" maxOccurs="unbounded" name="Property" nillable="true"
            type="tns:Property" />
        </s:sequence>
      </s:complexType>
      <s:complexType name="Property">
        <s:sequence>
          <s:element minOccurs="0" maxOccurs="1" name="Name" type="s:string" />
          <s:element minOccurs="0" maxOccurs="1" name="Value" type="s:string" />
        </s:sequence>
      </s:complexType>
      <s:element name="CreateAppIdResponse">
        <s:complexType>
          <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="CreateAppIdResult"
              type="tns:AppIdInfo" />
          </s:sequence>
        </s:complexType>
      </s:element>
      <s:complexType name="AppIdInfo">
```

```

<s:sequence>
  <s:element minOccurs="0" maxOccurs="1" name="AppId" type="s:string" />
  <s:element minOccurs="0" maxOccurs="1" name="AdminKey" type="s:string" />
</s:sequence>
</s:complexType>
<s:element name="UpdateAppIdCertificate">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="appIdAdminKey"
        type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="newCertificate"
        type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="UpdateAppIdCertificateResponse">
  <s:complexType />
</s:element>
<s:element name="UpdateAppIdProperties">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="properties"
        type="tns:ArrayOfProperty" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="UpdateAppIdPropertiesResponse">
  <s:complexType />
</s:element>
<s:element name="AddUri">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="ownerAppId"
        type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="uri" type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="AddUriResponse">
  <s:complexType />
</s:element>
<s:element name="RemoveUri">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="ownerAppId"
        type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="uri" type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="RemoveUriResponse">
  <s:complexType />
</s:element>
<s:element name="ReserveDomain">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="ownerAppId"
        type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="domainName"
        type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="programId"
        type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="ReserveDomainResponse">
  <s:complexType />

```

```

</s:element>
<s:element name="ReleaseDomain">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="ownerAppId"
        type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="domainName"
        type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="ReleaseDomainResponse">
  <s:complexType />
</s:element>
<s:element name="GetDomainInfo">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="ownerAppId"
        type="s:string" />
      <s:element minOccurs="0" maxOccurs="1" name="domainName"
        type="s:string" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:element name="GetDomainInfoResponse">
  <s:complexType>
    <s:sequence>
      <s:element minOccurs="0" maxOccurs="1" name="GetDomainInfoResult"
        type="tns:DomainInfo" />
    </s:sequence>
  </s:complexType>
</s:element>
<s:complexType name="DomainInfo">
  <s:sequence>
    <s:element minOccurs="0" maxOccurs="1" name="DomainName"
      type="s:string" />
    <s:element minOccurs="0" maxOccurs="1" name="AppId" type="s:string" />
    <s:element minOccurs="1" maxOccurs="1" name="DomainState"
      type="tns:DomainState" />
  </s:sequence>
</s:complexType>
<s:simpleType name="DomainState">
  <s:restriction base="s:string">
    <s:enumeration value="PendingActivation" />
    <s:enumeration value="Active" />
    <s:enumeration value="PendingRelease" />
  </s:restriction>
</s:simpleType>
</s:schema>
</wsdl:types>
<wsdl:message name="CreateAppIdSoapIn">
  <wsdl:part name="parameters" element="tns:CreateAppId" />
</wsdl:message>
<wsdl:message name="CreateAppIdSoapOut">
  <wsdl:part name="parameters" element="tns:CreateAppIdResponse" />
</wsdl:message>
<wsdl:message name="UpdateAppIdCertificateSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificate" />
</wsdl:message>
<wsdl:message name="UpdateAppIdCertificateSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificateResponse" />
</wsdl:message>
<wsdl:message name="UpdateAppIdPropertiesSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdProperties" />
</wsdl:message>
<wsdl:message name="UpdateAppIdPropertiesSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAppIdPropertiesResponse" />
</wsdl:message>
<wsdl:message name="AddUriSoapIn">

```

```

    <wsdl:part name="parameters" element="tns:AddUri" />
</wsdl:message>
<wsdl:message name="AddUriSoapOut">
  <wsdl:part name="parameters" element="tns:AddUriResponse" />
</wsdl:message>
<wsdl:message name="RemoveUriSoapIn">
  <wsdl:part name="parameters" element="tns:RemoveUri" />
</wsdl:message>
<wsdl:message name="RemoveUriSoapOut">
  <wsdl:part name="parameters" element="tns:RemoveUriResponse" />
</wsdl:message>
<wsdl:message name="ReserveDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReserveDomain" />
</wsdl:message>
<wsdl:message name="ReserveDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReserveDomainResponse" />
</wsdl:message>
<wsdl:message name="ReleaseDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReleaseDomain" />
</wsdl:message>
<wsdl:message name="ReleaseDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReleaseDomainResponse" />
</wsdl:message>
<wsdl:message name="GetDomainInfoSoapIn">
  <wsdl:part name="parameters" element="tns:GetDomainInfo" />
</wsdl:message>
<wsdl:message name="GetDomainInfoSoapOut">
  <wsdl:part name="parameters" element="tns:GetDomainInfoResponse" />
</wsdl:message>
<wsdl:portType name="ManageDelegationSoap">
  <wsdl:operation name="CreateAppId">
    <wsdl:input message="tns:CreateAppIdSoapIn" />
    <wsdl:output message="tns:CreateAppIdSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdCertificate">
    <wsdl:input message="tns:UpdateAppIdCertificateSoapIn" />
    <wsdl:output message="tns:UpdateAppIdCertificateSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdProperties">
    <wsdl:input message="tns:UpdateAppIdPropertiesSoapIn" />
    <wsdl:output message="tns:UpdateAppIdPropertiesSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="AddUri">
    <wsdl:input message="tns:AddUriSoapIn" />
    <wsdl:output message="tns:AddUriSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="RemoveUri">
    <wsdl:input message="tns:RemoveUriSoapIn" />
    <wsdl:output message="tns:RemoveUriSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="ReserveDomain">
    <wsdl:input message="tns:ReserveDomainSoapIn" />
    <wsdl:output message="tns:ReserveDomainSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="ReleaseDomain">
    <wsdl:input message="tns:ReleaseDomainSoapIn" />
    <wsdl:output message="tns:ReleaseDomainSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="GetDomainInfo">
    <wsdl:input message="tns:GetDomainInfoSoapIn" />
    <wsdl:output message="tns:GetDomainInfoSoapOut" />
  </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="ManageDelegationSoap" type="tns:ManageDelegationSoap">
  <soap:binding transport="http://schemas.xmlsoap.org/soap/http" />
  <wsdl:operation name="CreateAppId">
    <soap:operation
      soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/CreateAppId"
      style="document" />

```

```

        <wsdl:input>
          <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
          <soap:body use="literal" />
        </wsdl:output>
      </wsdl:operation>
      <wsdl:operation name="UpdateAppIdCertificate">
        <soap:operation
          soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdCertificate"
          style="document" />
        <wsdl:input>
          <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
          <soap:body use="literal" />
        </wsdl:output>
      </wsdl:operation>
      <wsdl:operation name="UpdateAppIdProperties">
        <soap:operation
          soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdProperties"
          style="document" />
        <wsdl:input>
          <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
          <soap:body use="literal" />
        </wsdl:output>
      </wsdl:operation>
      <wsdl:operation name="AddUri">
        <soap:operation
          soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/AddUri"
          style="document" />
        <wsdl:input>
          <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
          <soap:body use="literal" />
        </wsdl:output>
      </wsdl:operation>
      <wsdl:operation name="RemoveUri">
        <soap:operation
          soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/RemoveUri"
          style="document" />
        <wsdl:input>
          <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
          <soap:body use="literal" />
        </wsdl:output>
      </wsdl:operation>
      <wsdl:operation name="ReserveDomain">
        <soap:operation
          soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/ReserveDomain"
          style="document" />
        <wsdl:input>
          <soap:body use="literal" />
        </wsdl:input>
        <wsdl:output>
          <soap:body use="literal" />
        </wsdl:output>
      </wsdl:operation>
      <wsdl:operation name="ReleaseDomain">
        <soap:operation
          soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/ReleaseDomain"
          style="document" />
        <wsdl:input>

```

```

        <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetDomainInfo">
    <soap:operation
        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/GetDomainInfo"
style="document" />
    <wsdl:input>
        <soap:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:binding name="ManageDelegationSoap12" type="tns:ManageDelegationSoap">
    <soap12:binding transport="http://schemas.xmlsoap.org/soap/http" />
    <wsdl:operation name="CreateAppId">
        <soap12:operation
            soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/CreateAppId"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
<wsdl:operation name="UpdateAppIdCertificate">
        <soap12:operation
            soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdCertificate"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
<wsdl:operation name="UpdateAppIdProperties">
        <soap12:operation
            soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/UpdateAppIdProperties"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
<wsdl:operation name="AddUri">
        <soap12:operation
            soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/AddUri"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
<wsdl:operation name="RemoveUri">
        <soap12:operation

```

```

        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/RemoveUri"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReserveDomain">
    <soap12:operation
        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/ReserveDomain"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReleaseDomain">
    <soap12:operation
        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/ReleaseDomain"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetDomainInfo">
    <soap12:operation
        soapAction="http://domains.live.com/Service/ManageDelegation/V1.0/GetDomainInfo"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:binding
    name="ManageDelegation"
    type="tns:ManageDelegationSoap">
    <wsdl:port name="ManageDelegationSoap" binding="tns:ManageDelegationSoap">
        <soap:address location="https://domains-tst.live-int.com/service/
            managedelegation.asmx" />
    </wsdl:port>
    <wsdl:port name="ManageDelegationSoap12" binding="tns:ManageDelegationSoap12">
        <soap12:address location="https://domains-tst.live-int.com/service/
            managedelegation.asmx" />
    </wsdl:port>
</wsdl:binding>
</wsdl:service>
</wsdl:definitions>

```

## 6.2 ManageDelegation2Soap WSDL

This section contains the **WSDL** that defines the operations, messages, types, and elements used by the **ManageDelegation2Soap** client protocol described in section [3.2](#).

```

<?xml version="1.0" encoding="utf-8"?>
<wsdl:definitions xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
    xmlns:s3="http://www.w3.org/2000/09/xmldsig#"
    xmlns:tns="http://domains.live.com/Service/ManageDelegation2/V1.0"
    xmlns:s1="http://docs.oasis-open.org/wss/2004/01/
        oasis-200401-wss-wssecurity-secext-1.0.xsd"

```

```

xmlns:s="http://www.w3.org/2001/XMLSchema"
xmlns:s2="http://docs.oasis-open.org/
wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd"
xmlns:soap12="http://schemas.xmlsoap.org/wsdl/soap12/"
targetNamespace="http://domains.live.com/Service/ManageDelegation2/V1.0"
xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
<wsdl:types>
  <s:schema elementFormDefault="qualified"
    targetNamespace="http://domains.live.com/Service/ManageDelegation2/V1.0">
    <s:element name="CreateAppId">
      <s:complexType>
        <s:sequence>
          <s:element minOccurs="0" maxOccurs="1" name="uri" type="s:string" />
          <s:element minOccurs="0" maxOccurs="1" name="properties"
            type="tns:ArrayOfProperty" />
        </s:sequence>
      </s:complexType>
    </s:element>
    <s:complexType name="ArrayOfProperty">
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="unbounded" name="Property"
          type="tns:Property" />
      </s:sequence>
    </s:complexType>
    <s:complexType name="Property">
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="Name" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="Value" type="s:string" />
      </s:sequence>
    </s:complexType>
    <s:element name="CreateAppIdResponse">
      <s:complexType>
        <s:sequence>
          <s:element minOccurs="0" maxOccurs="1" name="CreateAppIdResult"
            type="tns:AppIdInfo" />
        </s:sequence>
      </s:complexType>
    </s:element>
    <s:complexType name="AppIdInfo">
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="AppId" type="s:string" />
      </s:sequence>
    </s:complexType>
    <s:element name="DomainOwnershipProofHeader" type="tns:DomainOwnershipProofHeader" />
    <s:complexType name="DomainOwnershipProofHeader">
      <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="Domain" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="HashAlgorithm"
          type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="Signature"
          type="s:string" />
      </s:sequence>
      <s:anyAttribute />
    </s:complexType>
    <s:element name="UpdateAppIdCertificate">
      <s:complexType>
        <s:sequence>
          <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
          <s:element minOccurs="0" maxOccurs="1" name="newCertificate"
            type="s:string" />
        </s:sequence>
      </s:complexType>
    </s:element>
    <s:element name="UpdateAppIdCertificateResponse">
      <s:complexType />
    </s:element>
    <s:element name="UpdateAppIdProperties">
      <s:complexType>
        <s:sequence>

```

```

        <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="properties"
            type="tns:ArrayOfProperty" />
    </s:sequence>
</s:complexType>
</s:element>
<s:element name="UpdateAppIdPropertiesResponse">
    <s:complexType />
</s:element>
<s:element name="AddUri">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="uri" type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="AddUriResponse">
    <s:complexType />
</s:element>
<s:element name="RemoveUri">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="uri" type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="RemoveUriResponse">
    <s:complexType />
</s:element>
<s:element name="ReserveDomain">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="domainName"
                type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="programId" type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="ReserveDomainResponse">
    <s:complexType />
</s:element>
<s:element name="ReleaseDomain">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="domainName"
                type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="ReleaseDomainResponse">
    <s:complexType />
</s:element>
<s:element name="GetDomainInfo">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="appId" type="s:string" />
            <s:element minOccurs="0" maxOccurs="1" name="domainName"
                type="s:string" />
        </s:sequence>
    </s:complexType>
</s:element>
<s:element name="GetDomainInfoResponse">
    <s:complexType>
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" name="GetDomainInfoResult"

```

```

        type="tns:DomainInfo" />
    </s:sequence>
</s:complexType>
</s:element>
<s:complexType name="DomainInfo">
    <s:sequence>
        <s:element minOccurs="0" maxOccurs="1" name="DomainName"
            type="s:string" />
        <s:element minOccurs="0" maxOccurs="1" name="AppId" type="s:string" />
        <s:element minOccurs="1" maxOccurs="1" name="DomainState"
            type="tns:DomainState" />
    </s:sequence>
</s:complexType>
<s:simpleType name="DomainState">
    <s:restriction base="s:string">
        <s:enumeration value="PendingActivation" />
        <s:enumeration value="Active" />
        <s:enumeration value="PendingRelease" />
    </s:restriction>
</s:simpleType>
</s:schema>
<s:schema elementFormDefault="qualified"
    targetNamespace="http://docs.oasis-open.org/wss/2004/01/
    oasis-200401-wss-wssecurity-secext-1.0.xsd">
    <s:import
        namespace="http://docs.oasis-open.org/wss/2004/01/
        oasis-200401-wss-wssecurity-utility-1.0.xsd" />
    <s:import namespace="http://www.w3.org/2000/09/xmldsig#" />
    <s:element name="Security" type="s1:WSSecurityHeader" />
    <s:complexType name="WSSecurityHeader">
        <s:sequence>
            <s:element minOccurs="0" maxOccurs="1" ref="s2:Timestamp" />
            <s:element minOccurs="0" maxOccurs="1" ref="s3:Signature" />
        </s:sequence>
        <s:anyAttribute />
    </s:complexType>
</s:schema>
<s:schema elementFormDefault="qualified"
    targetNamespace="http://docs.oasis-open.org/wss/2004/01/
    oasis-200401-wss-wssecurity-utility-1.0.xsd">
    <s:element name="Timestamp">
        <s:complexType mixed="true">
            <s:sequence>
                <s:any maxOccurs="unbounded" />
            </s:sequence>
            <s:anyAttribute />
        </s:complexType>
    </s:element>
</s:schema>
<s:schema elementFormDefault="qualified"
    targetNamespace="http://www.w3.org/2000/09/xmldsig#">
    <s:element name="Signature">
        <s:complexType mixed="true">
            <s:sequence>
                <s:any maxOccurs="unbounded" />
            </s:sequence>
            <s:anyAttribute />
        </s:complexType>
    </s:element>
</s:schema>
</wsdl:types>
<wsdl:message name="CreateAppIdSoapIn">
    <wsdl:part name="parameters" element="tns:CreateAppId" />
</wsdl:message>
<wsdl:message name="CreateAppIdSoapOut">
    <wsdl:part name="parameters" element="tns:CreateAppIdResponse" />
</wsdl:message>
<wsdl:message name="CreateAppIdSecurity">
    <wsdl:part name="Security" element="s1:Security" />

```

```

</wsdl:message>
<wsdl:message name="CreateAppIdDomainOwnershipProofHeader">
  <wsdl:part name="DomainOwnershipProofHeader"
    element="tns:DomainOwnershipProofHeader" />
</wsdl:message>
<wsdl:message name="UpdateAppIdCertificateSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificate" />
</wsdl:message>
<wsdl:message name="UpdateAppIdCertificateSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAppIdCertificateResponse" />
</wsdl:message>
<wsdl:message name="UpdateAppIdCertificateSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:message name="UpdateAppIdPropertiesSoapIn">
  <wsdl:part name="parameters" element="tns:UpdateAppIdProperties" />
</wsdl:message>
<wsdl:message name="UpdateAppIdPropertiesSoapOut">
  <wsdl:part name="parameters" element="tns:UpdateAppIdPropertiesResponse" />
</wsdl:message>
<wsdl:message name="UpdateAppIdPropertiesSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:message name="AddUriSoapIn">
  <wsdl:part name="parameters" element="tns:AddUri" />
</wsdl:message>
<wsdl:message name="AddUriSoapOut">
  <wsdl:part name="parameters" element="tns:AddUriResponse" />
</wsdl:message>
<wsdl:message name="AddUriSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:message name="AddUriDomainOwnershipProofHeader">
  <wsdl:part name="DomainOwnershipProofHeader"
    element="tns:DomainOwnershipProofHeader" />
</wsdl:message>
<wsdl:message name="RemoveUriSoapIn">
  <wsdl:part name="parameters" element="tns:RemoveUri" />
</wsdl:message>
<wsdl:message name="RemoveUriSoapOut">
  <wsdl:part name="parameters" element="tns:RemoveUriResponse" />
</wsdl:message>
<wsdl:message name="RemoveUriSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:message name="ReserveDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReserveDomain" />
</wsdl:message>
<wsdl:message name="ReserveDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReserveDomainResponse" />
</wsdl:message>
<wsdl:message name="ReserveDomainSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:message name="ReserveDomainDomainOwnershipProofHeader">
  <wsdl:part name="DomainOwnershipProofHeader"
    element="tns:DomainOwnershipProofHeader" />
</wsdl:message>
<wsdl:message name="ReleaseDomainSoapIn">
  <wsdl:part name="parameters" element="tns:ReleaseDomain" />
</wsdl:message>
<wsdl:message name="ReleaseDomainSoapOut">
  <wsdl:part name="parameters" element="tns:ReleaseDomainResponse" />
</wsdl:message>
<wsdl:message name="ReleaseDomainSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:message name="GetDomainInfoSoapIn">
  <wsdl:part name="parameters" element="tns:GetDomainInfo" />

```

```

</wsdl:message>
<wsdl:message name="GetDomainInfoSoapOut">
  <wsdl:part name="parameters" element="tns:GetDomainInfoResponse" />
</wsdl:message>
<wsdl:message name="GetDomainInfoSecurity">
  <wsdl:part name="Security" element="s1:Security" />
</wsdl:message>
<wsdl:portType name="ManageDelegation2Soap">
  <wsdl:operation name="CreateAppId">
    <wsdl:input message="tns:CreateAppIdSoapIn" />
    <wsdl:output message="tns:CreateAppIdSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdCertificate">
    <wsdl:input message="tns:UpdateAppIdCertificateSoapIn" />
    <wsdl:output message="tns:UpdateAppIdCertificateSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdProperties">
    <wsdl:input message="tns:UpdateAppIdPropertiesSoapIn" />
    <wsdl:output message="tns:UpdateAppIdPropertiesSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="AddUri">
    <wsdl:input message="tns:AddUriSoapIn" />
    <wsdl:output message="tns:AddUriSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="RemoveUri">
    <wsdl:input message="tns:RemoveUriSoapIn" />
    <wsdl:output message="tns:RemoveUriSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="ReserveDomain">
    <wsdl:input message="tns:ReserveDomainSoapIn" />
    <wsdl:output message="tns:ReserveDomainSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="ReleaseDomain">
    <wsdl:input message="tns:ReleaseDomainSoapIn" />
    <wsdl:output message="tns:ReleaseDomainSoapOut" />
  </wsdl:operation>
  <wsdl:operation name="GetDomainInfo">
    <wsdl:input message="tns:GetDomainInfoSoapIn" />
    <wsdl:output message="tns:GetDomainInfoSoapOut" />
  </wsdl:operation>
</wsdl:portType>
<wsdl:binding name="ManageDelegation2Soap" type="tns:ManageDelegation2Soap">
  <soap:binding transport="http://schemas.xmlsoap.org/soap/http" />
  <wsdl:operation name="CreateAppId">
    <soap:operation
      soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/CreateAppId"
      style="document" />
    <wsdl:input>
      <soap:body use="literal" />
      <soap:header message="tns:CreateAppIdSecurity" part="Security"
        use="literal" />
      <soap:header message="tns:CreateAppIdDomainOwnershipProofHeader"
        part="DomainOwnershipProofHeader" use="literal" />
    </wsdl:input>
    <wsdl:output>
      <soap:body use="literal" />
    </wsdl:output>
  </wsdl:operation>
  <wsdl:operation name="UpdateAppIdCertificate">
    <soap:operation
      soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/UpdateAppIdCertificate"
      style="document" />
    <wsdl:input>
      <soap:body use="literal" />
      <soap:header message="tns:UpdateAppIdCertificateSecurity"
        part="Security" use="literal" />
    </wsdl:input>
    <wsdl:output>

```

```

        <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="UpdateAppIdProperties">
    <soap:operation
        soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/UpdateAppIdProperties"
        style="document" />
        <wsdl:input>
            <soap:body use="literal" />
            <soap:header message="tns:UpdateAppIdPropertiesSecurity" part="Security"
                use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
<wsdl:operation name="AddUri">
    <soap:operation
        soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/AddUri"
        style="document" />
        <wsdl:input>
            <soap:body use="literal" />
            <soap:header message="tns:AddUriSecurity" part="Security" use="literal" />
            <soap:header message="tns:AddUriDomainOwnershipProofHeader"
                part="DomainOwnershipProofHeader" use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
<wsdl:operation name="RemoveUri">
    <soap:operation
        soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/RemoveUri"
        style="document" />
        <wsdl:input>
            <soap:body use="literal" />
            <soap:header message="tns:RemoveUriSecurity" part="Security"
                use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
<wsdl:operation name="ReserveDomain">
    <soap:operation
        soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/ReserveDomain"
        style="document" />
        <wsdl:input>
            <soap:body use="literal" />
            <soap:header message="tns:ReserveDomainSecurity" part="Security"
                use="literal" />
            <soap:header message="tns:ReserveDomainDomainOwnershipProofHeader"
                part="DomainOwnershipProofHeader" use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
<wsdl:operation name="ReleaseDomain">
    <soap:operation
        soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/ReleaseDomain"
        style="document" />
        <wsdl:input>
            <soap:body use="literal" />
            <soap:header message="tns:ReleaseDomainSecurity" part="Security"
                use="literal" />
        </wsdl:input>
        <wsdl:output>

```

```

        <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetDomainInfo">
    <soap:operation
        soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/GetDomainInfo"
style="document" />
    <wsdl:input>
        <soap:body use="literal" />
        <soap:header message="tns:GetDomainInfoSecurity" part="Security"
            use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:binding name="ManageDelegation2Soap12" type="tns:ManageDelegation2Soap">
    <soap12:binding transport="http://schemas.xmlsoap.org/soap/http" />
    <wsdl:operation name="CreateAppId">
        <soap12:operation
            soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/CreateAppId"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
            <soap12:header message="tns:CreateAppIdSecurity" part="Security"
                use="literal" />
            <soap12:header message="tns:CreateAppIdDomainOwnershipProofHeader"
                part="DomainOwnershipProofHeader" use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UpdateAppIdCertificate">
        <soap12:operation
            soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/UpdateAppIdCertificate"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
            <soap12:header message="tns:UpdateAppIdCertificateSecurity" part="Security"
                use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="UpdateAppIdProperties">
        <soap12:operation
            soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/UpdateAppIdProperties"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
            <soap12:header message="tns:UpdateAppIdPropertiesSecurity" part="Security"
                use="literal" />
        </wsdl:input>
        <wsdl:output>
            <soap12:body use="literal" />
        </wsdl:output>
    </wsdl:operation>
    <wsdl:operation name="AddUri">
        <soap12:operation
            soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/AddUri"
style="document" />
        <wsdl:input>
            <soap12:body use="literal" />
            <soap12:header message="tns:AddUriSecurity" part="Security" use="literal" />

```

```

        <soap12:header message="tns:AddUriDomainOwnershipProofHeader"
            part="DomainOwnershipProofHeader" use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="RemoveUri">
    <soap12:operation
        soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/RemoveUri"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:RemoveUriSecurity" part="Security"
            use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReserveDomain">
    <soap12:operation
        soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/ReserveDomain"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:ReserveDomainSecurity" part="Security"
            use="literal" />
        <soap12:header message="tns:ReserveDomainDomainOwnershipProofHeader"
            part="DomainOwnershipProofHeader" use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="ReleaseDomain">
    <soap12:operation
        soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/ReleaseDomain"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:ReleaseDomainSecurity" part="Security"
            use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
<wsdl:operation name="GetDomainInfo">
    <soap12:operation
        soapAction="http://domains.live.com/Service/ManageDelegation2/V1.0/GetDomainInfo"
style="document" />
    <wsdl:input>
        <soap12:body use="literal" />
        <soap12:header message="tns:GetDomainInfoSecurity" part="Security"
            use="literal" />
    </wsdl:input>
    <wsdl:output>
        <soap12:body use="literal" />
    </wsdl:output>
</wsdl:operation>
</wsdl:binding>
<wsdl:service name="ManageDelegation2">
    <wsdl:port name="ManageDelegation2Soap" binding="tns:ManageDelegation2Soap">
        <soap:address
            location="https://domains-dev.live-int.com/
            service/ManageDelegation2.asmx" />
    </wsdl:port>
    <wsdl:port name="ManageDelegation2Soap12"

```

```
        binding="tns:ManageDelegation2Soap12">
      <soap12:address
        location="https://domains-dev.live-int.com/
        service/ManageDelegation2.asmx" />
    </wsdl:port>
  </wsdl:service>
</wsdl:definitions>
```

## 7 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include updates to those products.

- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Microsoft Exchange Server 2016
- Microsoft Exchange Server 2019
- Microsoft Exchange Server Subscription Edition

Exceptions, if any, are noted in this section. If an update version, service pack or Knowledge Base (KB) number appears with a product name, the behavior changed in that update. The new behavior also applies to subsequent updates unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

[<1> Section 3.1.3](#): By default, Exchange 2010, Exchange 2013, Exchange 2016, and Exchange 2019 get the Federation Metadata Document from the URL <http://nexus.passport.com/FederationMetadata/2006-12/FederationMetadata.xml>. This URL can be modified when establishing the federated domain.

[<2> Section 3.1.3](#): Exchange 2010, Exchange 2013, Exchange 2016, and Exchange 2019 store the URL of the delegation management service in **Active Directory** when the server is loaded. The URL is stored in the **serviceBindingInformation** property of the **Active Directory object** CN=DomainPartnerManageDelegation,CN=ServiceEndpoints,CN=FirstOrganization,CN=MicrosoftExchange,CN=Services,CN=Configuration,DC=

When the server calls the delegation management service, this object is read to obtain the URL of the service.

[<3> Section 3.1.4.6.2.1](#): Exchange 2010, Exchange 2013, Exchange 2016, and Exchange 2019 set this element to the string "ExchangeConnector".

[<4> Section 3.2.3](#): By default, Exchange 2010, Exchange 2013, Exchange 2016, and Exchange 2019 get the Federation Metadata Document from the URL <http://nexus.passport.com/FederationMetadata/2006-12/FederationMetadata.xml>. This URL can be modified when establishing the federated domain.

[<5> Section 3.2.3](#): Exchange 2010, Exchange 2013, Exchange 2016, and Exchange 2019 store the URL of the delegation management service in Active Directory when the server is loaded. The URL is stored in the **serviceBindingInformation** property of the Active Directory object CN=DomainPartnerManageDelegation,CN=ServiceEndpoints,CN=FirstOrganization,CN=MicrosoftExchange,CN=Services,CN=Configuration,DC=

When the server calls the delegation management service, this object is read to obtain the URL of the service.

[<6> Section 3.2.4.6.2.1](#): Exchange 2010, Exchange 2013, Exchange 2016, and Exchange 2019 set this element to the string "ExchangeConnector".

<7> [Section 3.3.4.1.1](#): The duration of the offer depends on the type of offer made. Exchange 2010, Exchange 2013, Exchange 2016, and Exchange 2019 create an offer with the duration set to the following values.

Offer type	Default duration
<b>MSExchange.SharingInviteMessage</b>	15 days
<b>MSExchange.SharingCalendarFreeBusy</b>	5 minutes
<b>MSExchange.SharingRead</b>	60 minutes
<b>MSExchange.DeliveryExternalSubmit</b>	48 hours
<b>MSExchange.DeliveryInternalSubmit</b>	48 hours
<b>MSExchange.MailboxMove</b>	60 minutes
<b>MSExchange.Autodiscover</b>	5 minutes

<8> [Section 3.3.4.1.1](#): Exchange 2010 stores this value in the directory service property **msExchFedApplicationURI** of the **msExchFedTrust** object.

<9> [Section 3.3.4.1.1](#): Exchange 2010 stores this value in the directory service property **msExchFedTokenIssuerURI** of the **msExchFedTrust** object. Exchange 2010 uses the value "uri:WindowsLiveID".

<10> [Section 3.3.4.1.1](#): Exchange 2010 obtains the value of the **saml:NameIdentifier** element from the **user** object in the directory service of the user for whom the token is requested. If the directory service **user** object has the **msExchImmutable** property set, that value is used; otherwise, Exchange 2010 uses the **objectGuid** property of the **user** object, which is encoded using **base64 encoding**, concatenated with the **msExchFedAccountNamespace** property of the **msExchFedOrgId** object.

<11> [Section 3.3.4.1.1](#): Exchange 2010 obtains the value of the **saml:NameIdentifier** element from the **user** object in the directory service of the user for whom the token is requested. If the directory service **user** object has the **msExchImmutable** property set, that value is used; otherwise, Exchange 2010 uses the **objectGuid** property of the **user** object, which is encoded using base64 encoding, concatenated with the **msExchFedAccountNamespace** property of the **msExchFedOrgId** object.

<12> [Section 3.3.4.1.1](#): Exchange 2010 sets the **URI** to the attribute value found in the directory service property **msExchFedPolicyReferenceURI** of the **msExchFedTrust** object. The default value is "EX\_MBI\_FED\_SSL".

## 8 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as Major, Minor, or None.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements.
- A document revision that captures changes to protocol functionality.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **None** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the relevant technical content is identical to the last released version.

The changes made to this document are listed in the following table. For more information, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

Section	Description	Revision class
<a href="#">Z</a> Appendix B: Product Behavior	Updated list of supported products.	Major

## 9 Index

### A

Abstract data model  
client ([section 3.1.1](#) 20, [section 3.2.1](#) 42, [section 3.3.1](#) 71)  
[Applicability](#) 12  
[Attribute groups](#) 19  
[Attributes](#) 19

### C

[Capability negotiation](#) 12  
[Change tracking](#) 107  
Client  
abstract data model ([section 3.1.1](#) 20, [section 3.2.1](#) 42, [section 3.3.1](#) 71)  
[Federation Metadata](#) 70  
initialization ([section 3.1.3](#) 21, [section 3.2.3](#) 43, [section 3.3.3](#) 71)  
local events ([section 3.1.6](#) 42, [section 3.2.6](#) 70, [section 3.3.6](#) 81)  
[ManageDelegation2Soap](#) 42  
[ManageDelegationSoap](#) 20  
message processing ([section 3.1.4](#) 21, [section 3.2.4](#) 43, [section 3.3.4](#) 71)  
sequencing rules ([section 3.1.4](#) 21, [section 3.2.4](#) 43, [section 3.3.4](#) 71)  
timer events ([section 3.1.5](#) 42, [section 3.2.5](#) 70, [section 3.3.5](#) 81)  
timers ([section 3.1.2](#) 20, [section 3.2.2](#) 43, [section 3.3.2](#) 71)  
[Complex types](#) 14  
[s1:WSSecurityHeader Complex Type](#) 17  
[tns:ArrayOfProperty Complex Type](#) 15  
[tns:DomainInfo Complex Type](#) 15  
[tns:DomainOwnershipProofHeader Complex Type](#) 16  
[tns:Property Complex Type](#) 17

### D

Data model - abstract  
client ([section 3.1.1](#) 20, [section 3.2.1](#) 42, [section 3.3.1](#) 71)

### E

Elements  
[s:Security Element](#) 14  
[tns:DomainOwnershipProofHeader Element](#) 14  
Events  
local - client ([section 3.1.6](#) 42, [section 3.2.6](#) 70, [section 3.3.6](#) 81)  
timer - client ([section 3.1.5](#) 42, [section 3.2.5](#) 70, [section 3.3.5](#) 81)  
Examples  
[register with a security token service](#) 82

### F

[Fields - vendor-extensible](#) 12

[Full WSDL](#) 89  
[ManageDelegation2Soap WSDL](#) 95  
[ManageDelegationSoap WSDL](#) 89

### G

[Glossary](#) 8  
[Groups](#) 19

### I

[Implementer - security considerations](#) 88  
[Index of security parameters](#) 88  
[Informative references](#) 11  
Initialization  
client ([section 3.1.3](#) 21, [section 3.2.3](#) 43, [section 3.3.3](#) 71)  
[Introduction](#) 8

### L

Local events  
client ([section 3.1.6](#) 42, [section 3.2.6](#) 70, [section 3.3.6](#) 81)

### M

Message processing  
client ([section 3.1.4](#) 21, [section 3.2.4](#) 43, [section 3.3.4](#) 71)  
Messages  
[attribute groups](#) 19  
[attributes](#) 19  
[complex types](#) 14  
[elements](#) 14  
[enumerated](#) 13  
[groups](#) 19  
[namespaces](#) 13  
[s:Security Element element](#) 14  
[s1:WSSecurityHeader Complex Type complex type](#) 17  
[simple types](#) 18  
[syntax](#) 13  
[tns:ArrayOfProperty Complex Type complex type](#) 15  
[tns:DomainInfo Complex Type complex type](#) 15  
[tns:DomainOwnershipProofHeader Complex Type complex type](#) 16  
[tns:DomainOwnershipProofHeader Element element](#) 14  
[tns:DomainState Simple Type simple type](#) 18  
[tns:Property Complex Type complex type](#) 17  
[transport](#) 13

### N

[Namespaces](#) 13  
[Normative references](#) 10

### O

[Overview \(synopsis\)](#) 11

## P

[Parameters - security index](#) 88

[Preconditions](#) 12

[Prerequisites](#) 12

[Product behavior](#) 105

Protocol Details

[overview](#) 20

## R

[References](#) 10

[informative](#) 11

[normative](#) 10

[Register with a security token service example](#) 82

[Relationship to other protocols](#) 11

## S

[s:Security Element element](#) 14

[s1:WSSecurityHeader Complex Type complex type](#)  
17

Security

[implementer considerations](#) 88

[parameter index](#) 88

Sequencing rules

client ([section 3.1.4](#) 21, [section 3.2.4](#) 43, [section 3.3.4](#) 71)

[Simple types](#) 18

[tns:DomainState Simple Type](#) 18

[Standards assignments](#) 12

Syntax

[messages - overview](#) 13

## T

Timer events

client ([section 3.1.5](#) 42, [section 3.2.5](#) 70, [section 3.3.5](#) 81)

Timers

client ([section 3.1.2](#) 20, [section 3.2.2](#) 43, [section 3.3.2](#) 71)

[tns:ArrayOfProperty Complex Type complex type](#) 15

[tns:DomainInfo Complex Type complex type](#) 15

[tns:DomainOwnershipProofHeader Complex Type complex type](#) 16

[tns:DomainOwnershipProofHeader Element element](#)  
14

[tns:DomainState Simple Type simple type](#) 18

[tns:Property Complex Type complex type](#) 17

[Tracking changes](#) 107

[Transport](#) 13

Types

[complex](#) 14

[simple](#) 18

## V

[Vendor-extensible fields](#) 12

[Versioning](#) 12

## W

[WSDL](#) 89

[ManageDelegation2Soap WSDL](#) 95

[ManageDelegationSoap WSDL](#) 89